

minet

October 5, 2010

aracne

Algorithm for the Reconstruction of Accurate Cellular NETWORKs

Description

This function takes the mutual information matrix as input in order to return the inferred network according to the Aracne algorithm. This algorithm applies the data processing inequality to all triplets of nodes in order to remove the least significant edge in each triplet.

Usage

```
aracne( mim, eps=0 )
```

Arguments

mim	A square matrix whose i,j th element is the mutual information between variables X_i and X_j - see build.mim .
eps	Numeric value indicating the threshold used when removing an edge : for each triplet of nodes (i,j,k) , the weakest edge, say (ij) , is removed if its weight is below $\min\{(ik),(jk)\}-\text{eps}$ - see references.

Details

The Aracne procedure starts by assigning to each pair of nodes a weight equal to their mutual information. Then, the weakest edge of each triplet is interpreted as an indirect interaction and is removed if the difference between the two lowest weights is above a threshold `eps`.

Value

`aracne` returns a matrix which is the weighted adjacency matrix of the network. In order to display the network, load the package `Rgraphviz` and use the following command:
`plot(as(returned.matrix , "graphNEL"))`

References

Adam A. Margolin, Ilya Nemenman, Katia Basso, Chris Wiggins, Gustavo Stolovitzky, Riccardo Dalla Favera, and Andrea Califano. Aracne : An algorithm for the reconstruction of gene regulatory networks in a mammalian cellular context. BMC Bioinformatics, 2006.

See Also

[build.mim](#), [clr](#), [mrnet](#), [mrnetb](#)

Examples

```
data(syn.data)
mim <- build.mim(syn.data, estimator="spearman")
net <- aracne(mim)
```

build.mim

Build Mutual Information Matrix

Description

`build.mim` takes the dataset as input and computes the mutual information between all pair of variables according to the mutual information estimator `estimator`. The results are saved in the mutual information matrix (MIM), a square matrix whose (i,j) element is the mutual information between variables X_i and X_j .

Usage

```
build.mim(dataset, estimator = "spearman", disc = "none", nbins = sqrt(NROW(data)))
```

Arguments

<code>dataset</code>	data.frame containing gene expression data or any dataset where columns contain variables/features and rows contain outcomes/samples.
<code>estimator</code>	The name of the entropy estimator to be used. The package implements four estimators for discrete data: "mi.empirical", "mi.mm", "mi.shrink", "mi.sg" and three estimators based on correlation (can be used with continuous data): "pearson", "spearman", "kendall"(default:"spearman") - see details.
<code>disc</code>	The name of the discretization method to be used with one of the discrete estimators: "none", "equalfreq", "equalwidth" or "globalequalwidth" (default : "none") - see infotheo package.
<code>nbins</code>	Integer specifying the number of bins to be used for the discretization if disc is different from "none". By default the number of bins is set to \sqrt{m} where m is the number of samples.

Details

- "mi.empirical" : This estimator computes the entropy of the empirical probability distribution.
- "mi.mm" : This is the Miller-Madow asymptotic bias corrected empirical estimator.
- "mi.shrink" : This is a shrinkage estimate of the entropy of a Dirichlet probability distribution.
- "mi.sg" : This is the Schurmann-Grassberger estimate of the entropy of a Dirichlet probability distribution.
- "pearson" : This computes mutual information for normally distributed variable using Pearson's correlation.
- "spearman" : This computes mutual information for normally distributed variable using Spearman's correlation
- "kendall" : This computes mutual information for normally distributed variable using Kendall's correlation

Value

`build.mim` returns the mutual information matrix.

Author(s)

Patrick E. Meyer, Frederic Lafitte, Gianluca Bontempi

References

Patrick E. Meyer, Frederic Lafitte, and Gianluca Bontempi. *minet: A R/Bioconductor Package for Inferring Large Transcriptional Networks Using Mutual Information*. BMC Bioinformatics, Vol 9, 2008.

J. Beirlant, E. J. Dudewica, L. Gyöfi, and E. van der Meulen. *Nonparametric entropy estimation : An overview*. Journal of Statistics, 1997.

Jean Hausser. *Improving entropy estimation and the inference of genetic regulatory networks*. Master thesis of the National Institute of Applied Sciences of Lyon, 2006.

See Also

[clr](#), [aracne](#), [mrnet](#), [mrnetb](#)

Examples

```
data(syn.data)
mim <- build.mim(syn.data, estimator="spearman")
```

 clr

Context Likelihood or Relatedness Network

Description

`clr` takes the mutual information matrix as input in order to return the inferred network - see details.

Usage

```
clr( mim )
```

Arguments

`mim` A square matrix whose *i,j* th element is the mutual information between variables X_i and X_j - see [build.mim](#).

Details

The CLR algorithm is an extension of relevance network. Instead of considering the mutual information $I(X_i; X_j)$ between features X_i and X_j , it takes into account the score $\sqrt{z_i^2 + z_j^2}$, where

$$z_i = \max \left\{ 0, \frac{I(X_i; X_j) - \mu_i}{\sigma_i} \right\}$$

and μ_i and σ_i are, respectively, the mean and the standard deviation of the empirical distribution of the mutual information values $I(X_i; X_k)$, $k=1, \dots, n$.

Value

`clr` returns a matrix which is the weighted adjacency matrix of the network. In order to display the network, load the package `Rgraphviz` and use the following comand `plot(as(returned.matrix , "graphNEL"))`

References

Jeremiah J. Faith, Boris Hayete, Joshua T. Thaden, Ilaria Mogno, Jamey Wierzbowski, Guillaume Cottarel, Simon Kasif, James J. Collins, and Timothy S. Gardner. Large-scale mapping and validation of escherichia coli transcriptional regulation from a compendium of expression profiles. *PLoS Biology*, 2007.

See Also

[build.mim](#), [aracne](#), [mrnet](#), [mrnetb](#)

Examples

```
data(syn.data)
mim <- build.mim(syn.data, estimator="spearman")
net <- clr(mim)
```

minet

Mutual Information Network

Description

For a given dataset, `minet` infers the network in two steps. First, the mutual information between all pairs of variables in `dataset` is computed according to the `estimator` argument. Then the algorithm given by `method` considers the estimated mutual informations in order to build the network.

Usage

```
minet(dataset, method="mrnet", estimator="spearman", disc="none", nbins=sqrt(NRO))
```

Arguments

<code>dataset</code>	<code>data.frame</code> where columns contain variables/features and rows contain outcomes/samples.
<code>method</code>	The name of the inference algorithm : "clr", "aracne", "mrnet" or "mrnetb" (default: "mrnet") - see references.
<code>estimator</code>	The name of the entropy estimator to be used for mutual information computation: "mi.empirical", "mi.mm", "mi.shrink", "mi.sg", "spearman", "kendall", "pearson" (default: "spearman"). - see build.mim .
<code>disc</code>	The name of the discretization method to be used, if required by the estimator : "none", "equalfreq", "equalwidth" or "globalequalwidth" (default : "none") - see <code>infotheo</code> package.
<code>nbins</code>	Integer specifying the number of bins to be used for the discretization if <code>disc</code> is set properly. By default the number of bins is set to \sqrt{N} where N is the number of samples.

Value

`minet` returns a matrix which is the weighted adjacency matrix of the network. The weights range from 0 to 1 and can be seen as a confidence measure on the presence of the arcs. In order to display the network, load the package `Rgraphviz` and use the following command:
`plot(as(returned.matrix , "graphNEL"))`

Author(s)

Patrick E. Meyer, Frederic Lafitte, Gianluca Bontempi

References

Patrick E. Meyer, Frederic Lafitte, and Gianluca Bontempi. `minet`: A R/Bioconductor Package for Inferring Large Transcriptional Networks Using Mutual Information. *BMC Bioinformatics*, Vol 9, 2008.

See Also

`build.mim`, `clr`, `mrnet`, `mrnetb`, `aracne`

Examples

```
data(syn.data)
net1 <- minet( syn.data )
net2 <- minet( syn.data, estimator="pearson" )
net3 <- minet( syn.data, method="clr", estimator="spearman" )
```

 mrnet

Maximum Relevance Minimum Redundancy

Description

`mrnet` takes the mutual information matrix as input in order to infer the network using the maximum relevance/minimum redundancy feature selection method - see details.

Usage

```
mrnet(mim)
```

Arguments

`mim` A square matrix whose *i,j* th element is the mutual information between variables X_i and X_j - see `build.mim`.

Details

The MRNET approach consists in repeating a MRMR feature selection procedure for each variable of the dataset. The MRMR method starts by selecting the variable X_i having the highest mutual information with the target Y . In the following steps, given a set \mathcal{S} of selected variables, the criterion updates \mathcal{S} by choosing the variable X_k that maximizes $I(X_k; Y) - \frac{1}{|\mathcal{S}|} \sum_{X_i \in \mathcal{S}} I(X_k; X_i)$. The weight of each pair X_i, X_j will be the maximum score between the one computed when X_i is the target and the one computed when X_j is the target.

Value

`mrnet` returns a matrix which is the weighted adjacency matrix of the network. In order to display the network, load the package `Rgraphviz` and use the following command:
`plot(as(returned.matrix , "graphNEL"))`

Author(s)

Patrick E. Meyer, Frederic Lafitte, Gianluca Bontempi

References

Patrick E. Meyer, Kevin Kontos, Frederic Lafitte, and Gianluca Bontempi. Information-theoretic inference of large transcriptional regulatory networks. *EURASIP Journal on Bioinformatics and Systems Biology*, 2007.

H. Peng, F.long and C.Ding. Feature selection based on mutual information: Criteria of max-dependency, max relevance and min redundancy. *IEEE transaction on Pattern Analysis and Machine Intelligence*, 2005

See Also

[build.mim](#), [clr](#), [aracne](#), [mrnetb](#)

Examples

```
data(syn.data)
mim <- build.mim(syn.data, estimator="spearman")
net <- mrnet(mim)
```

mrnetb

Maximum Relevance Minimum Redundancy

Description

`mrnetb` takes the mutual information matrix as input in order to infer the network using the maximum relevance/minimum redundancy feature selection method - see details. This method is a variant of `mrnet` (not yet available).

Usage

```
mrnetb(mim)
```

Arguments

`mim` A square matrix whose i,j th element is the mutual information between variables X_i and X_j - see [build.mim](#).

Details

to complete.

Value

`mrnetb` returns a matrix which is the weighted adjacency matrix of the network. In order to display the network, load the package `Rgraphviz` and use the following command:
`plot(as(returned.matrix , "graphNEL"))`

Author(s)

Patrick E. Meyer, Frederic Lafitte, Gianluca Bontempi

References

to complete.

Patrick E. Meyer, Kevin Kontos, Frederic Lafitte, and Gianluca Bontempi. Information-theoretic inference of large transcriptional regulatory networks. *EURASIP Journal on Bioinformatics and Systems Biology*, 2007.

See Also

[build.mim](#), [clr](#), [mrnet](#), [aracne](#)

Examples

```
data(syn.data)
mim <- build.mim(syn.data, estimator="spearman")
net <- mrnetb(mim)
```

syn.data

Simulated Gene Expression Data

Description

Dataset containing 100 samples and 50 genes generated by the publicly available SynTReN generator using a yeast source network - see [syn.net](#)

Usage

```
data(syn.data)
```

Format

`syn.data` is a data frame containing 100 rows and 50 columns. Each row contains a microarray experiment and each column contains a gene.

Source

SynTReN 1.1.3 with source network : yeast_nn.sif

References

Tim Van den Bulcke, Koenraad Van Leemput, Bart Naudts, Piet van Remortel, Hongwu Ma, Alain Verschoren, Bart De Moor, and Kathleen Marchal. Syntren : a generator of synthetic gene expression dataset for design and analysis of structure learning algorithms. *BMC Bioinformatics*, 2006.

Examples

```
data(syn.data)
data(syn.net)
mim <- build.mim(syn.data, estimator="spearman")
inferred.net <- mrnet(mim)
max(fscores(validate( inferred.net, syn.net )))
```

syn.net

SynTReN Source Network

Description

This is the true underlying network used to generate the dataset loaded by `data(syn.data)` - see [syn.data](#).

Usage

```
data(syn.net)
```

Format

`syn.net` is a boolean adjacency matrix representing an undirected graph of 50 nodes.

Source

`syn.net` is the "yeast_nn.sif" source network from the SynTReN generator where all the variables/nodes not in `syn.data` were removed.

References

Tim Van den Bulcke, Koenraad Van Leemput, Bart Naudts, Piet van Remortel, Hongwu Ma, Alain Verschoren, Bart De Moor, and Kathleen Marchal. Syntren : a generator of synthetic gene expression dataset for design and analysis of structure learning algorithms. BMC Bioinformatics, 2006.

Examples

```
data(syn.data)
data(syn.net)
mim <- build.mim(syn.data, estimator="spearman")
inferred.net <- mrnet(mim)
max(fscores(validate( inferred.net, syn.net )))
```

validate	<i>Inference Validation</i>
----------	-----------------------------

Description

`validate` compares the inferred network to the true underlying network for several threshold values and appends the resulting confusion matrices to the returned object.

Usage

```
validate(inet, tnet, steps=50, thresholds=pretty(inet, steps))
```

Arguments

<code>inet</code>	This is the inferred network, a data.frame or matrix obtained by one of the functions minet , aracne , clr or mrnet .
<code>tnet</code>	The true underlying network. This network must have the same size and variable names as <code>inet</code> .
<code>steps</code>	The number of threshold values to be used in the validation process - see details .
<code>thresholds</code>	The vector of thresholds to be used. By default it is a sequence of about <code>steps+1</code> equally spaced intervals.

Details

For each of the `steps` threshold values I_0 , the edges whose weight are (strictly) below I_0 are eliminated. All the other edges will have a weight 1. Thus for each threshold, we obtain a boolean network from the inferred network. This network is compared to the true underlying network, `tnet`, in order to compute a confusion (adjacency) matrix. All the confusion matrices, obtained with different threshold values, are appended to the returned object. In the end the `validate` function returns a data.frame containing `steps+1` confusion matrices.

Value

`validate` returns a data.frame with four columns named `thrsh`, `tp`, `fp`, `fn`. These values are computed for each of the `steps` thresholds. Thus each row of the returned object contains the confusion matrix for a different threshold.

See Also

[minet](#), [vis.res](#)

Examples

```
data(syn.data)
data(syn.net)
inf.net <- mrnet(build.mim(syn.data, estimator="spearman"))
table <- validate(inf.net, syn.net, steps=100)
table <- validate(inf.net, syn.net, steps=1, thresholds=0.5)
```

vis.res

*Visualize Results***Description**

A group of functions to plot precision-recall and ROC curves and to compute f-scores from the data.frame returned by the `validate` function.

Usage

```
pr(table)
rates(table)
fscores(table, beta=1)
show.pr(table, device=-1, ...)
show.roc(table, device=-1, ...)
```

Arguments

table	This is the (steps x 5) data.frame returned by the <code>validate</code> function where <code>steps</code> is the number of thresholds used in the validation process and where columns contain TP,FP,TN,FN values (confusion matrix) as well as the threshold value used - see <code>validate</code> .
beta	Numeric used as the weight of the recall in the f-score formula - see details. The default value of this argument is 1, meaning precision as important as recall.
device	The device to be used. This parameter allows the user to plot precision-recall and receiver operating characteristic curves for various inference algorithms on the same plotting window - see examples.
...	arguments passed to <code>plot</code>

Details

A confusion matrix contains FP,TP,FN,FP values.

- "true positive rate" $tpr = \frac{TP}{TN+TP}$
- "false positive rate" $fpr = \frac{FP}{FN+FP}$
- "precision" $p = \frac{TP}{FP+TP}$
- "recall" $r = \frac{TP}{TP+FN}$
- "f-beta-score" $F_\beta = (1 + \beta) \frac{pr}{r + \beta p}$

Value

The function `show.roc` (`show.pr`) plots the ROC-curve (PR-curve) and returns the device associated with the plotting window.

The function `pr` returns a (steps x 2) data.frame where `steps` is the number of thresholds used in the validation process. The first column contains precisions and the second recalls - see details.

The function `rates` also returns a (steps x 2) data.frame where the first column contains true positive rates and the second column false positive rates - see details.

The function `fscores` returns `steps` fscores according to the `steps` confusion matrices contained in the 'table' argument - see details.

References

Patrick E. Meyer, Frederic Lafitte, and Gianluca Bontempi. minet: A R/Bioconductor Package for Inferring Large Transcriptional Networks Using Mutual Information. BMC Bioinformatics, Vol 9, 2008.

See Also

[validate](#), [plot](#)

Examples

```
data(syn.data)
data(syn.net)
# Inference
mr <- minet( syn.data, method="mrnet", estimator="spearman" )
ar <- minet( syn.data, method="aracne", estimator="spearman" )
clr<- minet( syn.data, method="clr", estimator="spearman" )
# Validation
mr.tbl <- validate(mr,syn.net)
ar.tbl <- validate(ar,syn.net)
clr.tbl<- validate(clr,syn.net)
# Plot PR-Curves
max(fscores(mr.tbl))
dev <- show.pr(mr.tbl, col="green", type="b")
dev <- show.pr(ar.tbl, device=dev, col="blue", type="b")
show.pr(clr.tbl, device=dev, col="red",type="b")
```

Index

*Topic **datasets**

syn.data, 7

syn.net, 8

*Topic **misc**

aracne, 1

build.mim, 2

clr, 3

minet, 4

mrnet, 5

mrnetb, 6

validate, 9

vis.res, 10

aracne, 1, 3–7, 9

build.mim, 1, 2, 2–7

clr, 2, 3, 3, 5–7, 9

fscores (*vis.res*), 10

minet, 4, 9

mrnet, 2–4, 5, 5, 7, 9

mrnetb, 2–5, 6, 6

plot, 11

pr (*vis.res*), 10

rates (*vis.res*), 10

show.pr (*vis.res*), 10

show.roc (*vis.res*), 10

syn.data, 7, 8

syn.net, 7, 8

validate, 9, 10, 11

vis.res, 9, 10