

Package ‘Rhtslib’

October 16, 2019

Type Package

Title HTSlib high-throughput sequencing library as an R package

Version 1.16.3

Description This package provides version 1.7 of the 'HTSlib' C library for high-throughput sequence analysis. The package is primarily useful to developers of other R packages who wish to make use of HTSlib. Motivation and instructions for use of this package are in the vignette, `vignette(package="`Rhtslib", `Rhtslib")`.

License LGPL (>= 2)

Copyright Unless otherwise noted in the file, all files outside `src/htslib-1.7` and `inst/include` copyright Bioconductor; for files inside `src/htslib-1.7` or `inst/include`, see file `src/htslib/LICENSE`.

Imports zlibbioc

LinkingTo zlibbioc

Suggests BiocStyle, knitr

SystemRequirements libbz2 & liblzma (with header files)

StagedInstall no

VignetteBuilder knitr

URL <https://github.com/Bioconductor/Rhtslib>, <http://www.htslib.org/>

BugReports <https://github.com/Bioconductor/Rhtslib>

biocViews DataImport, Sequencing

git_url <https://git.bioconductor.org/packages/Rhtslib>

git_branch RELEASE_3_9

git_last_commit 3ed0b5d

git_last_commit_date 2019-09-27

Date/Publication 2019-10-15

Author Nathaniel Hayden [led, aut],
Martin Morgan [aut],
Bioconductor Package Maintainer [cre]

Maintainer Bioconductor Package Maintainer <maintainer@bioconductor.org>

R topics documented:

Rhtslib-package	2
pkgconfig	2

Index	4
--------------	----------

Rhtslib-package	<i>An R packaged HTSlib 1.7</i>
-----------------	---------------------------------

Description

This package is interesting to package developers only, and provides a compiled HTSlib for developers to use in their own packages. See the vignette for instructions on use.

Details

Instructions for use are in the vignette, available with `browseVignettes(package="Rhtslib")`

Author(s)

Nathaniel Hayden nhayden@fredhutch.org

References

The HTSlib included in the package is based on release 1.7 of HTSlib found in the GitHub repository at <https://github.com/samtools/htslib>

See Also

[pkgconfig](#)

Examples

```
packageDescription('Rhtslib')
Rhtslib:::htsVersion()
```

pkgconfig	<i>Compiler configuration arguments for use of Rhtslib</i>
-----------	--

Description

This function returns values for `PKG_LIBS` and `PKG_CPPFLAGS` variables for use in Makevars files. See `vignette("Rhtslib", "Rhtslib")` for details. Only `PKG_LIBS` should be needed in most cases. The environment variable `RHTSLIB_RPATH` can be used to over-ride the inferred location of the installed package.

Usage

```
pkgconfig(opt = c("PKG_LIBS", "PKG_CPPFLAGS"))
```

Arguments

opt A scalar character from the list of available options; default is PKG_LIBS.

Value

NULL; prints the corresponding value to stdout.

Author(s)

Nathaniel Hayden <mailto:nhayden@fredhutch.org>

Examples

```
pkgconfig("PKG_LIBS")  
pkgconfig("PKG_CPPFLAGS")
```

Index

*Topic **manip**

pkgconfig, [2](#)

*Topic **package**

Rhtslib-package, [2](#)

htsVersion (Rhtslib-package), [2](#)

pkgconfig, [2](#), [2](#)

Rhtslib (Rhtslib-package), [2](#)

Rhtslib-package, [2](#)