

Package ‘d4storagehub4R’

September 1, 2025

Version 0.4-5

Date 2025-09-01

Title Interface to 'D4Science' 'StorageHub' API

Maintainer Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Depends R (>= 3.3.0), methods

Imports R6, httr, jsonlite, XML, xml2, keyring, tools

Suggests testthat, parallel

Description Provides an interface to 'D4Science' 'StorageHub' API (<<https://dev.d4science.org/>>). Allows to get user profile, and perform actions over the 'StorageHub' (workspace) including creation of folders, files management (upload/update/deletion/sharing), and listing of stored resources.

License MIT + file LICENSE

URL <https://github.com/eblondel/d4storagehub4R>,
<https://www.d4science.org/>, <https://dev.d4science.org/>

BugReports <https://github.com/eblondel/d4storagehub4R/issues>

LazyLoad yes

RoxygenNote 7.3.1

Encoding UTF-8

NeedsCompilation no

Author Emmanuel Blondel [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5870-5762>>)

Repository CRAN

Date/Publication 2025-09-01 06:00:02 UTC

Contents

d4storagehub4R	2
d4storagehub4RLogger	2
StoragehubManager	4

Index**12**

d4storagehub4R	<i>Interface to 'D4Science' 'StorageHub' API</i>
----------------	--

Description

Provides an interface to 'D4Science' 'StorageHub' API (<<https://dev.d4science.org/>>). Allows to get user profile, and perform actions over the 'StorageHub' (workspace) including creation of folders, files management (upload/update/deletion/sharing), and listing of stored resources.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

d4storagehub4RLogger	<i>d4storagehub4RLogger</i>
----------------------	-----------------------------

Description

d4storagehub4RLogger
d4storagehub4RLogger

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a simple logger

Abstract Methods

INFO(text) Logger to report information. Used internally
WARN(text) Logger to report warnings. Used internally
ERROR(text) Logger to report errors. Used internally

Public fields

verbose.info verbose info, default is FALSE
verbose.debug verbose debug, default is FALSE
loggerType logger type

Methods

Public methods:

- [d4storagehub4RLogger\\$logger\(\)](#)
- [d4storagehub4RLogger\\$INFO\(\)](#)
- [d4storagehub4RLogger\\$WARN\(\)](#)
- [d4storagehub4RLogger\\$ERROR\(\)](#)
- [d4storagehub4RLogger\\$new\(\)](#)
- [d4storagehub4RLogger\\$getClassname\(\)](#)
- [d4storagehub4RLogger\\$getClass\(\)](#)
- [d4storagehub4RLogger\\$clone\(\)](#)

Method `logger()`: Logger function

Usage:

```
d4storagehub4RLogger$logger(type, text)
```

Arguments:

type type

text text

Method `INFO()`: INFO logger function

Usage:

```
d4storagehub4RLogger$INFO(text)
```

Arguments:

text text

Method `WARN()`: WARN logger function

Usage:

```
d4storagehub4RLogger$WARN(text)
```

Arguments:

text text

Method `ERROR()`: ERROR logger function

Usage:

```
d4storagehub4RLogger$ERROR(text)
```

Arguments:

text text

Method `new()`: Initializes a basic logger class

Usage:

```
d4storagehub4RLogger$new(logger = NULL)
```

Arguments:

logger the type of logger, either NULL (default), INFO, or DEBUG

Method `getClassName()`: Get class name

Usage:

`d4storagehub4RLogger$getClassName()`

Returns: the class name

Method `getClass()`: Get class

Usage:

`d4storagehub4RLogger$getClass()`

Returns: the class

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`d4storagehub4RLogger$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Logger class used internally by `d4storagehub4R`

StoragehubManager

StoragehubManager

Description

StoragehubManager

StoragehubManager

Value

Object of [R6Class](#) for modelling a D4Science StoragehubManager

Super class

`d4storagehub4R:d4storagehub4RLogger` -> StoragehubManager

Methods

Public methods:

- `StoragehubManager$new()`
- `StoragehubManager$getToken()`
- `StoragehubManager$getUserProfile()`
- `StoragehubManager$getUserWorkspace()`
- `StoragehubManager$fetchWSEndpoint()`

- `StoragehubManager$fetchUserProfile()`
- `StoragehubManager$getWSRoot()`
- `StoragehubManager$getWSRootID()`
- `StoragehubManager$getWSItem()`
- `StoragehubManager$getWSItemID()`
- `StoragehubManager$getWSVREFolder()`
- `StoragehubManager$getWSVREFolderID()`
- `StoragehubManager$listWSItems()`
- `StoragehubManager$listWSItemsByPath()`
- `StoragehubManager$searchWSItem()`
- `StoragehubManager$searchWSItemID()`
- `StoragehubManager$createFolder()`
- `StoragehubManager$uploadFile()`
- `StoragehubManager$deleteItem()`
- `StoragehubManager$shareItem()`
- `StoragehubManager$unshareItem()`
- `StoragehubManager$downloadItem()`
- `StoragehubManager$downloadItemByPath()`
- `StoragehubManager$getPublicFileLinkByID()`
- `StoragehubManager$getPublicFileLink()`
- `StoragehubManager$clone()`

Method `new()`: Method is used to instantiate the `StoragehubManager`.

Usage:

```
StoragehubManager$new(
  token,
  token_type = "gcube",
  logger = NULL,
  keyring_backend = "env"
)
```

Arguments:

`token` user access token

`token_type` token type, either 'gcube' (default) or 'jwt'

`logger` logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs)

`keyring_backend` keyring backend to use. it can be set to use a different backend for storing the D4science gcube token with **keyring** (Default value is 'env').

Method `getToken()`: Get token

Usage:

```
StoragehubManager$getToken()
```

Returns: the user access token

Method `getUserProfile()`: Get user profile

Usage:

```
StoragehubManager$getUserProfile()
```

Returns: the user profile

Method `getUserWorkspace()`: Get user workspace

Usage:

```
StoragehubManager$getUserWorkspace()
```

Returns: the user workspace root path

Method `fetchWSEndpoint()`: Fetches the workspace endpoint from the D4Science ICProxy service

Usage:

```
StoragehubManager$fetchWSEndpoint()
```

Method `fetchUserProfile()`: Fetches the user profile

Usage:

```
StoragehubManager$fetchUserProfile()
```

Method `getWSRoot()`: Get workspace root

Usage:

```
StoragehubManager$getWSRoot()
```

Returns: the workspace root, as list

Method `getWSRootID()`: Get workspace root ID

Usage:

```
StoragehubManager$getWSRootID()
```

Returns: the workspace root ID, as character

Method `getWSItem()`: Get workspace item given a `itemPath` in a parent folder

Usage:

```
StoragehubManager$getWSItem(  
  parentFolderID = NULL,  
  itemPath,  
  showHidden = FALSE  
)
```

Arguments:

`parentFolderID` parent folder ID

`itemPath` item path

`showHidden` show hidden files

Returns: the workspace item, NULL if no workspace item existing

Method `getWSItemID()`: Get workspace item ID given a `itemPath` in a parent folder

Usage:

```
StoragehubManager$getWSItemID(  
  parentFolderID = NULL,  
  itemPath,  
  showHidden = FALSE  
)
```

Arguments:

parentFolderID parent folder ID

itemPath item path

showHidden show hidden files

Returns: the workspace item ID, NULL if no workspace item existing

Method getWSVREFolder(): Get VRE Folder

Usage:

```
StoragehubManager$getWSVREFolder()
```

Returns: the VRE folder, as list

Method getWSVREFolderID(): Get VRE Folder ID

Usage:

```
StoragehubManager$getWSVREFolderID()
```

Returns: the VRE folder ID, as character

Method listWSItems(): Lists workspace items given a parentFolder ID

Usage:

```
StoragehubManager$listWSItems(parentFolderID = NULL, showHidden = FALSE)
```

Arguments:

parentFolderID parent folder ID

showHidden show hidden files

Returns: an object of class data.frame

Method listWSItemsByPath(): Lists workspace items given a folder path

Usage:

```
StoragehubManager$listWSItemsByPath(folderPath, showHidden = FALSE)
```

Arguments:

folderPath folder path where to list items

showHidden show hidden files

Returns: an object of class data.frame

Method searchWSItem(): Searches for a workspace item given a item path

Usage:

```
StoragehubManager$searchWSItem(  
  itemPath,  
  includeVreFolder = TRUE,  
  showHidden = FALSE  
)
```

Arguments:

itemPath path of the item
 includeVreFolder search also in VRE folder
 showHidden show hidden files

Returns: the item, NULL if nothing found

Method searchWSItemID(): Searches for a workspace item ID given a item path

Usage:

```
StoragehubManager$searchWSItemID(
    itemPath,
    includeVreFolder = TRUE,
    showHidden = FALSE
)
```

Arguments:

itemPath path of the item
 includeVreFolder search also in VRE folder
 showHidden show hidden files

Returns: the item, NULL if nothing found

Method createFolder(): Creates a folder, given a folder path, a folder name/description. By default recursive = TRUE meaning that a folder path matching nested folders will trigger all nested folders. Setting recursive = FALSE, the folder creation will work only if the folder path matches an existing folder. The hidden (default FALSE) argument can be used to set hidden folders on the workspace. Using folderID, recursive will be set to FALSE.

Usage:

```
StoragehubManager$createFolder(
    folderPath = NULL,
    folderID = NULL,
    name,
    description = "",
    hidden = FALSE,
    recursive = TRUE
)
```

Arguments:

folderPath parent folder path where to create the folder
 folderID parent folder ID where to create the folder
 name name of the folder
 description description of the folder
 hidden hidden, default is FALSE
 recursive recursive, default is TRUE

Returns: the ID of the created folder

Method uploadFile(): Uploads a file to a folder (given a folder path). The argument description can be used to further describe the file to upload. The argument archive (default = FALSE) indicates the type of item (FILE or ARCHIVE) to be uploaded.

Usage:

```
StoragehubManager$uploadFile(  
  folderPath = NULL,  
  folderID = NULL,  
  file,  
  description = basename(file),  
  archive = FALSE  
)
```

Arguments:

folderPath folder path where to upload the file

folderID folder ID where to upload the file

file file to upload

description file description, default would be the file basename

archive archive, default is FALSE

Returns: the ID of the uploaded file

Method deleteItem(): Deletes an item given its path on the workspace

Usage:

```
StoragehubManager$deleteItem(itemPath, force = FALSE)
```

Arguments:

itemPath item path

force whether to force deletion, default is FALSE

Returns: TRUE if deleted, FALSE otherwise

Method shareItem(): Shares an item with users

Usage:

```
StoragehubManager$shareItem(itemPath, defaultAccessType, users)
```

Arguments:

itemPath item path

defaultAccessType access type to use for sharing, among 'WRITE_ALL', 'WRITE_OWNER', 'READ_ONLY', 'ADMINISTRATOR'

users one or more user names with whom the item has to be shared

Returns: TRUE if shared, FALSE otherwise

Method unshareItem(): unshare an item

Usage:

```
StoragehubManager$unshareItem(itemPath, users)
```

Arguments:

itemPath item path

users users

Returns: TRUE if unshared, FALSE otherwise

Method downloadItem(): Download item

Usage:

StoragehubManager\$downloadItem(item = NULL, wd = NULL)

Arguments:

item item

wd working directory where to download the item

Method downloadItemByPath(): Download item by path

Usage:

StoragehubManager\$downloadItemByPath(path, wd = NULL)

Arguments:

path path

wd working directory where to download the item

Method getPublicFileLinkByID(): Get public file link by ID

Usage:

StoragehubManager\$getPublicFileLinkByID(pathID)

Arguments:

pathID file item ID

Returns: the public file URL

Method getPublicFileLink(): Get public file link

Usage:

StoragehubManager\$getPublicFileLink(path)

Arguments:

path file path

Returns: the public file URL

Method clone(): The objects of this class are cloneable with this method.

Usage:

StoragehubManager\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Main user class to be used with **d4storagehub4R**

Deprecated

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  manager <- StoragehubManager$new(
    token = "<your token>",
    logger = "DEBUG"
  )

## End(Not run)
```

Index

- * **logger**
 - d4storagehub4RLogger, [2](#)
- * **manager**
 - StoragehubManager, [4](#)
- * **storagehub**
 - StoragehubManager, [4](#)
- d4storagehub4R, [2](#)
- d4storagehub4R-package
 - (d4storagehub4R), [2](#)
- d4storagehub4R::d4storagehub4RLogger,
[4](#)
- d4storagehub4RLogger, [2](#)
- R6Class, [2](#), [4](#)
- StoragehubManager, [4](#), [5](#)