

How to create a form in RunCms

1. Outline of the class xoopsform
2. Method of construction of the form
3. Elements of the form
4. Concrete example

1. ***Outline of the class xoopsform***

- ❖ RunCms root path/
 - class/ xoopsformloader.php
 - class/xoopsform/
 - form.php - formbutton.php - formcheckbox.php - formdatetime.php -
formdhtmltextarea.js.php - formdhtmltextarea.php - formelement.php -
formelementtray.php - formfile.php - formhidden.php - formlabel.php -
formpassword.php – formradio.php – formradioyn.php – formselect.php –
formselectcountry.php – formselectgroup.php – formselectlang.php –
formselectmatchoption.php – formselectmodule.php –
formselecttheme.php – formselecttimezone.php – formselectuser.php –
formtext.php – formtextarea.php – formtextdateselect.php –
simpleform.php – tableform.php – themeform.php
 - include/ calendar.js – calendarjs.php – calendarblue.css
 - language/english
 calendar.php

2. Method of construction of the form

// load form
`Include_once XOOPS_ROOT_PATH."/class/xoopsformloader.php";`

// create the form
☒ 3 types of forms can be built

Simple :

```
$my_form = new XoopsSimpleForm($title,$name,$action,$method);
```

Table :

```
$my_form = new XoopsTableForm($title,$name,$action,$method);
```

With Theme :

```
$my_form = new XoopsThemeForm($title,$name,$action,$method);
```

\$title - it is the title which you want for your form
\$name - it is the name which you want for your form
\$action - it is the action which you want for your form
\$method – you can omit, default is POST

EXAMPLE :

```
$my_form = new XoopsThemeForm("My form", "MyName", "register.php", $method);
```

// create the elements of the form

```
$field = new XoopsFormText(_MI_TITLE, "name", $size, $maxlenght, $value);
```

The elements of the forms will be detailed in the following chapter

// add a option for the elements “checkbox”, “radio” and “select”

The elements “checkbox”, “radio” and “select” must be supplemented with their options

☒ 2 methods are possible

Insertion in only once using an associative table - array ()

EXAMPLE :

```
$field = new XoopsFormCheckbox($caption,$name);
$option = array ("value1"=>"name1", "value2"=>"name2", "value3"=>"name3");
$field->addOptionArray($option);
```

insertion of the options one to one

EXAMPLE :

```
$field = new XoopsFormCheckbox($caption,$name);
$field->addOptionArray("value1","Name1");
$field->addOptionArray("value2","Name2");
```

// add elements in form

```
$my_form->addElement($field, true);
```

// declare the required fields

```
$required = array("field1", "field2", "field3");
$my_form->setRequired($required);
```

// display the form

```
$my_form->display();
```

3. Elements of form.

Hidden field

XoopsFormHidden (\$name, \$value)

Parameter	Type	Function	Default value
\$name	string	name of the variable	
\$value	string	default value	

Label field

- do not return any value
- allows you to insert an element or a text in a form

XoopsFormLabel (\$caption="", \$value="")

Parameter	Type	Function	Default value
\$caption	string	field name (displayed on the left)	
\$value	string	value to display	

Button

XoopsFormButton (\$caption, \$name, \$value="", \$type="button")

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	mixed	value to display on the button	
\$type	string	type of button (button, submit, reset)	button

Text field

XoopsFormText (\$caption, \$name, \$size, \$maxlength, \$value="")

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$size	int	size of the field	
\$maxlength	int	max length of the chain	
\$value	string	default value	

Text Area field

XoopsFormTextArea (\$caption, \$name, \$value="", \$rows=5, \$cols=50)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	mixed	default value	
\$rows	int	number of lines	5
\$cols	int	number of columns	50

Text Area field with formatting options

XoopsFormDhtmlTextArea (\$caption, \$name, \$value="", \$rows=5, \$cols=50, \$hiddentext = "xoopsHiddenText")

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	mixed	default value	
\$rows	int	number of lines	5
\$cols	int	number of columns	50
\$hiddentext	string	this value can be changed if you use several text area	

Password

XoopsFormPassword (\$caption, \$name, \$size, \$maxlength, \$value="")

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$size	int	size of the field	
\$maxlength	int	max length of password	
\$value	string	default value	

Radio button yes/no

return 1 for yes, 0 for no

XoopsFormRadioYN (\$caption, \$name, \$value=null, \$yes=_YES, \$no=_NO)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	int	default value 1 for yes, 0 for no	null
\$yes	string	text for yes	Yes
\$no	string	text for no	No

Radio button opt 1 opt 2 opt 3

return the value associated with the option

XoopsFormRadio (\$caption, \$name, \$value=null)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	int	preselected value (1,2,3 ...)	null

Check box check 1 check 2 check 3

return a table of the selected values

XoopsFormCheckBox (\$caption, \$name, \$value=null)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	mixed	preselected value(s)	null

Selectselection 1 

- return the value associated with the option (table if multiple selection)

XoopsFormSelect (\$caption, \$name, \$value=null, \$size=1, \$multiple=false)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	mixed	preselected value(s) or array	null
\$size	int	a number of displayed lines	1
\$multiple	bool	authorized multiple selection	false

File[Parcourir...](#)

- return the file name (with the path)

XoopsFormFile (\$caption, \$name, \$maxfilesize)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$maxfilesize	int	max size	

Timezone

(GMT+7:00) Bangkok, Hanoi, Djakarta



- return a -12 to +12 value

XoopsFormSelectTimezone (\$caption, \$name, \$value = null, \$size=1)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	int	default value	null
\$size	int	a number of displayed lines	1

Date

- return a date in the form yyyy-mm-dd

XoopsFormTextDateSelect (\$caption, \$name, \$size=15, \$value = 0)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$size	int	field size	15
\$value	int	default value	null = 01/01/1970



Check the file calendarjs.php
in line 36 to correct if needed
{ echo ' new Date(\"'.jstime.'\"'); }
in { echo ' new Date('.jstime.');

To also correct
language/french/calendar.php by
replacing the ´ by é, etc.....

Date + Hour 2004-07-27 ... 11:50

- return a date + hour in a table

XoopsFormDateTime (\$caption, \$name, \$size=15, \$value = 0)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$size	int	field size	15
\$value	timestamp	default value	Time ()

Select a user group webmaster

- return a id of group (f.ex : 1 for webmaster...) table if multiple selection.

XoopsFormSelectGroup (\$caption, \$name, \$include_anon=false, \$value =null, \$size=1, \$multiple=false)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$include_anon	string	to include the anonymous group	false
\$value	mixed	default value: id of group or array	null
\$size	int	a number of displayed lines	1
\$multiple	bool	authorized multiple selections	false

Select a user essebe

- return a id of user (0 for anonymous) table if multiple selection.

XoopsFormSelectUser (\$caption, \$name, \$include_anon=false, \$value =null, \$size=1, \$multiple=false)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$include_anon	string	to include anonymous user	false
\$value	mixed	default value: id of user or array	null
\$size	int	a number of displayed lines	1
\$multiple	bool	authorized multiple selections	false

Select a language english

- selection starting from the Xoops_ROOT_PATH."/language/" repertory
 return a string containing the selected language (english, french,...)

XoopsFormSelectLang (\$caption, \$name, \$value =null, \$size=1)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	string	default value	null
\$size	int	a number of displayed lines	1

Select a country

return a string containing the country code (FR, EN, BE, ZW, ...)

XoopsFormSelectCountry (\$caption, \$name, \$value =null, \$size=1)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	string	default value: country code	null
\$size	int	a number of displayed lines	1

Select a options of research

Starts with

return 0 (Starts with), 1 (Ends with), 2 (Matches), 3(Contains), values XOOPS_MATCH_* defined in common.php

XoopsFormSelectMatchOption (\$caption, \$name, \$value =null, \$size=1)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	string	default value: country code	null
\$size	int	a number of displayed lines	1

Select a theme

runcms

return a string with the theme name (e-xoops, ipb_blue,.....)

XoopsFormSelectTheme (\$caption, \$name, \$value =null, \$size=1)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$value	string	default value	null
\$size	int	a number of displayed lines	1

Select a module

Contact

return a id of module (0=All, 1, 2, 5,...) table if multiple selection

XoopsFormSelectModule(\$caption, \$name, \$include_system=false, \$value=0, \$size=1, \$multiple=false)

Parameter	Type	Function	Default value
\$caption	string	field name	
\$name	string	name of the variable	
\$include_system	bool	include system	false
\$value	mixed	id of module or array	null
\$size	int	a number of displayed lines	1
\$multiple	bool	authorized multiple selections	false

Element tray

Name of Element	Champ <input type="text"/>
	Mot de passe <input type="password"/>

allows you to build a group of fields
XoopsFormElementTray(\$caption, \$delimiter)

Parameter	Type	Function	Default value
\$caption	string	element name	
\$delimiter	string	delimiter	

Example :

```
$field1 = new XoopsFormText("Field1","field1",50,49,"");
$field2 = new XoopsFormPassword("Mot de passe","pass",10,6,"");

$element_tray = new XoopsFormElementTray("Name of Element", "<br />");
$element_tray->addElement($field1);
$element_tray->addElement($field2);

$my_form->addElement($element_tray);
```

4. Concrete example

```
<?php

include("../mainfile.php");
include(XOOPS_ROOT_PATH."/header.php");
include(XOOPS_ROOT_PATH."/class/xoopsformloader.php");

global $xoopsTheme, $xoopsconfig,$HTTP_POST_VARS,$HTTP_GET_VARS;
$xoopsOption['show_rblock']=0;

opentable($width='100%');

$action = "form.php";
$title = "Test";
$name = "uname";
$my_form = new XoopsThemeForm($title,$name,$action,$method="POST");

#####
//hidden field
//XoopsFormHidden($name,$value="");
$hidden = new XoopsFormHidden("hidden","Value of hidden fields");

#####
//Label
//The Label field does not turn over any value
//XoopsFormLabel($caption,$value="");
$label = new XoopsFormLabel("", "<hr>");

#####
//Text field
//XoopsFormText($caption,$name,$size,$maxlength,$value="");
$fields = new XoopsFormText("Field","field",50,49,"");

#####
//Text zone
//XoopsFormTextArea($caption,$name,$value="",$rows,$cols);
$zonetext = new XoopsFormTextArea("Text Zone", "zonetext", "", 5, 50);

#####
//Text zone with working (icons,url,mail,quote, etc..)
//XoopsFormDhtmlTextArea($caption,$name,$value="",$rows,$cols,$hiddentext="");
$textenforme = new XoopsFormDhtmlTextArea("Working text zone", "textenforme", "", 5, 50, $hiddentext="xoopsHiddenText");

#####
//Password
//XoopsFormPassword($caption,$name,$size,$maxlength,$value="");
$pass = new XoopsFormPassword("Password","pass",10,6,"");

#####
//yes - no field
//XoopsFormRadioYN($caption,$name,$value= "1 for yes 0 for no",$yes,$no);

$yesno = new XoopsFormRadioYN("Yes,No","yesno",$value=null," I say Yes","I say No");

#####
//check box
//XoopsFormCheckBox($caption,$name,$value ="preselected value");
$checkbox = new XoopsFormCheckBox("Checkboxes","check",null);
$options = array("Option1","Option2","Option3");
$checkbox->addOptionArray($options);
```

```

#####
//Select
//turn over a table if selection multiple
//XoopsFormSelect($caption,$name,$value ="preselected value",$size=a number of posted lines,$multiple=False/true);
$select = new XoopsFormSelect("Selection","select",$value = null,1,$multiple=False);
$options = array("Option1","Option2","Option3");
$select->addOptionArray($options);

#####
//Button submit or reset
//XoopsFormButton($caption,$name,$value="", $type (button,submit,reset));
$submit = new XoopsFormButton("Submit","send","Go",submit);

$my_form->addElement($hidden, true);
$my_form->addElement($label, true);
$my_form->addElement($fields, true);
$my_form->addElement($zonetext);
$my_form->addElement($textenforme, true);
$my_form->addElement($pass, true);
$my_form->addElement($yesno, true);
$my_form->addElement($checkbox, true);
$my_form->addElement($select, true);
$my_form->addElement($submit, true);

$reqired = array("fields","pass","zonetext");
$my_form->setRequired($reqired);

$my_form->display();

closetable();
include(XOOPS_ROOT_PATH."/footer.php");
?>

```