

Package ‘OAtools’

March 2, 2026

Title Analysis of OpenArray PCR Data

Version 0.99.10

Description Provides a suite of R functions to analyze gene expression experiments on the OpenArray real-time PCR platform. OAtools fits logistic regressions to fluorescence curves to distinguish between real amplification and false positives. OAtools supports data import, analysis, and visualization through plots and a dynamic HTML report.

License GPL (>= 3)

LazyData FALSE

Depends R (>= 4.6)

Imports basilisk (>= 1.20.0), Biobase (>= 2.70.0), dplyr (>= 1.1.4), DT (>= 0.34.0), ggplot2 (>= 3.5.2), janitor (>= 2.2.1), methods (>= 4.5.2), plotly (>= 4.11.0), purrr (>= 1.2.0), ReadqPCR (>= 1.56.0), readxl (>= 1.4.5), reticulate (>= 1.43.0), rlang (>= 1.1.6), rmarkdown (>= 2.29), S4Vectors (>= 0.48.0), shiny (>= 1.13.0), SummarizedExperiment (>= 1.40.0), tibble (>= 3.3.0), tidyr (>= 1.3.1), writexl (>= 1.5.4)

Suggests testthat (>= 3.0.0), knitr, kableExtra (>= 1.4.0), NormqPCR (>= 1.56.0), BiocManager (>= 1.30.27)

biocViews qPCR, GeneExpression, DataImport, Regression

BugReports <https://github.com/uwvirology-ngs/OAtools/issues>

URL <https://github.com/uwvirology-ngs/OAtools>

BiocType Software

Config/testthat/edition 3

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Encoding UTF-8

VignetteBuilder knitr

StagedInstall no

git_url <https://git.bioconductor.org/packages/OAtools>

git_branch devel

git_last_commit f88ada9

git_last_commit_date 2026-02-28

Repository Bioconductor 3.23

Date/Publication 2026-03-01

Author Aidan Shea [aut, cre] (ORCID: <<https://orcid.org/0009-0001-9256-7439>>)

Maintainer Aidan Shea <aidantshea@gmail.com>

Contents

.buildServer	3
.buildUI	3
.runFitCurve	4
.serverDataImport	4
.serverFitCurves	5
.serverGraphics	5
.serverReporting	6
.uiDataImport	6
.uiFitCurves	7
.uiGraphics	7
.uiReporting	8
buildApp	8
computeModels	9
determinePCRResults	10
example_se	11
excelToSE	12
generateReport	12
oa_gene_expression_1	13
oa_gene_expression_2	14
plotCrt	14
plotModel	15
plotOverview	16
plotQC	16
seToQPCRBatch	17
target_threshold_key	18

Index	19
--------------	-----------

<i>.buildServer</i>	<i>Web Server</i>
---------------------	-------------------

Description

Helper method to `buildApp()` responsible for construction of the Shiny web server

Usage

```
.buildServer(input, output, session)
```

Arguments

<code>input</code>	reactive values from UI widgets
<code>output</code>	render functions for results
<code>session</code>	environment for user session

Value

A Shiny web server

<i>.buildUI</i>	<i>User Interface</i>
-----------------	-----------------------

Description

Helper method to `buildApp()` responsible for construction of the graphical user interface

Usage

```
.buildUI()
```

Value

A Shiny UI

.runFitCurve	<i>Run the fit_curve() function</i>
--------------	-------------------------------------

Description

A thin R wrapper for the python3 function fit_curve(), which attempts to optimize 5-parameter logistic regressions to PCR fluorescence curves.

Usage

```
.runFitCurve(pcr_data, linear_threshold)
```

Arguments

pcr_data	A data.frame with the following required columns: cycle PCR cycle number fluo observed fluorescence
linear_threshold	numeric value specifying the minimum overall change-in-fluorescence over the PCR reaction required for the optimizer to attempt fitting a logistic model

Value

The model as a nested list

.serverDataImport	<i>Data Import Server</i>
-------------------	---------------------------

Description

Data Import Server

Usage

```
.serverDataImport(id)
```

Arguments

id	identifier unique to Data Import page
----	---------------------------------------

Value

The Data Import server component

.serverFitCurves	<i>Curve Fitting Server</i>
------------------	-----------------------------

Description

Curve Fitting Server

Usage

```
.serverFitCurves(id, se)
```

Arguments

id	identifier unique to Fit Curves page
se	SummarizedExperiment with OpenArray assay data

Value

The Fit Curves server component

.serverGraphics	<i>Graphics Server</i>
-----------------	------------------------

Description

Graphics Server

Usage

```
.serverGraphics(id, se)
```

Arguments

id	identifier unique to Graphics page
se	SummarizedExperiment with OpenArray assay data

Value

The Graphics server component

.serverReporting	<i>Reporting Server</i>
------------------	-------------------------

Description

Reporting Server

Usage

.serverReporting(id, se_fit)

Arguments

- | | |
|--------|--|
| id | identifier unique to Reporting page |
| se_fit | SummarizedExperiment with OpenArray assay data |

Value

The Reporting server component

.uiDataImport	<i>Data Import UI</i>
---------------	-----------------------

Description

Data Import UI

Usage

.uiDataImport(id)

Arguments

- | | |
|----|---------------------------------------|
| id | identifier unique to Data Import page |
|----|---------------------------------------|

Value

The Data Import page

.uiFitCurves	<i>Curve Fitting UI</i>
--------------	-------------------------

Description

Curve Fitting UI

Usage

.uiFitCurves(id)

Arguments

id identifier unique to Fit Curves page

Value

The Fit Curves page

.uiGraphics	<i>Graphics UI</i>
-------------	--------------------

Description

Graphics UI

Usage

.uiGraphics(id)

Arguments

id identifier unique to Graphics page

Value

The Graphics page

`.uiReporting`*Reporting UI*

Description

Reporting UI

Usage

```
.uiReporting(id)
```

Arguments

`id` identifier unique to Reporting page

Value

The Reporting page

`buildApp`*A Shiny App for OAtools*

Description

Builds a Shiny application for interactively running OAtools

Usage

```
buildApp()
```

Value

A Shiny web application

Examples

```
app <- buildApp()
```

computeModels

*Optimize SPL models to OpenArray PCR data and save as metadata***Description**

Computes 5-parameter logistic models optimized to PCR data contained in the specified assay matrix, either `fluo_normalized` or `fluo_reporter`. The former refers to the base-line adjusted, normalized fluorescence from the Amplification Data tab of the original Excel output. The latter refers to the multicomponent fluorescence from the Multicomponent Data tab.

The expected input for this function is a `SummarizedExperiment` object containing OpenArray PCR data, which can be generated by calling the `excelToSE()` function of the package on the raw Excel output from QuantStudio software.

Usage

```
computeModels(se, assay_name, linear_threshold = 400)
```

Arguments

<code>se</code>	OpenArray PCR data as a <code>SummarizedExperiment</code> object
<code>assay_name</code>	character value specifying the assay matrix from which to load PCR data for curve-fitting, either <code>fluo_normalized</code> or <code>fluo_reporter</code>
<code>linear_threshold</code>	numeric value specifying the minimum overall change-in-fluorescence over the PCR reaction required for the optimizer to attempt fitting a logistic model

Details

Under the hood, this function invokes `.runFitCurve()`, a thin wrapper which calls python3 code to fit models with `scipy.optimize`, on each PCR reaction of the OpenArray plate separately. The computed models are added to the `SummarizedExperiment` container in metadata, named as `assay_name + _models`. For example, `fluo_normalized_models` would be created in the experiment metadata if `computeModels(assay_name = "fluo_normalized")` is called.

Value

OpenArray PCR data as a `SummarizedExperiment` object with information from the computed model stored as metadata.

Examples

```
path <- system.file(
  "extdata",
  "oa_gene_expression_1.xlsx",
  package = "OAtools"
)
```

```
se <- excelToSE(excel_path = path) |>
  computeModels(assay_name = "fluo_normalized") |>
  computeModels(assay_name = "fluo_reporter")
```

determinePCRResults	<i>Determine PCR results from features of multicomponent fluorescence curves</i>
---------------------	--

Description

Assigns positive or negative PCR results to every PCR reaction depending on the equation of the model curve optimized to the fluorescence curve. In particular, the reporter dye fluorescence without normalization is used to distinguish between real amplification and false positives.

Usage

```
determinePCRResults(se, key_path)
```

Arguments

se	a SummarizedExperiment object containing OpenArray qPCR Data
key_path	file path to the target-threshold key

Details

The target-threshold key is an Excel file which stores threshold values used to separate PCR curves. These thresholds are defined across metrics such as cycle threshold, overall change-in-fluorescence, and slope of the fluorescence curve during the exponential phase. The thresholds are separately defined for each gene to accommodate inherent differences in assays.

Value

a SummarizedExperiment

Examples

```
data(example_se)

key_path = system.file(
  "extdata",
  "target_threshold_key.xlsx",
  package = "OAtools"
)

se <- example_se |>
  determinePCRResults(key_path = key_path)
```

example_se*Example OpenArray Gene Expression Data Contained in a SummarizedExperiment*

Description

A sample of OpenArray gene expression data from respiratory tract microbiota profiling experiments conducted at the UW Virology research lab on human nasal swabs. This file (.rda) stores the PCR data in a SummarizedExperiment container and is intended for use with package examples and unit testing.

Format

a SummarizedExperiment object with the following:

colData information associated with each PCR well

rowData cycle numbers

assays matrices of fluorescence values by PCR well and cycle

Details

Load this object into the environment with: `data(example_se)`

Source

This object contains PCR data imported from the initial Excel QuantStudio output. Logistic and linear models were fit to the PCR data and stored as metadata.

The object can be reproduced from the package example data by running the following commands in the R console:

```
path <- system.file(
  "extdata",
  "oa_gene_expression_1.xlsx",
  package = "OAtools"
)

se <- excelToSE(excel_path = path) |>
  computeModels(assay_name = "fluo_normalized") |>
  computeModels(assay_name = "fluo_reporter")
```

excelToSE

Convert OpenArray data from Excel to a Summarized Experiment

Description

Transforms raw gene expression run data exported from the OpenArray QuantStudio 12K Flex Software from .xlsx format into an instance of the SummarizedExperiment class from Bioconductor.

Usage

```
excelToSE(excel_path, header_rows = 17, skip = 19)
```

Arguments

excel_path	file path to the Excel document containing the PCR data
header_rows	number of rows of run metadata to read in from the header
skip	number of rows to skip when reading fluorescence data or results

Value

OpenArray PCR data as a SummarizedExperiment object

Examples

```
path = system.file(
  "extdata",
  "oa_gene_expression_1.xlsx",
  package = "OAtools"
)

se <- excelToSE(excel_path = path)
```

generateReport

Generate a PCR Report

Description

Knits an HTML report summarizing the OpenArray experiment and saves to the specified directory.

Usage

```
generateReport(se, path = tempdir(), model_results = FALSE)
```

Arguments

se	a SummarizedExperiment containing OpenArray qPCR data
path	intended outfile path, defaults to a temporary directory
model_results	boolean value indicating whether to include the results column, which is created when deriving results using the curve-fitting method

Value

An HTML Report summarizing the OpenArray experiment

Examples

```
data(example_se)
generateReport(se = example_se)
```

oa_gene_expression_1	<i>Example Raw OpenArray Gene Expression Data</i>
----------------------	---

Description

The first of two Excel files storing run data from separate OpenArray gene expression experiments. The context behind the experiment was respiratory tract microbiota profiling on human nasopharyngeal swabs from patients experiencing respiratory syndromes.

Format

An Excel file (.xlsx) with three tabs:

Amplification Data normalized fluorescence by cycle number

Multicomponent Data spectral contribution of the reporter dye by cycle number

Results PCR results, PCR well metadata, and QC metrics

Details

Access this file with: `system.file("extdata", "oa_gene_expression_1.xlsx", package = "OATools")`

Source

This file was exported from QuantStudio 12K Flex Software after a gene expression run, then filtered down to include 12 samples and 4 genes for file size concerns.

oa_gene_expression_2	<i>Example Raw OpenArray Gene Expression Data</i>
----------------------	---

Description

The second of two Excel files storing run data from separate OpenArray gene expression experiments. The context behind the experiment was respiratory tract microbiota profiling on human nasopharyngeal swabs on patients experiencing respiratory syndromes.

Format

An Excel file (.xlsx) with three tabs:

Amplification Data normalized fluorescence by cycle number

Multicomponent Data spectral contribution of the reporter dye by cycle number

Results PCR results, sample metadata, and QC metrics

Details

Access this file with: `system.file("extdata", "oa_gene_expression_2.xlsx", package = "OAtools")`

Source

This file was exported from QuantStudio 12K Flex Software after a gene expression run, then filtered down to include 12 samples and 4 genes for file size concerns.

plotCrt	<i>Plot Relative Cycle Threshold Values by Gene</i>
---------	---

Description

Generates a box and whisker plot visualizing the distribution of Crt values measured on an OpenArray plate by Gene.

Usage

```
plotCrt(se)
```

Arguments

se a SummarizedExperiment object containing OpenArray qPCR data

Value

a ggplot2 figure

Examples

```
data(example_se)

plotCrt(example_se)
```

plotModel

Plot Fluorescence Values Predicted by Model

Description

Juxtaposes the fluorescence values predicted by the model optimized to the measured fluorescence vs. cycle data for a particular well.

Usage

```
plotModel(
  se,
  well_id,
  assay_name,
  include_mdpt_tangent = FALSE,
  include_coldata_annotation = FALSE
)
```

Arguments

se	a SummarizedExperiment object containing OpenArray qPCR data
well_id	a character representing the name of the well to plot as listed in the assay matrix
assay_name	name for the assay matrix from which to pull observed fluorescence values, either fluo_reporter or fluo_normalized
include_mdpt_tangent	boolean determines whether to annotate the midpoint of the reaction and draw a tangent line to the model curve at that point
include_coldata_annotation	boolean determines whether to annotate the coldata onto the top left of the plot.

Value

a ggplot2 figure

Examples

```
data(example_se)

plotModel(
  example_se,
  well_id = "well_2665",
  assay_name = "fluo_reporter",
```

```

      include_mdpt_tangent = TRUE,
      include_coldata_annotation = TRUE
    )

```

plotOverview

Plot Amplification Status by Sample and Gene

Description

Generates an overview graphic summarizing qPCR results for each combination of sample and gene on an OpenArray experiment.

Usage

```
plotOverview(se)
```

Arguments

se a SummarizedExperiment object containing OpenArray qPCR data

Value

a ggplot2 figure

Examples

```

data(example_se)

plotOverview(example_se)

```

plotQC

Plot a 3D Quality Control Graphic from a SummarizedExperiment

Description

Generates a 3-dimensional quality control plot comparing the amplification status to the crt, Cq conf, and amplification score metrics output by QuantStudio 12K Flex Software.

Usage

```
plotQC(se)
```

Arguments

se a SummarizedExperiment object containing OpenArray qPCR data

Value

a plotly figure

Examples

```
data(example_se)
plotQC(example_se)
```

seToQPCRBatch	<i>Convert to qPCRBatch Object</i>
---------------	------------------------------------

Description

Transforms OpenArray run data contained within the SummarizedExperiment container into a qPCRBatch object. This conversion allows for convenient gene expression analyses with the NormqPCR package.

Usage

```
seToQPCRBatch(se)
```

Arguments

se	A SummarizedExperiment object with OpenArray run data
----	---

Value

a qPCRBatch object

Examples

```
path = system.file(
  "extdata",
  "oa_gene_expression_1.xlsx",
  package = "OAtools"
)

se <- excelToSE(excel_path = path)

qpcr <- seToQPCRBatch(se)
```

target_threshold_key	<i>Target Threshold Key</i>
----------------------	-----------------------------

Description

This Excel file (.xlsx) contains a table associating each assay target contained in the example gene expression run data with thresholds values. This key is optionally used to aid in concurrently interpreting data including numerous targets with dissimilar behaviors.

Format

An Excel sheet (.xlsx) with four columns:

target the target assay ID

slope_threshold minimum acceptable slope in the exponential phase for a positive result

delta_threshold minimum acceptable overall change in fluorescence for a positive result

crt_threshold maximum acceptable crt for a positive result

Details

The example key is stored in the inst/extdata/ directory of the package. Access this file with:
`system.file("extdata", "target_threshold_key.xlsx", package = "OAtools").`

Source

Written manually for use with resulting functions.

Index

- * **data**
 - example_se, [11](#)
 - oa_gene_expression_1, [13](#)
 - oa_gene_expression_2, [14](#)
 - target_threshold_key, [18](#)
- .buildServer, [3](#)
- .buildUI, [3](#)
- .runFitCurve, [4](#)
- .serverDataImport, [4](#)
- .serverFitCurves, [5](#)
- .serverGraphics, [5](#)
- .serverReporting, [6](#)
- .uiDataImport, [6](#)
- .uiFitCurves, [7](#)
- .uiGraphics, [7](#)
- .uiReporting, [8](#)
- buildApp, [8](#)
- computeModels, [9](#)
- determinePCRResults, [10](#)
- example_se, [11](#)
- excelToSE, [12](#)
- generateReport, [12](#)
- oa_gene_expression_1, [13](#)
- oa_gene_expression_2, [14](#)
- plotCrt, [14](#)
- plotModel, [15](#)
- plotOverview, [16](#)
- plotQC, [16](#)
- seToQPCRBatch, [17](#)
- target_threshold_key, [18](#)