

Package ‘faahKO’

November 13, 2025

Version 1.51.0

Date 2025-04-23

Title Saghatelian et al. (2004) FAAH knockout LC/MS data

Author Colin A. Smith <csmith@scripps.edu>

Maintainer Steffen Neumann <sneumann@ipb-halle.de>

Depends R (>= 3.5)

Imports xcms (>= 4.5.4)

Suggests MSnbase (>= 2.33.3)

ZipData no

Description Positive ionization mode data in NetCDF file format.
Centroided subset from 200-600 m/z and 2500-4500 seconds. Data
originally reported in ``Assignment of Endogenous Substrates to Enzymes
by Global Metabolite Profiling" Biochemistry; 2004; 43(45). Also
includes detected peaks in an xcmsSet.

biocViews ExperimentData, MassSpectrometryData

License LGPL

URL <http://dx.doi.org/10.1021/bi0480335>

git_url <https://git.bioconductor.org/packages/faahKO>

git_branch devel

git_last_commit 620ca15

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2025-11-13

Contents

faahko	2
faahko3	3

Index	6
--------------	----------

faahko

*FAAH knockout LC/MS data xcmsSet***Description**

xcmsSet object containing quantitated LC/MS peaks from the spinal cords of 6 wild-type and 6 FAAH knockout mice. The data is a subset of the original data from 200-600 m/z and 2500-4500 seconds. It was collected in positive ionization mode.

Usage

```
data(faahko)
```

Format

The format is:

```
Formal class 'xcmsSet' [package "xcms"] with 8 slots
..@ peaks      : num [1:4776, 1:11] 200 201 205 206 207 ...
..@ groups     : logi[0 , 0 ]
..@ groupidx   : list()
..@ sampnames  : chr [1:12] "ko15" "ko16" "ko18" "ko19" ...
..@ sampclass  : Factor w/ 2 levels "K0","WT": 1 1 1 1 1 1 2 2 2 2 ...
..@ rt         :List of 2
.. ..$ raw     :List of 12
.. ..$ corrected:List of 12
..@ filepaths  : chr [1:12] ...
..@ profinfo   :List of 2
.. ..$ method  : chr "bin"
.. ..$ step    : num 0.1
```

Details

The corresponding raw NetCDF files are located in the cdf subdirectory of this package.

Source

<http://dx.doi.org/10.1021/bi0480335>

References

Saghatelian A, Trauger SA, Want EJ, Hawkins EG, Siuzdak G, Cravatt BF. Assignment of endogenous substrates to enzymes by global metabolite profiling. *Biochemistry*. 2004 Nov 16;43(45):14332-9.

See Also

[xcmsSet](#), [xcmsRaw](#)

Examples

```
## The directory with the NetCDF LC/MS files
cdfpath <- file.path(find.package("faahKO"), "cdf")
cdfpath
list.files(cdfpath, recursive = TRUE)

if (require(xcms)) {

## xcmsSet Summary
show(faahko)

## Access raw data file
ko15 <- xcmsRaw(filepaths(faahko)[1], profmethod = "bin", profstep = 0.1)
ko15

}
```

faahko3

FAAH knockout LC/MS data XCMSnExp

Description

XCMSnExp object containing quantitated LC/MS peaks from the spinal cords of 6 wild-type and 6 FAAH knockout mice. The data is a subset of the original data from 200-600 m/z and 2500-4500 seconds. It was collected in positive ionization mode.

Usage

```
data(faahko3)
```

Format

The format is:

```
MSn experiment data ("XCMSnExp")
Object size in memory: 4.59 Mb
- - - Spectra data - - -
  MS level(s): 1
  Number of spectra: 15336
  MSn retention times: 41:32 - 75:14 minutes
- - - Processing information - - -
Data loaded [Tue Mar 24 13:28:38 2020]
  MSnbase version: 2.13.2
- - - Meta data - - -
phenoData
  rowNames: 1 2 ... 12 (12 total)
  varLabels: sample_name sample_group
  varMetadata: labelDescription
```

```

Loaded from:
  [1] ko15.CDF... [12] wt22.CDF
  Use 'fileNames(.)' to see all files.
protocolData: none
featureData
  featureNames: F01.S0001 F01.S0002 ... F12.S1278 (15336 total)
  fvarLabels: fileIdx spIdx ... spectrum (33 total)
  fvarMetadata: labelDescription
experimentData: use 'experimentData(object)'
- - - xcms preprocessing - - -
Chromatographic peak detection:
  method: centWave
  5627 peaks identified in 12 samples.
  On average 469 chromatographic peaks per sample.
Alignment/retention time adjustment:
  method: peak groups
Correspondence:
  method: chromatographic peak density
  206 features identified.
  Median mz range of features: 0.10001
  Median rt range of features: 28.965
  325 filled peaks (on average 27.08333 per sample).

```

Details

The corresponding raw NetCDF files are located in the `cdf` subdirectory of this package.

Source

<http://dx.doi.org/10.1021/bi0480335>

References

Saghatelian A, Trauger SA, Want EJ, Hawkins EG, Siuzdak G, Cravatt BF. Assignment of endogenous substrates to enzymes by global metabolite profiling. *Biochemistry*. 2004 Nov 16;43(45):14332-9.

See Also

[OnDiskMSnExp](#), [XCMSnExp](#)

Examples

```

## The directory with the NetCDF LC/MS files
cdfpath <- file.path(find.package("faahko3"), "cdf")
cdfpath
list.files(cdfpath, recursive = TRUE)

data(faahko3)

```

faahko3

5

```
## XCMSnExp Summary  
show(faahko3)
```

Index

* **datasets**

faahko, [2](#)

faahko3, [3](#)

faahK0 (faahko), [2](#)

faahko, [2](#)

faahK03 (faahko3), [3](#)

faahko3, [3](#)

OnDiskMSnExp, [4](#)

XCMSnExp, [4](#)

xcmsRaw, [2](#)

xcmsSet, [2](#)