

# Package ‘TargetScoreData’

June 19, 2025

**Title** TargetScoreData

**Version** 1.45.0

**Author** Yue Li

**Maintainer** Yue Li <yueli@cs.toronto.edu>

**Description** Precompiled and processed miRNA-overexpression fold-changes from 84 Gene Expression Omnibus (GEO) series corresponding to 6 platforms, 77 human cells or tissues, and 113 distinct miRNAs. Accompanied with the data, we also included in this package the sequence feature scores from TargetScanHuman 6.1 including the context+ score and the probabilities of conserved targeting for each miRNA-mRNA interaction. Thus, the user can use these static sequence-based scores together with user-supplied tissue/cell-specific fold-change due to miRNA overexpression to predict miRNA targets using the package TargetScore (download separately)

**biocViews** ExperimentData, RNASeqData, miRNAData

**License** GPL-2

**Suggests** TargetScore, gplots

**git\_url** <https://git.bioconductor.org/packages/TargetScoreData>

**git\_branch** devel

**git\_last\_commit** 6bd5166

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.22

**Date/Publication** 2025-06-19

## Contents

TargetScoreData-package . . . . .	2
get_miRNA_family_info . . . . .	3
get_miRNA_transfection_data . . . . .	3
get_precomputed_logFC . . . . .	4
get_precomputed_targetScores . . . . .	4
get_TargetScanHuman_contextScore . . . . .	5
get_TargetScanHuman_PCT . . . . .	5
get_validated_targets . . . . .	5

<b>Index</b>	<b>6</b>
--------------	----------

---

TargetScoreData-package

*Processed human microRNA perturbation data from GEO, and sequence information from TargetScan, and targetScore from TargetScore*

---

## Description

To automate the pipeline of calculating targetScore using [targetScore](#), we compiled, processed and generated miRNA-overexpression fold-changes from 84 Gene Expression Omnibus (GEO) series corresponding to 6 platforms, 77 human cells or tissues, and 113 distinct miRNAs. To our knowledge, this is by far the largest miRNA-perturbation data compendium. Accompanied with the data, we also included in this package the sequence feature scores from TargetScanHuman 6.1 including the context+ score and the probabilities of conserved targeting for each miRNA-mRNA interaction. Thus, the user can use these static sequence-based scores together with user-supplied tissue/cell-specific fold-change due to miRNA overexpression to predict miRNA targets using [targetScore](#).

## Details

Package: TargetScoreData  
 Type: Package  
 Version: 0.99.4  
 Date: 2013-07-13  
 License: GPL-2

get\_TargetScanHuman\_contextScore: TargetScan context score for all of the predicted sites (including conserved and nonconserved sites) downloaded from TargetScan 6 website ([http://www.targetscan.org/cgi-bin/targetscan/data\\_download.cgi?db=vert\\_61](http://www.targetscan.org/cgi-bin/targetscan/data_download.cgi?db=vert_61))

get\_TargetScanHuman\_PCT: TargetScan PCT for all of the predicted sites (including conserved and nonconserved sites) downloaded from TargetScan 6 website ([http://www.targetscan.org/cgi-bin/targetscan/data\\_download.cgi?db=vert\\_61](http://www.targetscan.org/cgi-bin/targetscan/data_download.cgi?db=vert_61))

get\_miRNA\_family\_info: Get miRNA family information obtained TargetScanHuman 6

get\_precomputed\_targetScores: Pre-calculated targetScores for 112 miRNAs using logFC and sequence scores from TargetScan context score and PCT from the RData files above.

get\_precomputed\_logFC: We combined all of the logFC data columns into a single N x M matrix for all of the N = 19177 RefSeq mRNAs (NM\_\* obtained from UCSC) and M = 286 datasets. Missing data (logFC) for some genes across studies were imputed using impute from impute.knn.

get\_miRNA\_transfection\_data: Get log fold-changes (logFC) from each study organized in a list with each item corresponding to a miRNA. Notably, some miRNAs (e.g., hsa-miR-1) appear more than once in the list corresponding to different studies.

get\_validated\_targets: Get validated targets of human miRNA obtained from mirTarBase v3.5

## Author(s)

Yue Li

Maintainer: Yue Li <yueli@cs.toronto.edu>

## References

miRTarBase: a database curates experimentally validated microRNA-target interactions. (2011). miRTarBase: a database curates experimentally validated microRNA-target interactions., 39(Database issue), D163-9. doi:10.1093/nar/gkq1107

Friedman, R. C., Farh, K. K.-H., Burge, C. B., & Bartel, D. P. (2009). Most mammalian mRNAs are conserved targets of microRNAs. *Genome Research*, 19(1), 92-105. doi:10.1101/gr.082701.108

Garcia, D. M., Baek, D., Shin, C., Bell, G. W., Grimson, A., & Bartel, D. P. (2011). Weak seed-pairing stability and high target-site abundance decrease the proficiency of lsy-6 and other microRNAs. *Nature structural & molecular biology*, 18(10), 1139-1146. doi:10.1038/nsmb.2115

Please follow the GEO series number to find the references for each microRNA-transfection dataset.

## See Also

[get\\_TargetScanHuman\\_contextScore](#), [get\\_TargetScanHuman\\_PCT](#), [get\\_validated\\_targets](#), [get\\_miRNA\\_family\\_info](#), [get\\_precomputed\\_targetScores](#), [get\\_precomputed\\_logFC](#), [get\\_miRNA\\_transfection\\_data](#)

## Examples

```
ls("package:TargetScoreData")
```

---

```
get_miRNA_family_info  MicroRNA family information
```

---

## Description

Get human miRNA family information obtained from TargetScanHuman 6 website

## Usage

```
get_miRNA_family_info(datapath = system.file("extdata/miR_Family_Info.txt", package = "TargetScoreData"))
```

## Arguments

datapath	data path
----------	-----------

---

```
get_miRNA_transfection_data
  get_miRNA_transfection_data
```

---

## Description

Get log fold-changes (logFC) from each study organized in a list with each item corresponding to a miRNA. Notably, some miRNAs (e.g., hsa-miR-1) appear more than once in the list corresponding to different studies.

## Usage

```
get_miRNA_transfection_data(datapath = system.file("extdata/miRNA_transfection_data.RData", package = "TargetScoreData"))
```

**Arguments**

datapath            data path

---

`get_precomputed_logFC`   *get\_precomputed\_logFC*

---

**Description**

We combined all of the logFC data columns into a single N x M matrix for all of the N = 19177 RefSeq mRNAs (NM\_\* obtained from UCSC) and M = 286 datasets. Missing data (logFC) for some genes across studies were imputed using `impute` from `impute.knn`.

**Usage**

```
get_precomputed_logFC(datapath = system.file("extdata/logFC.RData", package = "TargetScoreData"))
```

**Arguments**

datapath            data path

---

`get_precomputed_targetScores`  
*get\_precomputed\_targetScores*

---

**Description**

Pre-calculated targetScores for 112 miRNAs using logFC and sequence scores from TargetScan context score and PCT from the RData files above.

**Usage**

```
get_precomputed_targetScores(datapath = system.file("extdata/targetScores.RData", package = "TargetScoreData"))
```

**Arguments**

datapath            data path

---

```
get_TargetScanHuman_contextScore  
    get_TargetScanHuman_contextScore
```

---

**Description**

TargetScan context score for all of the predicted sites (including conserved and nonconserved sites) downloaded from TargetScan 6 website ([http://www.targetscan.org/cgi-bin/targetscan/data\\_download.cgi?db=vert\\_61](http://www.targetscan.org/cgi-bin/targetscan/data_download.cgi?db=vert_61))

**Usage**

```
get_TargetScanHuman_contextScore(datapath = system.file("extdata/TargetScanHuman_contextScore.RD
```

**Arguments**

datapath	data path
----------	-----------

---

```
get_TargetScanHuman_PCT  
    get_TargetScanHuman_PCT
```

---

**Description**

TargetScan PCT for all of the predicted sites (including conserved and nonconserved sites) downloaded from TargetScan 6 website ([http://www.targetscan.org/cgi-bin/targetscan/data\\_download.cgi?db=vert\\_61](http://www.targetscan.org/cgi-bin/targetscan/data_download.cgi?db=vert_61))

**Usage**

```
get_TargetScanHuman_PCT(datapath = system.file("extdata/TargetScanHuman_PCT.RData", package = "Tar
```

**Arguments**

datapath	data path
----------	-----------

---

```
get_validated_targets  get_validated_targets
```

---

**Description**

Get validated targets of human miRNA obtained from mirTarBase v3.5

**Usage**

```
get_validated_targets(datapath = system.file("extdata/hsa_MTI.xls", package = "TargetScoreData"))
```

**Arguments**

datapath	data path
----------	-----------

# Index

## \* data package

TargetScoreData-package, [2](#)

get\_miRNA\_family\_info, [3](#), [3](#)

get\_miRNA\_transfection\_data, [3](#), [3](#)

get\_precomputed\_logFC, [3](#), [4](#)

get\_precomputed\_targetScores, [3](#), [4](#)

get\_TargetScanHuman\_contextScore, [3](#), [5](#)

get\_TargetScanHuman\_PCT, [3](#), [5](#)

get\_validated\_targets, [3](#), [5](#)

targetScore, [2](#)

TargetScoreData

(TargetScoreData-package), [2](#)

TargetScoreData-package, [2](#)