

Package ‘sagenhaft’

August 16, 2025

Version 1.79.0

Date 2020-01-10

Title Collection of functions for reading and comparing SAGE libraries

Author Tim Beissbarth <tim.beissbarth@bioinf.med.uni-goettingen.de>, with contributions from Gordon Smyth <smyth@wehi.edu.au>

Reference Beissbarth T, Hyde L, Smyth GK, Job C, Boon WM, Tan SS, Scott HS, Speed TP: Statistical modeling of sequencing errors in SAGE libraries, *Bioinformatics*, 2004 20(Suppl. 1):i31-9.

Maintainer Tim Beissbarth <tim.beissbarth@bioinf.med.uni-goettingen.de>

Depends R (>= 2.10), SparseM (>= 0.73), methods

Imports graphics, stats, utils

Description This package implements several functions useful for analysis of gene expression data by sequencing tags as done in SAGE (Serial Analysis of Gene Expressen) data, i.e. extraction of a SAGE library from sequence files, sequence error correction, library comparison. Sequencing error correction is implementing using an Expectation Maximization Algorithm based on a Mixture Model of tag counts.

biocViews SAGE

License GPL (>= 2)

URL <http://www.bioinf.med.uni-goettingen.de>

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/sagenhaft>

git_branch devel

git_last_commit 70dd910

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-08-15

Contents

error.correction	2
extract.lib	3

sage.library	5
sage.library.comparison	6
sage.test	7
sage.utilities	8
sagelibrary.simulate	9
Index	11

error.correction	<i>Estimate sequencing errors and compute corrected counts</i>
------------------	--

Description

These functions are used to compute sequencing error correction in a library. They are automatically called when extracting tags from sequences and therefore usually do not have to be called directly.

Usage

```
estimate.errors.mean(lib)
compute.sequence.neighbors(tags, taglength=10, quality.scores=NULL,
                           output="character")
em.estimate.error.given(lib, maxstep=50, ...)
```

Arguments

lib	A sage library object
tags	A character vector or numeric vector containing tags
taglength	length of tag
quality.scores	A matrix containing base quality scores as $-10 \log_{10} P_e$
maxstep	iterations of EM algorithm
output	Output type for compute.sequence.neighbors, either character or numeric
...	Other arguments ignored.

Author(s)

Tim Beissbarth

References

<http://tagcalling.mbgproject.org>

See Also

[extract.lib](#), [sage.library](#)

Examples

```
library(sagenhaft)
B6Hypo <- read.sage.library(system.file("extdata", "B6HypoHFI.sage",
                                         package="sagenhaft"))
E15post <- read.sage.library(system.file("extdata", "E15postHFI.sage",
                                         package="sagenhaft"))
testlib <- combine.libs(B6Hypo, E15post)
testlib <- estimate.errors.mean(testlib)
testlib <- em.estimate.error.given(testlib)
tagneighbors <- compute.sequence.neighbors(testlib$seqs[, "seq"], 10,
                                           testlib$seqs[, paste("q", 1:10, sep="")])
```

extract.lib

Functions for SAGE library extraction

Description

Functions to extract the tags in a library from sequences or base-caller output.

Usage

```
extract.lib.from.zip(zipfile, libname=sub(".zip","",basename(zipfile)),
                    ...)
extract.lib.from.directory(dirname, libname=basename(dirname),
                           pattern, ...)
extract.library.tags(filelist, base.caller.format="phd",
                    remove.duplicate.ditags=TRUE,
                    remove.N=FALSE, remove.low.quality=10,
                    taglength=10, min.ditag.length=(2*taglength-2),
                    max.ditag.length=(2*taglength+4),
                    cut.site="catg", default.quality=NA, verbose=TRUE,
                    ...)
reestimate.lib.from.tagcounts(tagcounts, libname, default.quality=20, ...)
compute.unique.tags(lib)
combine.libs(..., artifacts=c("Linker", "Ribosomal", "Mitochondrial"))
remove.sage.artifacts(lib,
                     artifacts=c("Linker", "Ribosomal", "Mitochondrial"),
                     ...)
read.phd.file(file)
read.seq.qual.filepair(file, default.quality=NA)
extract.ditags(sequence, taglength=10, filename=NA,
               min.ditag.length=(2*taglength-2),
               max.ditag.length=(2*taglength+4), cut.site="catg")
```

Arguments

zipfile, dirname	Name of a ZIP file or a directory that contains base-caller output files
libname	libname a character string to be assigned as library name
pattern	Regular expression to specify pattern for the files that will be read

filelist	List of files to be read
base.caller.format	base.caller.format can be "phd" or "seq" or a character vector of the length of the filelist
remove.duplicate.ditags	Remove duplicate ditags. TRUE or FALSE
remove.N	Remove all tags that contain N. TRUE or FALSE
remove.low.quality	Remove all tags with an average quality score of less than remove.low.quality. Skipped if < 0
taglength	Length of tags. Usually 10 or 17
min.ditag.length, max.ditag.length	Minimum and maximum length for ditags
cut.site	Restriction enzyme cut site. Usually CATG
verbose	Display information during process
lib	Library object
file, filename	Character string indicating file name
default.quality	Quality value to use on sequences, if quality files are missing
sequence	Construct containing sequence and quality values returned by read.phd.file or read.seq.qual.filepair
artifacts	Types of artificially generated tags to remove.
...	Arguments passed on to extraction functions.
tagcounts	Tagcounts from library. Integer Vecotor with Tag sequences as names.

Details

The functions `extract.lib.from.zip` or `extract.lib.from.directory` should be used to extract the SAGE TAGS from the sequences of a library, the sequences need to be provided by the output files from the base caller software either in a ZIP archive or in a directory. These are usually the only functions that should directly be called by the user. The other functions are called by these and should only be used directly by experienced users to get more direct control over the process. Most arguments are passed on and can be specified in the high level functions. Zipfilenames must be specified using relative pathnames!

Value

`lib` returns an SAGE library object.

Author(s)

Tim Beissbarth

References

<http://tagcalling.mbgproject.org>

See Also

[sage.library](#), [error.correction](#)

Examples

```
#library(sagenhaft)
#file.copy(system.file("extdata", "E15postHFI.zip", package="sagenhaft"),
#           "E15postHFI.zip")
#E15post<-extract.lib.from.zip("E15postHFI.zip", taglength=10,
#                               min.ditag.length=20, max.ditag.length=24)
#E15post
```

sage.library

*Class sage.library***Description**

The SAGE library class contains all the data and annotation for a SAGE library. It can contain two data.frames.

Usage

```
read.sage.library(file)
write.sage.library(x, file=paste(x$libname, "sage", sep="."),
                   what="complete")
```

Arguments

x	A sage library object
file	File name to read or write to
what	"complete", read complete library tags and sequences; "tags", read only tags and counts

Details

SAGE library objects consists of one or two data.frames. The data.frame "tags" contains all the unique tags in the library and its counts. The data.frame "seqs" contains all the individual tag sequences and associated quality values. read.sage.library and write.sage.library are utility functions to read and write SAGE libraries.

Author(s)

Tim Beissbarth

References

<http://tagcalling.mbgproject.org>

See Also

[extract.lib](#)

Examples

```
library(sagenhaft)
E15postHFI <- read.sage.library(system.file("extdata", "E15postHFI.sage",
                                             package="sagenhaft"))
E15postHFI
```

```
sage.library.comparison
```

Class sage.library.comparison

Description

Class for storing the data of a pairwise comparison between two SAGE libraries.

Usage

```
read.sage.library.comparison(file)
write.sage.library.comparison(x, file=paste(x$name, "sagecomp", sep="."))
compare.lib.pair(lib1, lib2)
```

Arguments

x, lib1, lib2	A sage library object
file	File name to read or write to

Details

SAGE library comparison objects consists of one data.frames. It stores a A and an M value which are the log2 average expression and log2 ratio, respectively. It also has a column for the resulting p.values from [sage.test](#). `read.sage.library.comparison` and `write.sage.library.comparison` are utility functions to read and write SAGE library comparisons. `compare.lib.pair` can be used to generate SAGE library comparisons.

Author(s)

Tim Beissbarth

References

<http://tagcalling.mbgproject.org>

See Also

[sage.test](#)

Examples

```
library(sagenhaft)
B6Hypo <- read.sage.library(system.file("extdata", "B6HypoHFI.sage",
                                         package="sagenhaft"))
E15post <- read.sage.library(system.file("extdata", "E15postHFI.sage",
                                         package="sagenhaft"))
libcomp <- compare.lib.pair(B6Hypo, E15post)
plot(libcomp)
libcomp
```

sage.test

*Compare Two SAGE Libraries***Description**

Compute p-values for differential expression for each tag between two SAGE libraries.

Usage

```
sage.test(x, y, n1=sum(x), n2=sum(y))
```

Arguments

x	integer vector giving counts in first library. Non-integer values are rounded to the nearest integer.
y	integer vector giving counts in second library. Non-integer values are rounded to the nearest integer.
n1	total number of tags in first library. Non-integer values are rounded to the nearest integer.
n2	total number of tags in second library. Non-integer values are rounded to the nearest integer.

Details

This function uses a binomial approximation to the Fisher Exact test for each tag. The approximation is accurate when n1 and n2 are large and x and y are small in comparison.

Value

Numeric vector of p-values.

Author(s)

Gordon Smyth

See Also

[fisher.test](#)

Examples

```
library(sagenhaft)
sage.test(c(0,5,10),c(0,30,50),n1=10000,n2=15000)
# Exact equivalents
fisher.test(matrix(c(0,0,10000-0,15000-0),2,2))$p.value
fisher.test(matrix(c(5,30,10000-5,15000-30),2,2))$p.value
fisher.test(matrix(c(10,50,10000-10,15000-50),2,2))$p.value
```

sage.utilities

Utilities

Description

Different utilities to use with SAGE data.

Usage

```
tagnum2tagmatrix(tags, length)
tagmatrix2tagnum(tags, length=ncol(tags))
tagnum2tagsequence(tags, length)
tagsequence2tagnum(tags, length)
revcomp(seq)
```

Arguments

tags	integer or character vector giving SAGE tags.
length	Length of SAGE tags.
seq	Character vector or list of sequences.
...	SAGE library objects.

Details

These functions are utility functions used in SAGE tag extraction, e.g. to convert SAGE tag sequences to numeric values, i.e. base 4 for efficient storage and handling, and to reverse complement sequences.

Author(s)

Tim Beissbarth

Examples

```
library(sagenhaft)
tags <- c("aaa", "ttt", "ccc")
tagsnumeric <- tagsequence2tagnum(tags, 3)
tagmatrix <- tagnum2tagmatrix(tagsnumeric, 3)
tags <- tagnum2tagsequence(tagmatrix2tagnum(tagmatrix, 3), 3)
revcomp(tags)
```

`sagelibrary.simulate` *Simulate SAGE libraries*

Description

Function to simulate SAGE libraries with sequencing errors.

Usage

```
sagelibrary.simulate(taglength = 4, lambda = 1000, mean.error = 0.01,
                    error.sd = 1, withintagerror.sd = 0.2,
                    ngenes = min(4^taglength, 1e+05), base.lib = NULL,
                    libseed = -1, ...)
```

Arguments

<code>taglength</code>	Tag length for library.
<code>lambda</code>	Aproximate size of library.
<code>mean.error</code>	Mean amount of sequencing errors.
<code>error.sd</code>	Standard deviation for sequencing errors.
<code>withintagerror.sd</code>	Standard deviation for sequencing errors within tags.
<code>ngenes</code>	Number of genes to generate tags from.
<code>base.lib</code>	Simulate library based on tags in other lib and create variations.
<code>libseed</code>	Seed for random number generator.
<code>...</code>	Arguments passed to <code>em.estimate</code> .

Details

We set the number of possible transcripts and assign a random SAGE tag to each of them out of all $4^{\text{taglength}}$ possible SAGE tags. For each SAGE tag a random proportion p within the library is generated from a log-normal distribution, and the proportions are then adjusted to have a sum of 1. The true counts of a tag are simulated by sampling from Poisson distributions with parameters p λ , where p is the proportion of the tag in the library and λ is a parameter for setting the size of the library. The simulation of the sequencing errors is done on each individual occurrence of a tag sequence. For each tag sequence a mean sequencing quality value is generated from a log-normal distribution. The individual quality values for each base are then generated from log-normal distributions with means equal to the simulated sequencing quality values for the tag sequences. We have noticed that with experimentally generated data the within tag sequence variation of sequencing quality values is usually about 1/5 of the between tag sequence variation. From each true tag sequence one observed tag sequence is generated using the simulated quality values of the true sequence as the multinomial probabilities, i.e. replacing each base with either one of the 3 other bases with the probability specified by the sequencing quality value of that base. The counts of these generated tags are then summed to represent the observed tags. When generating several simulated libraries for comparisons, we use the same proportions of the genes for all libraries, replacing up to 1/3 of the proportions by proportions with a known differential factor.

Author(s)

Tim Beissbarth

References

<http://tagcalling.mbgproject.org>

See Also

[sage.library.error.correction](#)

Examples

```
library(sagenhaft)
testlib1 <- sagelibrary.simulate(taglength=10, lambda=10000,
                                mean.error=0.01)
testlib2 <- sagelibrary.simulate(taglength=10, lambda=20000,
                                mean.error=0.02, base.lib=testlib1)
testlib3 <- sagelibrary.simulate(taglength=10, lambda=10000,
                                mean.error=0.01, libseed=testlib1$seed)
```

Index

- * **IO**
 - sage.library, 5
 - sage.library.comparison, 6
- * **SAGE**
 - sage.library, 5
 - sage.library.comparison, 6
- * **error**
 - error.correction, 2
- * **htest**
 - sage.test, 7
- * **manip**
 - extract.lib, 3
- * **misc**
 - sagelibrary.simulate, 9
- * **utilities**
 - sage.utilities, 8
- combine.libs(extract.lib), 3
- compare.lib.pair
 - (sage.library.comparison), 6
- compute.sequence.neighbors
 - (error.correction), 2
- compute.unique.tags(extract.lib), 3
- create.matrix.csr(sage.utilities), 8
- difference.scatter.plot
 - (sage.utilities), 8
- em.estimate.error.given
 - (error.correction), 2
- error.correction, 2, 4, 10
- estimate.errors.mean
 - (error.correction), 2
- extract.ditags(extract.lib), 3
- extract.lib, 2, 3, 5
- extract.lib.from.directory
 - (extract.lib), 3
- extract.lib.from.zip(extract.lib), 3
- extract.library.tags(extract.lib), 3
- fisher.test, 7
- plot.sage.library(sage.library), 5
- plot.sage.library.comparison
 - (sage.library.comparison), 6
- print.sage.library(sage.library), 5
- print.sage.library.comparison
 - (sage.library.comparison), 6
- read.phd.file(extract.lib), 3
- read.sage.library(sage.library), 5
- read.sage.library.comparison
 - (sage.library.comparison), 6
- read.seq.qual.filepair(extract.lib), 3
- reestimate.lib.from.tagcounts
 - (extract.lib), 3
- remove.sage.artifacts(extract.lib), 3
- revcomp(sage.utilities), 8
- sage.library, 2, 4, 5, 10
- sage.library.comparison, 6
- sage.test, 6, 7
- sage.utilities, 8
- SAGEartifacts(extract.lib), 3
- sagelibrary.simulate, 9
- summary.sage.library(sage.library), 5
- summary.sage.library.comparison
 - (sage.library.comparison), 6
- table.sparse(sage.utilities), 8
- tagmatrix2tagnum(sage.utilities), 8
- tagnum2tagmatrix(sage.utilities), 8
- tagnum2tagsequence(sage.utilities), 8
- tagsequence2tagnum(sage.utilities), 8
- write.sage.library(sage.library), 5
- write.sage.library.comparison
 - (sage.library.comparison), 6