

Package ‘PlinkMatrix’

April 22, 2026

Title DelayedArray interface for plink bed files

Version 0.99.8

Description This package provides a DelayedArray interface for plink bed files.

There is support for interfacing to plink genotype data via RangedSummarizedExperiment.

Example data from the GEUVADIS project (internationalgenome.org) are used for demonstration.

Depends R (>= 4.1.0), methods, Rcpp, DelayedArray,
SummarizedExperiment

Suggests knitr, BiocStyle, testthat, rmarkdown, irlba, GenomeInfoDb

Imports BiocFileCache, GenomicRanges, IRanges

License MIT + file LICENSE

VignetteBuilder knitr

biocViews Infrastructure, Genetics

Encoding UTF-8

URL <https://github.com/vjcitn/PlinkMatrix>

BugReports <https://github.com/vjcitn/PlinkMatrix/issues>

RoxygenNote 7.3.3

LinkingTo Rcpp

git_url <https://git.bioconductor.org/packages/PlinkMatrix>

git_branch devel

git_last_commit b2afa0b

git_last_commit_date 2026-04-15

Repository Bioconductor 3.24

Date/Publication 2026-04-21

Author Vince Carey [aut, cre] (ORCID: <<https://orcid.org/0000-0003-4046-0063>>),
NHGRI U24HG004059 [fnd]

Maintainer Vince Carey <stvjc@channing.harvard.edu>

Contents

decode_bed_genotypes	2
dim,PlinkSeed-method	3
dimnames,PlinkSeed-method	3

example_GRanges	4
example_PlinkMatrix	4
extract_array,PlinkSeed-method	5
g445samples	5
getSampleData	6
getVariantData	6
get_plink_example_path	7
plid2gr	7
PlinkMatrix	8
PlinkMatrix-pkg	8
PlinkSeed	8
PlinkSeed-class	9
read_bed_subset	9
selectSome	10
show,PlinkSeed-method	10

Index	11
--------------	-----------

decode_bed_genotypes *Helper function to decode BED format*

Description

Helper function to decode BED format

Usage

```
decode_bed_genotypes(raw_bytes, n_samples)
```

Arguments

raw_bytes	byte stream from file
n_samples	number of samples

Value

numeric vector

Examples

```
PlinkMatrix:::decode_bed_genotypes(raw(4), 4L)
```

dim,PlinkSeed-method *Method: dim for delayed plink*

Description

Method: dim for delayed plink

Usage

```
## S4 method for signature 'PlinkSeed'  
dim(x)
```

Arguments

x PlinkSeed instance

Value

2-vector

Examples

```
methods(class="PlinkSeed")
```

dimnames,PlinkSeed-method
Method: dimnames for delayed plink

Description

Method: dimnames for delayed plink

Usage

```
## S4 method for signature 'PlinkSeed'  
dimnames(x)
```

Arguments

x PlinkSeed instance

Value

list of dimnames

example_GRanges *sample GRanges coordinated with example_PlinkMatrix*

Description

sample GRanges coordinated with example_PlinkMatrix

Usage

```
data("example_GRanges", package="PlinkMatrix")
```

Format

GRanges

Examples

```
data("example_GRanges", package="PlinkMatrix")
head(example_GRanges)
```

example_PlinkMatrix *produce PlinkMatrix from example data*

Description

produce PlinkMatrix from example data

Usage

```
example_PlinkMatrix(folder = tempdir(), as_RSE = FALSE)
```

Arguments

folder	a path where unzipped example data will be managed
as_RSE	logical(1) if TRUE (default is FALSE) a RangedSummarizedExperiment is returned

Value

a SummarizedExperiment or RangedSummarizedExperiment with rowRanges calculated from SNP ids

Examples

```
example_PlinkMatrix()
```

extract_array,PlinkSeed-method

Method: extract_array, internal

Description

Method: extract_array, internal

Usage

```
## S4 method for signature 'PlinkSeed'  
extract_array(x, index)
```

Arguments

x	seed instance
index	list of suitable values for extracting elements

Value

method definition

Examples

```
methods(class="PlinkSeed")
```

g445samples

sample characteristics of 445 GEUVADIS samples

Description

sample characteristics of 445 GEUVADIS samples

Usage

```
data("g445samples", package="PlinkMatrix")
```

Format

data.frame

Note

Example data are those provided with tensorqtl, see <https://github.com/broadinstitute/tensorqtl/tree/0c4db65a0cdc47f3b824ae530b89d270ef5e0096/example/data>.

Examples

```
data("g445samples", package="PlinkMatrix")  
g445samples[seq_len(4), seq_len(4)]
```

getSampleData	<i>Get sample metadata</i>
---------------	----------------------------

Description

Get sample metadata

Usage

```
getSampleData(x)
```

Arguments

x DelayedArray instance

Value

data.frame

Examples

```
tst <- example_PlinkMatrix()
head(getSampleData(tst))
```

getVariantData	<i>Get variant metadata</i>
----------------	-----------------------------

Description

Get variant metadata

Usage

```
getVariantData(x)
```

Arguments

x DelayedArray instance

Value

data.frame

Examples

```
tst <- example_PlinkMatrix()
dim(getVariantData(tst))
```

`get_plink_example_path`*operate with BiocFileCache to retrieve zip file of plink example data*

Description

operate with BiocFileCache to retrieve zip file of plink example data

Usage

```
get_plink_example_path(ca = BiocFileCache::BiocFileCache())
```

Arguments

ca BiocFileCache instance

Value

character string with path to example in cache

Examples

```
get_plink_example_path()
```

`plid2gr`*produce GRanges from variant notation for plink example from geuvadis*

Description

produce GRanges from variant notation for plink example from geuvadis

Usage

```
plid2gr(x, sepused = "_")
```

Arguments

x character vector of variant names
sepused single character, defaults to "_"

Value

GRanges instance

Examples

```
plid2gr("chr18_80259028_AG_A_b38")
```

PlinkMatrix	<i>Constructor for DelayedArray</i>
-------------	-------------------------------------

Description

Constructor for DelayedArray

Usage

PlinkMatrix(filepath)

Arguments

filepath path to plink bed, bim, fam resources without suffixes

Value

An instance of PlinkMatrix

Examples

PlinkMatrix

PlinkMatrix-pkg	<i>Delayed interface to Plink genotype files</i>
-----------------	--

Description

This package includes C++ code to interface to Plink files. Large-scale genotype calls can be managed in a RangedSummarized Experiment instance.

Value

side effects

PlinkSeed	<i>Constructor function for seed for plink bed format</i>
-----------	---

Description

Constructor function for seed for plink bed format

Usage

PlinkSeed(filepath)

Arguments

filepath character string without suffixes

Value

PlinkSeed instance

Examples

PlinkSeed

PlinkSeed-class	<i>Define the PlinkSeed class</i>
-----------------	-----------------------------------

Description

Define the PlinkSeed class

Value

class definition

Examples

`getClass("PlinkSeed")`

read_bed_subset	<i>read subset for use in delayed matrix approach</i>
-----------------	---

Description

read subset for use in delayed matrix approach

Usage

`read_bed_subset(prefix, snp_indices, sample_indices, n_total_samples = NULL)`

Arguments

prefix	character path to bed resources and file prefix
snp_indices	integer vector of snp indices
sample_indices	integer vector of sample indices
n_total_samples	optional

Value

matrix

Examples

read_bed_subset

selectSome	<i>abbreviated display</i>
------------	----------------------------

Description

abbreviated display

Usage

```
selectSome(obj, maxToShow = 5)
```

Value

abbreviated display

show,PlinkSeed-method	<i>present seed concisely</i>
-----------------------	-------------------------------

Description

present seed concisely

Usage

```
## S4 method for signature 'PlinkSeed'  
show(object)
```

Arguments

object	instance of PlinkSeed
--------	-----------------------

Value

side effect of cat

Examples

```
ex <- example_PlinkMatrix()  
ex
```

Index

* datasets

- example_GRanges, 4
- g445samples, 5

* internal

- decode_bed_genotypes, 2
- extract_array, PlinkSeed-method, 5
- PlinkSeed, 8
- PlinkSeed-class, 9
- selectSome, 10

- decode_bed_genotypes, 2
- dim, PlinkSeed-method, 3
- dimnames, PlinkSeed-method, 3

- example_GRanges, 4
- example_PlinkMatrix, 4
- extract_array, PlinkSeed-method, 5

- g445samples, 5
- get_plink_example_path, 7
- getSampleData, 6
- getVariantData, 6

- plid2gr, 7
- PlinkMatrix, 8
- PlinkMatrix-pkg, 8
- PlinkSeed, 8
- PlinkSeed-class, 9

- read_bed_subset, 9

- selectSome, 10
- show, PlinkSeed-method, 10