

# Package ‘PlinkMatrix’

April 25, 2026

**Title** DelayedArray interface for plink bed files

**Version** 0.99.8

**Description** This package provides a DelayedArray interface for plink bed files.

There is support for interfacing to plink genotype data via RangedSummarizedExperiment.

Example data from the GEUVADIS project ([internationalgenome.org](http://internationalgenome.org)) are used for demonstration.

**Depends** R (>= 4.1.0), methods, Rcpp, DelayedArray,  
SummarizedExperiment

**Suggests** knitr, BiocStyle, testthat, rmarkdown, irlba, GenomeInfoDb

**Imports** BiocFileCache, GenomicRanges, IRanges

**License** MIT + file LICENSE

**VignetteBuilder** knitr

**biocViews** Infrastructure, Genetics

**Encoding** UTF-8

**URL** <https://github.com/vjcitn/PlinkMatrix>

**BugReports** <https://github.com/vjcitn/PlinkMatrix/issues>

**RoxygenNote** 7.3.3

**LinkingTo** Rcpp

**git\_url** <https://git.bioconductor.org/packages/PlinkMatrix>

**git\_branch** devel

**git\_last\_commit** b2afa0b

**git\_last\_commit\_date** 2026-04-15

**Repository** Bioconductor 3.23

**Date/Publication** 2026-04-24

**Author** Vince Carey [aut, cre] (ORCID: <<https://orcid.org/0000-0003-4046-0063>>),  
NHGRI U24HG004059 [fnd]

**Maintainer** Vince Carey <stvjc@channing.harvard.edu>

## Contents

decode_bed_genotypes . . . . .	2
dim,PlinkSeed-method . . . . .	3
dimnames,PlinkSeed-method . . . . .	3
example_GRanges . . . . .	4
example_PlinkMatrix . . . . .	4
extract_array,PlinkSeed-method . . . . .	5
g445samples . . . . .	5
getSampleData . . . . .	6
getVariantData . . . . .	6
get_plink_example_path . . . . .	7
plid2gr . . . . .	7
PlinkMatrix . . . . .	8
PlinkMatrix-pkg . . . . .	8
PlinkSeed . . . . .	9
PlinkSeed-class . . . . .	9
read_bed_subset . . . . .	10
selectSome . . . . .	10
show,PlinkSeed-method . . . . .	11
<b>Index</b>	<b>12</b>

---

decode\_bed\_genotypes *Helper function to decode BED format*

---

### Description

Helper function to decode BED format

### Usage

```
decode_bed_genotypes(raw_bytes, n_samples)
```

### Arguments

raw_bytes	byte stream from file
n_samples	number of samples

### Value

numeric vector

### Examples

```
PlinkMatrix:::decode_bed_genotypes(raw(4), 4L)
```

---

dim,PlinkSeed-method *Method: dim for delayed plink*

---

### Description

Method: dim for delayed plink

### Usage

```
## S4 method for signature 'PlinkSeed'  
dim(x)
```

### Arguments

x                   PlinkSeed instance

### Value

2-vector

### Examples

```
methods(class="PlinkSeed")
```

---

dimnames,PlinkSeed-method  
*Method: dimnames for delayed plink*

---

### Description

Method: dimnames for delayed plink

### Usage

```
## S4 method for signature 'PlinkSeed'  
dimnames(x)
```

### Arguments

x                   PlinkSeed instance

### Value

list of dimnames

---

example\_GRanges      *sample GRanges coordinated with example\_PlinkMatrix*

---

**Description**

sample GRanges coordinated with example\_PlinkMatrix

**Usage**

```
data("example_GRanges", package="PlinkMatrix")
```

**Format**

GRanges

**Examples**

```
data("example_GRanges", package="PlinkMatrix")
head(example_GRanges)
```

---

example\_PlinkMatrix      *produce PlinkMatrix from example data*

---

**Description**

produce PlinkMatrix from example data

**Usage**

```
example_PlinkMatrix(folder = tempdir(), as_RSE = FALSE)
```

**Arguments**

folder	a path where unzipped example data will be managed
as_RSE	logical(1) if TRUE (default is FALSE) a RangedSummarizedExperiment is returned

**Value**

a SummarizedExperiment or RangedSummarizedExperiment with rowRanges calculated from SNP ids

**Examples**

```
example_PlinkMatrix()
```

---

 extract\_array,PlinkSeed-method

*Method: extract\_array, internal*


---

**Description**

Method: extract\_array, internal

**Usage**

```
## S4 method for signature 'PlinkSeed'
extract_array(x, index)
```

**Arguments**

x	seed instance
index	list of suitable values for extracting elements

**Value**

method definition

**Examples**

```
methods(class="PlinkSeed")
```

---

 g445samples

*sample characteristics of 445 GEUVADIS samples*


---

**Description**

sample characteristics of 445 GEUVADIS samples

**Usage**

```
data("g445samples", package="PlinkMatrix")
```

**Format**

data.frame

**Note**

Example data are those provided with tensorqtl, see <https://github.com/broadinstitute/tensorqtl/tree/0c4db65a0cdc47f3b824ae530b89d270ef5e0096/example/data>.

**Examples**

```
data("g445samples", package="PlinkMatrix")
g445samples[seq_len(4), seq_len(4)]
```

---

getSampleData	<i>Get sample metadata</i>
---------------	----------------------------

---

**Description**

Get sample metadata

**Usage**

```
getSampleData(x)
```

**Arguments**

x                      DelayedArray instance

**Value**

data.frame

**Examples**

```
tst <- example_PlinkMatrix()
head(getSampleData(tst))
```

---

getVariantData	<i>Get variant metadata</i>
----------------	-----------------------------

---

**Description**

Get variant metadata

**Usage**

```
getVariantData(x)
```

**Arguments**

x                      DelayedArray instance

**Value**

data.frame

**Examples**

```
tst <- example_PlinkMatrix()  
dim(getVariantData(tst))
```

---

`get_plink_example_path`

*operate with BiocFileCache to retrieve zip file of plink example data*

---

**Description**

operate with BiocFileCache to retrieve zip file of plink example data

**Usage**

```
get_plink_example_path(ca = BiocFileCache::BiocFileCache())
```

**Arguments**

ca                    BiocFileCache instance

**Value**

character string with path to example in cache

**Examples**

```
get_plink_example_path()
```

---

`plid2gr`

*produce GRanges from variant notation for plink example from geuvadis*

---

**Description**

produce GRanges from variant notation for plink example from geuvadis

**Usage**

```
plid2gr(x, sepused = "_")
```

**Arguments**

x                    character vector of variant names  
sepused              single character, defaults to "\_"

**Value**

GRanges instance

**Examples**

```
plid2gr("chr18_80259028_AG_A_b38")
```

---

PlinkMatrix	<i>Constructor for DelayedArray</i>
-------------	-------------------------------------

---

**Description**

Constructor for DelayedArray

**Usage**

```
PlinkMatrix(filepath)
```

**Arguments**

filepath            path to plink bed, bim, fam resources without suffixes

**Value**

An instance of PlinkMatrix

**Examples**

```
PlinkMatrix
```

---

PlinkMatrix-pkg	<i>Delayed interface to Plink genotype files</i>
-----------------	--

---

**Description**

This package includes C++ code to interface to Plink files. Large-scale genotype calls can be managed in a RangedSummarized Experiment instance.

**Value**

side effects

---

PlinkSeed	<i>Constructor function for seed for plink bed format</i>
-----------	---

---

**Description**

Constructor function for seed for plink bed format

**Usage**

```
PlinkSeed(filepath)
```

**Arguments**

filepath	character string without suffixes
----------	-----------------------------------

**Value**

PlinkSeed instance

**Examples**

```
PlinkSeed
```

---

PlinkSeed-class	<i>Define the PlinkSeed class</i>
-----------------	-----------------------------------

---

**Description**

Define the PlinkSeed class

**Value**

class definition

**Examples**

```
getClass("PlinkSeed")
```

---

read_bed_subset	<i>read subset for use in delayed matrix approach</i>
-----------------	---

---

**Description**

read subset for use in delayed matrix approach

**Usage**

```
read_bed_subset(prefix, snp_indices, sample_indices, n_total_samples = NULL)
```

**Arguments**

prefix	character path to bed resources and file prefix
snp_indices	integer vector of snp indices
sample_indices	integer vector of sample indices
n_total_samples	optional

**Value**

matrix

**Examples**

```
read_bed_subset
```

---

selectSome	<i>abbreviated display</i>
------------	----------------------------

---

**Description**

abbreviated display

**Usage**

```
selectSome(obj, maxToShow = 5)
```

**Value**

abbreviated display

---

show,PlinkSeed-method *present seed concisely*

---

### **Description**

present seed concisely

### **Usage**

```
## S4 method for signature 'PlinkSeed'  
show(object)
```

### **Arguments**

object            instance of PlinkSeed

### **Value**

side effect of cat

### **Examples**

```
ex <- example_PlinkMatrix()  
ex
```

# Index

## \* datasets

example\_GRanges, 4  
g445samples, 5

## \* internal

decode\_bed\_genotypes, 2  
extract\_array, PlinkSeed-method, 5  
PlinkSeed, 9  
PlinkSeed-class, 9  
selectSome, 10

decode\_bed\_genotypes, 2  
dim, PlinkSeed-method, 3  
dimnames, PlinkSeed-method, 3

example\_GRanges, 4  
example\_PlinkMatrix, 4  
extract\_array, PlinkSeed-method, 5

g445samples, 5  
get\_plink\_example\_path, 7  
getSampleData, 6  
getVariantData, 6

plid2gr, 7  
PlinkMatrix, 8  
PlinkMatrix-pkg, 8  
PlinkSeed, 9  
PlinkSeed-class, 9

read\_bed\_subset, 10

selectSome, 10  
show, PlinkSeed-method, 11