

Package ‘GSABenchmark’

May 8, 2026

Type Package

Title Tools for benchmarking single-cell gene set analysis methods

Version 1.0.0

Description GSABenchmark is a package designed for benchmarking scRNA-seq gene set analysis (scGSA) methods. It provides both traditional and novel benchmark metrics, as well as visualization tools. Currently, GSABenchmark supports 17 scGSA methods.

License MIT + file LICENSE

Imports abdiv, CSOA, decoupleR, dplyr, escape, fabR, ggplot2, ggrepel, GSVA, hammers, henna, jaccard, lsa, Matrix, MLmetrics, methods, mltools, pagoda2, paletteer, reshape2, rlang, scLang, singscore, SiPSiC, stringr, stats, VAM, withr

Encoding UTF-8

RoxygenNote 7.3.3

Suggests AUCCell, BiocStyle, knitr, qs2, ranger, rmarkdown, rpart, scater, scRNAseq, scuttle, Seurat, testthat (>= 3.0.0), UCell

biocViews Software, SingleCell, GeneSetEnrichment, GeneExpression, Visualization

VignetteBuilder knitr

URL <https://github.com/andrei-stoica26/GSABenchmark>

BugReports <https://github.com/andrei-stoica26/GSABenchmark/issues>

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/GSABenchmark>

git_branch RELEASE_3_23

git_last_commit e13f1cc

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-05-07

Author Andrei-Florian Stoica [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5253-0826>>)

Maintainer Andrei-Florian Stoica <andreistoica@foxmail.com>

Contents

GSABenchmark-package	3
accuracyBenchmark	4
accuracyBenchmarkMultiple	5
addGlobalAverage	6
addMethodInfo	6
addMetricSummary	7
addModuleScoreHelper	7
aggregateRankPlot	8
aggregateRanks	9
alignmentScore	9
allBenchmarkPlots	10
allBenchmarkResults	10
allGeneSetRanks	12
allMetricRanks	12
allTopRatios	13
benchmarkPlots	13
benchmarkSummary	14
binaryPredMetric	15
binaryPredMetricCore	15
bindSummary	16
boundaryBenchmark	17
boundaryBenchmarkMultiple	17
boundaryMCCBenchmark	18
computeBoundaryMetrics	19
computeGlobalMetrics	19
computeMCC	20
computeMCCMetric	20
computeMetricMeans	21
corrPlots	21
corrSummary	22
directMCCBenchmark	23
directMCCBenchmarkMultiple	23
efficiencyBenchmark	24
extractCellScores	25
geneSetRankPlots	25
geneSetRanks	26
globalBenchmark	27
globalBenchmarkMultiple	28
globalBenchmarkSummary	29
mdsPlots	30
mdsScoreSummary	31
memoryPlot	31
metricRankPlots	32
metricRanks	33
plotList	33
predJaccardPlots	34

predJaccards	35
ratioPlot	36
runAddModuleScore	37
runAUCell	38
runBenchmark	38
runBenchmarkShuffle	39
runDecoupleRMethod	40
runEscapeMethod	41
runGSAMethods	42
runGSVA	43
runGSVAMethod	43
runJASMINE	44
runMDT	45
runMethodShuffle	46
runMLM	47
runORA	48
runPagoda2	48
runPLAGE	49
runSingscore	50
runSiPSiC	50
runssGSEA	51
runUCell	52
runUDT	52
runVAM	53
runZscore	54
scorePlot	55
supportedMethods	56
timeExpr	56
timePlot	57
Index	58

GSABenchmark-package *GSABenchmark: Tools for benchmarking single-cell gene set analysis methods*

Description

GSABenchmark is a package designed for benchmarking scRNA-seq gene set analysis (scGSA) methods. It provides both traditional and novel benchmark metrics, as well as visualization tools. Currently, GSABenchmark supports 17 scGSA methods.

Author(s)

Maintainer: Andrei-Florian Stoica <andreistoica@foxmail.com> ([ORCID](#))

See Also

Useful links:

- <https://github.com/andrei-stoica26/GSABenchmark>
- Report bugs at <https://github.com/andrei-stoica26/GSABenchmark/issues>

accuracyBenchmark	<i>Perform an accuracy benchmark on a set of gene set analysis method scores</i>
-------------------	--

Description

This function perform an accuracy benchmark on a set of gene set analysis method scores.

Usage

```
accuracyBenchmark(  
  scObj,  
  labelCol,  
  scoreCol,  
  label,  
  checkLabel = TRUE,  
  computeMetricsFun,  
  ...  
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
scoreCol	The metadata column containing the gene set analysis method score.
label	The identity assessed from the labelCol column.
checkLabel	Whether to check that label is found in labelCol.
computeMetricsFun	Function used to compute metrics. Options are computeBoundaryMetrics and computeDistributionMetrics.
...	Additional parameters passed to computeMetricsFun.

Value

A benchmark data frame.

`accuracyBenchmarkMultiple`

Perform accuracy benchmarks for multiple sets of gene set analysis method scores and class labels

Description

This function performs accuracy benchmarks for multiple sets of gene set analysis method scores and class labels.

Usage

```
accuracyBenchmarkMultiple(  
  scObj,  
  labelCol,  
  geneSetNames,  
  gsaMethods,  
  checkLabels = TRUE,  
  verbose = FALSE,  
  benchmarkFun,  
  ...  
)
```

Arguments

<code>scObj</code>	A Seurat or SingleCellExperiment object.
<code>labelCol</code>	The metadata column containing the ground truth annotation.
<code>geneSetNames</code>	Gene set names.
<code>gsaMethods</code>	Character vector of gene set analysis methods.
<code>checkLabels</code>	Whether to check that <code>geneSetNames</code> is a subset of the values in <code>labelCol</code> .
<code>verbose</code>	Whether to output a message whenever the benchmarking begins for a gene set.
<code>benchmarkFun</code>	Benchmark function. Must be either <code>boundaryBenchmark</code> or <code>distributionBenchmark</code> .
<code>...</code>	Additional parameters passed to <code>benchmarkFun</code> .

Value

A list of lists of benchmark data frames.

addGlobalAverage *Add gene set averages to the global summary list*

Description

This function adds gene set averages to the global summary list.

Usage

```
addGlobalAverage(globalSmr, gsaMethods)
```

Arguments

globalSmr	Global summary.
gsaMethods	Character vector of gene set analysis methods.

Value

Extended summary list with an additional data frame showing the average results obtained for each gene set.

addMethodInfo *Add method information to a summary data frame*

Description

This function adds gene set analysis method information to a summary data frame. It sets the names of the gene set analysis method as the rownames of the data frame, and optionally computes the mean score for each method and decreasingly sorts the data frame by these scores.

Usage

```
addMethodInfo(df, gsaMethods, doAverage = TRUE)
```

Arguments

df	A data frame where the values represent the scores obtained by a gene set analysis method (row) on a gene set (column) for a metric.
gsaMethods	Character vector of gene set analysis methods.
doAverage	Whether to add an average column to each data frame, sorting each data frame decreasingly by the average column in the process.

Value

A summary data frame with added method information.

addMetricSummary *Add metric information to the summary list*

Description

This function adds metric information to the summary list and optionally extends the list by adding overall results for each metric.

Usage

```
addMetricSummary(smr, metrics, gsaMethods, doSummarize = TRUE)
```

Arguments

smr	List of result data frames for each metrics. Each data frame contains the results for each tested gene set analysis method for each gene set for the corresponding method.
metrics	Metrics.
gsaMethods	Character vector of gene set analysis methods.
doSummarize	Whether to add a metric summary. Must be set to FALSE when summarizing a MCC benchmark list of lists.

Value

Extended summary list with an additional data frame showing the average results obtained for each metric.

addModuleScoreHelper *Helper used to run AddModuleScore*

Description

This function is used to run AddModuleScore.

Usage

```
addModuleScoreHelper(  
  scObj,  
  geneSets,  
  slot = "data",  
  pool = rownames(scObj),  
  nbin = 24,  
  ctrl = 100  
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
pool	The set from which features to be compared with signature genes are selected. Defaults to all features.
nbin	Number of bins of aggregate expression levels for pool features.
ctrl	Number of control features chosen from the same bin for each feature.

Value

A single-cell expression object with the results saved as a metadata column.

aggregateRankPlot *Create an aggregate rank plot from a summary object*

Description

This function creates an aggregate rank plot from a summary object.

Usage

```
aggregateRankPlot(
  smr,
  title = NULL,
  xLab = "Method",
  sigDigits = 2,
  rankMethod = c("min", "average", "first", "last", "random", "max"),
  ...
)
```

Arguments

smr	Complete summary list generated with allBenchmarkResults or runBenchmark.
title	Plot title.
xLab	x axis label.
sigDigits	Number of significant digits used when displaying mean ranks. If NULL, the mean ranks will not be displayed.
rankMethod	Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.
...	Additional parameters passed to other functions.

Value

A ggplot object.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
p <- aggregateRankPlot(smr)
```

aggregateRanks	<i>Compute aggregate ranks</i>
----------------	--------------------------------

Description

This function computes aggregate ranks from a list of summary data frames.

Usage

```
aggregateRanks(
  smr,
  rankMethod = c("min", "average", "first", "last", "random", "max")
)
```

Arguments

smr	List containing boundary, MCC and global lists of data frames.
rankMethod	Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.

Value

A data frame of aggregate summary results.

alignmentScore	<i>Calculate the alignment between two numeric vectors of the same length</i>
----------------	---

Description

This function calculates the alignment between two numeric vectors of the same length.

Usage

```
alignmentScore(v, w)
```

Arguments

v	A vector.
w	A vector of the same length as

Value

Alignment score.

allBenchmarkPlots	<i>Plot the complete list of benchmark summaries</i>
-------------------	--

Description

This function plots the complete list of benchmark summaries.

Usage

```
allBenchmarkPlots(smr, titleSuffix = NULL, ...)
```

Arguments

smr	Complete summary list generated with allBenchmarkResults or runBenchmark.
titleSuffix	Suffix used to create plot titles. If NULL, the plots will have no titles.
...	Additional parameters passed to other functions.

Value

A list of ggplot objects.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
plots <- allBenchmarkPlots(smr)
```

allBenchmarkResults	<i>Generate all benchmark results with some precomputed arguments. This function generates all benchmark results by using precomputed values for normSilDF, dimMat and maxDist.</i>
---------------------	---

Description

Generate all benchmark results with some precomputed arguments. This function generates all benchmark results by using precomputed values for normSilDF, dimMat and maxDist.

Usage

```
allBenchmarkResults(
  scObj,
  labelCol,
  geneSets,
  gsaMethods,
  checkLabels = TRUE,
  normSilDF = NULL,
  dimMat = NULL,
  maxDist = NULL,
  efBenchmark = NULL,
  runEFBenchmark = TRUE,
  verbose = TRUE
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSets	A list of gene sets. If not NULL while efBenchmark is NULL, the efficiency benchmark will be run.
gsaMethods	Character vector of gene set analysis methods.
checkLabels	Whether to check that geneSetNames is a subset of the values in labelCol.
normSilDF	Data frame of normalized silhouettes.
dimMat	UMAP dimensionality reduction matrix of the single-cell expression object. Unused if normSilDF is NULL.
maxDist	Maximum UMAP distance in the single-cell expression object. Unused if normSilDF or dimMat is NULL.
efBenchmark	A list of data frames generated with efficiencyBenchmark.
runEFBenchmark	Whether to run efficiency benchmark.
verbose	Whether the output of the efficiency benchmark should be verbose. Ignored if runEFBenchmark is FALSE.

Details

This function is designed to save some computational time when multiple runs are sequentially performed for the same single-cell expression object and cell identity classes, but different choices of gene sets (so long as they still describe the same classes) or methods. If a single run is planned rather than multiple ones, runBenchmark is a more straightforward choice, as it takes care of generating normSilDF and dimMat.

Value

A list of benchmark results.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- hammers::computeSilhouette(scObj, 'label')
normSilDF <- hammers::normalizeSilhouette(scObj, 'label')
dimMat <- sLang::scPCAMat(scObj)
maxDist <- max(dist(dimMat))
smr <- allBenchmarkResults(scObj, 'label', geneSets, c('CSOA', 'Zscore'),
TRUE, normSilDF, dimMat, maxDist, runEFBenchmark=FALSE)
```

allGeneSetRanks	<i>Extract all gene set ranks list of summary data frames</i>
-----------------	---

Description

This function extracts all gene set ranks list from a list of summary data frames.

Usage

```
allGeneSetRanks(smr, rankMethod = "min")
```

Arguments

smr	List of summary data frames.
rankMethod	Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.

Value

List of gene set ranks.

allMetricRanks	<i>Extract all metric ranks list of summary data frames</i>
----------------	---

Description

This function extracts metric ranks from a list of summary data frames.

Usage

```
allMetricRanks(smr, rankMethod = "min")
```

Arguments

smr List of summary data frames.
 rankMethod Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.

Value

List of metric ranks.

allTopRatios	<i>Extract all ratio ranks list of summary data frames</i>
--------------	--

Description

This function extracts all ratio ranks list from a list of summary data frames.

Usage

```
allTopRatios(smr, nItems = 25)
```

Arguments

smr List of summary data frames.
 nItems Number of retained items.

Value

List of gene set ranks.

benchmarkPlots	<i>Plot a list of summary data frames</i>
----------------	---

Description

This function plots a list of summary data frames with methods as rows, gene sets and the average of scores across all gene sets as columns.

Usage

```
benchmarkPlots(smr, titleSuffix = NULL, lastPlotLegendLab = "Metric", ...)
```

Arguments

smr List of summary data frames, whether boundary, MCC or global.
titleSuffix Suffix used to create plot titles. If NULL, the plots will have no titles.
lastPlotLegendLab The legend label of the last plot.
... Additional arguments passed to scorePlot.

Value

A list of ggplot objects.

Examples

```

sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
plots <- benchmarkPlots(smr[[1]])
  
```

benchmarkSummary	<i>Compares the identification of different labels through different gene set analysis methods</i>
------------------	--

Description

This function compares the identification of different labels through different gene set analysis methods.

Usage

```
benchmarkSummary(benchmarkLL, doAverage = TRUE, doSummarize = TRUE)
```

Arguments

benchmarkLL A list of lists of benchmark data frames.
doAverage Whether to add an average column to each data frame, sorting each data frame decreasingly by the average column in the process.
doSummarize Whether to add a metric summary. Must be set to FALSE when summarizing a MCC benchmark list of lists.

Value

A list of summary data frames.

binaryPredMetric	<i>Generate metric results using binary predictions</i>
------------------	---

Description

This function generates metric results using binary predictions.

Usage

```
binaryPredMetric(
  globalSmr,
  geneSetNames,
  gsaMethods,
  predList,
  smrCol,
  metricFun
)
```

Arguments

globalSmr	Global summary.
gsaMethods	Character vector of gene set analysis methods.
predList	A list of data frames of the same length as the number of gene sets, in which predictions made by each gene set analysis method are represented as binary columns.
smrCol	Summary column to be added
metricFun	Metric function. Choose between jaccard and numCosine.

Value

A global summary object with an added binary prediction data frame.

binaryPredMetricCore	<i>Generate metric results for a gene set using binary predictions</i>
----------------------	--

Description

This function generates metric results for a gene set using binary predictions.

Usage

```
binaryPredMetricCore(gsetName, gsaMethods, predList, metricFun)
```

Arguments

gsName	Gene set name.
gsaMethods	Character vector of gene set analysis methods.
predList	A list of data frames of the same length as the number of gene sets, in which predictions made by each gene set analysis method are represented as binary columns.
metricFun	Metric function. Choose between jaccard and numCosine.

Value

A numeric vector.

bindSummary	<i>Extract results list of summary data frames</i>
-------------	--

Description

This function extracts results from a list of summary data frames.

Usage

```
bindSummary(smr, nAggDFs = 0, nAvgCols = 0)
```

Arguments

smr	List of summary data frames.
nAggDFs	Number of data frames of aggregate results in the list of summary data frames.
nAvgCols	Number of average columns for each data frame in the list.

Value

A data frame of aggregate summary results.

boundaryBenchmark	<i>Perform a class boundary accuracy benchmark on a set of GSA method scores</i>
-------------------	--

Description

This function performs a class boundary accuracy benchmark on a set of GSA method scores.

Usage

```
boundaryBenchmark(scObj, labelCol, scoreCol, label, checkLabel = TRUE)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
scoreCol	The metadata column containing the gene set analysis method score.
label	The identity assessed from the labelCol column.
checkLabel	Whether to check that label is found in labelCol.

Value

A benchmark data frame with cells as row names, and labels, GSA scores, and class boundary metric scores as columns.

boundaryBenchmarkMultiple	<i>Perform boundary accuracy benchmarks for multiple sets of gene set analysis method scores and class labels</i>
---------------------------	---

Description

This function performs boundary accuracy benchmarks for multiple sets of gene set analysis method scores and class labels.

Usage

```
boundaryBenchmarkMultiple(
  scObj,
  labelCol,
  geneSetNames,
  gsaMethods,
  checkLabels = TRUE,
  verbose = FALSE
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSetNames	Gene set names.
gsaMethods	Character vector of gene set analysis methods.
checkLabels	Whether to check that geneSetNames is a subset of the values in labelCol.
verbose	Whether to output a message whenever the benchmarking begins for a gene set.

Value

A list of lists of boundary benchmark data frames.

boundaryMCCBenchmark *Compute the MCC based on the previously identified boundary cutoff*

Description

This function computes the MCC based on the previously identified boundary cutoff.

Usage

```
boundaryMCCBenchmark(boundaryBenchmarkLL)
```

Arguments

boundaryBenchmarkLL
A list of lists of data frames generated with boundaryBenchmarkMultiple.

Value

A benchmark data frame with cells as row names, and labels, GSA scores, and MCC scores as columns.

`computeBoundaryMetrics`*Compute the class boundary metrics*

Description

This function computes the class boundary metrics.

Usage

```
computeBoundaryMetrics(df)
```

Arguments

`df` A data frame consisting of cells with a binary label column (1) and a column containing the scores obtained by a gene set analysis method (2).

Value

A benchmark data frame with cells as row names, labels in the first column, gene set analysis method scores in the second column, and computed metric scores in the remaining columns.

`computeGlobalMetrics` *Compute the global evaluation metrics*

Description

This function computes the global evaluation metrics.

Usage

```
computeGlobalMetrics(df, normSi1DF = NULL, dimMat = NULL, maxDist = NULL)
```

Arguments

`df` A data frame consisting of cells with a binary label column (1) and a column containing the scores obtained by a gene set analysis method (2).

`normSi1DF` Data frame of normalized silhouettes.

`dimMat` UMAP dimensionality reduction matrix of the single-cell expression object. Unused if `normSi1DF` is NULL.

`maxDist` Maximum UMAP distance in the single-cell expression object. Unused if `normSi1DF` or `dimMat` is NULL.

Value

A benchmark data frame with one row and computed metric scores in the columns.

computeMCC	<i>Compute the Matthews correlation coefficient</i>
------------	---

Description

This function computes the Matthews correlation coefficient for an input data frame generated through class boundary determination benchmarking. The first column contains labels while the second is binarized based on the previously determined cutoff (the first element in the second column).

Usage

```
computeMCC(boundaryResDF, threshold = boundaryResDF[1, 2])
```

Arguments

boundaryResDF A data frame generated with the boundary benchmark.
 threshold Threshold that determines class boundary.

Value

The Matthews correlation coefficient.

computeMCCMetric	<i>Compute the MCC at each threshold</i>
------------------	--

Description

This function computes the MCC at each threshold.

Usage

```
computeMCCMetric(df)
```

Arguments

df A data frame consisting of cells with a binary label column (1) and a column containing the scores obtained by a gene set analysis method (2).

Value

A benchmark data frame with cells as row names, labels in the first column, gene set analysis method scores in the second column, and MCC scores in the third column.

computeMetricMeans *Add overall scores to a benchmark data frame*

Description

This function adds overlap scores to a benchmark data frame.

Usage

```
computeMetricMeans(df, startCol)
```

Arguments

df	Benchmark data frame.
startCol	Column where metric scores start.

Value

The input data frame sorted decreasingly by the newly added overall column.

corrPlots *Create correlation plots for method results*

Description

This function creates correlation plots for method results.

Usage

```
corrPlots(
  scObj,
  smr,
  titlePrefix = "Correlation plot",
  titleInfixes = NULL,
  titleSuffix = NULL,
  ...
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
smr	Complete summary list generated with allBenchmarkResults or runBenchmark.
titlePrefix	Prefix used to create a title with subplotTitle. Ignored if titleSuffix is NULL.

titleInfixes A character vector of title infixes used to create a title with subplotTitle. Ignored if titleSuffix is NULL.
titleSuffix Suffix used to create plot titles. If NULL, the plots will have no titles.
... Additional arguments passed to `henna::correlationPlot`.

Value

A named list of ggplot objects.

Examples

```

scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
plots <- corrPlots(scObj, smr)
  
```

corrSummary

Calculate correlation matrix for method results

Description

This function calculates the correlation matrix for all the methods for an identity class.

Usage

```
corrSummary(scObj, smr, corMethod = "spearman")
```

Arguments

scObj A Seurat or SingleCellExperiment object.
smr List containing boundary, MCC and global lists of data frames.
corMethod Correlation method.

Value

A list of correlation matrices.

Examples

```

scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
m <- corrSummary(scObj, smr)
  
```

directMCCBenchmark	<i>Perform a direct MCC benchmark on a set of gene set analysis method scores</i>
--------------------	---

Description

This function performs a direct MCC benchmark on a set of gene set analysis method scores.

Usage

```
directMCCBenchmark(scObj, labelCol, scoreCol, label, checkLabel = TRUE)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
scoreCol	The metadata column containing the gene set analysis method score.
label	The identity assessed from the labelCol column.
checkLabel	Whether to check that label is found in labelCol.

Value

A benchmark data frame with cells as row names, and labels, gene set analysis scores, and MCC scores as columns.

directMCCBenchmarkMultiple	<i>Perform direct MCC benchmarks for multiple sets of gene set analysis method scores and class labels</i>
----------------------------	--

Description

This function performs direct MCC benchmarks for multiple sets of gene set analysis method scores and class labels.

Usage

```
directMCCBenchmarkMultiple(
  scObj,
  labelCol,
  geneSetNames,
  gsaMethods,
  checkLabels = TRUE,
  verbose = FALSE
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSetNames	Gene set names.
gsaMethods	Character vector of gene set analysis methods.
checkLabels	Whether to check that geneSetNames is a subset of the values in labelCol.
verbose	Whether to output a message whenever the benchmarking begins for a gene set.

Value

A list of lists of boundary benchmark data frames.

efficiencyBenchmark	<i>Extract running times and peak memory usage for gene set analysis methods</i>
---------------------	--

Description

This function extracts running times and peak memory usage for gene set analysis methods.

Usage

```
efficiencyBenchmark(
  scObj,
  labelCol,
  geneSets,
  gsaMethods,
  checkLabels = TRUE,
  verbose = TRUE
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSets	A list of gene sets. If not NULL while efBenchmark is NULL, the efficiency benchmark will be run.
gsaMethods	Character vector of gene set analysis methods.
checkLabels	Whether to check that geneSetNames is a subset of the values in labelCol.
verbose	Whether output should be verbose.

Value

A list of two data frames, the first comprising running times in seconds, the second comprising peak memory usage in mebibytes.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
ef <- efficiencyBenchmark(scObj, 'label', geneSets[1], 'CSOA',
  verbose=FALSE)
```

extractCellScores	<i>Extract gene set analysis method scores and truth labels from single-cell expression object</i>
-------------------	--

Description

This function extracts gene set analysis method scores and truth labels from a single-cell expression object.

Usage

```
extractCellScores(scObj, labelCol, scoreCol, label)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
scoreCol	The metadata column containing the gene set analysis method score.
label	The identity assessed from the labelCol column.

Value

A data frame with two columns: truth labels (1 or 0) and gene set analysis method scores.

geneSetRankPlots	<i>Create gene set rank plots for the method results</i>
------------------	--

Description

This function creates gene set rank plots for method results.

Usage

```
geneSetRankPlots(
  smr,
  rankMethod = "min",
  titlePrefix = "Distribution of ranks",
  titleInfixes = NULL,
  titleSuffix = NULL,
  xLab = "Method",
  ...
)
```

Arguments

smr	Complete summary list generated with <code>allBenchmarkResults</code> or <code>runBenchmark</code> .
rankMethod	Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.
titlePrefix	Prefix used to create a title with <code>subplotTitle</code> . Ignored if <code>titleSuffix</code> is NULL.
titleInfixes	A character vector of title infixes used to create a title with <code>subplotTitle</code> . Ignored if <code>titleSuffix</code> is NULL.
titleSuffix	Suffix used to create plot titles. If NULL, the plots will have no titles.
xLab	x axis label.
...	Additional arguments passed to <code>henna::rankPlot</code> .

Value

A named list of ggplot objects.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
plots <- geneSetRankPlots(smr)
```

geneSetRanks

Extract gene set ranks list from a list of summary data frames

Description

This function extracts gene set ranks list from a list of summary data frames.

Usage

```
geneSetRanks(  
  smr,  
  nAggDFs = 0,  
  nAvgCols = 0,  
  rankMethod = c("min", "average", "first", "last", "random", "max")  
)
```

Arguments

smr	List of summary data frames.
nAggDFs	Number of data frames of aggregate results in the list of summary data frames.
nAvgCols	Number of average columns for each data frame in the list.
rankMethod	Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.

Value

List of gene set ranks.

globalBenchmark	<i>Perform a global evaluation benchmark on a set of gene set analysis method scores</i>
-----------------	--

Description

This function performs a global evaluation benchmark on a set of gene set analysis method scores.

Usage

```
globalBenchmark(  
  scObj,  
  labelCol,  
  scoreCol,  
  label,  
  checkLabel = TRUE,  
  normSilDF = NULL,  
  dimMat = NULL,  
  maxDist = NULL  
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
scoreCol	The metadata column containing the gene set analysis method score.
label	The identity assessed from the labelCol column.
checkLabel	Whether to check that label is found in labelCol.
normSilDF	Data frame of normalized silhouettes.
dimMat	UMAP dimensionality reduction matrix of the single-cell expression object. Unused if normSilDF is NULL.
maxDist	Maximum UMAP distance in the single-cell expression object. Unused if normSilDF or dimMat is NULL.

Value

A one-row benchmark data frame with global metric scores as columns.

globalBenchmarkMultiple

Perform distribution accuracy benchmarks for multiple sets of gene set analysis method scores and class labels

Description

This function performs distribution accuracy benchmarks for multiple sets of gene set analysis method scores and class labels.

Usage

```
globalBenchmarkMultiple(  
  scObj,  
  labelCol,  
  geneSetNames,  
  gsaMethods,  
  checkLabels = TRUE,  
  verbose = FALSE,  
  normSilDF = NULL,  
  dimMat = NULL,  
  maxDist = NULL  
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSetNames	Gene set names.
gsaMethods	Character vector of gene set analysis methods.
checkLabels	Whether to check that geneSetNames is a subset of the values in labelCol.
verbose	Whether to output a message whenever the benchmarking begins for a gene set.
normSilDF	Data frame of normalized silhouettes.
dimMat	UMAP dimensionality reduction matrix of the single-cell expression object. Unused if normSilDF is NULL.
maxDist	Maximum UMAP distance in the single-cell expression object. Unused if normSilDF or dimMat is NULL.

Value

A list of lists of distribution benchmark data frames.

globalBenchmarkSummary

Compares the identification of different labels through different gene set analysis methods

Description

This function compares the identification of different labels through different gene set analysis methods.

Usage

```
globalBenchmarkSummary(globalBenchmarkLL, geneSetNames, gsaMethods, predList)
```

Arguments

globalBenchmarkLL
A list of lists of benchmark data frames.

Value

A list of summary data frames.

`mdsPlots`*Create MDS plots for method results*

Description

This function creates MDS plots for method results.

Usage

```
mdsPlots(  
  scObj,  
  smr,  
  titlePrefix = "MDS plot",  
  titleInfixes = NULL,  
  titleSuffix = NULL,  
  drawScores = TRUE,  
  ...  
)
```

Arguments

<code>scObj</code>	A Seurat or SingleCellExperiment object.
<code>smr</code>	Complete summary list generated with <code>allBenchmarkResults</code> or <code>runBenchmark</code> .
<code>titlePrefix</code>	Prefix used to create a title with <code>subplotTitle</code> . Ignored if <code>titleSuffix</code> is NULL.
<code>titleInfixes</code>	A character vector of title infixes used to create a title with <code>subplotTitle</code> . Ignored if <code>titleSuffix</code> is NULL.
<code>titleSuffix</code>	Suffix used to create plot titles. If NULL, the plots will have no titles.
<code>drawScores</code>	Whether to render scores on the plot. If set to TRUE, the third column of the input data frame will be numeric and scores will be taken from there.
<code>...</code>	Additional arguments passed to <code>henna::densityPlot</code> .

Value

A named list of ggplot objects.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')  
scObj <- qs2::qs_read(scoPath)  
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')  
smr <- qs2::qs_read(sPath)  
plots <- mdsPlots(scObj, smr)
```

mDSScoreSummary	<i>Compute the scored MDS summary</i>
-----------------	---------------------------------------

Description

This function computes the score MDS summary. For each gene set, MDS is performed for the cell-level method predicted scores. The resulting two-column data frame is appended the average accuracy benchmark score of each method, obtained on the gene set.

Usage

```
mDSScoreSummary(scObj, smr)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
smr	List containing boundary, MCC and global lists of data frames.

Value

A list containing a data frame with three columns (two MDS coordinates and method score) for each gene set.

memoryPlot	<i>Plot a data frame consisting of gene set analysis method peak memory usage This function plots data frame consisting of method peak memory usages with methods as rows, gene sets and the gene set average as columns.</i>
------------	---

Description

Plot a data frame consisting of gene set analysis method peak memory usage This function plots data frame consisting of method peak memory usages with methods as rows, gene sets and the gene set average as columns.

Usage

```
memoryPlot(efBenchmark, title = NULL, xLab = "Peak memory usage (MiB)", ...)
```

Arguments

efBenchmark	A list of dataframes generated with efficiencyBenchmark.
title	Plot title.
xLab	x axis label.
...	Additional parameters to be passed to scorePlot.

Value

A ggplot object.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
memoryPlot(smr[[5]])
```

metricRankPlots *Create metric rank plots for the method results*

Description

This function creates metric rank plots for method results.

Usage

```
metricRankPlots(
  smr,
  titlePrefix = "Distribution of ranks",
  titleInfixes = metricNames(),
  titleSuffix = NULL,
  rankMethod = "min",
  xLab = "Method",
  ...
)
```

Arguments

smr	Complete summary list generated with <code>allBenchmarkResults</code> or <code>runBenchmark</code> .
titlePrefix	Prefix used to create a title with <code>subplotTitle</code> . Ignored if <code>titleSuffix</code> is <code>NULL</code> .
titleInfixes	A character vector of title infixes used to create a title with <code>subplotTitle</code> . Ignored if <code>titleSuffix</code> is <code>NULL</code> .
titleSuffix	Suffix used to create plot titles. If <code>NULL</code> , the plots will have no titles.
rankMethod	Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.
xLab	x axis label.
...	Additional arguments passed to <code>henna::rankPlot</code> .

Value

A named list of ggplot objects.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
plots <- metricRankPlots(smr)
```

metricRanks

Extract metric ranks list from a list of summary data frames

Description

This function extracts metric ranks from a list of summary data frames.

Usage

```
metricRanks(smr, nAggDFs = 0, nAvgCols = 0, rankMethod = "min")
```

Arguments

smr	List of summary data frames.
nAggDFs	Number of data frames of aggregate results in the list of summary data frames.
nAvgCols	Number of average columns for each data frame in the list.
rankMethod	Rank method. Choose between 'min', 'average', 'first', 'last', 'random' and 'max'. Default in 'min'.

Value

List of metric ranks.

plotList

Create a list of plots from a list of arguments

Description

This function creates a list of plots from a list of arguments by first converting the arguments into results that can be plotted using calcFun, then plotting these results using plotFun.

Usage

```
plotList(
  args,
  calcFun,
  plotFun,
  unlistPlotArgs = FALSE,
  titlePrefix = NULL,
  titleInfixes = NULL,
  titleSuffix = NULL,
  ...
)
```

Arguments

args	A list of arguments passed to calcFun.
calcFun	The function used for generating the results that will be plotted
plotFun	The function used for plotting.
unlistPlotArgs	Whether the additional arguments passed to plotFun have to be unlisted (that is, they are provided as a list).
titlePrefix	Prefix used to create a title with subplotTitle. Ignored if titleSuffix is NULL.
titleInfixes	A character vector of title infixes used to create a title with subplotTitle. Ignored if titleSuffix is NULL.
titleSuffix	Suffix used to create plot titles If NULL, the plots will have no titles.
...	Additional arguments passed to plotFun.

Value

A named list of ggplot objects.

predJaccardPlots *Create Jaccard tile plots for method binary predictions*

Description

This function creates Jaccard tile plots for method binary predictions.

Usage

```
predJaccardPlots(
  predictionsSmr,
  titlePrefix = "Binary prediction Jaccard plot",
  titleInfixes = NULL,
  titleSuffix = NULL,
  ...
)
```

Arguments

predictionsSmr	Binary predictions summary.
titlePrefix	Prefix used to create a title with subplotTitle. Ignored if titleSuffix is NULL.
titleInfixes	A character vector of title infixes used to create a title with subplotTitle. Ignored if titleSuffix is NULL.
titleSuffix	Suffix used to create plot titles If NULL, the plots will have no titles.
...	Additional arguments passed to henna::tilePlot.

Value

A named list of ggplot objects.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')
smr <- qs2::qs_read(sPath)
plots <- predJaccardPlots(smr$predictions)
```

predJaccards

Calculate the Jaccard scores of method binary predictions

Description

This function calculates the Jaccard scores of method binary predictions.

Usage

```
predJaccards(predictionsSmr)
```

Arguments

predictionsSmr	Binary predictions summary.
----------------	-----------------------------

Value

A list of numeric matrices.

`ratioPlot`*Create a ratio rank plot for the method results*

Description

This function creates a ratio rank plot for the method results.

Usage

```
ratioPlot(  
  smr,  
  title = NULL,  
  nItems = 25,  
  xLab = "Maximum over mean ratio",  
  yLab = "Metric",  
  legendLab = "Method",  
  ...  
)
```

Arguments

<code>smr</code>	Complete summary list generated with <code>allBenchmarkResults</code> or <code>runBenchmark</code> .
<code>title</code>	Plot title.
<code>nItems</code>	Number of retained items.
<code>xLab</code>	x axis label.
<code>yLab</code>	y axis label.
<code>legendLab</code>	Legend label.
<code>...</code>	Additional arguments passed to <code>henna::classRank</code> .

Value

A `ggplot` object.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')  
smr <- qs2::qs_read(sPath)  
p <- ratioPlot(smr)
```

runAddModuleScore	<i>Run AddModuleScore</i>
-------------------	---------------------------

Description

This function runs AddModuleScore.

Usage

```
runAddModuleScore(  
  scObj,  
  geneSets,  
  slot = "data",  
  pool = rownames(scObj),  
  nbin = 24,  
  ctrl = 100,  
  seed = 1  
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
pool	The set from which features to be compared with signature genes are selected. Defaults to all features.
nbin	Number of bins of aggregate expression levels for pool features.
ctrl	Number of control features chosen from the same bin for each feature.
seed	Random seed.

Details

Reimplemented from <https://github.com/satijalab>.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')  
scObj <- qs2::qs_read(scoPath)  
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')  
geneSets <- qs2::qs_read(gsPath)  
scObj <- runAddModuleScore(scObj, geneSets)
```

runAUCell

Run AUCell

Description

This function runs AUCell using escape.

Usage

```
runAUCell(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runEscapeMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
if (requireNamespace("AUCell", quietly=TRUE)){
  scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
  scObj <- qs2::qs_read(scoPath)
  gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
  geneSets <- qs2::qs_read(gsPath)
  scObj <- runAUCell(scObj, geneSets)
}
```

runBenchmark

Generate all benchmark results This function performs the entire GSABenchmark pipeline.

Description

Generate all benchmark results This function performs the entire GSABenchmark pipeline.

Usage

```
runBenchmark(
  scObj,
  labelCol,
  geneSets,
  gsaMethods,
  runEFBenchmark = TRUE,
  verbose = TRUE
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSets	A list of gene sets. If not NULL while efBenchmark is NULL, the efficiency benchmark will be run.
gsaMethods	Character vector of gene set analysis methods.
runEFBenchmark	Whether to run efficiency benchmark.
verbose	Whether the output of the efficiency benchmark should be verbose. Ignored if runEFBenchmark is FALSE.

Details

A wrapper around allBenchmarkResults. Slower for repeated runs, but it does not require users to manually generate normSILDF and dimMat.

Value

A list of benchmark results.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
smr <- runBenchmark(scObj, 'label', geneSets, c('CSOA', 'Zscore'), FALSE)
```

runBenchmarkShuffle	<i>Generate all benchmark results for shuffled gene sets This function generates all benchmark results for shuffled gene sets.</i>
---------------------	--

Description

Generate all benchmark results for shuffled gene sets This function generates all benchmark results for shuffled gene sets.

Usage

```
runBenchmarkShuffle(
  scObj,
  labelCol,
  geneSets,
  gsaMethod,
  runEFBenchmark = TRUE
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSets	A list of gene sets. If not NULL while efBenchmark is NULL, the efficiency benchmark will be run.
gsaMethod	Name of the gene set analysis method.
runEFBenchmark	Whether to run efficiency benchmark.

Value

A list of benchmark results.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runMethodShuffle(scObj, 'label', geneSets, 'CSOA', 0.2, 0.2)
smr <- runBenchmarkShuffle(scObj, 'label', geneSets, 'CSOA', FALSE)
```

runDecoupleRMethod	<i>Run a gene set analysis method using decoupleR</i>
--------------------	---

Description

This function runs one of the gene set analysis methods supported by decoupleR.

Usage

```
runDecoupleRMethod(scObj, geneSets, method, slot = "data", ...)
```

Arguments

<code>scObj</code>	A Seurat or SingleCellExperiment object.
<code>geneSets</code>	A named list of gene sets.
<code>method</code>	Gene set analysis method.
<code>slot</code>	Gene expression slot.
<code>...</code>	Additional arguments passed to gene set analysis method.

Value

A single-cell expression object with the results saved as a metadata column.

<code>runEscapeMethod</code>	<i>Run a gene set analysis method using escape</i>
------------------------------	--

Description

This function runs one of the gene set analysis methods supported by escape.

Usage

```
runEscapeMethod(scObj, geneSets, method, slot = "data", ...)
```

Arguments

<code>scObj</code>	A Seurat or SingleCellExperiment object.
<code>geneSets</code>	A named list of gene sets.
<code>method</code>	Gene set analysis method.
<code>slot</code>	Gene expression slot.
<code>...</code>	Additional arguments passed to gene set analysis method.

Value

A single-cell expression object with the results saved as a metadata column.

runGSAMethods	<i>Run gene set analysis methods</i>
---------------	--------------------------------------

Description

This function runs the gene set analysis methods.

Usage

```
runGSAMethods(  
  scObj,  
  labelCol,  
  geneSets,  
  gsaMethods,  
  infix = NULL,  
  outputFun = silently_run  
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSets	A named list of gene sets.
gsaMethods	Character vector of gene set analysis methods.
infix	Infix to add between method name and gene set name in single-cell expression object. The string consisting of the method name and the infix is separated by the gene set name with a '_' character.
outputFun	Choose between silently_run (suppress all warnings and messages) or identity (do not suppress them). Default is silently_run.

Value

A Seurat or SingleCellExpression object with the results of the runs stored as metadata columns.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')  
scObj <- qs2::qs_read(scoPath)  
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')  
geneSets <- qs2::qs_read(gsPath)  
scObj <- runGSAMethods(scObj, 'label', geneSets, c('CSOA', 'Zscore'))
```

runGSVA	<i>Run GSVA</i>
---------	-----------------

Description

This function runs GSVA using GSVA.

Usage

```
runGSVA(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runGSVAMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runGSVA(scObj, geneSets)
```

runGSVAMethod	<i>Run a gene set analysis method using GSVA</i>
---------------	--

Description

This function runs one of the gene set analysis methods supported by GSVA.

Usage

```
runGSVAMethod(
  scObj,
  geneSets,
  method,
  slot = "data",
  invert = FALSE,
  filter = FALSE,
  ...
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
method	Gene set analysis method.
slot	Gene expression slot.
invert	Whether to transform the scores from x to $1 - x$.
filter	Whether to filter the expression matrix as to contain only signature genes.
...	Additional parameters passed to other functions.

Value

A single-cell expression object with the results saved as a metadata column.

runJASMINE

Run JASMINE

Description

This function runs JASMINE.

Usage

```
runJASMINE(
  scObj,
  geneSets,
  slot = "data",
  method = c("oddsratio", "likelihood")
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
method	One of 'oddsratio' and 'likelihood'.

Details

Reimplemented from <https://github.com/NNoureen/JASMINE>. The method's paper can be found at <https://doi.org/10.7554/eLife.71994>.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runJASMINE(scObj, geneSets)
```

runMDT

Run MDT using decoupleR

Description

This function runs MDT using decoupleR.

Usage

```
runMDT(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runDecoupleRMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
if (requireNamespace("ranger", quietly=TRUE)){
  scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
  scObj <- qs2::qs_read(scoPath)
  gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
  geneSets <- qs2::qs_read(gsPath)
  scObj <- runMDT(scObj, geneSets)
}
```

runMethodShuffle *Run gene set analysis method on shuffled gene sets*

Description

This function runs a gene set analysis method on shuffled gene sets.

Usage

```
runMethodShuffle(
  scObj,
  labelCol,
  geneSets,
  gsaMethod,
  loss = c(0, 0.2),
  noise = c(0, 0.2),
  doGrid = TRUE,
  averageReplicates = TRUE,
  seeds = c(1, 2, 3),
  outputFun = identity
)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
labelCol	The metadata column containing the ground truth annotation.
geneSets	A named list of gene sets.
gsaMethod	Name of the gene set analysis method.
loss	A numeric vector of gene loss values. Must be in [0, 1).
noise	A numeric vector of noise values. Must be in [0, 1).
doGrid	Whether to run the methods for each loss-noise combination.
averageReplicates	Whether to average replicates. If TRUE, a single set of scores will be returned for each loss-noise combination for which the method is run. If FALSE, distinct sets of scores will be returned for each replicate.
seeds	A numeric vector of random seeds passed to <code>hammers::shuffleGenes</code> . Its length determines the number of replicates.
outputFun	Choose between <code>silently_run</code> (suppress all warnings and messages) or <code>identity</code> (do not suppress them). Default is <code>silently_run</code> .

Value

A Seurat or SingleCellExpression object with the results of the runs stored as metadata columns.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runMethodShuffle(scObj, 'label', geneSets, 'CSOA', 0.2, 0.2)
```

runMLM

Run MLM using decoupleR

Description

This function runs MLM using decoupleR.

Usage

```
runMLM(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runDecoupleRMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runMLM(scObj, geneSets)
```

runORA	<i>Run ORA using decoupleR</i>
--------	--------------------------------

Description

This function runs ORA using decoupleR.

Usage

```
runORA(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runDecoupleRMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runORA(scObj, geneSets)
```

runPagoda2	<i>Run pagoda2</i>
------------	--------------------

Description

This function runs pagoda2.

Usage

```
runPagoda2(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional arguments passed to <code>pagoda2::score.cells.puram</code> .

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runPagoda2(scObj, geneSets)
```

runPLAGE

Run PLAGE

Description

This function runs PLAGE using GSVA.

Usage

```
runPLAGE(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to <code>runGSVAMethod</code> .

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runPLAGE(scObj, geneSets)
```

runSingscore	<i>Run Singscore</i>
--------------	----------------------

Description

This function runs Singscore.

Usage

```
runSingscore(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional arguments passed to <code>singscore::simpleScore</code> .

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runSingscore(scObj, geneSets)
```

runSiPSiC	<i>Run SiPSiC</i>
-----------	-------------------

Description

This function runs SiPSiC.

Usage

```
runSiPSiC(scObj, geneSets, slot = "counts", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional arguments passed to SiPSiC::getPathwayScores.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runSiPSiC(scObj, geneSets)
```

runssGSEA

Run ssGSEA

Description

This function runs ssGSEA using escape.

Usage

```
runssGSEA(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runEscapeMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runssGSEA(scObj, geneSets)
```

runUCell

Run UCell

Description

This function runs UCell using escape.

Usage

```
runUCell(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runEscapeMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
if (requireNamespace("UCell", quietly=TRUE)){
  scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
  scObj <- qs2::qs_read(scoPath)
  gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
  geneSets <- qs2::qs_read(gsPath)
  scObj <- runUCell(scObj, geneSets)
}
```

runUDT

Run UDT using decoupleR

Description

This function runs UDT using decoupleR.

Usage

```
runUDT(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runDecoupleRMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
if (requireNamespace("rpart", quietly=TRUE)){
  scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
  scObj <- qs2::qs_read(scoPath)
  gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
  geneSets <- qs2::qs_read(gsPath)
  scObj <- runUDT(scObj, geneSets)
}
```

runVAM

Run VAM

Description

This function runs VAM.

Usage

```
runVAM(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional arguments passed to VAM::vam.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runVAM(scObj, geneSets)
```

runZscore

Run Zscore

Description

This function runs Zscore using GSVA.

Usage

```
runZscore(scObj, geneSets, slot = "data", ...)
```

Arguments

scObj	A Seurat or SingleCellExperiment object.
geneSets	A named list of gene sets.
slot	Gene expression slot.
...	Additional parameters passed to runGSVAMethod.

Value

A single-cell expression object with the results saved as a metadata column.

Examples

```
scoPath <- system.file('extdata', 'scObj.qs2', package='GSABenchmark')
scObj <- qs2::qs_read(scoPath)
gsPath <- system.file('extdata', 'geneSets.qs2', package='GSABenchmark')
geneSets <- qs2::qs_read(gsPath)
scObj <- runZscore(scObj, geneSets)
```

scorePlot	<i>Plot a data frame consisting of gene set analysis method scores This function plots a data frame consisting of method scores with methods as rows, gene sets and the gene set average as columns.</i>
-----------	--

Description

Plot a data frame consisting of gene set analysis method scores This function plots a data frame consisting of method scores with methods as rows, gene sets and the gene set average as columns.

Usage

```
scorePlot(  
  scoreDF,  
  title = NULL,  
  xLab = "Score",  
  yLab = "Method",  
  isDecreasing = FALSE,  
  palette = "grDevices::Plasma",  
  legendLab = "Gene set",  
  pointSize = 1.5  
)
```

Arguments

scoreDF	A summary data frame.
title	Plot title.
xLab	x axis label.
yLab	y axis label.
isDecreasing	Logical; whether the methods should be displayed on the plot in decreasing order of the obtained average scores. If FALSE (as default), the methods will be displayed in increasing order of the average scores.
palette	Color palette.
legendLab	Legend label.
pointSize	Point size.

Value

A ggplot object.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')  
smr <- qs2::qs_read(sPath)  
scorePlot(smr[[1]][[1]])
```

supportedMethods	<i>Show supported methods</i>
------------------	-------------------------------

Description

This function shows the methods currently supported by GSABenchmark.

Usage

```
supportedMethods()
```

Value

A character vector of supported methods.

Examples

```
supportedMethods()
```

timeExpr	<i>Time the evaluation of an expression</i>
----------	---

Description

This function computes the time required to evaluate an expression.

Usage

```
timeExpr(expr, verbose = FALSE)
```

Arguments

expr	An expression to be evaluated.
verbose	Whether to display the elapsed time as output.

Value

A numeric value representing elapsed time.

timePlot	<i>Plot a data frame consisting of gene set analysis method running times This function plots data frame consisting of method running times with methods as rows, gene sets and the gene set average as columns.</i>
----------	--

Description

Plot a data frame consisting of gene set analysis method running times This function plots data frame consisting of method running times with methods as rows, gene sets and the gene set average as columns.

Usage

```
timePlot(efBenchmark, title = NULL, xLab = "Running time (s)", ...)
```

Arguments

efBenchmark	A list of dataframes generated with efficiencyBenchmark.
title	Plot title.
xLab	x axis label.
...	Additional parameters to be passed to scorePlot.

Value

A ggplot object.

Examples

```
sPath <- system.file('extdata', 'smr.qs2', package='GSABenchmark')  
smr <- qs2::qs_read(sPath)  
timePlot(smr[[5]])
```

Index

* internal

- accuracyBenchmark, 4
- accuracyBenchmarkMultiple, 5
- addGlobalAverage, 6
- addMethodInfo, 6
- addMetricSummary, 7
- addModuleScoreHelper, 7
- aggregateRanks, 9
- alignmentScore, 9
- allGeneSetRanks, 12
- allMetricRanks, 12
- allTopRatios, 13
- benchmarkSummary, 14
- binaryPredMetric, 15
- binaryPredMetricCore, 15
- bindSummary, 16
- boundaryBenchmark, 17
- boundaryBenchmarkMultiple, 17
- boundaryMCCBenchmark, 18
- computeBoundaryMetrics, 19
- computeGlobalMetrics, 19
- computeMCC, 20
- computeMCCMetric, 20
- computeMetricMeans, 21
- directMCCBenchmark, 23
- directMCCBenchmarkMultiple, 23
- extractCellScores, 25
- geneSetRanks, 26
- globalBenchmark, 27
- globalBenchmarkMultiple, 28
- globalBenchmarkSummary, 29
- GSABenchmark-package, 3
- mdsScoreSummary, 31
- metricRanks, 33
- plotList, 33
- predJaccards, 35
- runDecoupleRMethod, 40
- runEscapeMethod, 41
- runGSVAMethod, 43

- timeExpr, 56

- accuracyBenchmark, 4
- accuracyBenchmarkMultiple, 5
- addGlobalAverage, 6
- addMethodInfo, 6
- addMetricSummary, 7
- addModuleScoreHelper, 7
- aggregateRankPlot, 8
- aggregateRanks, 9
- alignmentScore, 9
- allBenchmarkPlots, 10
- allBenchmarkResults, 10
- allGeneSetRanks, 12
- allMetricRanks, 12
- allTopRatios, 13

- benchmarkPlots, 13
- benchmarkSummary, 14
- binaryPredMetric, 15
- binaryPredMetricCore, 15
- bindSummary, 16
- boundaryBenchmark, 17
- boundaryBenchmarkMultiple, 17
- boundaryMCCBenchmark, 18

- computeBoundaryMetrics, 19
- computeGlobalMetrics, 19
- computeMCC, 20
- computeMCCMetric, 20
- computeMetricMeans, 21
- corrPlots, 21
- corrSummary, 22

- directMCCBenchmark, 23
- directMCCBenchmarkMultiple, 23

- efficiencyBenchmark, 24
- extractCellScores, 25

- geneSetRankPlots, 25

geneSetRanks, [26](#)
globalBenchmark, [27](#)
globalBenchmarkMultiple, [28](#)
globalBenchmarkSummary, [29](#)
GSABenchmark (GSABenchmark-package), [3](#)
GSABenchmark-package, [3](#)

mdsPlots, [30](#)
mdsScoreSummary, [31](#)
memoryPlot, [31](#)
metricRankPlots, [32](#)
metricRanks, [33](#)

plotList, [33](#)
predJaccardPlots, [34](#)
predJaccards, [35](#)

ratioPlot, [36](#)
runAddModuleScore, [37](#)
runAUCell, [38](#)
runBenchmark, [38](#)
runBenchmarkShuffle, [39](#)
runDecoupleRMethod, [40](#)
runEscapeMethod, [41](#)
runGSAMethods, [42](#)
runGSVA, [43](#)
runGSVAMethod, [43](#)
runJASMINE, [44](#)
runMDT, [45](#)
runMethodShuffle, [46](#)
runMLM, [47](#)
runORA, [48](#)
runPagoda2, [48](#)
runPLAGE, [49](#)
runSingscore, [50](#)
runSiPSiC, [50](#)
runssGSEA, [51](#)
runUCell, [52](#)
runUDT, [52](#)
runVAM, [53](#)
runZscore, [54](#)

scorePlot, [55](#)
supportedMethods, [56](#)

timeExpr, [56](#)
timePlot, [57](#)