

Package ‘Xplortext’

January 14, 2021

Type Package

Encoding UTF-8

Title Statistical Analysis of Textual Data

Version 1.4.1

Date 2021-01-14

Author Mónica Bécue-Bertaut, Ramón Alvarez-Esteban, Josep-Anton Sánchez-Espigares, Belchin Kostov

Maintainer Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>

Description Provides a set of functions devoted to multivariate exploratory statistics on textual data. Classical methods such as correspondence analysis and agglomerative hierarchical clustering are available. Chronologically constrained agglomerative hierarchical clustering enriched with labelled-by-words trees is offered. Given a division of the corpus into parts, their characteristic words and documents are identified. Further, accessing to 'FactoMineR' functions is very easy. Two of them are relevant in textual domain. MFA() addresses multiple lexical table allowing applications such as dealing with multilingual corpora as well as simultaneously analyzing both open-ended and closed questions in surveys. See <<http://xplortext.unileon.es>> for examples.

License GPL (>=2.0)

Depends R (>= 4.0), FactoMineR(>= 2.4), ggplot2, tm(>= 0.7-8)

Imports ggdendro(>= 0.1.22),
ggforce(>= 0.3.2),
ggrepel(>= 0.9.0),
graphics,
gridExtra(>= 2.3),
MASS(>= 7.3-53),
methods,
stringi(>= 1.5.3),
stringr(>= 1.4.0),
slam(>= 0.1-48),
stats,
utils,
flexclust(>= 1.4-0),
flashClust(>= 1.01-2)

URL <https://xplortext.unileon.es>

RoxygenNote 6.1.1

R topics documented:

Xplortext-package	2
ellipseLexCA	3
LabelTree	5
LexCA	6
LexChar	9
LexCHCca	11
LexGalt	13
LexHCca	15
open.question	17
plot.LexCA	18
plot.LexChar	21
plot.LexCHCca	22
plot.LexGalt	23
plot.LexHCca	26
plot.TextData	30
print.LexCA	31
print.LexChar	32
print.TextData	33
summary.LexCA	34
summary.LexChar	35
summary.TextData	36
TextData	37
Index	41

Xplortext-package	<i>Textual Analysis</i>
-------------------	-------------------------

Description

Provides a set of functions devoted to multivariate exploratory statistics on textual data. Classical methods such as correspondence analysis and agglomerative hierarchical clustering are available. Chronologically constrained agglomerative hierarchical clustering enriched with labelled-by-words trees is offered. Given a division of the corpus into parts, their characteristic words and documents are identified. Further, accessing to 'FactoMineR' functions is very easy. Two of them are relevant in textual domain. MFA() addresses multiple lexical table allowing applications such as dealing with multilingual corpora as well as simultaneously analyzing both open-ended and closed questions in surveys. See <https://xplortext.unileon.es> for examples.

Details

Package:	Xplortext
Type:	Package
Version:	1.4.1
Date:	2021-01-14
License:	GPL (>=2.0)

Author(s)

Mónica Bécue-Bertaut, Ramón Alvarez-Esteban, Josep-Anton Sánchez- Espigares, Belchin Kostov
Maintainer: <ramon.alvarez@unileon.es>

References

Bécue, M. (2019). Textual Data Science with R. Chapman & Hall/CRC. doi: [10.1201/9781315212661](https://doi.org/10.1201/9781315212661).
Husson F., Lê S., Pagès J. (2011). Exploratory Multivariate Analysis by Example Using R. Chapman & Hall/CRC. doi: [10.1201/b10345](https://doi.org/10.1201/b10345).
Lebart, L., Salem, A., & Berry, L. (1998). Exploring textual data. (D. Kluwer, Ed.). doi: [10.1007/9789401715256](https://doi.org/10.1007/9789401715256).
A website <https://xplortext.unileon.es>

ellipseLexCA

*Confidence ellipses on textual correspondence analysis graphs***Description**

Draws confidence ellipses around documents and/or words on a textual CA graph.

Usage

```
ellipseLexCA(object, selWord="ALL", selDoc="ALL", nbsample=100, level.conf=0.95,
  axes=c(1, 2), ncp=NULL, xlim=NULL, ylim=NULL, title=NULL, col.doc="blue",
  col.word="red", col.doc.ell=col.doc, col.word.ell=col.word, cex=1)
```

Arguments

object	object of LexCA class
selWord	selected words (indexes or names; by default "ALL"); see the details section
selDoc	selected docs (indexes or names; by default "ALL"); see the details section
nbsample	number of samples drawn to evaluate the stability of the points
level.conf	confidence level used to construct the ellipses (by default 0.95)
axes	length 2 vector specifying the dimensions to plot
ncp	maximum number of dimension to draw (by default NULL and ncp is the number of dimensions from LexCA object)
xlim	range for the plotted 'x' values, defaulting to the range of the finite values of 'x' (by default NULL)
ylim	range for the plotted 'y' values, defaulting to the range of the finite values of 'y' (by default NULL)
title	title of the graph (by default NULL and the title is automatically assigned)
col.doc	color for the documents-points (by default "blue")
col.word	color for words-points (by default "red")
col.doc.ell	color for the ellipses around documents-points (by default the same as col.doc)
col.word.ell	color for the ellipses around words-points (by default the same as col.word)
cex	text and symbol size is scaled by cex, in relation to size 1 (by default 1)

Details

The method "multinomial" is used to generate the replicated tables. So, the active lexical table contained in the LexCA object (active table) is taken as a reference.

Then, replicated lexical tables are generated by repeating `nbsample` times the following process: `N` (the sum of active table elements) values are drawn from a multinomial distribution with theoretical frequencies equal to the values in the active table cells divided by `N`. A replicated table is built from each drawing.

The `nbsample` documents-rows and/or words-columns of the replicated tables are projected as supplementary documents (rows) and/or supplementary words (columns) on the graph computed from the active lexical table. Then, confidence ellipses are drawn around each active element from the `nbsample` supplementary points.

The replicated samples with empty row-documents and/or word-columns with null frequency are dropped.

If over 10% of the total of replicated samples are dropped, the execution is stopped. Information is given through a stop-message.

The `selDoc` and `selWord` arguments allow for selecting the documents and/ or words.

The syntax for these arguments is similar to the one used in `plot.LexCA`.

However they only concern the active elements and selecting the characteristic words is not allowed.

Some examples follow: `selDoc=c(1:5)`: the documents 1 to 5 are represented.

`selDoc=c("doc1","doc5")`: documents with labels `doc1` or `doc5` are represented.

`selWord=c("word1","word3")`: words with labels `word1` or `word3` are represented.

`selDoc/selWord = "coord 10"`: the 10 documents/words with the highest coordinates on the 2 chosen axes are selected.

`selDoc/selWord="contrib 10"`: documents/words with a contribution to the inertia of any of both axes over 10% of the axis inertia are selected.

`selDoc/selWord="cos2 0.85"`: the documents/words with `cos2` over 0.85 (as summed on the 2 axes) are selected.

`selDoc = "meta 3"`: documents/words with a contribution over 3 times the average document/word contribution on any of both axes are selected.

Value

Returns a LexCA-like map representing the selected points and their confidence ellipses

Author(s)

Monica Bécue-Bertaut, Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Josep-Antón Sánchez-Espigares

References

Husson F., Lê S., Pagès J. (2011). Exploratory Multivariate Analysis by Example Using R. Chapman & Hall/CRC. doi: [10.1201/b10345](https://doi.org/10.1201/b10345).

Lebart, L., Piron, M., & Morineau, A. (2006). Statistique exploratoire multidimensionnelle. (Dunod, Ed.).

Lebart, L., Salem, A., & Berry, L. (1998). Exploring textual data. (Kluwer, Ed.). doi: [10.1007/9789401715256](https://doi.org/10.1007/9789401715256).

See Also

[LexCA](#), [print.LexCA](#), [plot.LexCA](#), [summary.LexCA](#)

Examples

```
## Not run:
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), remov.number=TRUE, Fmin=10, Dmin=10,
  stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"),
  context.quanti=c("Age"))
res.LexCA<-LexCA(res.TD, graph=FALSE,ncp=8)
ellipseLexCA(res.LexCA, selWord="meta 1", selDoc=NULL, col.word="brown")
ellipseLexCA(res.LexCA, selWord="contrib 10", selDoc=NULL, col.word="brown")
ellipseLexCA(res.LexCA, selWord=c("work","job","money","comfortable"), selDoc=NULL,
  col.word="brown")
ellipseLexCA(res.LexCA, selWord="cos2 0.2", selDoc=NULL, col.word="brown")

## End(Not run)
## Not run:
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Age", Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, graph=FALSE)
ellipseLexCA(res.LexCA, selWord=NULL, col.doc="black")
ellipseLexCA(res.LexCA, selWord="meta 3", selDoc=NULL, col.word="brown")
ellipseLexCA(res.LexCA, selWord="contrib 10", selDoc=NULL, col.word="brown")
ellipseLexCA(res.LexCA, selWord=c("work","job","money","comfortable"), selDoc=NULL,
  col.word="brown")
ellipseLexCA(res.LexCA, selWord="cos2 0.2", selDoc=NULL, col.word="brown")

## End(Not run)
```

LabelTree

Hierarchical words (LabelTree)

Description

Extracts the hierarchical characteristic words associated to the nodes of a hierarchical tree; the characteristic words of each node are extracted, then each word is associated to the node that it best characterizes.

Usage

```
LabelTree(object, proba=0.05)
```

Arguments

object	object of LexHCca or LexCHCca class
proba	threshold on the p-value when the characteristic words are computed (by default 0.05)

Value

Returns a list including:

`hierWord` list of the characteristic words associated to the nodes of a hierarchical tree; only the non-empty nodes are included

Author(s)

Monica Bécue-Bertaut, Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Josep-Anton Sánchez-Espigares, Belchin Kostov

References

Bécue-Bertaut, M., Kostov, B., Morin, A., & Naro, G. (2014). Rhetorical Strategy in Forensic Speeches: Multidimensional Statistics-Based Methodology. *Journal of Classification*, 31, 85-106. doi: [10.1007/s0035701491489](https://doi.org/10.1007/s0035701491489).

Lebart, L., Salem, A., & Berry, L. (1998). Exploring textual data. (D. Kluwer, Ed.). doi: [10.1007/9789401715256](https://doi.org/10.1007/9789401715256).

See Also

[LexCA](#), [LexCHCca](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question,var.text=c(9,10), var.agg="Age_Group", Fmin=10, Dmin=10,
  stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, graph=FALSE)
res.LexCHCca<-LexCHCca(res.LexCA, nb.clust=4, min=3)
res.LabelTree<-LabelTree(res.LexCHCca)
```

LexCA

Correspondence Analysis of a Lexical Table from a TextData object (LexCA)

Description

Performs Correspondence Analysis on the working lexical table contained in TextData object. Supplementary documents, words, segments, contextual quantitative and qualitative variables can be considered if previously selected in TextData function.

Usage

```
LexCA(object, ncp=5, context.sup="ALL", doc.sup=NULL, word.sup=NULL,
  segment=FALSE, graph=TRUE, axes=c(1, 2), lmd=3, lmw=3)
```

Arguments

<code>object</code>	object of <code>TextData</code> class
<code>ncp</code>	number of dimensions kept in the results (by default 5)
<code>context.sup</code>	column index(es) or name(s) of the contextual qualitative or quantitative variables among those selected in <code>TextData</code> function (by default "ALL")
<code>doc.sup</code>	vector indicating the index(es) or name(s) of the supplementary documents (rows) (by default NULL)
<code>word.sup</code>	vector indicating the index(es) or name(s) of the supplementary words (columns) (by default NULL)
<code>segment</code>	if TRUE, the repeated segments identified by <code>TextData</code> function will be considered as supplementary columns (by default FALSE)
<code>graph</code>	if TRUE, basic graphs are displayed; use <code>plot.LexCA</code> to obtain more graphs (by default TRUE)
<code>axes</code>	length-2 vector indicating the axes to plot (by default <code>axes=c(1,2)</code>)
<code>lmd</code>	only the documents whose contribution is over <code>lmd</code> times the average-document-contribution are plotted (by default <code>lmd=3</code>)
<code>lmw</code>	only the words whose contribution is over <code>lmw</code> times the average-word-contribution are plotted (by default <code>lmw=3</code>)

Details

In the case of a direct CA, `DocTerm` is a non-aggregate table and:

1. the contextual quantitative variables are considered as supplementary quantitative columns in CA.
2. the categories of the contextual qualitative variables are considered as supplementary columns in CA.

In the case of an aggregate CA, `DocTerm` is an aggregate table and:

1. the contextual quantitative variables are considered as supplementary quantitative columns in CA; the value of an active aggregate-document for a variable is the mean of the values corresponding to the source-documents belonging to this aggregate-document.
2. the categories of the contextual qualitative variables are threatened as supplementary rows in CA; these rows contain the frequency with which each the set of documents belonging to this category has used the different words.

Value

Returns a list including:

<code>eig</code>	matrix with the eigenvalues, the percentages of inertia and the cumulative percentages of inertia
<code>row</code>	list of matrices with all the results for the documents (coordinates, square cosines, contributions, inertia)
<code>col</code>	list of matrices with all the results for the words (coordinates, square cosines, contributions, inertia)
<code>row.sup</code>	if <code>row.sup</code> is non-NULL, list of matrices with all the results for the supplementary documents (coordinates, square cosines)

<code>col.sup</code>	if <code>col.sup</code> is non-NULL, list of matrices with all the results for the supplementary words (coordinates, square cosines)
<code>quanti.sup</code>	if <code>quanti.sup</code> is non-NULL, list of matrices containing the results for the supplementary quantitative variables (coordinates, square cosines)
<code>quali.sup</code>	if <code>quali.sup</code> is non-NULL, list of matrices with all the results for the supplementary categorical variables; see section details
<code>meta</code>	list of the documents/words whose contribution is over <code>lmd/lmw</code> times the average document/word contribution
<code>VCr</code>	Cramer's V coefficient
<code>Inertia</code>	total inertia
<code>info</code>	information about the corpus
<code>segment</code>	if <code>segment</code> is TRUE, list of matrices with the results for the repeated segments (coordinates, square cosines)
<code>var.agg</code>	name of the aggregation variable in the case of an aggregate correspondence analysis
<code>call</code>	a list with some statistics

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Mónica Bécue-Bertaut, Josep-Anton Sánchez-Espigares

References

- Benzécri, J. P. (1981). *Pratique de l'analyse des donnees. Linguistique & lexicologie (Vol.3)*. (P. Dunod., Ed).
- Husson F., Lê S., Pagès J. (2011). *Exploratory Multivariate Analysis by Example Using R*. Chapman & Hall/CRC. doi: [10.1201/b10345](https://doi.org/10.1201/b10345).
- Lebart, L., Salem, A., & Berry, L. (1998). *Exploring textual data*. (D. Kluwer, Ed.). doi: [10.1007/9789401715256](https://doi.org/10.1007/9789401715256).
- Murtagh F. (2005). *Correspondence Analysis and Data Coding with R and Java*. Chapman & Hall/CRC.

See Also

[TextData](#), [print.LexCA](#), [plot.LexCA](#), [summary.LexCA](#), [ellipseLexCA](#)

Examples

```
data(open.question)
## Not run:
### non-aggregate CA
res.TD<-TextData(open.question, var.text=c(9,10), Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, lmd=0, lmw=1)

## End(Not run)

### aggregate CA
```



```
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Age_Group", Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, lmd=0, lmw=1)
```

LexChar

*Characteristic words and documents (LexChar)***Description**

Characteristic words of documents from TextData or DocumentTermMatrix objects.

Usage

```
LexChar(object, proba=0.05, maxDocs=20, maxCharDoc=10, maxPrnDoc=100,
  marg.doc="before", correct=TRUE, context.sup="ALL", nbsample=500,
  seed=12345)
```

Arguments

object	TextData, DocumentTermMatrix, dataframe or matrix object
proba	threshold on the p-value used when selecting the characteristic words (by default 0.05)
maxDocs	maximum number of documents in the working lexical table (by default 20). See details
maxCharDoc	maximum number of characteristic source-documents to extract (by default 10). See details
maxPrnDoc	maximum length to be printed for a characteristic document (by default 100 characters)
marg.doc	if before, frequencies before TextData selection are used as document weighting; if after, frequencies after TextData selection (by default before); if object is not TextData only after selection is used
correct	if TRUE, pvalue correction test is applied for WordsQuanti analysis (by default TRUE)
context.sup	column index(es) or name(s) of the contextual quantitative variables among those selected in TextData function (by default "ALL"); if object is not TextData context.sup must be a data frame with the same rows (documents or categories in the case of aggregated documents) as object
nbsample	number of samples drawn to evaluate the pvalues in quantitative contextual variables
seed	Seed to obtain the same results using permutation tests (by default 12345)

Details

The lexical table provided by TextData can consider either source-documents or aggregate-documents, in accordance with the value of argument "var.agg" in TextData.

If the object is a DocumentTermMatrix, dataframe or matrix object it is possible to build aggregate-documents, in accordance with the value of argument "context.sup" in TextData.

Extracting the characteristic words (CharWord) for a too high number of documents is of no interest and time-consuming. So that, this function can be applied only when the number of documents in the lexical table is under or equal to maxDocs (by default 20).

In the case of aggregate documents, extracting the characteristic source-documents is possible but of interest only if the source-documents are not too long. In any case, only the first maxPrnDoc characters of each characteristic document are printed (by default 100).

Vocab\$quali\$CharWord provides the qualitative variables and their categories. Vocab\$quali\$stats provides association statistics for vocabulary and qualitative variables. Vocab\$quanti\$CharWord provides characteristic quantitative variables for each word. Vocab\$quali\$stats provides statistics for vocabulary and quantitative variables.

Value

Returns a list including:

CharWord	characteristic words of all the documents
stats	association statistics of the lexical table
CharDoc	characteristic source-documents of all the aggregate-documents
Vocab	characteristic quantitative and qualitative variables of the words. CharWord and stats are provided

Author(s)

Monica Bécue-Bertaut, Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Josep-Antón Sánchez-Espigares, Belchin Kostov

References

Lebart, L., Salem, A., & Berry, L. (1998). Exploring textual data. (D. Kluwer, Ed.). doi: [10.1007/9789401715256](https://doi.org/10.1007/9789401715256).

See Also

[TextData](#), [print.LexChar](#), [plot.LexChar](#), [summary.LexChar](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Edu", Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
# res.LexChar <-LexChar(res.TD)
```

LexCHCca	<i>Chronologically Constrained Agglomerative Hierarchical Clustering on Correspondence Analysis Components (LexCHCca)</i>
----------	---

Description

Chronologically constrained agglomerative hierarchical clustering on a corpus of documents.

Usage

LexCHCca (object, nb.clust=0, min=3, max=NULL, nb.par=5, graph=TRUE, proba=0.05)

Arguments

object	object of LexCA class
nb.clust	number of clusters (see details). If 0, the tree is cut at the level the user clicks on. If -1, the tree is automatically cut at the suggested level. If a (positive) integer, the tree is cut with nb.clust clusters (by default 0)
min	minimum number of clusters (by default 3)
max	maximum number of clusters (by default NULL and then max is computed as the minimum between 10 and the number of documents divided by 2)
nb.par	number of edited paragons (para) and specific documents labels (dist) (by default 5)
graph	if TRUE, graphs are displayed (by default TRUE)
proba	threshold on the p-value used in selecting the characteristic words of the clusters and in selecting the axes when describing the clusters by the axes (by default 0.05)

Details

LexCHCca starts from the documents coordinates on textual correspondence analysis axes. The hierarchical tree is built taking into account that only chronological contiguous nodes can be grouped. The documents have to be ranked in the lexical table in the chronological order. Euclidean metric and complete linkage method are used.

The number of clusters is determined either a priori or from the constrained hierarchical tree structure. If nb.clust=0, a level for cutting the tree is automatically suggested. This is computed in the following way, reading the tree downward. At a given step, the tree could be cut into Q clusters (Q varying between min and max). The distance between the two nodes that are no longer grouped together using complete linkage method when passing from Q-1 to Q clusters and the distance between the two nodes that are no longer grouped together when passing from Q to Q+1 are computed. The suggested level corresponds to the maximum value of the ratio between the former and the latter of these values. These distances correspond to the criterion value when building the tree bottom up. The user can choose to cut the tree at this level or at another one.

The results include a thorough description of the clusters. Graphs are provided.

The tree is plotted jointly with a barchart of the successive values of the aggregation criterion.

Value

Returns a list including:

<code>data.clust</code>	the original active lexical table with a supplementary column called <code>clust</code> containing the partition
<code>desc.word</code>	description of the clusters by their characteristic words
<code>desc.axes</code>	description of the clusters by the characteristic axes
<code>call</code>	list of parameters and internal objects
<code>desc.doc</code>	labels of the paragon (<code>para</code>) and specific documents (<code>dist</code>) of each cluster
<code>dendro</code>	list with the succession of nodes that are found when reading the tree downward

Returns the graphs with the tree and the correspondence analysis map where the documents are colored according to the cluster they belong to (2D).

Author(s)

Monica Bécue-Bertaut, Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Josep-Antón Sánchez-Espigares, Belchin Kostov

References

- Bécue-Bertaut, M., Kostov, B., Morin, A., & Naro, G. (2014). Rhetorical Strategy in Forensic Speeches: Multidimensional Statistics-Based Methodology. *Journal of Classification*, 31, 85-106. doi: [10.1007/s0035701491489](https://doi.org/10.1007/s0035701491489).
- Lebart L. (1978). Programme d'agrégation avec contraintes. *Les Cahiers de l'Analyse des Données*, 3, pp. 275–288.
- Legendre, P. & Legendre, L. (1998), *Numerical Ecology* (2nd ed.), Amsterdam: Elsevier Science.
- Murtagh F. (1985). *Multidimensional Clustering Algorithms*. Vienna: Physica-Verlag, COMP-STAT Lectures.

See Also

[plot.LexCHCca](#), [LabelTree](#), [LexCA](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question,var.text=c(9,10), var.agg="Age_Group", Fmin=10, Dmin=10,
  stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, graph=FALSE)
res.ccah<-LexCHCca(res.LexCA, nb.clust=4, min=3)
```

LexGalt

*Generalised Aggregate Lexical Table (LexGalt)***Description**

Performs Dual Correspondence Analysis in Generalised Aggregate Lexical Table

Usage

```
LexGalt(object, context="ALL", ncp=NULL, level.ventil = 0, scale=TRUE,
        conf.ellip =FALSE, nb.ellip = 100, graph=TRUE, axes = c(1, 2), label.group=NULL)
```

Arguments

object	object(s) of TextData class (see details)
context	column index(es) or name(s) of the contextual qualitative or quantitative variables among those selected in TextData function (by default "ALL")
ncp	number of dimensions kept to compute (by default NULL to indicate all dimensions)
level.ventil	a proportion corresponding to the level under which the category is ventilated; by default, 0 and no ventilation is done
scale	variables are scaled to unit variance (standardized) (by default TRUE)
conf.ellip	if condifence ellipses are computed (by default FALSE)
nb.ellip	number of samples drawn to evaluate the stability of the points only if conf.ellip=TRUE (by default 100)
graph	if TRUE, all several graphs are displayed; use plot.LexGalt to obtain detailed graphs (by default TRUE)
axes	length-2 vector indicating the axes to plot (by default axes=c(1,2))
label.group	a vector containing the name of the groups (by default, NULL and the group are named GROUP.1, GROUP.2 and so on)

Details

If multiple analysis, each TextData object must be created in advance (object1, object2, object3) and joined in a list: LexGalt(list=c(object1,object2,object3),...) Ellipses only are computed for simple analysis.

Value

Returns a list including SQL object for simple qualitative analysis, SQN object for simple quantitative analysis, MQL object for multiple qualitative analysis, MQN object for multiple quantitative analysis:

eig	matrix with the eigenvalues, the percentages of inertia and the cumulative percentages of inertia
doc	a list of matrices containing all the results for the documents (coordinates, square cosine)
word	a list of matrices containing all the results for the words (coordinates, square cosine, contributions)

<code>quali.var</code>	a list of matrices containing all the results for the categorical variables (coordinates of each categories of each variables, square cosine)
<code>quanti.var</code>	a list of matrices containing all the results for the quantitative variables (coordinates, correlation between variables and axes, square cosine)
<code>ellip</code>	coordinates for confidence ellipses are drawn. In simple qualitative analysis (SQL) they are words and categories
<code>group</code>	coordinates, contributions and square cosine for each group in multiple analysis (MQL or MQN)

Returns the factor maps. The plots may be improved using the `plot.LexGalt` function.

Author(s)

Belchin Kostov, Monica Bécue-Bertaut, Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Josep-Antón Sánchez-Espigares

References

Bécue-Bertaut M. and Pagès J. (2015). Correspondence analysis of textual data involving contextual information: CA-GALT on principal components. *Advances in Data Analysis and Classification*, vol.(9) 2: 125-142.

Bécue-Bertaut M., Pagès J. and Kostov B. (2014). Untangling the influence of several contextual variables on the respondents' lexical choices. A statistical approach. *SORT - Statistics and Operations Research Transactions*, vol.(38) 2: 285-302.

Kostov B. A. (2015). A principal component method to analyse disconnected frequency tables by means of contextual information. (Doctoral dissertation). Retrieved from <http://upcommons.upc.edu/handle/2117/95759>.

See Also

[plot.LexGalt](#)

Examples

```
## Not run:
data(open.question)

res.TD<-TextData(open.question,var.text=c(9,10), Fmin=10, Dmin=10,
  context.quali=c("Gender", "Age_Group", "Education"),
  remov.number=TRUE, stop.word.tm=TRUE)

res.LexGalt <- LexGalt(res.TD, graph=FALSE, nb.ellip =0)
plot(res.LexGalt, selQualiVar="ALL")

## End(Not run)
```

LexHCca	<i>Hierarchical Clustering of Documents on Textual Correspondence Analysis Coordinates (LexHCca)</i>
---------	--

Description

Agglomerative hierarchical clustering on documents or words

Usage

```
LexHCca(x, cluster.CA="docs", marg.doc="before", nb.clust="click", min=2,
        max=NULL, kk=Inf, consol=FALSE, iter.max=500, graph=TRUE, description=TRUE,
        proba=0.05, nb.desc=5, size.desc=80, seed=12345,...)
```

Arguments

x	object of LexCA class
cluster.CA	if "rows" or "docs" cluster analysis is performed on documents; "columns" or "words" and cluster is performed on words (by default "docs")
marg.doc	This parameter concerns only the description of the clusters by the characteristic words in case of using TextData function to build the lexical table. To compute the corresponding p-value, document weightings correspond to their relative lengths either "before" or "after" word selection in TextData (by default before)
nb.clust	number of clusters (see details). If 0 (or "click"), the tree is cut at the level the user clicks on. If -1 (or "auto"), the tree is automatically cut at the suggested level. If a (positive) integer, the tree is cut with nb.clust clusters (by default "click")
min	minimum number of clusters (by default 2)
max	maximum number of clusters (by default NULL and then max is computed as the minimum between 10 and the number of documents divided by 2)
kk	An integer corresponding to the number of clusters used in a Kmeans preprocessing before the hierarchical clustering; the top of the hierarchical tree is then constructed from this partition. This is very useful if the number of individuals is high. Inf is used by default and no Kmeans preprocessing is performed. It can be used with nb.clust values
consol	if TRUE, consolidation is performed after hierarchical clustering (by default FALSE)
iter.max	maximum number of iterations in the consolidation step (by default 500)
graph	if TRUE, graphs are displayed (by default TRUE)
description	if TRUE, description of the clusters by characteristic words/documents, characteristic axes, paragon (para), specific words/documents (dist) and contextual variables if considered in LexCA (by default TRUE)
proba	threshold on the p-value used in selecting words, documents, axes and contextual variables when describing the clusters (by default 0.05)
nb.desc	number of edited paragons (para) and specific documents/words (dist) when describing the clusters (by default 5)

<code>size.desc</code>	text size of edited paragons (<code>para</code>) and specific documents (<code>dist</code>) when describing the clusters (by default 80)
<code>seed</code>	Seed to obtain the same results in successive Kmeans (by default 12345)
<code>...</code>	other arguments from other methods

Details

LexHCca starts from the documents/words coordinates issued from correspondence analysis axes. Euclidean metric and Ward method are used.

The number of clusters is determined either a priori or from the hierarchical tree structure. If `nb.clust=0` (or `'auto'`), a level for cutting the tree is automatically suggested. This is computed in the following way, reading the tree downward. At a given step, the tree could be cut into Q clusters (Q varying between min and max). The between-inertia gain when passing from $Q-1$ to Q clusters and the between-inertia gain when passing from Q to $Q+1$ clusters are computed. The suggested level corresponds to the maximum value of the ratio between the former and the latter of these inertia-gains. Note that the between-inertia gain when passing from Q to $Q+1$ clusters is equal to the value of the Ward criterion when passing from $Q+1$ to Q clusters when building the tree bottom up. In this latter case, a level where to cut the tree is suggested. The user can choose to cut the tree at this level or at another one.

The results include a thorough description of the clusters, taking into account contextual variables. Graphs are provided.

Frequencies before TextData selection are the marginal frequencies for documents in description analysis.

Value

Returns a list including:

<code>data.clust</code>	the active lexical table used in LexCA plus a new column called <code>Clust_</code> containing the partition
<code>coord.clust</code>	coordinates table issued from CA plus a new column called <code>Clust_</code> containing the partition
<code>centers</code>	coordinates of centers
<code>clust.count</code>	counts of documents/words belonging to each cluster and contribution of the clusters to the variability decomposition
<code>clust.content</code>	list of the document/word labels according to the cluster they belong to
<code>call</code>	list of internal objects. <code>call\$t</code> giving the results for the hierarchical tree; See the first reference for more details
<code>description</code>	<p><code>\$desc.axes</code> for description of the clusters by the characteristic axes (<code>\$axes</code>) and eta-squared between axes and clusters (<code>\$quanti.var</code>).</p> <p><code>\$des.cluster.doc</code> for description of the clusters of documents by their characteristic words (<code>\$word</code>), supplementary words (<code>\$wordsup</code>) and, if contextual variables were considered in LexCA, description of the partition/clusters by qualitative (<code>\$qualisup</code>) and quantitative (<code>\$quantisup</code>) variables, paragons (<code>\$para</code>) and specific words (<code>\$dist</code>) of each cluster.</p> <p><code>\$des.word.doc</code> description of the clusters of words by their characteristic documents (<code>\$docs</code>), paragons (<code>\$para</code>) and specific documents (<code>\$dist</code>) of each cluster.</p>

Returns the hierarchical tree with a barplot of the successive inertia gains, and the first CA map of the documents/words with the labels colored according to their cluster.

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Monica Bécue-Bertaut, Josep-Anton Sánchez-Espigares

References

- Bécue-Bertaut M. Textual Data Science with R. Chapman & Hall/CRC. doi: [10.1201/9781315212661](https://doi.org/10.1201/9781315212661).
- Husson F., Lê S., Pagès J. (2011). Exploratory Multivariate Analysis by Example Using R. Chapman & Hall/CRC. doi: [10.1201/b10345](https://doi.org/10.1201/b10345).
- Lebart, L., Salem, A., & Berry, L. (1998). Exploring textual data. (D. Kluwer, Ed.). doi: [10.1007/9789401715256](https://doi.org/10.1007/9789401715256).

See Also

[LexCA](#), [plot.LexHCca](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), Fmin=10, Dmin=10, stop.word.tm=TRUE,
                 context.quali=c("Gender","Age_Group","Education"), context.quant=c("Age"))
res.LexCA<-LexCA(res.TD, graph=FALSE, ncp=8)
res.hcca<-LexHCca(res.LexCA, graph=TRUE, nb.clust=5)
```

open.question	<i>Open.question (data)</i>
---------------	-----------------------------

Description

Extract of the answers provided in a survey designed to better know opinions about what is most important in life.

Two open-ended questions are included in the questionnaire "What is most important to you in life?" and "What are other very important things to you? (relaunch of the first question).

Usage

```
data(open.question)
```

Format

Data frame with 300 rows and 10 columns. The rows correspond to the respondents. The first 8 columns correspond to socio-demographic variables collected through closed questions: Gender, Age_Group, Age, Education level, Genre crossed with Age, Genre crossed with Education level, Age crossed with Education level and, finally Genre crossed with Education level and Age. Age is a quantitative variable while the other variables are qualitative. The last two columns contain the answers to the open-ended questions.

plot.LexCA

*Plot of LexCA objects***Description**

Plots textual correspondence analysis (CA) graphs from a LexCA object.

Usage

```
## S3 method for class 'LexCA'
plot(x, selDoc="ALL", selWord="ALL", selSeg=NULL, selDocSup=NULL,
     selWordSup=NULL, quanti.sup=NULL, quali.sup=NULL, maxDocs=20, eigen=FALSE,
     title=NULL, axes=c(1,2), col.doc="blue", col.word="red", col.doc.sup="darkblue",
     col.word.sup="darkred", col.quanti.sup = "blue", col.quali.sup="darkgreen",
     col.seg="cyan4", col="grey", cex=1, xlim=NULL, ylim=NULL, shadowtext=FALSE,
     habillage="none", unselect=1, label="all", autoLab=c("auto", "yes", "no"),
     new.plot=TRUE, graph.type = c("classic", "ggplot"),...)
```

Arguments

x	object of LexCA class
selDoc	vector with the active documents to plot (indexes, names or rules; see details; by default "ALL")
selWord	vector with the active words to plot (indexes, names or rules; see details; by default "ALL")
selSeg	vector with the supplementary repeated segments to plot (indexes, names or rules; see details; by default NULL)
selDocSup	vector with the supplementary documents to plot (indexes, names or rules; see details; by default NULL)
selWordSup	vector of the supplementary words to plot (indexes, names or rules; see details; by default NULL)
quanti.sup	vector of the supplementary quantitative variables to plot (indexes, names or rules; see details; by default NULL)
quali.sup	vector with the supplementary categorical variables/categories to plot (indexes, names or rules; see details; by default NULL). The selected categories (through the variables or directly) are plotted
maxDocs	limit to the number of active documents in the lexical table when selecting the words to be plotted for being characteristic of the selected documents (by default 20)
eigen	if TRUE, the eigenvalues barplot is drawn (by default FALSE); no other elements can be simultaneously selected
title	title of the graph (by default NULL and the title is automatically assigned)
axes	length-2 vector indicating the axes considered in the graph (by default c(1,2))
col.doc	color for the point-documents (by default "blue")
col.word	color for the point-words (by default "red")
col.doc.sup	color for the supplementary point-documents (by default "darkblue")

col.word.sup	color for the supplementary point-words (by default "darkred")
col.quant.sup	color for the quanti.sup variables (by default "blue")
col.quali.sup	color for the categorical supplementary point-categories, (by default "darkgreen")
col.seg	color for the supplementary point-repeated segments, (by default "cyan4")
col	color for the bars in the eigenvalues barplot (by default "grey")
cex	text and symbol size is scaled by cex, in relation to size 1 (by default 1)
xlim	range for 'x' values on the graph, defaulting to the finite values of 'x' range (by default NULL)
ylim	range for the 'y' values on the graph, defaulting to the the finite values of 'y' range (by default NULL)
shadowtext	if TRUE, shadow on the labels (rectangles are written under the labels which may lead to difficulties to modify the graph with another program) (by default FALSE)
habillage	index or name of the categorical variable used to differentiate the documents by colors given according to the category; by default "none")
unselect	either a value between 0 and 1 or a color. In the first case, transparency level of the unselected objects (if unselect=1 the transparency is total and the elements are not represented; if unselect=0 the elements are represented as usual but without any label); in the case of a color (e.g. unselect="grey60"), the non-selected points are given this color (by default 1)
label	a list of character for the variables which are labelled (by default NULL and all the drawn variables are labelled). You can label all the active variables by putting "var" and/or all the supplementary variables by putting "quanti.sup" and/or a list with the names of the variables which should be labelled. Value should be one of "all", "none", "row", "row.sup", "col", "col.sup", "quali.sup" or NULL.
autoLab	if autoLab="auto", autoLab turns to be equal to "yes" if there are less than 50 elements and equal to "no" otherwise; if "yes", the labels are moved, as little as possible, to avoid overlapping (time-consuming if many elements); if "no" the labels are placed quickly but may overlap
new.plot	if TRUE, a new graphical device is created (by default FALSE)
graph.type	a string that gives the type of graph used: "ggplot" or "classic" (by default classic)
...	further arguments passed from other methods...

Details

The argument autoLab = "yes" is time-consuming if many overlapping labels. Furthermore, the visualization of the words cloud can result distorted because of the apparent greater dispersion of the words labels. An alternative would be reducing the character size of the words labels to reduce overlapping (e.g. cex=0.7).

selDoc, selWord, selSeg, selDocSup, selWordSup, quanti.sup and quali.sup allow for selecting all or part of the elements of the corresponding type, using either labels, indexes or rules.

The syntax is the same for all types.

1. Using labels:

`selDoc = c("doc1", "doc5")`: only the documents with labels doc1 and doc5 are plotted.
`quali.sup=c("varcateg1", "category12")`: only the categories (all of them) of categorical variable labeled "varcateg1" and the category labeled "category12" are plotted.

2.- Using indexes:

`selDoc = c(1:5)`: documents 1 to 5 are plotted.
`quali.sup=c(1:5,7)`: categories 1 to 5 and 7 are plotted. The numbering of the categories have to be consulted in the LexCA numerical results.

3.- Using rules: Rules are based on the coordinates (coord), the contribution (contrib or meta; concerning only active elements) or the square cosine (cos2). Some examples are given hereafter:

`selDoc="coord 10"`: only the 10 documents with the highest coordinates, as globally computed on the 2 axes, are plotted.
`selWord="contrib 10"`: the words with a contribution to the inertia, of any of the 2 axes.
`selWord="meta 3"`: the words with a contribution over 3 times the average word contribution on any of the two axes are plotted. Only active words or documents can be selected.
`selDocSup="cos2 .85"`: the supplementary documents with a cos2 over 0.85, as summed on the 2 axes, are plotted.
`selWord="char 0.05"`: only the characteristic words of the documents selected in `SelDoc` are plotted. The selection of the words follow the rationale used in function `LexChar` using as limit for the p-value the value given, here 0.05.

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Mónica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

References

Husson F., Lê S., Pagés J. (2011). Exploratory Multivariate Analysis by Example Using R. Chapman & Hall/CRC. doi: [10.1201/b10345](https://doi.org/10.1201/b10345).

See Also

[LexCA](#), [print.LexCA](#), [summary.LexCA](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question,var.text=c(9,10), var.agg="Age_Group", Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
res.CA <- LexCA(res.TD, graph=FALSE)
plot(res.CA, selDoc="contrib 30", selWord="coord 20")
```

plot.LexChar

*Plot LexChar objects***Description**

Draws the characteristic and anti-characteristic words of documents from a LexChar object.

Usage

```
## S3 method for class 'LexChar'
plot(x, char.negat=TRUE, col.char.posit="blue", col.char.negat="red",
     col.lines="black", theme=theme_bw(), text.size=12, numr=1, numc=2, top=NULL,
     max.posit=15, max.negat=15, type=c("CharWord","quanti","quali"),context.sup=NULL, ...)
```

Arguments

x	object of LexChar class
char.negat	if TRUE, the anti-characteristic words are plotted (by default TRUE)
col.char.posit	color for the characteristic words (by default "blue")
col.char.negat	color for the anti-characteristic words (by default "red")
col.lines	color for the lines of barplot (by default "black")
theme	used to modify the theme settings by ggplot2 package (by default theme_bw())
text.size	size of the font (by default 12)
numr	number of rows in each multiple graph (by default 1 row)
numc	number of columns in each multiple graph (by default 2 columns)
top	title of the graph (by default NULL)
max.posit	maximum number of characteristic words (by default 15)
max.negat	maximum number of anti-characteristic words (by default 15)
type	CharWord and draws the characteristic and anti-characteristic words; quanti draws characteristic words for all quantitative variables; quali draws only the words for one qualitative variable (by default CharWord)
context.sup	number or index of qualitative contextual variable to be plotted (only one at a time) (by default NULL)
...	further arguments passed to or from other methods...

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Monica Bécue-Bertaut, Josep-Anton Sánchez-Espigares

See Also

[LexChar](#), [print.LexChar](#), [summary.LexChar](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Edu", Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
LD<-LexChar(res.TD,maxCharDoc = 0)
# plot(LD)
```

plot.LexCHCca

*Plots for Chronological Constrained Hierarchical Clustering from
LexCHCca Objects*

Description

Plots graphs from LexCHCca results: tree, barplot of the aggregation criterion values and first CA map with the documents colored in accordance with the cluster.

Usage

```
## S3 method for class 'LexCHCca'
plot(x, axes=c(1, 2), choice="tree", rect=TRUE, title=NULL, ind.names=TRUE,
  new.plot=FALSE, max.plot=15, tree.barplot=TRUE,...)
```

Arguments

x	object of LexCHCca class
axes	length-2 vector defining the axes of the CA map to plot (by default (1,2))
choice	type of graph. "tree" plots the tree; "bar" plots the barplot of the successive values of the aggregation criterion (downward reading of the tree); "map" plots the CA map where the individuals are colored in accordances with the cluster of belonging (by default "tree")
rect	if TRUE, when choice="tree" rectangles are drawn around the clusters (by default TRUE)
title	title of the graph. If NULL, a title is automatically defined (by default NULL)
ind.names	if TRUE, the document labels are written on the CA map (by default TRUE)
new.plot	if TRUE, a new window is opened (by default FALSE)
max.plot	maximum of bars in the bar plot of the aggregation criterion (by default 15)
tree.barplot	if TRUE, the barplot of intra inertia losses is added on the tree graph (by default TRUE)
...	further arguments passed from other methods...

Value

Returns the chosen plot

Author(s)

Mónica Bécue-Bertaut, Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Josep-Anton Sánchez-Espigares

See Also[LexCHCca](#)**Examples**

```
## Not run:
data(open.question)
res.TD<-TextData(open.question,var.text=c(9,10), var.agg="Age_Group", Fmin=10, Dmin=10,
  stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, graph=FALSE)
res.chcca<-LexCHCca(res.LexCA, nb.clust=4, min=3, graph=FALSE)
plot(res.chcca, choice="tree")
plot(res.chcca, choice="map")
plot(res.chcca, choice="bar", max.plot=5)

## End(Not run)
```

plot.LexGalt

*Plot of LexGalt objects***Description**

Plots Generalised Aggregate Lexical Tables (LexGalt) graphs from a LexGalt object

Usage

```
## S3 method for class 'LexGalt'
plot(x,type="QL", selDoc=NULL, selWord=NULL, selQualiVar=NULL,
  selQuantiVar=NULL, conf.ellip=FALSE, selWordEllip=NULL, selQualiVarEllip=NULL,
  selQuantiVarEllip=NULL, level.conf=0.95, eigen=FALSE, title = NULL, axes = c(1, 2),
  xlim = NULL, ylim = NULL, col.eig="grey", col.doc = "black", col.word = NULL,
  col.quali = "blue", col.quant = "blue", col="grey", pch = 20, label = TRUE,
  autoLab = c("auto", "yes", "no"), palette = NULL, unselect = 1,
  selCov=FALSE, selGroup="ALL", partial=FALSE, plot.group=FALSE,
  col.group=NULL, label.group=NULL, legend=TRUE, pos.legend="topleft",
  new.plot = TRUE, cex=1,...)
```

Arguments

x	object of LexGalt class
type	results from a qualitative analysis (type="QL") or quantitative analysis (type="QN"); see details; by default Q)
selDoc	vector with the documents to plot (indexes, names or rules; see details; by default NULL)
selWord	vector with the words to plot (indexes, names or rules (indexes, names or rules; see details; by default NULL)
selQualiVar	vector with the categories of categorical variables to plot (indexes, names or rules; see details; by default NULL)
selQuantiVar	vector with the numerical variables to plot (indexes, names or rules; see details; by default NULL)

<code>conf.ellip</code>	to drawn confidence ellipses, by default FALSE
<code>selWordEllip</code>	vector with the words that defines which ellipses are drawn (indexes, names or rules; see details; by default NULL)
<code>selQualiVarEllip</code>	vector with the categories of categorical variables which ellipses are drawn (indexes, names or rules; see details; by default NULL)
<code>selQuantiVarEllip</code>	vector with the numerical variables which ellipses are drawn (indexes, names or rules; see details; by default NULL)
<code>level.conf</code>	level of confidence used to construct the ellipses; by default 0.95
<code>eigen</code>	if TRUE, the eigenvalues barplot is drawn (by default FALSE); other elements can be simultaneously selected
<code>title</code>	title of the graph (by default NULL and the title is automatically assigned)
<code>axes</code>	length-2 vector indicating the axes considered in the graph; by default c(1,2)
<code>xlim</code>	range for 'x' values on the graph, defaulting to the finite values of 'x' range (by default NULL)
<code>ylim</code>	range for the 'y' values on the graph, defaulting to the the finite values of 'y' range (by default NULL)
<code>col.eig</code>	value or vector with colors for the bars of eigenvalues (by default "grey")
<code>col.doc</code>	color for the point-documents (by default "black")
<code>col.word</code>	color for the point-words (by default NULL is darkred in simple analysis; see details)
<code>col.quali</code>	color for the categories of categorical variables (by default "blue")
<code>col.quant</code>	color for the numerical variables (by default "blue")
<code>col</code>	color for the bars in the eigenvalues barplot (by default "grey")
<code>pch</code>	plotting character for coordinates, cf. points function in the graphics package
<code>label</code>	a list of character for the elements which are labelled (by default TRUE and all the drawn elements are labelled).
<code>autoLab</code>	if autoLab="auto", autoLab turns to be equal to "yes" if there are less than 50 elements and equal to "no" otherwise; if "yes", the labels are moved, as little as possible, to avoid overlapping (time-consuming if many elements); if "no" the labels are placed quickly but may overlap
<code>palette</code>	the color palette used to draw the points. By default colors are chosen. If you want to define the colors : <code>palette=palette(c("black", "red", "blue"))</code> ; or you can use: <code>palette=palette(rainbow(30))</code> , or in black and white for example: <code>palette=palette(gray(seq(0,.9,len=25)))</code>
<code>unselect</code>	may be either a value between 0 and 1 that gives the transparency of the unselected objects (if unselect=1 the transparency is total and the elements are not drawn, if unselect=0 the elements are drawn as usual but without any label) or may be a color (for example unselect="grey60")
<code>selCov</code>	a boolean, if TRUE then data are scaled to unit variance (by default TRUE)
<code>selGroup</code>	vector with the groups to plot if multiple analysis was performed (indexes, names or rules; see details; by default NULL)
<code>partial</code>	if partial elements (results for the groups) are shown (TRUE or ALL) and results for the conjoint analysis (FALSE or ALL); by default FALSE

plot.group	draw a plot comparing the groups in multiple case (by default TRUE)
col.group	color for the groups if multiple analysis was performed (by default NULL and they are selected from palette)
label.group	a vector containing the new name of the groups. If "BLANK" no labels with the group are added at the end of the drawn elements (by default, NULL and the name of each group is added)
legend	sho2 the legend of labels of groups. See legend from graphics package (by default TRUE)
pos.legend	position of the legend of labels of groups. See legend from graphics package (by default "topleft")
new.plot	if TRUE, a new graphical device is created (by default TRUE)
cex	text and symbol size is scaled by cex, in relation to size 1 (by default 1)
...	further arguments passed from other methods...

Details

The argument `autoLab = "yes"` is time-consuming if many overlapping labels. Furthermore, the visualization of the words cloud can result distorted because of the apparent greater dispersion of the words labels. An alternative would be reducing the character size of the words labels to reduce overlapping (e.g. `cex=0.7`).

`selDoc`, `selWord`, `selQualiVar=NULL` and `selQuantiVar=NULL`, `selWordEllip`, `selQualiVarEllip`, `selQuantiVarEllip` allow for selecting all or part of the elements of the corresponding type, using either labels, indexes or rules.

The syntax is the same for all types.

1. Using labels:

`selDoc = c("doc1", "doc5")`: only the documents with labels `doc1` and `doc5` are plotted.
`selQualiVar=c("category1", "category2")`: only the categories labeled `category1` and `category2` are plotted.

2.- Using indexes:

`selDoc = c(1:5)`: documents 1 to 5 are plotted.
`quali.sup=c(1:5,7)`: categories 1 to 5 and 7 are plotted. The numbering of the categories have to be consulted in the LexGalt numerical results.

3.- Using rules: Rules are based on the coordinates (`coord`), the contribution (`contrib` or `meta`) or the square cosine (`cos2`).

Somes examples are given hereafter:

`selDoc="coord 10"`: only the 10 documents with the highest coordinates, as globally computed on the 2 axes, are plotted.
`selWord="contrib 10"`: the words with a contribution to the inertia, of any of the 2 axes.
`selWord="meta 3"`: the words with a contribution over 3 times the average word contribution on any of the two axes are plotted.
`selWord="cos2 .85"`: the words with a `cos2` over 0.85, as summed on the 2 axes, are plotted.

```
col.word by default NULL is "darkred" for simple analysis, if it is null takes
the colors from col.group
i.e. col.group=c("red","blue"). To select the colors for some words in object res,
we can use:
str.col.words <- rep("darkred",nrow(res$MQL$word$coord))
str.col.words[which(rownames(res$MQL$word$coord) == "kids")] <- "red"
str.col.words[which(rownames(res$MQL$word$coord) == "friends")] <- "green"
str.col.words[which(rownames(res$MQL$word$coord) == "job")] <- "pink"
plot(res, selGroup=1, selWord=c("friends", "job", "kids", "at"),new.plot=FALSE,
col.group=c("darkred","blue"), autoLab = "yes", col.word=str.col.words)
```

Author(s)

Belchin Kostov, Monica Bécue-Bertaut, Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Josep-Antón Sánchez-Espigares

References

Bécue-Bertaut M. and Pagès J. (2015). Correspondence analysis of textual data involving contextual information: CA-GALT on principal components. *Advances in Data Analysis and Classification*, vol.(9) 2: 125-142.

Bécue-Bertaut M., Pagès J. and Kostov B. (2014). Untangling the influence of several contextual variables on the respondents' lexical choices. A statistical approach. *SORT - Statistics and Operations Research Transactions*, vol.(38) 2: 285-302.

Kostov B. A. (2015). A principal component method to analyse disconnected frequency tables by means of contextual information. (Doctoral dissertation). Retrieved from <http://upcommons.upc.edu/handle/2117/95759>.

See Also

[LexGalt](#)

Examples

```
## Not run:
data(open.question)

res.TD<-TextData(open.question,var.text=c(9,10), Fmin=10, Dmin=10,
context.quali=c("Gender", "Age_Group", "Education"),
remov.number=TRUE, stop.word.tm=TRUE)

res.LexGalt <- LexGalt(res.TD, graph=FALSE, nb.ellip =0)
plot(res.LexGalt, selQualiVar="ALL")

## End(Not run)
```

plot.LexHCca

Plots for Hierarchical Clustering from LexHCca Objects

Description

Plots graphs from LexHCca results: tree and CA maps with the documents or words colored in accordance with the cluster.

Usage

```
## S3 method for class 'LexHCca'
plot(x, type="map", plot=c("points", "labels", "centers"), selClust="ALL",
     selInd="ALL", axes=c(1, 2), theme=theme_bw(), palette=NULL, title=NULL,
     axis.title=NULL, axis.text=NULL, points=NULL, labels=NULL, centers=NULL,
     traject=NULL, hull=NULL, xlim=NULL, ylim=NULL, hvline=TRUE,...)
```

Arguments

x	object of LexHCca class
type	type of graph. "map" plots the CA map where the individuals are colored in accordance with the cluster of belonging (by default); "tree" plots the dendrogram if hierarchical method without consolidation is performed from LexHCca. See details)
plot	elements to plot for map graph: points, labels, centers, hull or traject; by default "ALL" and points, labels and centers are plotted. Also combinations are allowed, i.e: plot=c(points,centers)
selClust	vector indexes with the numbers of the clusters to plot (by default "ALL")
selInd	vector with the active documents/words to plot (indexes, names or rules; see details; by default "ALL")
axes	length-2 vector indicating the axes of the CA map to plot; by default (1,2)
theme	used to modify the theme settings by ggplot2 package (by default theme_bw())
palette	color palette used to draw the clusters. As many numbers as clusters. See details
title	title of the graph. If NULL, a title is automatically defined (by default NULL). Other parameters can be chosen using a list: text, color, size, family, face, just; See details
axis.title	axis titles parameters can be used: text.x, text.y, color, size, family, face, just; If text.x and text.y are NULL automatic texts are plotted (by default NULL). See details
axis.text	format of numbers can be chosen: color, size, family, face; See details
hvline	horizontal (intercept.y) and vertical line (intercept.x) added by default at (0,0) position in map. Parameters: intercept.y, intercept.x, linetype (by default "dashed"), color, size, alpha.t
points	format of points. Parameters: size (if size=0 the points are no plotted), shape (by default 21), fill (if a color, the same for all the points, if color is NULL palette colors used for the clusters are applied; if more than one color use palette argument; only for shapes from 21 to 25 to fill the point), stroke (controls the edge of the point (by default 0 no edge), border (color of the border, same specifications than fill), alpha.t (by default 1). See geom_point() in ggplot2 library. See details
labels	format of labels. Parameters: size (if size=0 the labels are not plotted; by default 4), family, face, hjust, vjust, color.text, alpha.t.text, numbers(if TRUE the label will be replaced by the number of the cluster to which it belongs, by default FALSE), rect (if TRUE a rectangle will be drawn around the label, by default FALSE), color.fill (color into the rectangle, by default FALSE is transparent), alpha.t.fill, force (to do repulsive textual annotations and make it easier to read), max.overlaps (maximum number of overlapped points, by default 10, can be Inf) set.seed (by default a new seed for each plot draws different positions, for the same seed i.e: set.seed=1234)

traject	draws trajectory arrows in accordance with the order of clusters or in the selInd order. Parameters: color (by default blue), linetype (by default 1 solid), space (by default 0 and no space is added from point to arrow, be careful with this value), size (width, by default 1), arrow.length (of the arrow, by default .3), arrow.type (by default "closed"), arrow.angle (by default 30), alpha.t. See geom_segment for details
centers	draws the barycenter of the clusters. Parameters: size (by default 5), family, face, color (of the border, only one), fill, alpha.t, labels (string vector with the names of the clusters)
hull	draws a hull containing all the elements of each cluster. Parameters: type (ellipse, by default, hull), alpha.t, color, linetype (by default "dotted")
xlim	pair of values xlim=c(xmin,ymax). If a NA value, this limit is automatically calculated
ylim	pair of values ylim=c(ymin,ymax). If a NA value, this limit is automatically calculated
...	other arguments from other methods

Details

Parameter type="tree" shows the dendrogram

- if hierarchical cluster without consolidation is performed.
- if hierarchical cluster with consolidation before the consolidation.
- if kmeans the hierarchical tree with the output of kmeans.

You can make customer dendrograms by accessing the hclust format object located inside the object in hclust format from object\$call\$tree

Selection of individuals (documents or words) to plot:

1. Using labels:

selInd = c("doc1", "doc5"): only the documents with labels doc1 and doc5 are plotted.

2. Using indexes:

selInd = c(1:5): cases 1 to 5 are plotted.

3. Using rules:

Rules are based on the coordinates (coord), the contribution (contrib or meta; concerning only active elements) or the square cosine (cos2).

Somes examples hereafter:

selInd="coord 10": only the 10 cases with the highest coordinates, as globally computed on the 2 axes, are plotted.

selInd="contrib 10": the cases with a contribution to the inertia, of any of the 2 axes over 10 percent.

selInd="meta 3": the cases with a contribution over 3 times the average word/document contribution on any of the two axes are plotted.

selInd="cos2 .85": the documents with a cos2 over 0.85, as summed on the 2 axes, are plotted.

Parameters can be used in combination, e.g.: `title=c("text"="CA", "color"="red")`.

See `grDevices` package (The R Graphics Devices and Support for Colours and Fonts).

`palette`, the color of the palette used to draw the points. By default colors are chosen. If you want to define the colors : `palette=c("black","red","blue")`; or you can use: `palette=palette(rainbow(30))`, or in black and white for example: `palette=palette(gray(seq(0,.9,len=25)))`.

Family Fonts (`family`). Also see the `extrafont` package for a much better support of fonts: `library(extrafont)`; `font_import()`. By default `"family"='serif'`.

Face fonts (`face`). Can be `'plain'`, `'bold'`, `'italic'`, `'bold.italic'`, `'symbol'`. By default `'plain'`.

`alpha.t` is the level of transparency for some objects. 0 value means full transparency and 1 opacity. By default 1.

Values for horizontal justification `hjust`, vertical `vjust` and both `hjust` can be (`c`,centered or 0.5 if centered; `l`,left or 0 if left; `r`, right or 1 if right)

By default in:

```
* title= text="Clusters on the CA map"; color=black; size=18; family=serif; face=plain;
  hjust=0.5.
```

```
* axis titles: text.x=Dim x (%), text.y=Dim y (%), color=black, size=12, family=serif,
  face=plain, just=centered.
```

```
* axis.text: color=black, size=8, family=serif, face=plain.
```

```
* hvline: intercept.x=0, intercept.y=0, linetype=dashed, color=gray, size=0.5, alpha.t=1.
```

```
* points: size=2, shape=21, border:automatic cluster color, fill:automatic cluster color,
  stroke=0, border: automatic cluster color, alpha.t=1.
```

```
* labels: size=4, family=serif, face=plain, hjust=1, vjust=1, color.text=same of points,
  alpha.t.text=1, numbers=FALSE, rect=FALSE, color.fill=transparent, alpha.t.fill=1,
  force=1, max.overlaps=10.
```

```
* trajet: color=blue, linetype=solid, space=1, arrow.length=.3, arrow.type= closed,
  arrow.angle=30, alpha.t=1.
```

```
* centers: size=5, family=serif, face=italic, color, fill=automatic cluster color,
  alpha.t=1, labels=automatic string vector with the names of the clusters.
```

```
* hull: type=ellipse, alpha.t=0.1, color=black, linetype=dotted
```

Author(s)

Ramón Álvarez-Esteban <ramon.alvarez@unileon.es>, Mónica Bécue-Bertaut, Josep-Anton Sánchez-Espigares

References

The Xplortext web site provides several examples at <https://xplortext.unileon.es/?page_id=766>.

See Also

[LexHCca](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question,var.text=c(9,10), var.agg="Age_Group", Fmin=10, Dmin=10,
  stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, graph=FALSE)
res.chcca<-LexHCca(res.LexCA, nb.clust=4, min=3, graph=FALSE)
plot(res.chcca, type="tree")
plot(res.chcca, type="map")
```

plot.TextData	<i>Plot TextData objects</i>
---------------	------------------------------

Description

Draws the barcharts of the longest documents, most frequent words and segments from a TextData object.

Usage

```
## S3 method for class 'TextData'
plot(x, ndoc=25, nword=25, nseg=25, sel=NULL, stop.word.tm=FALSE,
  stop.word.user=NULL, theme=theme_bw(), title=NULL, xtitle=NULL, col.fill="grey",
  col.lines="black", text.size=12, freq=NULL, vline=NULL,...)
```

Arguments

x	object of TextData class
ndoc	number of documents in the barchart (by default 25)
nword	number of words in the barchart (by default 25)
nseg	number of segments in the barchart (by default 25)
sel	type of barchart (doc, word or seg for documents, words or repeated segments) (by default NULL and all the barchart are draw)
stop.word.tm	the tm stopwords are not considered for the barchart (by default FALSE)
stop.word.user	the user's stopwords are not considered for the barchart (by default NULL)
theme	theme settings (see ggplot2 package; by default theme_bw())
title	title of the graph (by default NULL and the title is automatically assigned)
xtitle	x title of the graph (by default NULL and the x title is automatically assigned)
col.fill	background color for the barChart bars (by default grey)
col.lines	lines color for the barChart bars (by default black)
text.size	text font size (by default 12)
freq	add frequencies to word and document barplots, see details (by default NULL)
vline	if "YES" or TRUE add vertical line to barplot, see details (by default NULL)
...	further arguments passed to or from other methods...

Details

freq adds frequencies to barplot (by default NULL). If "YES" or TRUE displays the frequencies at the right of the bars at +5 position. Numerical values display the frequencies at the right positions (positive values) or at the left (negative values).

vline adds a vertical line to barplot (by default NULL). If TRUE a vertical line is added at mean level. If "median" a vertical line is added at median level. If a number a vertical line is added at the number frequency level.

By default barchart selected in sel argument (doc, word and/or repeated segments) in ggplot format. Barchart is used with geom_bar function of ggplot package. If it is only one element in sel argument the plot can be saved in ggplot format: newobject <- plot(TextDataObject,sel="word")

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Mónica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

See Also

[TextData](#), [print.TextData](#), [summary.TextData](#)

Examples

```
# Non aggregate analysis

data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), remov.number=TRUE, Fmin=10, Dmin=10,
stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"), context.quanti=c("Age"))
plot(res.TD)

# Aggregate analysis
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Age", remov.number=TRUE,
Fmin=10, Dmin=10, stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"),
context.quanti=c("Age"), segment=TRUE)
plot(res.TD)
```

print.LexCA

Print LexCA objects

Description

Prints the Textual Correspondence Analysis (CA) results from a LexCA object

Usage

```
## S3 method for class 'LexCA'
print(x, file = NULL, sep=";", ...)
```

Arguments

x	object of LexCA class
file	a connection, or a character string giving the name of the file to print to (in csv format). If NULL (the default), the results are not printed in a file
sep	character to insert between the objects to print (if the argument file is non-NULL) (by default ";")
...	further arguments passed to or from other methods

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Mónica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

See Also

[LexCA](#), [plot.LexCA](#), [summary.LexCA](#), [TextData](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question,var.text=c(9,10), var.agg="Age_Group", Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD,lmd=0,lmw=1)
print(res.LexCA)
```

print.LexChar	<i>Print LexChar objects</i>
---------------	------------------------------

Description

Prints characteristic words and documents from LexChar objects

Usage

```
## S3 method for class 'LexChar'
print(x, file = NULL, sep=";", dec=".", ...)
```

Arguments

x	object of LexChar class
file	a connection, or a character string giving the name of the file to print to (in csv format). If NULL (the default), the results are not printed in a file
sep	character to insert between the objects to print (if the argument file is non-NULL) (by default ";")
dec	decimal point (by default ".")
...	further arguments passed to or from other methods

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Mónica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

See Also

[LexChar](#), [plot.LexChar](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Edu", Fmin=10, Dmin=10,
  stop.word.tm=TRUE)
LD<-LexChar(res.TD, maxCharDoc = 0)
print(LD)
```

print.TextData	<i>Print TextData objects</i>
----------------	-------------------------------

Description

Print statistical results for documents, words and segments from TextData objects, in alphabetical and frequency order.

Usage

```
## S3 method for class 'TextData'
print(x, file = NULL, sep=";", ...)
```

Arguments

x	object of TextData class
file	connection, or character string giving the name of the file to print to (in csv format). If NULL (by default value), the results are not printed in a file
sep	character inserted between the objects to print (if file argument is non-NULL) (by default ";")
...	further arguments passed to or from other methods

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Monica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

See Also

[TextData](#), [plot.TextData](#), [summary.TextData](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), remov.number=TRUE, Fmin=10, Dmin=10,
  stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"),
  context.quantit=c("Age"))
print(res.TD)
```

summary.LexCA

*Summary LexCA object***Description**

Summarizes LexCA objects

Usage

```
## S3 method for class 'LexCA'
summary(object, ncp=5, nb.dec = 3, ndoc=10, nword=10, nseg=10,
        nsup=10, metaDocs=FALSE, metaWords=FALSE, file = NULL, ...)
```

Arguments

object	object of LexCA class
ncp	number of dimensions to be printed (by default 5)
nb.dec	number of decimal digits to be printed (by default 3)
ndoc	number of documents whose coordinates are listed (by default 10). Use ndoc="ALL" to have the results for all the documents. Use ndoc=0 or ndoc=NULL if the results for documents are not wanted.
nword	number of words whose coordinates are listed (by default 10). Use nword="ALL" to have the results for all the words. Use nword=0 or nword=NULL if the results for words are not wanted
nseg	number of repeated segments whose coordinates are listed (by default 10). Use nseg="ALL" to have the results for all the segments. Use nseg=0 or nseg=NULL if the results for segments are not wanted
nsup	number of supplementary elements whose coordinates are listed (by default 10). Use nsup="ALL" to have the results for all the elements. Use nsup=0 or nsup=NULL if the results for the supplementary elements are not wanted
metaDocs	axis by axis, the highest contributive documents are listed, separately for negative-part and positive-part documents; these documents have been identified in LexCA, taking into account lmd value (by default FALSE)
metaWords	axis by axis, the highest contributive words are listed, separately for negative-part and positive-part words; these words have been identified in LexCA, taking into account lmw value (by default FALSE)
file	a connection, or a character string naming the file to print to (csv format). If NULL (the default), the results are not printed in a file
...	further arguments passed from other methods

Author(s)

Ramón Álvarez-Esteban <ramon.alvarez@unileon.es>, Monica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

See Also

[LexCA](#), [print.LexCA](#), [plot.LexCA](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), Fmin=10, Dmin=10, stop.word.tm=TRUE)
res.LexCA<-LexCA(res.TD, lmd=1, lmw=1)
summary(res.LexCA)
```

summary.LexChar

*Summary LexChar object***Description**

Summarizes LexChar objects

Usage

```
## S3 method for class 'LexChar'
summary(object, CharWord=TRUE, stats=TRUE, CharDoc=TRUE, Vocab=TRUE,
        file = NULL, ...)
```

Arguments

object	object of TextData class
CharWord	if TRUE characteristic words of all the documents are shown (by default TRUE)
stats	if TRUE association statistics of lexical table are shown (by default TRUE)
CharDoc	if TRUE characteristic source-documents of all the aggregate-documents are shown (by default TRUE)
Vocab	if TRUE characteristic quantitative and qualitative variables of the words. CharWord and stats are provide
file	a connection, or a character string naming the file to print to in csv format. If NULL (the default), the results are not printed in a file
...	further arguments passed to or from other methods,...

Details

Vocab\$quali\$CharWord provides the qualitative variables and their categories. Vocab\$quali\$stats provides association statistics for vocabulary and qualitative variables. Vocab\$quanti\$CharWord provides characteristic quantitative variables for each word. This summary.LexChart function provides the characteristic words for each quantitative variable. Vocab\$quali\$stats provides statistics for vocabulary and quantitative variables.

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Monica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

See Also

[LexChar](#), [print.LexChar](#), [plot.LexChar](#)

Examples

```
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Edu", Fmin=10, Dmin=10,
  remov.number=TRUE, stop.word.tm=TRUE)
res.LexChar <-LexChar(res.TD)
summary(res.LexChar)
```

summary.TextData

*Summary of TextData objects***Description**

Summarizes TextData objects.

Usage

```
## S3 method for class 'TextData'
summary(object, ndoc=10, nword=50, nseg=50, ordFreq = TRUE, file = NULL, sep=";",
  ...)
```

Arguments

object	object of TextData class
ndoc	statistical report on the first ndoc documents (by default 10). Use ndoc="ALL" to have the results for all the documents. Use ndoc=0 or ndoc=NULL if the results on the documents are not wanted
nword	index of the nword first words (by default 50). Use nword="ALL" to have the complete index. Use nword=0 or nword=NULL if the results on the words are not wanted
nseg	index of the nfirst nseg repeated segments (by default 50). Use nseg="ALL" to have the complete list of segments. Use nseg=0 or nseg=NULL if the results on the segments are not wanted
ordFreq	if ordFreq=TRUE, glossaries of words and repeated segments, are listed in frequency order; if ordFreq=FALSE, glossaries are listed in alphabetic order (by default TRUE)
file	a connection, or a character string naming the file to print to in csv format. If NULL (the default), the results are not printed in a file
sep	character string to insert between the objects to print (if the argument file is not NULL) (by default ";")
...	further arguments passed to or from other methods,...

Author(s)

Ramón Álvarez-Esteban <ramon.alvarez@unileon.es>, Monica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

See Also

[TextData](#), [print.TextData](#), [plot.TextData](#)

Examples

```
# Non aggregate analysis
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), remov.number=TRUE, Fmin=10, Dmin=10,
  stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"), context.quanti=c("Age"))
summary(res.TD)

# Aggregate analysis and repeated segments
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Age", remov.number=TRUE,
  Fmin=10, Dmin=10, stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"),
  context.quanti=c("Age"), segment=TRUE)
summary(res.TD)
```

TextData

Building textual and contextual tables (TextData)

Description

Creates a textual and contextual working-base (TextData format) from a source-base (data frame format).

Usage

```
TextData(base, var.text=NULL, var.agg=NULL, context.quali=NULL, context.quanti=NULL,
  selDoc="ALL", lower=TRUE, remov.number=TRUE, lminword=1, Fmin=Dmin, Dmin=1, Fmax=Inf,
  stop.word.tm=FALSE, idiom="en", stop.word.user=NULL, segment=FALSE,
  sep.weak="(['?]|[:punct:]]|[:space:]]|[:cntrl:]])+",
  sep.strong="\u005B()\u00BF?./:\u00A1!=+;{}-\u005D", seg.nfreq=10, seg.nfreq2=10,
  seg.nfreq3=10, graph=FALSE)
```

Arguments

base	source data frame with at least one textual column
var.text	vector with index(es) or name(s) of the selected textual column(s) (by default NULL)
var.agg	index or name of the aggregation categorical variable (by default NULL)
context.quali	vector with index(es) or name(s) of the selected categorical variable(s) (by default NULL)
context.quanti	vector with index(es) or name(s) of the selected quantitative variable(s) (by default NULL)
selDoc	vector with index(es) or name(s) of the selected source-documents (rows of the source-base) (by default "ALL")
lower	if TRUE, the corpus is converted into lowercase (by default TRUE)
remov.number	if TRUE, numbers are removed (by default TRUE)
lminword	minimum length of a word to be selected (by default 1)
Fmin	minimum frequency of a word to be selected (by default Dmin)
Dmin	a word has to be used in at least Dmin source-documents to be selected (by default 1)

<code>Fmax</code>	maximum frequency of a word to be selected (by default <code>Inf</code>)
<code>stop.word.tm</code>	if <code>TRUE</code> , stoplist automatically provided in accordance with the idiom (by default <code>FALSE</code>)
<code>idiom</code>	declared idiom for the textual column(s) (by default English "en", see IETF language in package <code>NLP</code>)
<code>stop.word.user</code>	stoplist provided by the user
<code>segment</code>	if <code>TRUE</code> , the repeated segments are identified (by default <code>FALSE</code>)
<code>sep.weak</code>	string with the characters marking out the terms (by default punctuation characters, space and control). See details
<code>sep.strong</code>	string with the characters marking out the repeated segments (by default "[()??./:?!=+;-\\]")
<code>seg.nfreq</code>	minimum frequency of a more-than-three-words-long repeated segment (by default 10)
<code>seg.nfreq2</code>	minimum frequency of a two-words-long repeated segment (by default 10)
<code>seg.nfreq3</code>	minimum frequency of a three-words-long repeated segment (by default 10)
<code>graph</code>	if <code>TRUE</code> , documents, words and repeated segments barcharts are displayed; use <code>plot.TextData</code> to use more options (by default <code>FALSE</code>)

Details

Each row of the source-base is considered as a source-document. `TextData` function builds the working-documents-by-words table, submitted to the analysis.

`sep.weak` contains the string with the characters marking out the terms (by default punctuation characters, space and control). Backslash or double backslash are used to start an escape sequence defining special characters. Each special character must be separated the symbol `|` (or) in `sep.weak` and `sep.strong`. For example:

```
sep.weak = "[[space]]|!|;|\\.|\\.|\\(|\\)|#|:|_|%|_\\u0022"
```

Some special characters can be introduced as unicode characters.

Information related to `context.quant` and `context.quali` arguments:

1. If numeric, contextual variables can be included in both vectors. The function `TextData` converts the numeric variable into factor to include it in `context.quali` vector. This possibility is interesting in some cases. For example, when treating open-ended questions, we can be interested in computing the correlation between the contextual variable "Age" and the axes and, at the same time, to draw the trajectory of the different values of "Age" (year by year) on the CA maps.
2. In the case of one or several columns with textual data not selected in vector `var.text`, if the argument `context.quali` is equal to "ALL", these columns will be considered as categorical variables.

Non-aggregate table versus aggregate table.

If `var.agg=NULL`:

1. The work-documents are the non-empty-source-documents.
2. `DocTerm`: non-aggregate lexical table with:

as many rows as non-empty source-documents
as many columns as words are selected.

3. `context$quali`: data frame crossing the non-empty source-documents (rows) and the categorical contextual-variables (columns).
4. `context$quanti`: data frame crossing the non-empty source-documents (rows) and the quantitative contextual-variables (columns). Both contextual tables can be juxtaposed row-wise to DocTerm table.

If `var.agg` is NON-NULL:

1. The work-documents are aggregate-documents, issued from aggregating the source-documents depending on the categories of the aggregation variable; the aggregate-documents inherit the names of the corresponding categories.
2. DocTerm is an aggregate table with:
 - as many rows as as categories the aggregation variable has
 - as many columns as words are selected.
3. `context$quali$qualitable`: juxtaposes as many supplementary aggregate tables as categorical contextual variables. Each table has:
 - as many rows as categories the contextual categorical variable has
 - as many columns as selected words, i.e. as many columns as DocTerm has.
4. `context$quali$qualivar`: names of categories of the supplementary categorical variables.
5. `context$quanti`: data frame crossing the working aggregate-documents (rows) and the quantitative contextual-variables (columns). The value for an active aggregate-document is the mean-value of the source-documents belonging to this aggregate-document.

Value

A list including:

<code>summGen</code>	general summary
<code>summDoc</code>	document summary
<code>indexW</code>	index of words
<code>DocTerm</code>	working lexical table (non-aggregate or aggregate table depending on <code>var.agg</code> value); working-documents by words table in slam package compressed format
<code>context</code>	contextual variables if <code>context.quali</code> or <code>context.quanti</code> are non-NULL; the structure greatly differs in accordance with the nature of DocTerm table (non-aggregate/aggregate), see details
<code>info</code>	information about the selection of words
<code>var.agg</code>	a one-column data frame with the values of the aggregation variable; NULL if non-aggregate analysis
<code>SourceTerm</code>	in the case of DocTerm being an aggregate analysis, the source-documents by words table is kept in this data structure, in slam package compressed format
<code>indexS</code>	working-documents by repeated-segments table, in slam package compressed format
<code>remov.docs</code>	vector with the names of the removed empty source-documents

Author(s)

Ramón Alvarez-Esteban <ramon.alvarez@unileon.es>, Monica Bécue-Bertaut, Josep-Antón Sánchez-Espigares

References

Lebart, L., Salem, A., & Berry, L. (1998). Exploring textual data. (D. Kluwer, Ed.). doi: [10.1007/9789401715256](https://doi.org/10.1007/9789401715256).

See Also

[print.TextData](#), [summary.TextData](#), [plot.TextData](#)

Examples

```
# Non aggregate analysis
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), remov.number=TRUE, Fmin=10, Dmin=10,
  stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"), context.quanti=c("Age"))

# Aggregate analysis and repeated segments
data(open.question)
res.TD<-TextData(open.question, var.text=c(9,10), var.agg="Gen_Age", remov.number=TRUE,
  Fmin=10, Dmin=10, stop.word.tm=TRUE, context.quali=c("Gender","Age_Group","Education"),
  context.quanti=c("Age"), segment=TRUE)
```


Index

* **datasets**
open.question, 17

* **multivariate**
ellipseLexCA, 3
LabelTree, 5
LexCA, 6
LexChar, 9
LexCHCca, 11
LexGalt, 13
LexHCca, 15
TextData, 37

* **plot**
plot.LexCA, 18
plot.LexChar, 21
plot.LexCHCca, 22
plot.LexGalt, 23
plot.LexHCca, 26
plot.TextData, 30

* **print**
print.LexCA, 31
print.LexChar, 32
print.TextData, 33

* **summary**
summary.LexCA, 34
summary.LexChar, 35
summary.TextData, 36

ellipseLexCA, 3, 8

LabelTree, 5, 12

legend, 25

LexCA, 5, 6, 6, 12, 17, 20, 32, 34

LexChar, 9, 21, 33, 35

LexCHCca, 6, 11, 23

LexGalt, 13, 26

LexHCca, 15, 29

open.question, 17

plot.LexCA, 5, 8, 18, 32, 34

plot.LexChar, 10, 21, 33, 35

plot.LexCHCca, 12, 22

plot.LexGalt, 13, 14, 23

plot.LexHCca, 17, 26

plot.TextData, 30, 33, 36, 40

points, 24

print.LexCA, 5, 8, 20, 31, 34

print.LexChar, 10, 21, 32, 35

print.TextData, 31, 33, 36, 40

summary.LexCA, 5, 8, 20, 32, 34

summary.LexChar, 10, 21, 35

summary.TextData, 31, 33, 36, 40

TextData, 8, 10, 31–33, 36, 37

Xplor-text-package, 2