

# Package ‘BiostatsUHNplus’

September 10, 2025

**Title** Nested Data Summary, Adverse Events and REDCap

**Version** 1.0.3

**Description** Tools and code snippets for summarizing nested data, adverse events and REDCap study information.

**License** MIT + file LICENSE

**Depends** R (>= 4.2)

**Imports** afex, coda, cowplot, dplyr, forcats, ggh4x, ggplot2, ggpubr, lifecycle, MCMCglmm, modeest, openxlsx, parallel, parallelly, plyr, purrr, reportRmd, rlang, rstatix, stats, stringi, stringr, tibble, utils

**Suggests** testthat (>= 3.0.0)

**Config/testthat/edition** 3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.3.2

**Collate** 'data.R' 'globals.R' 'as\_numeric\_parse.R' 'covsum\_nested.R' 'dsmb\_ccru.R' 'nice\_mcmcglmm.R' 'nice\_mcmcglmm\_icc.R' 'ae\_timeline\_plot.R' 'caterpillar\_plot.R' 'redcap\_data\_out.R' 'rm\_ae\_all\_g3p.R' 'dsmb\_ddp.R'

**NeedsCompilation** no

**Author** Lisa Avery [aut] (ORCID: <<https://orcid.org/0000-0002-8431-5143>>),  
Zeynep Baskurt [aut],  
Osvaldo Espin-Garcia [aut],  
Katrina Hueniken [aut],  
Katherine Lajkosz [aut] (ORCID:  
<<https://orcid.org/0000-0003-3760-5401>>),  
Xuan Li [aut],  
Tyler Pittman [cre, aut] (ORCID:  
<<https://orcid.org/0000-0002-5013-6980>>),  
Anna Santiago [aut] (ORCID: <<https://orcid.org/0000-0002-0932-2386>>),  
Jessica Weiss [aut],  
Wei Xu [aut]

**Maintainer** Tyler Pittman <tyler.pittman@uhn.ca>

**Repository** CRAN

**Date/Publication** 2025-09-10 15:10:09 UTC

## Contents

ae . . . . .	2
ae_timeline_plot . . . . .	3
as_numeric_parse . . . . .	5
caterpillar_plot . . . . .	6
covsum_nested . . . . .	8
demography . . . . .	10
drug1_admin . . . . .	10
drug2_admin . . . . .	11
dsmb_ccru . . . . .	11
dsmb_ddp . . . . .	13
enrollment . . . . .	16
ineligibility . . . . .	16
nice_mcmcglmm . . . . .	17
nice_mcmcglmm_icc . . . . .	18
redcap_data_out . . . . .	19
rm_ae_all_g3p . . . . .	20
rm_covsum_nested . . . . .	22
<b>Index</b>	<b>26</b>

---

ae	<i>Simulated adverse events for patients receiving two study agents.</i>
----	--

---

## Description

Simulated adverse events for patients receiving two study agents.

## Usage

ae

## Format

A data frame with 394 rows and 9 variables:

**Subject** Patient ID

**ae\_detail** Adverse event detail, also known as lowest level term

**ae\_category** Adverse event category, also known as system organ class

**CTCAE5\_LLT\_NM** Common Terminology Criteria for Adverse Events (CTCAE) version 5

**AE\_VERBATIM\_TRM\_TXT** Adverse event verbatim text entered by clinical registered nurse, for "Other, specify"

**AE\_SEV\_GD** Adverse event severity grade, scale from 1 to 5

**AE\_ONSET\_DT\_INT** Adverse event onset date

**CTC\_AE\_ATTR\_SCALE** Attribution scale of adverse event to first study agent

**CTC\_AE\_ATTR\_SCALE\_1** Attribution scale of adverse event to second study agent

---

ae_timeline_plot	<i>Outputs related adverse event timeline plots including just system organ class (AE category), or system organ class and lowest level term (AE detail). This function can fit up to 5 different attributions. Modify width, height and scale parameters in ggsave() to customize fit for large plot.</i>
------------------	--

---

## Description

Outputs related adverse event timeline plots including just system organ class (AE category), or system organ class and lowest level term (AE detail). This function can fit up to 5 different attributions. Modify width, height and scale parameters in ggsave() to customize fit for large plot.

## Usage

```
ae_timeline_plot(
  subjID,
  subjID_ineligText = NULL,
  baseline_datasets,
  ae_dataset,
  ae_attribVars,
  ae_attribVarsName = NULL,
  ae_attribVarText = NULL,
  startDtVars,
  ae_detailVar,
  ae_categoryVar,
  ae_severityVar,
  ae_onsetDtVar,
  time_unit = c("day", "week", "month", "year"),
  include_ae_detail = TRUE,
  legendPerSpace = NULL,
  fonts = NULL,
  fontColours = NULL,
  panelColours = NULL,
  attribColours = NULL,
  attribSymbols = NULL,
  columnWidths = NULL
)
```

**Arguments**

subjID	key identifier field for participant ID in data sets
subjID_ineligText	character text that denotes participant IDs to exclude. For example, c("New Subject") (if provided)
baseline_datasets	list of data frames that contain baseline participant characteristics. For example, list(enrollment_DF,demography_DF,ineligibility_DF)
ae_dataset	data frame that contains subject AEs
ae_attrivVars	field(s) that denotes attribution to intervention under study. For example, c("CTC_AE_ATTR_SCALE","CTC_AE_ATTR_SCALE_1") (if provided)
ae_attrivVarsName	character text that denotes name of interventions under study. For example, c("Drug 1", "Drug 2") (if provided)
ae_attrivVarText	character text that denotes related attribution. For example c("Definite", "Probable", "Possible") (if provided)
startDtVars	field(s) that denotes participant start date (i.e. 10MAY2021). For example, it could be enrollment date or screening date. If more than one field given (unique names are required), each field is assumed to be specific start date for attribution in corresponding field order
ae_detailVar	field that denotes participant AE detail (lowest level term)
ae_categoryVar	field that denotes participant AE category (system organ class)
ae_severityVar	field that denotes participant AE severity grade (numeric)
ae_onsetDtVar	field that denotes participant AE onset date
time_unit	character text that denotes time unit for desired timeline. For example, could be one of c("day","week","month","year") (if provided)
include_ae_detail	boolean that denotes if AE detail should be included in timeline plot. Default is True
legendPerSpace	parameter at denotes proportion of vertical image space dedicated to legend at bottom. Default is 0.05 for AE detail and 0.1 for AE Category
fonts	character text that denotes font for AE category, AE detail, axis, legend and plot labels (if provided)
fontColours	character text that denotes system font colours for AE category and AE detail (if provided)
panelColours	character text that denotes panel background colours for AE category, AE detail and plot area (if provided)
attribColours	character text that denotes colours for attributions, supports up to 10 distinct colours (if provided)
attribSymbols	text that denotes median plot symbols for attributions, supports up to 10 distinct symbols (if provided)
columnWidths	text that denotes character columns widths for AE category and AE detail columns (if provided)

**Value**

ggplot object of AE timeline plot

**Examples**

```
data("drug1_admin", "drug2_admin", "ae");
p <- ae_timeline_plot(subjID="Subject",subjID_ineligText=c("01","11"),
  baseline_datasets=list(drug1_admin, drug2_admin),
  ae_dataset=ae,
  ae_attriVar=c("CTC_AE_ATTR_SCALE","CTC_AE_ATTR_SCALE_1"),
  ae_attriVarName=c("Drug 1","Drug 2"),
  ae_attriVarText=c("Definite", "Probable", "Possible"),
  startDtVars=c("TX1_DATE_INT","TX2_DATE_INT"),
  ae_detailVar="ae_detail",
  ae_categoryVar="ae_category",ae_severityVar="AE_SEV_GD",
  ae_onsetDtVar="AE_ONSET_DT_INT",time_unit="month",
  include_ae_detail=FALSE,
  fonts=c("Calibri","Albany AMT","Gadugi","French Script MT","Forte"),
  fontColours=c("#FFE135"),
  panelColours=c("#E52B50",NA,"#FFE4C4"),
  attribColours=c("#9AB973","#01796F","#FFA343","#CC7722"),
  attribSymbols=c(7,8,5,6),
  columnWidths=c(23))
```

---

as_numeric_parse	<i>Modification of the as.numeric function that prints entries that fail to parse as a message</i>
------------------	--

---

**Description**

Modification of the as.numeric function that prints entries that fail to parse as a message

**Usage**

```
as_numeric_parse(x)
```

**Arguments**

x                    string or vector to coerce to numeric

**Value**

No return value, called for side effects

**Examples**

```
z <- as_numeric_parse(c(1:5, "String1",6:10,"String2"))
z
```

---

caterpillar_plot	<i>Caterpillar plot. Useful for plotting random effects from hierarchical models, such as MCMCglmm::MCMCglmm() object, that have binary outcome.</i>
------------------	--

---

### Description

Caterpillar plot. Useful for plotting random effects from hierarchical models, such as MCMCglmm::MCMCglmm() object, that have binary outcome.

### Usage

```
caterpillar_plot(
  subjID,
  subjLabel = NULL,
  remove.text.subjID = FALSE,
  show.stats = TRUE,
  mcmcglmm_object,
  orig_dataset,
  binaryOutcomeVar,
  prob = NULL,
  title = NULL,
  no.title = FALSE,
  subtitle = NULL,
  ncol = NULL,
  fonts = NULL,
  columnTextWidth = NULL,
  break.label.summary = FALSE
)
```

### Arguments

subjID	key identifier field for participant ID in data sets
subjLabel	text label field in dataset to replace key identifier field for participant ID with in plot (if provided)
remove.text.subjID	boolean indicating if non-numeric text should be removed from subjID in plot label. Note that this can only be used if there are non-duplicate participant IDs when non-numeric text is removed. Default is FALSE (if provided)
show.stats	boolean indicating if (n, events) summary output should be shown in subject label
mcmcglmm_object	MCMCglmm model output
orig_dataset	data frame supplied to MCMCglmm function
binaryOutcomeVar	name of binary variable (0,1) that denotes outcome in MCMCglmm model

prob	probability for highest posterior density interval, similar to a confidence interval. Default is 0.95 (if provided)
title	title of the plot. Overrides default title (if provided)
no.title	boolean that denotes if title should be outputted in plot. Default is TRUE (if provided)
subtitle	subtitle of the plot. Overrides default subtitle (if provided)
ncol	number of columns in plot. Default is 2 (if provided)
fonts	character text that denotes font for title, subtitle, category labels, x-axis plot labels (if provided)
columnTextWidth	numeric that denotes character width for label text before breaking to start new line. Default is 20 characters (if provided)
break.label.summary	boolean to indicate if new line should start in label before (n, event) summary. Default is FALSE

### Value

ggplot object of caterpillar plot

### Examples

```

data("ae");

ae$G3Plus <- 0;
ae$G3Plus[ae$AE_SEV_GD %in% c("3", "4", "5")] <- 1;
ae$Drug_1_Attribution <- 0;
ae$Drug_1_Attribution[ae$CTC_AE_ATTR_SCALE %in% c("Definite", "Probable", "Possible")] <- 1;
ae$Drug_2_Attribution <- 0;
ae$Drug_2_Attribution[ae$CTC_AE_ATTR_SCALE_1 %in% c("Definite", "Probable", "Possible")] <- 1;

prior2RE <- list(R = list(V = diag(1), fix = 1),
  G=list(G1=list(V=1, nu=0.02), G2=list(V=1, nu=0.02)));

model1 <- MCMCglmm::MCMCglmm(G3Plus ~ Drug_1_Attribution + Drug_2_Attribution,
  random=~Subject + ae_category, family="categorical", data=ae, saveX=TRUE,
  verbose=FALSE, burnin=2000, nitt=10000, thin=10, pr=TRUE, prior=prior2RE);

p <- caterpillar_plot(subjID = "Subject",
  mcmcglmm_object = model1,
  prob = 0.99,
  orig_dataset = ae,
  binaryOutcomeVar = "G3Plus")

p <- caterpillar_plot(subjID = "ae_category",
  mcmcglmm_object = model1,
  prob = 0.95,
  orig_dataset = ae,
  remove.text.subjID = FALSE,

```

```

ncol = 4,
binaryOutcomeVar = "G3Plus",
subtitle = "System organ class (n, event)",
title = "Odds Ratio for G3+ Severity with 95% Highest Posterior Density Interval",
fonts = c("Arial", "Arial", "Arial", "Arial"),
break.label.summary = TRUE)

```

---

covsum\_nested

*Nested version of reportRmd covsum()*


---

### Description

Nested version of reportRmd covsum()

### Usage

```

covsum_nested(
  data,
  covs,
  maincov = NULL,
  id = NULL,
  digits = 1,
  numobs = NULL,
  markup = TRUE,
  sanitize = TRUE,
  nicenames = FALSE,
  IQR = FALSE,
  all.stats = FALSE,
  pvalue = TRUE,
  effSize = TRUE,
  show.tests = TRUE,
  nCores = NULL,
  nested.test = NULL,
  nsim = NULL,
  excludeLevels = NULL,
  dropLevels = TRUE,
  full = TRUE,
  digits.cat = 0,
  testcont = c("rank-sum test", "ANOVA"),
  testcat = c("Chi-squared", "Fisher"),
  include_missing = FALSE,
  percentage = c("column", "row")
)

```

### Arguments

data                    dataframe containing data



covs	character vector with the names of columns to include in table
maincov	covariate to stratify table by
id	covariates to nest summary by
digits	number of digits for summarizing mean data, does not affect p-values
numobs	named list overriding the number of people you expect to have the covariate
markup	boolean indicating if you want latex markup
sanitize	boolean indicating if you want to sanitize all strings to not break LaTeX
nicenames	boolean indicating if you want to replace . and _ in strings with a space
IQR	boolean indicating if you want to display the inter quantile range (Q1,Q3) as opposed to (min,max) in the summary for continuous variables
all.stats	boolean indicating if all summary statistics (Q1,Q3 + min,max on a separate line) should be displayed. Overrides IQR.
pvalue	boolean indicating if you want p-values included in the table
effSize	boolean indicating if you want effect sizes included in the table. Can only be obtained if p-value is also requested.
show.tests	boolean indicating if the type of statistical used should be shown in a column beside the p-values. Ignored if pvalue=FALSE.
nCores	if > 1, specifies number of cores to use for parallel processing for calculating the nested p-value (default: <code>parallely::availableCores</code> ).
nested.test	specifies test used for calculating nested p-value from <code>afex::mixed</code> function. Either <i>parametric bootstrap</i> method or <i>likelihood ratio test</i> method (default: "LRT"). Parametric bootstrap ("PB") takes longer. If no p-value is outputted, may need to compile lme4 package using <code>utils::install.packages("lme4", type = "source")</code> from sources.
nsim	specifies number of simulations to use for calculating nested p-value with <i>parametric bootstrap</i> method used for nested.test (default: 1000).
excludeLevels	a named list of covariate levels to exclude from statistical tests in the form <code>list(varname =c('level1','level2'))</code> . These levels will be excluded from association tests, but not the table. This can be useful for levels where there is a logical skip (i.e. not missing, but not presented). Ignored if pvalue=FALSE.
dropLevels	logical, indicating if empty factor levels be dropped from the output, default is TRUE.
full	boolean indicating if you want the full sample included in the table, ignored if maincov is NULL
digits.cat	number of digits for the proportions when summarizing categorical data (default: 0)
testcont	test of choice for continuous variables, one of <i>rank-sum</i> (default) or <i>ANOVA</i>
testcat	test of choice for categorical variables, one of <i>Chi-squared</i> (default) or <i>Fisher</i>
include_missing	Option to include NA values of maincov. NAs will not be included in statistical tests
percentage	choice of how percentages are presented, one of <i>column</i> (default) or <i>row</i>

**See Also**

[fisher.test](#), [chisq.test](#), [wilcox.test](#), [kruskal.test](#), and [anova](#)

---

demography

*Simulated demography for patients.*

---

**Description**

Simulated demography for patients.

**Usage**

demography

**Format**

A data frame with 12 rows and 2 variables:

**Subject** Patient ID

**GENDER\_CODE** Patient gender

---

drug1\_admin

*Simulated study agent 1 for patients.*

---

**Description**

Simulated study agent 1 for patients.

**Usage**

drug1\_admin

**Format**

A data frame with 12 rows and 2 variables:

**Subject** Patient ID

**TX1\_DATE\_INT** Study agent 1 start date of patient on study

---

drug2_admin	<i>Simulated study agent 2 for patients.</i>
-------------	--

---

**Description**

Simulated study agent 2 for patients.

**Usage**

drug2\_admin

**Format**

A data frame with 12 rows and 2 variables:

**Subject** Patient ID

**TX2\_DATE\_INT** Study agent 2 start date of patient on study

---

dsmb_ccru	<i>Outputs the three DSMB-CCRU AE summary tables in Excel format per UHN template</i>
-----------	---

---

**Description**

Outputs the three DSMB-CCRU AE summary tables in Excel format per UHN template

**Usage**

```
dsmb_ccru(
  protocol,
  setwd,
  title,
  comp = NULL,
  pi,
  presDate,
  cutDate,
  boundDate = NULL,
  subjID,
  subjID_ineligText = NULL,
  baseline_datasets,
  ae_dataset,
  ineligVar = NULL,
  ineligVarText = NULL,
  genderVar,
  enrolDtVar,
```

```

    ae_detailVar,
    ae_categoryVar,
    ae_severityVar,
    ae_onsetDtVar,
    ae_detailOtherText = NULL,
    ae_detailOtherVar = NULL,
    ae_verbatimVar = NULL,
    numSubj = NULL,
    fileNameUnderscore = TRUE
  )

```

### Arguments

protocol	study protocol name (uppercase, no spaces permitted)
setwd	directory to write Excel summary files to
title	full character vector with name of study
comp	baseline comparison group. For example, cohort (if provided)
pi	character vector name of study principal investigator
presDate	presentation date (i.e. 17NOV2023) for DSMB
cutDate	recent cutoff date for AEs (i.e. 31AUG2023)
boundDate	lower bound cutoff date for AEs (if provided)
subjID	key identifier field for participant ID in data sets
subjID_ineligText	character text that denotes participant IDs to exclude. For example, c("New Subject") (if provided)
baseline_datasets	list of data frames that contain baseline participant characteristics. For example, list(enrollment_DF,demography_DF,ineligibility_DF)
ae_dataset	data frame that contains subject AEs
ineligVar	field that denotes participant ineligibility (if provided)
ineligVarText	character text that denotes participant ineligibility. For example, c("Yes", "Y") (if provided)
genderVar	field that denotes participant gender
enrolDtVar	field that denotes participant enrollment date (i.e. 10MAY2021)
ae_detailVar	field that denotes participant AE detail (lowest level term)
ae_categoryVar	field that denotes participant AE category (system organ class)
ae_severityVar	field that denotes participant AE severity grade (numeric)
ae_onsetDtVar	field that denotes participant AE onset date
ae_detailOtherText	character text that denotes referencing verbatim AE field. For example, c("Other, specify", "OTHER") (if provided)
ae_detailOtherVar	field that denotes participant AE detail other (if provided)

ae\_verbatimVar field that denotes participant AE detail verbatim (if provided)  
 numSubj vector to override value for number of participants in summary (if provided)  
 fileNameUnderscore  
                   boolean that denotes if spaces should be underscore in filename

**Value**

three Excel files containing DSMB-CCRU AE summary tables

**Examples**

```
data("enrollment", "demography", "ineligibility", "ae");
dsmb_ccru(protocol="EXAMPLE_STUDY", setwd="./man/tables/",
  title="Phase X Study to Evaluate Treatments A-D",
  comp="COHORT", pi="Dr. Principal Investigator",
  presDate="30OCT2020", cutDate="31AUG2020",
  boundDate=NULL, subjID="Subject", subjID_ineligText=c("New Subject", "Test"),
  baseline_datasets=list(enrollment, demography, ineligibleity),
  ae_dataset=ae, ineligVar="INELIGIBILITY_STATUS", ineligVarText=c("Yes", "Y"),
  genderVar="GENDER_CODE", enrolDtVar="ENROL_DATE_INT", ae_detailVar="ae_detail",
  ae_categoryVar="ae_category", ae_severityVar="AE_SEV_GD",
  ae_onsetDtVar="AE_ONSET_DT_INT", ae_detailOtherText="Other, specify",
  ae_detailOtherVar="CTCAE5_LLT_NM", ae_verbatimVar="AE_VERBATIM_TRM_TXT",
  numSubj=c(2,4,5,6))
```

---

dsmb_ddp	<i>Outputs the DSMB-DDP AE summary tables in Excel format per UHN template</i>
----------	--

---

**Description**

Outputs the DSMB-DDP AE summary tables in Excel format per UHN template

**Usage**

```
dsmb_ddp(
  protocol,
  setwd,
  title,
  comp = NULL,
  pi,
  presDate,
  cutDate,
  boundDate = NULL,
  subjID,
  subjID_ineligText = NULL,
  baseline_datasets,
  ae_dataset,
```

```

ineligVar = NULL,
ineligVarText = NULL,
genderVar,
enrolDtVar,
ae_detailVar,
ae_categoryVar = NULL,
ae_severityVar,
ae_onsetDtVar,
ae_detailOtherText = NULL,
ae_detailOtherVar = NULL,
ae_verbatimVar = NULL,
ae_attribVars = NULL,
ae_attribVarsName = NULL,
ae_attribVarText = NULL,
related_ae = FALSE,
numSubj = NULL,
fileNameUnderscore = TRUE
)

```

### Arguments

protocol	study protocol name (uppercase, no spaces permitted)
setwd	directory to write Excel summary files to
title	full character vector with name of study
comp	baseline comparison group. For example, cohort (if provided)
pi	character vector name of study principal investigator
presDate	presentation date (i.e. 17NOV2023) for DSMB
cutDate	recent cutoff date for AEs (i.e. 31AUG2023)
boundDate	lower bound cutoff date for AEs (if provided)
subjID	key identifier field for participant ID in data sets
subjID_ineligText	character text that denotes participant IDs to exclude. For example, c("New Subject") (if provided)
baseline_datasets	list of data frames that contain baseline participant characteristics. For example, list(enrollment_DF,demography_DF,ineligibility_DF)
ae_dataset	data frame that contains subject AEs
ineligVar	field that denotes participant ineligibility (if provided)
ineligVarText	character text that denotes participant ineligibility. For example, c("Yes", "Y") (if provided)
genderVar	field that denotes participant gender
enrolDtVar	field that denotes participant enrollment date (i.e. 10MAY2021)
ae_detailVar	field that denotes participant AE detail (lowest level term)
ae_categoryVar	field that denotes participant AE category (system organ class)

ae\_severityVar field that denotes participant AE severity grade (numeric)

ae\_onsetDtVar field that denotes participant AE onset date

ae\_detailOtherText  
character text that denotes referencing verbatim AE field. For example, c("Other, specify", "OTHER") (if provided)

ae\_detailOtherVar  
field that denotes participant AE detail other (if provided)

ae\_verbatimVar field that denotes participant AE detail verbatim (if provided)

ae\_attrivVars field(s) that denotes attribution to intervention under study.  
For example, c("CTC\_AE\_ATTR\_SCALE", "CTC\_AE\_ATTR\_SCALE\_1") (if provided)

ae\_attrivVarsName  
character text that denotes name of interventions under study. For example, c("Drug 1", "Drug 2") (if provided)

ae\_attrivVarText  
character text that denotes related attribution. For example c("Definite", "Probable", "Possible") (if provided)

related\_ae boolean that denotes if summary is for related AEs. Default is False.

numSubj vector to override value for number of participants in summary (if provided)

fileNameUnderscore  
boolean that denotes if spaces should be underscore in filename

## Value

three Excel files containing DSMB-CCRU AE summary tables

## Examples

```
data("enrollment", "demography", "ineligibility", "ae");
dsmb_ddp(protocol="EXAMPLE_STUDY", setwd="./man/tables/",
  title="Phase X Study to Evaluate Treatments A-D",
  comp="COHORT", pi="Dr. Principal Investigator",
  presDate="30OCT2020", cutDate="31AUG2020",
  boundDate=NULL, subjID="Subject", subjID_ineligText=c("New Subject", "Test"),
  baseline_datasets=list(enrollment, demography, ineligibility),
  ae_dataset=ae, ineligVar="INELIGIBILITY_STATUS", ineligVarText=c("Yes", "Y"),
  genderVar="GENDER_CODE", enroldtVar="ENROL_DATE_INT", ae_detailVar="ae_detail",
  ae_categoryVar="ae_category", ae_severityVar="AE_SEV_GD",
  ae_onsetDtVar="AE_ONSET_DT_INT", ae_detailOtherText="Other, specify",
  ae_detailOtherVar="CTCAE5_LLT_NM", ae_verbatimVar="AE_VERBATIM_TRM_TXT",
  ae_attrivVars=c("CTC_AE_ATTR_SCALE", "CTC_AE_ATTR_SCALE_1"),
  ae_attrivVarsName=c("Drug 1", "Drug 2"),
  ae_attrivVarText=c("Definite", "Probable", "Possible"),
  numSubj=c(4, 4, 3, 4))
```

---

enrollment	<i>Enrollment data Simulated enrollment for patients.</i>
------------	---

---

**Description**

Enrollment data  
Simulated enrollment for patients.

**Usage**

enrollment

**Format**

A data frame with 12 rows and 3 variables:

**Subject** Patient ID

**COHORT** Study cohort for patient

**ENROL\_DATE\_INT** Enrollment date of patient to study

---

ineligibility	<i>Simulated ineligibility for patients.</i>
---------------	--

---

**Description**

Simulated ineligibility for patients.

**Usage**

ineligibility

**Format**

A data frame with 11 rows and 2 variables:

**Subject** Patient ID

**INELIGIBILITY\_STATUS** Recorded ineligibility status of patient to study



---

nice_mcmcglmm	<i>Nice table of model output from MCMCglmm::MCMCglmm()</i>
---------------	---

---

## Description

Nice table of model output from MCMCglmm::MCMCglmm()

## Usage

```
nice_mcmcglmm(mcmcglmm_object, dataset)
```

## Arguments

mcmcglmm_object	returned output from MCMCglmm()
dataset	dataframe containing data

## Value

grouped\_df

## Examples

```
## Not run:
data(ae)

ae$AE_SEV_GD <- as.numeric(ae$AE_SEV_GD);
ae$Drug_1_Attribution <- "No";
ae$Drug_1_Attribution[ae$CTC_AE_ATTR_SCALE %in% c("Definite", "Probable", "Possible")] <- "Yes";
ae$Drug_1_Attribution <- as.factor(ae$Drug_1_Attribution);
ae$Drug_2_Attribution <- "No";
ae$Drug_2_Attribution[ae$CTC_AE_ATTR_SCALE_1 %in% c("Definite", "Probable", "Possible")] <- "Yes";
ae$Drug_2_Attribution <- as.factor(ae$Drug_2_Attribution);

prior2RE <- list(R = list(V = diag(1), fix = 1), G=list(G1=list(V=1, nu=0.02),
  G2=list(V=1, nu=0.02)));

model1 <- MCMCglmm::MCMCglmm(Drug_1_Attribution ~ AE_SEV_GD + Drug_2_Attribution,
  random=~ae_detail + Subject, family="categorical", data=ae, saveX=TRUE,
  verbose=FALSE, burnin=2000, nitt=10000, thin=10, pr=TRUE, prior=prior2RE);

mcmcglmm_mva <- nice_mcmcglmm(model1, ae);

## End(Not run)
```

---

nice_mcmcglmm_icc	<i>Nice table of intraclass correlation coefficients from MCMCglmm::MCMCglmm() model output</i>
-------------------	---

---

### Description

Nice table of intraclass correlation coefficients from MCMCglmm::MCMCglmm() model output

### Usage

```
nice_mcmcglmm_icc(mcmcglmm_object, prob = NULL, decimals = NULL)
```

### Arguments

mcmcglmm_object	returned output from MCMCglmm()
prob	probability for highest posterior density interval, similar to a confidence interval. Default is 0.95 (if provided)
decimals	number of decimal places to use in estimates

### Value

grouped\_df

### Examples

```
## Not run:
data(ae)
ae$AE_SEV_GD <- as.numeric(ae$AE_SEV_GD);
ae$Drug_1_Attribution <- 0;
ae$Drug_1_Attribution[ae$CTC_AE_ATTR_SCALE %in% c("Definite", "Probable", "Possible")] <- 1;
ae$Drug_2_Attribution <- 0;
ae$Drug_2_Attribution[ae$CTC_AE_ATTR_SCALE_1 %in% c("Definite", "Probable", "Possible")] <- 1;
prior2RE <- list(R = list(V = diag(1), fix = 1), G=list(G1=list(V=1, nu=0.02),
  G2=list(V=1, nu=0.02)));
model1 <- MCMCglmm::MCMCglmm(Drug_1_Attribution ~ AE_SEV_GD + Drug_2_Attribution,
  random=~ae_detail + Subject, family="categorical", data=ae, saveX=TRUE,
  verbose=FALSE, burnin=2000, nitt=10000, thin=10, pr=TRUE, prior=prior2RE);
mcmcglmm_icc <- nice_mcmcglmm_icc(model1);

## End(Not run)
```

---

redcap_data_out	<i>Combines exported REDCap raw and label .csv files together with data dictionary. Transforms the exported data into Excel sheets by survey instrument with one row per participant</i>
-----------------	--

---

### Description

Combines exported REDCap raw and label .csv files together with data dictionary. Transforms the exported data into Excel sheets by survey instrument with one row per participant

### Usage

```
redcap_data_out(
  protocol,
  pullDate = NULL,
  subjID,
  subjID_ineligText = NULL,
  subjID_eligPattern = NULL,
  varFilter = NULL,
  varFilter_eligPattern = NULL,
  setWD_files,
  setWD_dataDict = NULL,
  outDir
)
```

### Arguments

protocol	study protocol name (i.e. Example_Study)
pullDate	date of data pull. For example, 2024_01_02 (if provided)
subjID	key identifier field(s) for participant ID in data sets
subjID_ineligText	character text that denotes participant IDs to exclude using first key identifier field. For example, c("New Subject") (if provided)
subjID_eligPattern	character text that denotes pattern for participant IDs to include using first key identifier field. For example, c("^Site_A") (if provided)
varFilter	field to use for filtering data (if provided)
varFilter_eligPattern	character text that denotes pattern for filter variable to include. For example, c("^Arm_A") (if provided)
setWD_files	directory where the both raw and label REDCap export .csv files are stored, following the convention for file names of 1_DATA.csv, 1_DATA_LABELs.csv, 2_DATA.csv, 2_DATA_LABELs.csv, etc
setWD_dataDict	directory where the REDCap .csv data dictionary is stored. Make sure that file is saved as CSV UTF-8 comma delimited. Must contain "ictionary" in file name (if provided)

outDir            output directory where the Excel files are saved

### Value

two Excel files, one containing variable names and labels and the other containing REDCap survey instrument data by sheet

### Examples

```
## Not run:
redcap_data_out(protocol="Example_Study", pullDate="2024_01_03",

## End(Not run)
```

---

rm_ae_all_g3p	<i>Outputs R Markdown table of all and grade 3+ adverse events by comparison group</i>
---------------	--

---

### Description

Outputs R Markdown table of all and grade 3+ adverse events by comparison group

### Usage

```
rm_ae_all_g3p(
  comp = NULL,
  presDate,
  cutDate,
  boundDate = NULL,
  subjID,
  subjID_ineligText = NULL,
  baseline_datasets,
  ae_dataset,
  ineligVar = NULL,
  ineligVarText = NULL,
  genderVar,
  enrolDtVar,
  ae_detailVar,
  ae_categoryVar = NULL,
  ae_severityVar,
  ae_onsetDtVar,
  ae_detailOtherText = NULL,
  ae_detailOtherVar = NULL,
  ae_verbatimVar = NULL,
  ae_attriVars = NULL,
  ae_attriVarsName = NULL,
  ae_attriVarText = NULL,
```

```

    related_ae = FALSE,
    numSubj = NULL
  )

```

### Arguments

comp	baseline comparison group. For example, cohort (if provided)
presDate	presentation date (i.e. 17NOV2023)
cutDate	recent cutoff date for AEs (i.e. 31AUG2023)
boundDate	lower bound cutoff date for AEs (if provided)
subjID	key identifier field for participant ID in data sets
subjID_ineligText	character text that denotes participant IDs to exclude. For example, c("New Subject") (if provided)
baseline_datasets	list of data frames that contain baseline participant characteristics. For example, list(enrollment_DF,demography_DF,ineligibility_DF)
ae_dataset	data frame that contains subject AEs
ineligVar	field that denotes participant ineligibility (if provided)
ineligVarText	character text that denotes participant ineligibility. For example, c("Yes", "Y") (if provided)
genderVar	field that denotes participant gender
enrolDtVar	field that denotes participant enrollment date (i.e. 10MAY2021)
ae_detailVar	field that denotes participant AE detail (lowest level term)
ae_categoryVar	field that denotes participant AE category (system organ class)
ae_severityVar	field that denotes participant AE severity grade (numeric)
ae_onsetDtVar	field that denotes participant AE onset date
ae_detailOtherText	character text that denotes referencing verbatim AE field. For example, c("Other, specify", "OTHER") (if provided)
ae_detailOtherVar	field that denotes participant AE detail other (if provided)
ae_verbatimVar	field that denotes participant AE detail verbatim (if provided)
ae_attribVars	field(s) that denotes attribution to intervention under study. For example, c("CTC_AE_ATTR_SCALE","CTC_AE_ATTR_SCALE_1") (if provided)
ae_attribVarsName	character text that denotes name of interventions under study. For example, c("Drug 1", "Drug 2") (if provided)
ae_attribVarText	character text that denotes related attribution. For example c("Definite", "Probable", "Possible") (if provided)
related_ae	boolean that denotes if summary is for related AEs. Default is False.
numSubj	vector to override value for number of participants in summary (if provided)

**Value**

R Markdown table of all and grade 3+ adverse events by treatment arm

**Examples**

```
data("enrollment", "demography", "ineligibility", "ae");
rm_ae_all_g3p(
  comp="COHORT",
  cutDate="31AUG2020",
  boundDate=NULL, subjID="Subject", subjID_ineligText=c("New Subject", "Test"),
  baseline_datasets=list(enrollment, demography, ineligibility),
  ae_dataset=ae, ineligVar="INELIGIBILITY_STATUS", ineligVarText=c("Yes", "Y"),
  genderVar="GENDER_CODE", enrolDtVar="ENROL_DATE_INT", ae_detailVar="ae_detail",
  ae_severityVar="AE_SEV_GD",
  ae_onsetDtVar="AE_ONSET_DT_INT", ae_detailOtherText="Other, specify",
  ae_detailOtherVar="CTCAE5_LLT_NM", ae_verbatimVar="AE_VERBATIM_TRM_TXT",
  ae_attriVar=c("CTC_AE_ATTR_SCALE", "CTC_AE_ATTR_SCALE_1"),
  ae_attriVarName=c("Drug 1", "Drug 2"),
  ae_attriVarText=c("Definite", "Probable", "Possible"),
  numSubj=c(2,4,5,6))
```

---

 rm\_covsum\_nested

*Outputs a nested version of reportRmd::rm\_covsum()*


---

**Description**

Outputs a nested version of reportRmd::rm\_covsum()

**Usage**

```
rm_covsum_nested(
  data,
  covs,
  maincov = NULL,
  id = NULL,
  caption = NULL,
  tableOnly = FALSE,
  covTitle = "",
  digits = 1,
  digits.cat = 0,
  nicenames = FALSE,
  IQR = FALSE,
  all.stats = FALSE,
  pvalue = TRUE,
  effSize = TRUE,
  p.adjust = "none",
  unformattedp = FALSE,
  show.tests = TRUE,
```

```

just.nested.pvalue = FALSE,
nCores = NULL,
nested.test = NULL,
nsim = NULL,
testcont = c("rank-sum test", "ANOVA"),
testcat = c("Chi-squared", "Fisher"),
full = TRUE,
include_missing = FALSE,
percentage = c("column", "row"),
dropLevels = TRUE,
excludeLevels = NULL,
numobs = NULL,
markup = TRUE,
sanitize = TRUE,
chunk_label
)

```

### Arguments

data	dataframe containing data
covs	character vector with the names of columns to include in table
maincov	covariate to stratify table by
id	covariates to nest summary by
caption	character containing table caption (default is no caption)
tableOnly	Logical, if TRUE then a dataframe is returned, otherwise a formatted printed object is returned (default).
covTitle	character with the names of the covariate (predictor) column. The default is to leave this empty for output or, for table only output to use the column name 'Covariate'.
digits	number of digits for summarizing mean data
digits.cat	number of digits for the proportions when summarizing categorical data (default: 0)
nicenames	boolean indicating if you want to replace . and _ in strings with a space
IQR	boolean indicating if you want to display the inter quantile range (Q1,Q3) as opposed to (min,max) in the summary for continuous variables
all.stats	boolean indicating if all summary statistics (Q1,Q3 + min,max on a separate line) should be displayed. Overrides IQR.
pvalue	boolean indicating if you want p-values included in the table
effSize	boolean indicating if you want effect sizes included in the table. Can only be obtained if pvalue is also requested.
p.adjust	p-adjustments to be performed
unformattedp	boolean indicating if you would like the p-value to be returned unformatted (ie not rounded or prefixed with '<'). Best used with tableOnly = T and outTable function.

<code>show.tests</code>	boolean indicating if the type of statistical used should be shown in a column beside the p-values. Ignored if <code>pvalue=FALSE</code> .
<code>just.nested.pvalue</code>	boolean indicating if the just the nested p-value should be shown in a column, and not unnested p-value, unnested statistical tests and effect size. Overrides <code>effSize</code> and <code>show.tests</code> arguments.
<code>nCores</code>	number of cores to use for parallel processing if calculating the nested p-value (if provided).
<code>nested.test</code>	specifies test used for calculating nested p-value from <code>afex::mixed</code> function. Either <i>parametric bootstrap</i> method or <i>likelihood ratio test</i> method (default: "LRT"). Parametric bootstrap takes longer.
<code>nsim</code>	specifies number of simulations to use for calculating nested p-value with <i>parametric bootstrap</i> method used for <code>nested.test</code> (default: 1000).
<code>testcont</code>	test of choice for continuous variables, one of <i>rank-sum</i> (default) or <i>ANOVA</i>
<code>testcat</code>	test of choice for categorical variables, one of <i>Chi-squared</i> (default) or <i>Fisher</i>
<code>full</code>	boolean indicating if you want the full sample included in the table, ignored if <code>maincov</code> is NULL
<code>include_missing</code>	Option to include NA values of <code>maincov</code> . NAs will not be included in statistical tests
<code>percentage</code>	choice of how percentages are presented, one of <i>column</i> (default) or <i>row</i>
<code>dropLevels</code>	logical, indicating if empty factor levels be dropped from the output, default is TRUE.
<code>excludeLevels</code>	a named list of covariate levels to exclude from statistical tests in the form <code>list(varname =c('level1','level2'))</code> . These levels will be excluded from association tests, but not the table. This can be useful for levels where there is a logical skip (ie not missing, but not presented). Ignored if <code>pvalue=FALSE</code> .
<code>numobs</code>	named list overriding the number of people you expect to have the covariate
<code>markup</code>	boolean indicating if you want latex markup
<code>sanitize</code>	boolean indicating if you want to sanitize all strings to not break LaTeX
<code>chunk_label</code>	only used if output is to Word to allow cross-referencing

**Value**

A character vector of the table source code, unless `tableOnly=TRUE` in which case a data frame is returned

**See Also**

[fisher.test](#), [chisq.test](#), [wilcox.test](#), [kruskal.test](#), and [anova](#)



**Examples**

```
## Not run:
# Example 1
data(ae)
rm_covsum_nested(data = ae, id = c("ae_detail", "Subject"), covs = c("AE_SEV_GD",
"AE_ONSET_DT_INT"), maincov = "CTC_AE_ATTR_SCALE")

# Example 2: set variable labels and other options, save output with markup
data("ae")
lbls <- data.frame(c1=c('AE_SEV_GD', 'AE_ONSET_DT_INT'),
  c2=c('Adverse event severity grade', 'Adverse event onset date'))
ae$AE_SEV_GD <- as.numeric(ae$AE_SEV_GD)
ae <- reportRmd::set_labels(ae, lbls)
output_tab <- rm_covsum_nested(data = ae, id = c("ae_detail", "Subject"),
  covs = c("AE_SEV_GD", "AE_ONSET_DT_INT"), maincov = "CTC_AE_ATTR_SCALE",
  testcat = "Fisher", percentage = c("col"), show.tests = FALSE, pvalue = TRUE,
  effSize = FALSE, full = TRUE, IQR = FALSE, nicens = TRUE, sanitize = TRUE,
  markup = TRUE, include_missing = TRUE, just.nested.pvalue = TRUE,
  tableOnly = TRUE)
cat(reportRmd::outTable(tab=output_tab))
cat(reportRmd::outTable(output_tab, format="html", file = paste("./man/tables/",
"output_tab.html", sep=""))
cat(reportRmd::outTable(output_tab, format="latex", file = paste("./man/tables/",
"output_tab.tex", sep=""))

## End(Not run)
```

# Index

- \* **as.numeric**
  - as\_numeric\_parse, 5
- \* **dataframe**
  - dsmb\_ccru, 11
  - dsmb\_ddp, 13
  - nice\_mcmcglmm, 17
  - nice\_mcmcglmm\_icc, 18
  - redcap\_data\_out, 19
  - rm\_ae\_all\_g3p, 20
  - rm\_covsum\_nested, 22
- \* **datasets**
  - ae, 2
  - demography, 10
  - drug1\_admin, 10
  - drug2\_admin, 11
  - enrollment, 16
  - ineligibility, 16
- \* **plot**
  - ae\_timeline\_plot, 3
  - caterpillar\_plot, 6

ae, 2

ae\_timeline\_plot, 3

anova, 10, 24

as\_numeric\_parse, 5

caterpillar\_plot, 6

chisq.test, 10, 24

covsum\_nested, 8

demography, 10

drug1\_admin, 10

drug2\_admin, 11

dsmb\_ccru, 11

dsmb\_ddp, 13

enrollment, 16

fisher.test, 10, 24

ineligibility, 16

kruskal.test, 10, 24

nice\_mcmcglmm, 17

nice\_mcmcglmm\_icc, 18

redcap\_data\_out, 19

rm\_ae\_all\_g3p, 20

rm\_covsum\_nested, 22

wilcox.test, 10, 24