

# Package ‘GenOU’

August 28, 2025

**Type** Package

**Title** Sequential Change-Point Tests for Generalized Ornstein-Uhlenbeck Processes

**Version** 0.2.1

**Description** Sequential change-point tests, parameters estimation, and goodness-of-fit tests for generalized Ornstein-Uhlenbeck processes.

**Depends** R (>= 3.5.0), doParallel, parallel, foreach, stats

**License** GPL (>= 2)

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Yunhong Lyu [aut, ctb, cph],  
Bouchra R. Nasri [aut, ctb, cph],  
Bruno N Remillard [aut, cre, cph]

**Maintainer** Bruno N Remillard <bruno.remillard@hec.ca>

**Repository** CRAN

**Date/Publication** 2025-08-28 08:40:02 UTC

## Contents

gof_stat . . . . .	2
kappa . . . . .	2
SimBM . . . . .	3
SimGOUexact . . . . .	4
SimQuantilesGoF . . . . .	5
SimQuantilesWBM . . . . .	5
StatGOU . . . . .	6
X . . . . .	7

## Index

8

<code>gof_stat</code>	<i>Function to estimate quantiles for a goodness-of-fit test for generalized Ornstein-Uhlenbeck process</i>
-----------------------	---

**Description**

Function to calculate the quantiles of Cramer-von Mise and Kolmogorov-Smirnov statistics.

**Usage**

```
gof_stat(X, T1, N, p, q)
```

**Arguments**

X	observations
T1	last time of observation
N	number of observations on from on interval (0,T1]
p	number of cosine coefficients >=1
q	number of sine coefficients >=0

**Value**

out	List of statistics (cvm and ks), estimated parameters, and pseudo-observations
-----	--

**Examples**

```
T1=20
N=500
data(X)
out = gof_stat(X,T1,N,2,0)
```

<code>kappa</code>	<i>Change-point statistics for GOU</i>
--------------------	--

**Description**

Function to compute Sigma covariance matrix and kappas of change-point statistics

**Usage**

```
kappa(theta, theta_star, sigma)
```

**Arguments**

theta	list of parameters before change-point: cos coefficients ( $\geq 1$ ), sine coefficients ( $\geq 0$ , and alpha
theta_star	list of parameters after change-point: cos coefficients ( $\geq 1$ ), sine coefficients ( $\geq 0$ , and alpha
sigma	volatility parameter of the GOU process

**Value**

out	List containing Sigma and kappas for Q and G statistics
-----	---

**Examples**

```
theta=list(cos=c(1,2),alpha=1)
theta_star=list(cos=c(2,4),alpha=2)
sigma=3
out = kappa(theta,theta_star, sigma)
```

**Description**

This function is used to simulate multidimensional Brownian motion at points  $0, 1/n, \dots, 1$ .

**Usage**

```
SimBM(n, d)
```

**Arguments**

n	Number of simulated
d	Dimension of BM

**Value**

W	Brownian motion
---	-----------------

**Examples**

```
W = SimBM(100,4)
```

**SimGOUexact***Simulation of generalized Ornstein-Uhlenbeck (GOU) process***Description**

Function to simulate exact N+K+1 values with change point after N+K\_star, with K\_star = floor(N\*t\_star), for a GOU process. Starting point is 0.

**Usage**

```
SimGOUexact(T1, N, t_star = 0, K, theta, theta_star, sigma)
```

**Arguments**

T1	Last time of observation
N	Number of observations on from on interval (0,T1]
t_star	Time of change-point after T1
K	Number of observation after change-point
theta	list of parameters before change-point: cos coefficients (>=1), sine and sigma
theta_star	list of parameters after change-point: cos coefficients (>=1), sine and sigma
sigma	volatility parameter of the GOU process

**Value**

X	Simulated path evaluated at points k x T1/N, 0 <= k <= N+K
---	--

**Examples**

```
set.seed(3253)
T1=20
N=500
K=2*N
t_star=0
theta=list(cos=c(1,2),alpha=1) # d=3 parameters for the drift
theta_star=list(cos=c(2,5),alpha=1)
sigma=3
X=SimGOUexact(T1,N,t_star,K,theta,theta_star,sigma)
```

---

SimQuantilesGoF	<i>Function to estimate quantiles for residuals of generalized Ornstein-Uhlenbeck (GOU) process</i>
-----------------	---

---

**Description**

Computation of quantiles for Cramer-von Mises and Kolmogorov-Smirnov statistics for testing goodness-of-fit of GOU

**Usage**

```
SimQuantilesGoF(n, B = 50000, alpha = c(0.9, 0.95, 0.975, 0.99), n_cores = 2)
```

**Arguments**

n	number of points
B	number of bootstrap samples (default 50000)
alpha	vector of probabilities (default is (.90,.95,.975,.99))
n_cores	number of cores for parallel computing (default is 2)

**Value**

q	Data frame of simulated quantiles of weighted BM
---	--

---

SimQuantilesWBM	<i>Function to estimate quantiles for weighthed Brownian Motion functional</i>
-----------------	--

---

**Description**

Function to calculate the critical value for the Euclidean norm of d-dimensional BM divided by  $t^{\gamma}$

**Usage**

```
SimQuantilesWBM(
  n,
  d,
  gamma,
  B = 50000,
  alpha = c(0.9, 0.95, 0.975, 0.99),
  n_cores = 2
)
```

**Arguments**

n	number of points
d	dimension of Brownian motion
gamma	parameter between 0 and 0.5 (not included)
B	number of bootstrap samples (default 50000)
alpha	vector of probabilities (default is (.90,.95,.975,.99))
n_cores	number of cores for parallel computing (default is 2)

**Value**

qs	Simulated quantiles of weighted BM
----	------------------------------------

StatGOU

*Change-point tests for generalized Ornstein-Uhlenbeck (GOU) process***Description**

Function to simulate exact N+K+1 values with change point after N+K\_star, with K\_star = floor(N\*t\_star), for a GOU process. Starting point is 0.

**Usage**

```
StatGOU(X, T1, N, p, q, gamma, c1, cd)
```

**Arguments**

X	observations
T1	last time of observation
N	number of observations on from on interval (0,T1]
p	number of cosine coefficients >=1
q	number of sine coefficients >=0
gamma	weight parameter >=0 and < 0.5
c1	critical value for Q stat (based on 1-dimensional weighed BM)
cd	critical value for G stat (based on d-dimensional weighed BM), where d = p+q+1 is the number of estimated parameters for the drift.

**Value**

out	List
-----	------

**References**

Lyu, Nasri and Remillard (2025): Sequential Change-point Detection with Generalized Ornstein–Uhlenbeck Processes

**Examples**

```
T1=20  
N=500  
gamma = 0.1  
p=2  
q=0  
c1 = 2.2838 # corresponding to gamma=0.1  
c3 = 3.0502 # corresponding to gamma=0.1 and d=3 estimated parameters for the drift  
data(X)  
out=StatGOU(X,T1,N,p,q,gamma,c1,c3)
```

---

X

*Simulated GOU process***Description**

Simulated GOU process with set.seed(3253), theta=list(cos=c(1,2),alpha=1) theta\_star=list(cos=c(2,4),alpha=2), using X=SimGOUexact(20,500,0,1000,theta,theta\_star,3)

**Usage**

```
data(X)
```

**Format**

Simulated GOU process (X)

**Examples**

```
data(X)
```

# Index

\* **datasets**

X, [7](#)

gof\_stat, [2](#)

kappa, [2](#)

SimBM, [3](#)

SimGOUexact, [4](#)

SimQuantilesGoF, [5](#)

SimQuantilesWBM, [5](#)

StatGOU, [6](#)

X, [7](#)