

# Package ‘ggplotAssist’

October 13, 2022

**Type** Package

**Title** 'RStudio' Addin for Teaching and Learning 'ggplot2'

**Version** 0.1.3

**Imports** shiny (>= 0.13), miniUI (>= 0.1.1), rstudioapi (>= 0.5), shinyWidgets, shinyAce, stringr, tidyverse, ggplot2, dplyr, magrittr, tibble, scales, ggthemes, gcookbook, moonBook, editData

**Suggests** knitr, rmarkdown, markdown

**URL** <https://github.com/cardiomoon/ggplotAssist>

**BugReports** <https://github.com/cardiomoon/ggplotAssist/issues>

**Description** An 'RStudio' addin for teaching and learning making plot using the 'ggplot2' package.

You can learn each steps of making plot by clicking your mouse without coding.

You can get resultant code for the plot.

**Depends** R (>= 2.10)

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.0.1

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Keon-Woong Moon [aut, cre]

**Maintainer** Keon-Woong Moon <[cardiomoon@gmail.com](mailto:cardiomoon@gmail.com)>

**Repository** CRAN

**Date/Publication** 2017-11-12 12:24:46 UTC

## R topics documented:

ggplotAssist . . . . .	2
selectizeInput3 . . . . .	3

splitData . . . . .	3
textAreaInput4 . . . . .	4
textFunction . . . . .	5
textFunctionInput . . . . .	5
textInput4 . . . . .	6
uiOutput3 . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

---

**ggplotAssist**            *A shiny app for learn ggplot2*

---

## Description

A shiny app for learn ggplot2

## Usage

```
ggplotAssist(df = NULL, viewer = "browser")
```

## Arguments

df	A tibble or a <code>tbl_df</code> or a <code>data.frame</code> to manipulate
viewer	Specify where the gadget should be displayed. Possible choices are c("dialog","browser","pane")

## Value

An R code for ggplot

## Examples

```
library(tidyverse)
library(rstudioapi)
library(miniUI)
library(moonBook)
library(shinyAce)
library(ggthemes)
library(shiny)
library(stringr)
library(editData)
library(shinyWidgets)
library(gcookbook)
library(shiny)
# Only run examples in interactive R sessions
if (interactive()) {
  result<-ggplotAssist(mtcars)
  result
}
```

---

selectizeInput3      *side-by-side selectizeInput*

---

## Description

side-by-side selectizeInput

## Usage

```
selectizeInput3(..., width = 100)
```

## Arguments

...	Further arguments to be passed to selectizeInput
width	Input width in pixel

## Examples

```
library(shiny)
# Only run examples in interactive R sessions
if (interactive()) {
  ui <- fluidPage(
    selectizeInput3("color", "color", choices=colors())
  )
  server <- function(input, output) {

  }
  shinyApp(ui, server)
}
```

---

splitData      *Elongate data.frame with column split by comma*

---

## Description

Elongate data.frame with column split by comma

## Usage

```
splitData(df, colname)
```

## Arguments

df	a data.frame
colname	column name

**Value**

An elongated data.frame

**textAreaInput4**

*Create side-by side textAreaInput with disabled spell check*

**Description**

Create side-by side textAreaInput with disabled spell check

**Usage**

```
textAreaInput4(inputId, label, value = "", bg = NULL, width = "100%",  
...)
```

**Arguments**

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value.
bg	background color
width	The width of the input in pixel
...	arguments to be passed to textInput

**Examples**

```
library(shiny)  
# Only run examples in interactive R sessions  
if (interactive()) {  
  ui <- fluidPage(  
    textAreaInput4("Code", "Code", "")  
  )  
  server <- function(input, output) {  
  }  
  shinyApp(ui, server)  
}
```

---

textFunction	<i>Server function of textFunction shiny module</i>
--------------	---

---

## Description

Server function of textFunction shiny module

## Usage

```
textFunction(input, output, session, argList = reactive(argList),  
            editCode = reactive(TRUE), settingData = reactive(NULL))
```

## Arguments

input	input
output	output
session	session
argList	A list containing options
editCode	Logical. Wheter or not edit initial R code
settingData	A data.frame contains information about functions

---

textFunctionInput	<i>UI of textFunction shiny module</i>
-------------------	--

---

## Description

UI of textFunction shiny module

## Usage

```
textFunctionInput(id)
```

## Arguments

id	A string
----	----------

## Examples

```
library(ggplotAssist)
library(shiny)
# Only run examples in interactive R sessions
if(interactive()){
  ui=fluidPage(
    textFunctionInput("text"),
    textOutput("text")
  )
  server=function(input,output,session){
    rv=reactiveValues()
    rawData=read.csv("data-raw/setting.csv",stringsAsFactors = FALSE)
    settingData=splitData(rawData,"setting")
    rv$argList<-list(label="text",mode="text",value="element_text()",choices=NULL,width=200,
                      bg="lightcyan",placeholder="")
    result=callModule(textFunction,"text",argList=reactive(rv$argList),
                      editCode=reactive(TRUE),settingData=reactive(settingData))
    output$text=renderText({
      result()
    })
  }
  shinyApp(ui,server)
}
```

**textInput4**

*Create side-by side textInput with disabled spell check*

## Description

Create side-by side textInput with disabled spell check

## Usage

```
textInput4(inputId, label, value = "", width = 100, bg = NULL, ...)
```

## Arguments

<code>inputId</code>	The input slot that will be used to access the value.
<code>label</code>	Display label for the control, or NULL for no label.
<code>value</code>	Initial value.
<code>width</code>	The width of the input in pixel
<code>bg</code>	background color
<code>...</code>	arguments to be passed to <code>textInput</code>

## Examples

```
library(shiny)
# Only run examples in interactive R sessions
if (interactive()) {
  ui <- fluidPage(
   textInput4("id", "id", ""),
   textInput4("name", "name", ""))
}
server <- function(input, output) {

}
shinyApp(ui, server)
}
```

---

uiOutput3

*Create side-by side uiOutput*

---

## Description

Create side-by side uiOutput

## Usage

```
uiOutput3(...)
```

## Arguments

```
... arguments to be passed to uiOutput
```

## Examples

```
library(shiny)
# Only run examples in interactive R sessions
if (interactive()) {
  ui <- fluidPage(
   textInput4("name", "name", ""),
    uiOutput3("test")
)
server <- function(input, output) {

}
shinyApp(ui, server)
}
```

# Index

ggplotAssist, 2  
selectizeInput3, 3  
splitData, 3  
textAreaInput4, 4  
textFunction, 5  
textFunctionInput, 5  
textInput4, 6  
uiOutput3, 7