

Package ‘surveysd’

August 26, 2025

Type Package

Title Survey Standard Error Estimation for Cumulated Estimates and their Differences in Complex Panel Designs

Version 2.0.0

Maintainer Johannes Gussenbauer <Johannes.Gussenbauer@statistik.gv.at>

Description Calculate point estimates and their standard errors in complex household surveys using bootstrap replicates. Bootstrapping considers survey design with a rotating panel. A comprehensive description of the methodology can be found under <<https://statistikat.github.io/surveysd/articles/methodology.html>>.

Encoding UTF-8

License GPL (>= 2)

Imports Rcpp (>= 0.12.12), data.table, ggplot2, laeken, methods

LinkingTo Rcpp

URL <https://github.com/statistikat/surveysd>

BugReports <https://github.com/statistikat/surveysd/issues>

RoxygenNote 7.3.2

Suggests testthat, knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation yes

Author Johannes Gussenbauer [aut, cre],
Alexander Kowarik [aut] (ORCID:
<<https://orcid.org/0000-0001-8598-4130>>),
Eileen Vatheuer [aut],
Gregor de Cillia [aut],
Matthias Till [ctb]

Repository CRAN

Date/Publication 2025-08-26 15:20:02 UTC

Contents

calc.stError	2
computeLinear	7
cpp_mean	9
demo.eusilc	10
draw.bootstrap	11
generate.HHID	15
get.selection	16
ipf	18
ipf_step	22
kishFactor	23
plot.surveysd	24
PointEstimates	26
print.summary.ipf	27
print.surveysd	27
recalib	28
rescaled.bootstrap	31
summary.ipf	33

Index	35
--------------	-----------

calc.stError	<i>Calculate point estimates and their standard errors using bootstrap weights.</i>
--------------	---

Description

Calculate point estimates as well as standard errors of variables in surveys. Standard errors are estimated using bootstrap weights (see [draw.bootstrap](#) and [recalib](#)). In addition the standard error of an estimate can be calculated using the survey data for 3 or more consecutive periods, which results in a reduction of the standard error.

Usage

```
calc.stError(
  dat,
  weights = attr(dat, "weights"),
  b.weights = attr(dat, "b.rep"),
  period = attr(dat, "period"),
  var = NULL,
  fun = weightedRatio,
  relative.share = FALSE,
  group = NULL,
  group.diff = FALSE,
  fun.adjust.var = NULL,
  adjust.var = NULL,
  period.diff = NULL,
```

```

    period.mean = NULL,
    bias = FALSE,
    size.limit = 20,
    cv.limit = 10,
    p = NULL,
    add.arg = NULL,
    national = FALSE,
    new_method = TRUE
  )

```

Arguments

<code>dat</code>	either <code>data.frame</code> or <code>data.table</code> containing the survey data. Surveys can be a panel survey or rotating panel survey, but does not need to be. For rotating panel survey bootstrap weights can be created using draw.bootstrap and recalib .
<code>weights</code>	character specifying the name of the column in <code>dat</code> containing the original sample weights. Used to calculate point estimates.
<code>b.weights</code>	character vector specifying the names of the columns in <code>dat</code> containing bootstrap weights. Used to calculate standard errors.
<code>period</code>	character specifying the name of the column in <code>dat</code> containing the sample periods.
<code>var</code>	character vector containing variable names in <code>dat</code> on which <code>fun</code> shall be applied for each sample period. If <code>var = NULL</code> the results will reflect the sum of weights.
<code>fun</code>	function which will be applied on <code>var</code> for each sample period. Predefined functions are weightedRatio , weightedSum , but can also take any other function which returns a double or integer and uses weights as its second argument.
<code>relative.share</code>	boolean, if <code>TRUE</code> point estimates resulting from <code>fun</code> will be divided by the point estimate at population level per period.
<code>group</code>	character vectors or list of character vectors containig variables in <code>dat</code> . For each list entry <code>dat</code> will be split in subgroups according to the containing variables as well as <code>period</code> . The pointestimates are then estimated for each subgroup seperately. If <code>group=NULL</code> the data will split into sample periods by default.
<code>group.diff</code>	boolean, if <code>TRUE</code> differences and the standard error between groups defined in <code>group</code> are calculated. See details for more explanations.
<code>fun.adjust.var</code>	can be either <code>NULL</code> or a function. This argument can be used to apply a function for each period and bootstrap weight to the data. The resulting estimates will be passed down to <code>fun</code> . See details for more explanations.
<code>adjust.var</code>	can be either <code>NULL</code> or a character specifying the first argument in <code>fun.adjust.var</code> .
<code>period.diff</code>	character vectors, defining periods for which the differences in the point estimate as well it's standard error is calculated. Each entry must have the form of "period1 - period2". Can be <code>NULL</code>
<code>period.mean</code>	odd integer, defining the range of periods over which the sample mean of point estimates is additionally calcaulted.
<code>bias</code>	boolean, if <code>TRUE</code> the sample mean over the point estimates of the bootstrap weights is returned.

size.limit	integer defining a lower bound on the number of observations on dat in each group defined by period and the entries in group. Warnings are returned if the number of observations in a subgroup falls below size.limit. In addition the concerned groups are available in the function output.
cv.limit	non-negativ value defining a upper bound for the standard error in relation to the point estimate. If this relation exceed cv.limit, for a point estimate, they are flagged and available in the function output.
p	numeric vector containing values between 0 and 1. Defines which quantiles for the distribution of var are additionally estimated.
add.arg	additional arguments which will be passed to fun. Can be either a named list or vector. The names of the object correspond to the function arguments and the values to column names in dat, see also examples.
national	DEPRECATED use relative.share instead! boolean, if TRUE point estimates resulting from fun will be divided by the point estimate at the national level.
new_method	used for testing new implementation; will be removed with new release.

Details

calc.stError takes survey data (dat) and returns point estimates as well as their standard Errors defined by fun and var for each sample period in dat. dat must be household data where household members correspond to multiple rows with the same household identifier. The data should at least contain the following columns:

- Column indicating the sample period;
- Column indicating the household ID;
- Column containing the household sample weights;
- Columns which contain the bootstrap weights (see output of [recalib](#));
- Columns listed in var as well as in group

For each variable in var as well as sample period the function fun is applied using the original as well as the bootstrap sample weights.

The point estimate is then selected as the result of fun when using the original sample weights and it's standard error is estimated with the result of fun using the bootstrap sample weights.

fun can be any function which returns a double or integer and uses sample weights as it's second argument. The predefined options are weightedRatio and weightedSum.

For the option weightedRatio a weighted ratio (in \ calculated for var equal to 1, e.g $\text{sum}(\text{weight}[\text{var}==1]) / \text{sum}(\text{weight})$). Additionally using the option national=TRUE the weighted ratio (in \ divided by the weighted ratio at the national level for each period.

If group is not NULL but a vector of variables from dat then fun is applied on each subset of dat defined by all combinations of values in group.

For instance if group = "sex" with "sex" having the values "Male" and "Female" in dat the point estimate and standard error is calculated on the subsets of dat with only "Male" or "Female" value for "sex". This is done for each value of period. For variables in group which have NAs in dat the rows containing the missings will be discarded.

When `group` is a list of character vectors, subsets of `dat` and the following estimation of the point estimate, including the estimate for the standard error, are calculated for each list entry.

If `group.diff = TRUE` difference between groups defined by `group` are calculated. Differences are only calculated within each variables of `group`, e.g `group = c("gender", "region")` will calculate estimates of each group and also differences within "gender" and "region" separately. If grouping is done with multiple variables e.g `group = list(c("gender", "region"))` (~ grouping by "gender" x "region") differences are calculated only between groups where one of the grouping variables is different. For instance the difference between `gender = "female" & region = "Vienna"` and `gender = "male" & region = "Vienna"` OR `gender = "female" & region = "Vienna"` and `gender = "female" & region = "Salzburg"` will be calculated. The difference between `gender = "female" & region = "Vienna"` and `gender = "male" & region = "Salzburg"` will not be calculated. The order of difference is determined by order of value (alpha-numerical order) or if grouping contains factor variables the factor levels determine the order.

The optional parameters `fun.adjust.var` and `adjust.var` can be used if the values in `var` are dependent on the weights. As is for instance the case for the poverty threshold calculated from EU-SILC. In such a case an additional function can be supplied using `fun.adjust.var` as well as its first argument `adjust.var`, which needs to be part of the data set `dat`. Then, before applying `fun` on variable `var` for all period and groups, the function `fun.adjust.var` is applied to `adjust.var` using each of the bootstrap weights separately (NOTE: `weight` is used as the second argument of `fun.adjust.var`). Thus creating `i=1,...,length(b.weights)` additional variables. For applying `fun` on `var` the estimates for the bootstrap replicate will now use each of the corresponding new additional variables. So instead of

$$fun(var, weights, \dots), fun(var, b.weights[1], \dots), fun(var, b.weights[2], \dots), \dots$$

the function `fun` will be applied in the way

$$fun(var, weights, \dots), fun(var.1, b.weights[1], \dots), fun(var.2, b.weights[2], \dots), \dots$$

where `var.1`, `var.2`, ... correspond to the estimates resulting from `fun.adjust.var` and `adjust.var`.

NOTE: This procedure is especially useful if the `var` is dependent on weights and `fun` is applied on subgroups of the data set. Then it is not possible to capture this procedure with `fun` and `var`, see examples for a more hands on explanation.

When defining `period.diff` the difference of point estimates between periods as well their standard errors are calculated.

The entries in `period.diff` must have the form of "period1 - period2" which means that the results of the point estimates for period2 will be subtracted from the results of the point estimates for period1.

Specifying `period.mean` leads to an improvement in standard error by averaging the results for the point estimates, using the bootstrap weights, over `period.mean` periods. Setting, for instance, `period.mean = 3` the results in averaging these results over each consecutive set of 3 periods.

Estimating the standard error over these averages gives an improved estimate of the standard error for the central period, which was used for averaging.

The averaging of the results is also applied in differences of point estimates. For instance defining `period.diff = "2015-2009"` and `period.mean = 3` the differences in point estimates of 2015 and 2009, 2016 and 2010 as well as 2014 and 2008 are calculated and finally the average over these 3 differences is calculated. The periods set in `period.diff` are always used as the middle periods

around which the mean over `period.mean` years is build.

Setting `bias` to `TRUE` returns the calculation of a mean over the results from the bootstrap replicates. In the output the corresponding columns is labeled `_mean` at the end.

If `fun` needs more arguments they can be supplied in `add.arg`. This can either be a named list or vector.

The parameter `size.limit` indicates a lower bound of the sample size for subsets in `dat` created by `group`. If the sample size of a subset falls below `size.limit` a warning will be displayed.

In addition all subsets for which this is the case can be selected from the output of `calc.stError` with `$smallGroups`.

With the parameter `cv.limit` one can set an upper bound on the coefficient of variation. Estimates which exceed this bound are flagged with `TRUE` and are available in the function output with `$cvHigh`. `cv.limit` must be a positive integer and is treated internally as `\` for `cv.limit=1` the estimate will be flagged if the coefficient of variation exceeds `1\`.

When specifying `period.mean`, the decrease in standard error for choosing this method is internally calculated and a rough estimate for an implied increase in sample size is available in the output with `$stEDecrease`. The rough estimate for the increase in sample size uses the fact that for a sample of size n the sample estimate for the standard error of most point estimates converges with a factor $1/\sqrt{n}$ against the true standard error σ .

Value

Returns a list containing:

- `Estimates`: data.table containing period differences and/or k period averages for estimates of `fun` applied to `var` as well as the corresponding standard errors, which are calculated using the bootstrap weights. In addition the sample size, `n`, and population size for each group is added to the output.
- `smallGroups`: data.table containing groups for which the number of observation falls below `size.limit`.
- `cvHigh`: data.table containing a boolean variable which indicates for each estimate if the estimated standard error exceeds `cv.limit`.
- `stEDecrease`: data.table indicating for each estimate the theoretical increase in sample size which is gained when averaging over `k` periods. Only returned if `period.mean` is not `NULL`.

Author(s)

Johannes Gussenbauer, Alexander Kowarik, Statistics Austria

See Also

[draw.bootstrap](#)
[recalib](#)

Examples

```
# Import data and calibrate
```

```

library(surveysd)
library(data.table)
setDTthreads(1)
set.seed(1234)
eusilc <- demo.eusilc(n = 4, prettyNames = TRUE)
dat_boot <- draw.bootstrap(eusilc, REP = 3, hid = "hid", weights = "pWeight",
                           strata = "region", period = "year")
dat_boot_calib <- recalib(dat_boot, conP.var = "gender", conH.var = "region")

# estimate weightedRatio for povertyRisk per period

err.est <- calc.stError(dat_boot_calib, var = "povertyRisk",
                        fun = weightedRatio)
err.est$Estimates

# calculate weightedRatio for povertyRisk and fraction of one-person
# households per period

dat_boot_calib[, onePerson := .N == 1, by = .(year, hid)]
err.est <- calc.stError(dat_boot_calib, var = c("povertyRisk", "onePerson"),
                        fun = weightedRatio)
err.est$Estimates

# estimate weightedRatio for povertyRisk per period and gender and
# period x region x gender

group <- list("gender", c("gender", "region"))
err.est <- calc.stError(dat_boot_calib, var = "povertyRisk",
                        fun = weightedRatio, group = group)
err.est$Estimates

# use average over 3 periods for standard error estimation
# and calculate estimate for difference of
# period 2011 and 2012 including standard errors
period.diff <- c("2012-2011")
err.est <- calc.stError(
  dat_boot_calib, var = "povertyRisk", fun = weightedRatio,
  period.diff = period.diff, # <- take difference of periods 2012 and 2011
  period.mean = 3) # <- average over 3 periods
err.est$Estimates

# for more examples see https://statistikat.github.io/surveysd/articles/error\_estimation.html

```

Description

Customize weight-updating within factor levels in case of numerical calibration. The functions described here serve as inputs for [ipf](#).

Usage

```
computeLinear(curValue, target, x, w, boundLinear = 10)

computeLinearG1_old(curValue, target, x, w, boundLinear = 10)

computeLinearG1(curValue, target, x, w, boundLinear = 10)

computeFrac(curValue, target, x, w)
```

Arguments

curValue	Current summed up value. Same as $\text{sum}(x*w)$
target	Target value. An element of conP in ipf
x	Vector of numeric values to be calibrated against
w	Vector of weights
boundLinear	The output f will satisfy $1/\text{boundLinear} \leq f \leq \text{boundLinear}$. See bound in ipf

Details

computeFrac provides the "standard" IPU updating scheme given as

$$f = \text{target} / \text{curValue}$$

which means that each weight inside the level will be multiplied by the same factor when doing the actual update step ($w := f*w$). computeLinear on the other hand calculates f as

$$f_i = ax_i + b$$

where a and b are chosen, so f satisfies the following two equations.

$$\begin{aligned} \sum f_i * w_i * x_i &= \text{target} \\ \sum f_i * w_i &= \sum w_i \end{aligned}$$

computeLinearG1 calculates f in the same way as computeLinear, but if $f_i * w_i < 1$ f_i will be set to $1/w_i$.

Value

A weight multiplier f

cpp_mean*Calculate mean by factors*

Description

These functions calculate the arithmetic and geometric mean of the weight for each class. `geometric_mean` and `arithmetic_mean` return a numeric vector of the same length as `w` which stores the averaged weight for each observation. `geometric_mean_reference` returns the same value by reference, i.e. the input value `w` gets overwritten by the updated weights. See examples.

Usage

```
geometric_mean_reference(w, classes)
```

Arguments

<code>w</code>	An numeric vector. All entries should be positive.
<code>classes</code>	A factor variable. Must have the same length as <code>w</code> .

Examples

```
## Not run:

## create random data
nobs <- 10
classLabels <- letters[1:3]
dat = data.frame(
  weight = exp(rnorm(nobs)),
  household = factor(sample(classLabels, nobs, replace = TRUE))
)
dat

## calculate weights with geometric_mean
geom_weight <- geometric_mean(dat$weight, dat$household)
cbind(dat, geom_weight)

## calculate weights with arithmetic_mean
arith_weight <- arithmetic_mean(dat$weight, dat$household)
cbind(dat, arith_weight)

## calculate weights "by reference"
geometric_mean_reference(dat$weight, dat$household)
dat

## End(Not run)
```

demo.eusilc

*Generate multiple years of EU-SILC data***Description**

Create a dummy dataset to be used for demonstrating the functionalities of the `surveysd` package based on [laeken::eusilc](#). Please refer to the documentation page of the original data for details about the variables.

Usage

```
demo.eusilc(n = 8, prettyNames = FALSE)
```

Arguments

<code>n</code>	Number of years to generate. Should be at least 1
<code>prettyNames</code>	Create easy-to-read names for certain variables. Recommended for demonstration purposes. Otherwise, use the original codes documented in laeken::eusilc .

Details

If `prettyNames` is `TRUE`, the following variables will be available in an easy-to-read manner.

- `hid` Household id. Consistent with respect to the reference period (year)
- `hsize` Size of the household. derived from `hid` and `period`
- `region` Federal state of austria where the household is located
- `pid` Personal id. Consistent with respect to the reference period (year)
- `age` Age-class of the respondent
- `gender` A persons gender ("male", "Female")
- `ecoStat` Economic status ("part time", "full time", "unemployed", ...)
- `citizenship` Citizenship ("AT", "EU", "other")
- `pWeight` Personal sample weight inside the reference period
- `year`. Simulated reference period
- `povertyRisk`. Logical variable determining whether a respondent is at risk of poverty

Examples

```
demo.eusilc(n = 1, prettyNames = TRUE)[, c(1:8, 26, 28:30)]
```

draw.bootstrap	<i>Draw bootstrap replicates</i>
----------------	----------------------------------

Description

Draw bootstrap replicates from survey data with rotating panel design. Survey information, like ID, sample weights, strata and population totals per strata, should be specified to ensure meaningful survey bootstrapping.

Usage

```
draw.bootstrap(
  dat,
  method = "Preston",
  REP = 1000,
  hid = NULL,
  weights,
  period = NULL,
  strata = NULL,
  cluster = NULL,
  totals = NULL,
  single.PSU = c("merge", "mean"),
  boot.names = NULL,
  split = FALSE,
  pid = NULL,
  seed = NULL,
  already.selected = NULL
)
```

Arguments

dat	either data.frame or data.table containing the survey data with rotating panel design.
method	for bootstrap replicates, either "Preston" or "Rao-Wu"
REP	integer indicating the number of bootstrap replicates.
hid	character specifying the name of the column in dat containing the household id. If NULL (the default), the household structure is not regarded.
weights	character specifying the name of the column in dat containing the sample weights.
period	character specifying the name of the column in dat containing the sample periods. If NULL (the default), it is assumed that all observations belong to the same period.
strata	character vector specifying the name(s) of the column in dat by which the population was stratified. If strata is a vector stratification will be assumed as the combination of column names contained in strata. Setting in addition cluster not NULL stratification will be assumed on multiple stages, where

	each additional entry in strata specifies the stratification variable for the next lower stage. see Details for more information.
cluster	character vector specifying cluster in the data. If not already specified in cluster household ID is taken as the lowest level cluster.
totals	character specifying the name of the column in dat containing the the totals per strata and/or cluster. Is ONLY optional if cluster is NULL or equal hid and strata contains one columnname! Then the households per strata will be calculated using the weights argument. If clusters and strata for multiple stages are specified totals needs to be a vector of length(strata) specifying the column on dat that contain the total number of PSUs at each stage. totals is interpreted from left the right, meaning that the first argument corresponds to the number of PSUs at the first and the last argument to the number of PSUs at the last stage.
single.PSU	either "merge" or "mean" defining how single PSUs need to be dealt with. For single.PSU="merge" single PSUs at each stage are merged with the strata or cluster with the next least number of PSUs. If multiple of those exist one will be select via random draw. For single.PSU="mean" single PSUs will get the mean over all bootstrap replicates at the stage which did not contain single PSUs.
boot.names	character indicating the leading string of the column names for each bootstrap replica. If NULL defaults to "w".
split	logical, if TRUE split households are considered using pid, for more information see Details.
pid	column in dat specifying the personal identifier. This identifier needs to be unique for each person through the whole data set. Can be NULL.
seed	integer specifying the seed for the random number generator.
already.selected	list of data.tables indicating if record was drawn in previous period. length(already.selected) must be equal to the number of sampling stages specified. See get.selection() for an example.

Details

draw.bootstrap takes dat and draws REP bootstrap replicates from it. dat must be household data where household members correspond to multiple rows with the same household identifier. For most practical applications, the following columns should be available in the dataset and passed via the corresponding parameters:

- Column indicating the sample period (parameter period).
- Column indicating the household ID (parameter hid)
- Column containing the household sample weights (parameter weights);
- Columns by which population was stratified during the sampling process (parameter: strata).

As methods either the rescaled bootstrap for stratified multistage sampling, presented by J. Preston (2009) (method = "Preston") or the Rao-Wu bootstrap by J. N. K. Rao and C. F. J. Wu (1988) (method = "Rao-Wu") are supported.

For single stage sampling design a column the argument totals is optional, meaning that a column

of the number of PSUs at the first stage does not need to be supplied. The number of PSUs is calculated and added to `dat` using `strata` and `weights`. By setting `cluster` to `NULL` single stage sampling design is always assumed and if `strata` contains of multiple column names the combination of all those column names will be used for stratification.

In the case of multi stage sampling design the argument `totals` needs to be specified and needs to have the same number of arguments as `strata`.

If `cluster` is `NULL` or does not contain `hid` at the last stage, `hid` will automatically be used as the final cluster. If, besides `hid`, clustering in additional stages is specified the number of column names in `strata` and `cluster` (including `hid`) must be the same. If for any stage there was no clustering or stratification one can set "1" or "I" for this stage.

For example `strata=c("REGION", "I"), cluster=c("MUNICIPALITY", "HID")` would specify a 2 stage sampling design where at the first stage the municipalities were drawn stratified by regions and at the 2nd stage households are drawn in each municipality without stratification.

Bootstrap replicates are drawn for each survey period consecutively (period) using the function [rescaled.bootstrap](#). Bootstrap replicates are drawn consistently in the way that in each period and sampling stage always $\lfloor n/2 \rfloor$ clusters are selected in each strata.

This ensures that the bootstrap replicates follow the same logic as the sampled households, making the bootstrap replicates more comparable to the actual sample units.

If `split` is set to `TRUE` and `pid` is specified, the bootstrap replicates are carried forward using the personal identifiers instead of the household identifier. This takes into account the issue of a household splitting up. Any person in this new split household will get the same bootstrap replicate as the person that has come from an other household in the survey. People who enter already existing households will also get the same bootstrap replicate as the other households members had in the previous periods.

`already.selected` can be specified in order to construct bootstrap replicates considering that already drawn bootstrap replicates from a previous period exist for the same survey. See [get.selection\(\)](#) for more explanations and examples.

Value

the survey data with the number of REP bootstrap replicates added as columns.

Returns a `data.table` containing the original data as well as the number of REP columns containing the bootstrap replicates for each repetition.

The columns of the bootstrap replicates are by default labeled "`wNumber`" where *Number* goes from 1 to REP. If the column names of the bootstrap replicates should start with a different character or string the parameter `boot.names` can be used.

Author(s)

Johannes Gussenbauer, Alexander Kowarik, Statistics Austria

References

Preston, J. (2009). Rescaled bootstrap for stratified multistage sampling. *Survey Methodology*. 35. 227-234. Rao, J. N. K., and C. F. J. Wu. (1988). Resampling Inference with Complex Survey Data. *Journal of the American Statistical Association* 83 (401): 231-41.

See Also

[data.table](#) for more information on data.table objects.

Examples

```
library(surveysd)
library(data.table)
setDTthreads(1)
set.seed(1234)
eusilc <- demo.eusilc(n = 3, prettyNames = TRUE)

## draw replicates without stratification or clustering
dat_boot <- draw.bootstrap(eusilc, REP = 1, weights = "pWeight",
                           period = "year")

## use stratification w.r.t. region and clustering w.r.t. households
dat_boot <- draw.bootstrap(
  eusilc, REP = 1, hid = "hid", weights = "pWeight",
  strata = "region", period = "year")

## use multi-level clustering
dat_boot <- draw.bootstrap(
  eusilc, REP = 1, hid = "hid", weights = "pWeight",
  strata = c("region", "hsize"), period = "year")

# create spit households
eusilc[, pidsplit := pid]
year <- eusilc[, unique(year)]
year <- year[-1]
leaf_out <- c()
for(y in year) {
  split.person <- eusilc[
    year == (y-1) & !duplicated(hid) & !(hid %in% leaf_out),
    sample(pid, 20)
  ]
  overwrite.person <- eusilc[
    (year == (y)) & !duplicated(hid) & !(hid %in% leaf_out),
    .(pid = sample(pid, 20))
  ]
  overwrite.person[, c("pidsplit", "year_curr") := .(split.person, y)]

  eusilc[overwrite.person, pidsplit := i.pidsplit,
    on = .(pid, year >= year_curr)]
  leaf_out <- c(leaf_out,
    eusilc[pid %in% c(overwrite.person$pid,
      overwrite.person$pidsplit),
      unique(hid)])
}

dat_boot <- draw.bootstrap(
  eusilc, REP = 1, hid = "hid", weights = "pWeight",
```

```

strata = c("region", "hsize"), period = "year", split = TRUE,
pid = "pidsplit")
# split households were considered e.g. household and
# split household were both selected or not selected
dat_boot[, data.table::uniqueN(w1), by = pidsplit][V1 > 1]

```

generate.HHID

Generate new houshold ID for survey data with rotating panel design taking into account split households

Description

Generating a new houshold ID for survey data using a houshold ID and a personal ID. For surveys with rotating panel design containing housholds, houshold members can move from an existing household to a new one, that was not originally in the sample. This leads to the creation of so called split households. Using a peronal ID (that stays fixed over the whole survey), an indicator for different time steps and a houshold ID, a new houshold ID is assigned to the original and the split household.

Usage

```
generate.HHID(dat, period = "RB010", pid = "RB030", hid = "DB030")
```

Arguments

dat	data table of data frame containing the survey data
period	column name of dat containing an indicator for the rotations, e.g years, quarters, months, ect...
pid	column name of dat containing the personal identifier. This needs to be fixed for an indiviual throught the whole survey
hid	column name of dat containing the household id. This needs to for a household throught the whole survey

Value

the survey data dat as data.table object containing a new and an old household ID. The new household ID which considers the split households is now named hid and the original household ID has a trailing "_orig".

Examples

```

## Not run:
library(surveysd)
library(laeken)
library(data.table)

```

```

eusilc <- surveysd::demo.eusilc(n=4)

# create spit households
eusilc[,rb030split:=rb030]
year <- eusilc[,unique(year)]
year <- year[-1]
leaf_out <- c()
for(y in year) {
  split.person <- eusilc[year==(y-1)&!duplicated(db030)&!db030%in%leaf_out,
    sample(rb030,20)]
  overwrite.person <- eusilc[year==(y)&!duplicated(db030)&!db030%in%leaf_out,
    .(rb030=sample(rb030,20))]
  overwrite.person[,c("rb030split","year_curr"):=.(split.person,y)]

  eusilc[overwrite.person,
    rb030split:=i.rb030split,on=.(rb030,year>=year_curr)]
  leaf_out <- c(
    leaf_out,
    eusilc[rb030%in%c(overwrite.person$rb030,overwrite.person$rb030split),
      unique(db030)])
}

# pid which are in split households
eusilc[,.(uniqueN(db030)),by=list(rb030split)][V1>1]

eusilc.new <- generate.HHID(eusilc, period = "year", pid = "rb030split",
  hid = "db030")

# no longer any split households in the data
eusilc.new[,.(uniqueN(db030)),by=list(rb030split)][V1>1]

## End(Not run)

```

get.selection

Get sample selection (~deltas) from drawn bootstrap replicates

Description

Reconstruct sample selection, e.g. record was drawn or not drawn ($\delta = 0/1$) in each sampling stage from bootstrap replicates. `get.selection()` needs the cluster, strata and hid/pid information (if not NULL) to correctly reconstruct if a record was drawn in each sampling stage for each bootstrap replicate. Is only needed if bootstrap replicates are drawn for a survey with existing bootstrap replicates from a previous period, see parameter `already.selected` in function `draw.bootstrap()`.

Usage

```

get.selection(
  dat,

```



```

    b.rep = attr(dat, "b.rep"),
    strata = attr(dat, "strata"),
    cluster = attr(dat, "cluster"),
    hid = attr(dat, "hid"),
    pid = attr(dat, "pid")
  )

```

Arguments

<code>dat</code>	either <code>data.frame</code> or <code>data.table</code> containing the survey data with rotating panel design. Should contain only survey data from a single time period.
<code>b.rep</code>	character specifying the names of the columns in <code>dat</code> containing bootstrap replicates.
<code>strata</code>	character vector specifying the name(s) of the column in <code>dat</code> by which the population was stratified.
<code>cluster</code>	character vector specifying cluster in the data.
<code>hid</code>	character specifying the name of the column in <code>dat</code> containing the household id. If <code>NULL</code> (the default), the household structure is not regarded. <code>hid</code> and <code>pid</code> cannot both be <code>NULL</code> .
<code>pid</code>	<code>pid</code> column in <code>dat</code> specifying the personal identifier. This identifier needs to be unique for each person through the whole data set. <code>hid</code> and <code>pid</code> cannot both be <code>NULL</code> .

Value

Returns a list of `data.tables`. The length of the list equals the number of sampling stages specified. Each list entry contains a `data.table` with variables for sampling stage and/or `hid/pid` as well as `length(attr(dat, "b.rep"))` columns each indicating if record/cluster was drawn in the respective sampling stage for the *i*-th bootstrap replicate.

Examples

```

library(surveysd)
library(data.table)
setDTthreads(1)
set.seed(1234)
eusilc <- demo.eusilc(n = 3, prettyNames = TRUE)

## draw replicates with stratification
dat_boot <- draw.bootstrap(eusilc[year<2012], REP = 3, weights = "pWeight",
                          strata = "region", hid = "hid",
                          period = "year")

## get selection matrix for year 2011
dat_selection <- get.selection(dat_boot[year==2011])
print(dat_selection)

## draw bootstrap replicates for year 2012
## respecting already selected units for year 2011 ~ dat_selection

```

```
## in order to mimic rotating panel design
dat_boot_2012 <- draw.bootstrap(eusilc[year==2012], REP = 3, weights = "pWeight",
                               strata = "region", hid = "hid",
                               period = "year",
                               already.selected = dat_selection)
```

ipf

Iterative Proportional Fitting

Description

Adjust sampling weights to given totals based on household-level and/or individual level constraints.

Usage

```
ipf(
  dat,
  hid = NULL,
  conP = NULL,
  conH = NULL,
  epsP = 1e-06,
  epsH = 0.01,
  verbose = FALSE,
  w = NULL,
  bound = 4,
  maxIter = 200,
  meanHH = TRUE,
  allPthenH = TRUE,
  returnNA = TRUE,
  looseH = FALSE,
  numericalWeighting = computeLinear,
  check_hh_vars = TRUE,
  conversion_messages = FALSE,
  nameCalibWeight = "calibWeight",
  minMaxTrim = NULL,
  print_every_n = 100
)
```

Arguments

dat a `data.table` containing household ids (optionally), base weights (optionally), household and/or personal level variables (numerical or categorical) that should be fitted.

hid	name of the column containing the household-ids within dat or NULL if such a variable does not exist.
conP	list or (partly) named list defining the constraints on person level. The list elements are contingency tables in array representation with dimnames corresponding to the names of the relevant calibration variables in dat. If a numerical variable is to be calibrated, the respective list element has to be named with the name of that numerical variable. Otherwise the list element should NOT be named.
conH	list or (partly) named list defining the constraints on household level. The list elements are contingency tables in array representation with dimnames corresponding to the names of the relevant calibration variables in dat. If a numerical variable is to be calibrated, the respective list element has to be named with the name of that numerical variable. Otherwise the list element should NOT be named.
epsP	numeric value or list (of numeric values and/or arrays) specifying the convergence limit(s) for conP. The list can contain numeric values and/or arrays which must appear in the same order as the corresponding constraints in conP. Also, an array must have the same dimensions and dimnames as the corresponding constraint in conP.
epsH	numeric value or list (of numeric values and/or arrays) specifying the convergence limit(s) for conH. The list can contain numeric values and/or arrays which must appear in the same order as the corresponding constraints in conH. Also, an array must have the same dimensions and dimnames as the corresponding constraint in conH.
verbose	if TRUE, some progress information will be printed.
w	name of the column containing the base weights within dat or NULL if such a variable does not exist. In the latter case, every observation in dat is assigned a starting weight of 1.
bound	numeric value specifying the multiplier for determining the weight trimming boundary if the change of the base weights should be restricted, i.e. if the weights should stay between $1/\text{bound} \cdot w$ and $\text{bound} \cdot w$.
maxIter	numeric value specifying the maximum number of iterations that should be performed.
meanHH	if TRUE, every person in a household is assigned the mean of the person weights corresponding to the household. If "geometric", the geometric mean is used rather than the arithmetic mean.
allPthenH	if TRUE, all the person level calibration steps are performed before the household level calibration steps (and meanHH, if specified). If FALSE, the household level calibration steps (and meanHH, if specified) are performed after every person level calibration step. This can lead to better convergence properties in certain cases but also means that the total number of calibration steps is increased.
returnNA	if TRUE, the calibrated weight will be set to NA in case of no convergence.
looseH	if FALSE, the actual constraints conH are used for calibrating all the hh weights. If TRUE, only the weights for which the lower and upper thresholds defined by conH and epsH are exceeded are calibrated. They are however not calibrated against the actual constraints conH but against these lower and upper thresholds, i.e. $\text{conH} - \text{conH} \cdot \text{epsH}$ and $\text{conH} + \text{conH} \cdot \text{epsH}$.

numericalWeighting	See numericalWeighting
check_hh_vars	If TRUE check for non-unique values inside of a household for variables in household constraints
conversion_messages	show a message, if inputs need to be reformatted. This can be useful for speed optimizations if ipf is called several times with similar inputs (for example bootstrapping)
nameCalibWeight	character defining the name of the variable for the newly generated calibrated weight.
minMaxTrim	numeric vector of length 2, first element a minimum value for weights to be trimmed to, second element a maximum value for weights to be trimmed to.
print_every_n	number of iteration steps after which a summary table is printed. The summary table shows all constraints which are not yet reached according to epsP and epsH

Details

This function implements the weighting procedure described here: [doi:10.17713/ajs.v45i3.120](https://doi.org/10.17713/ajs.v45i3.120). Usage examples can be found in the corresponding vignette (`vignette("ipf")`).

conP and conH are contingency tables, which can be created with `xtabs`. The dimnames of those tables should match the names and levels of the corresponding columns in `dat`.

maxIter, epsP and epsH are the stopping criteria. epsP and epsH describe relative tolerances in the sense that

$$1 - \text{epsP} < \frac{w_{i+1}}{w_i} < 1 + \text{epsP}$$

will be used as convergence criterium. Here i is the iteration step and w_i is the weight of a specific person at step i .

The algorithm performs best if all variables occurring in the constraints (conP and conH) as well as the household variable are coded as factor-columns in `dat`. Otherwise, conversions will be necessary which can be monitored with the `conversion_messages` argument. Setting `check_hh_vars` to FALSE can also increase the performance of the scheme.

Value

The function will return the input data `dat` with the calibrated weights `calibWeight` as an additional column as well as attributes. If no convergence has been reached in `maxIter` steps, and `returnNA` is TRUE (the default), the column `calibWeights` will only consist of NAs. The attributes of the table are attributes derived from the data, `table` class as well as the following.

<code>converged</code>	Did the algorithm converge in <code>maxIter</code> steps?
<code>iterations</code>	The number of iterations performed.
<code>conP</code> , <code>conH</code> , <code>epsP</code> , <code>epsH</code>	See Arguments.
<code>conP_adj</code> , <code>conH_adj</code>	Adjusted versions of <code>conP</code> and <code>conH</code>
<code>formP</code> , <code>formH</code>	Formulas that were used to calculate <code>conP_adj</code> and <code>conH_adj</code> based on the output table.

Author(s)

Alexander Kowarik, Gregor de Cillia

Examples

```
## Not run:

# load data
eusilc <- demo.eusilc(n = 1, prettyNames = TRUE)

# personal constraints
conP1 <- xtabs(pWeight ~ age, data = eusilc)
conP2 <- xtabs(pWeight ~ gender + region, data = eusilc)
conP3 <- xtabs(pWeight*eqIncome ~ gender, data = eusilc)

# household constraints
conH1 <- xtabs(pWeight ~ hsize + region, data = eusilc[!duplicated(hid)])

# simple usage -----

calibweights1 <- ipf(
  eusilc,
  conP = list(conP1, conP2, eqIncome = conP3),
  bound = NULL,
  verbose = TRUE
)

# compare personal weight with the calibweight
calibweights1[, .(hid, pWeight, calibWeight)]

# advanced usage -----

# use an array of tolerances
epsH1 <- conH1
epsH1[1:4, ] <- 0.005
epsH1[5, ] <- 0.2

# create an initial weight for the calibration
eusilc[, regSamp := .N, by = region]
eusilc[, regPop := sum(pWeight), by = region]
eusilc[, baseWeight := regPop/regSamp]

calibweights2 <- ipf(
  eusilc,
  conP = list(conP1, conP2),
  conH = list(conH1),
  epsP = 1e-6,
  epsH = list(epsH1),
  bound = 4,
  w = "baseWeight",
  verbose = TRUE
)

# show an adjusted version of conP and the original
attr(calibweights2, "conP_adj")
attr(calibweights2, "conP")
```

```
## End(Not run)
```

ipf_step

Perform one step of iterative proportional updating

Description

C++ routines to invoke a single iteration of the Iterative proportional updating (IPU) scheme. Targets and classes are assumed to be one dimensional in the ipf_step functions. combine_factors aggregates several vectors of type factor into a single one to allow multidimensional ipu-steps. See examples.

Usage

```
ipf_step_ref(w, classes, targets)
```

```
ipf_step(w, classes, targets)
```

```
ipf_step_f(w, classes, targets)
```

```
combine_factors(dat, targets)
```

Arguments

w	a numeric vector of weights. All entries should be positive.
classes	a factor variable. Must have the same length as w.
targets	key figure to target with the ipu scheme. A numeric vector of the same length as levels(classes). This can also be a table produced by xtabs. See examples.
dat	a data.frame containing the factor variables to be combined.

Details

ipf_step returns the adjusted weights. ipf_step_ref does the same, but updates w by reference rather than returning. ipf_step_f returns a multiplier: adjusted weights divided by unadjusted weights. combine_factors is designed to make ipf_step work with contingency tables produced by [xtabs](#).

Examples

```
##### one-dimensional ipu #####

## create random data
nobs <- 10
classLabels <- letters[1:3]
dat = data.frame(
  weight = exp(rnorm(nobs)),
```

```

    household = factor(sample(classLabels, nobs, replace = TRUE))
  )
  dat

  ## create targets (same lenght as classLabels!)
  targets <- 3:5

  ## calculate weights
  new_weight <- ipf_step(dat$weight, dat$household, targets)
  cbind(dat, new_weight)

  ## check solution
  xtabs(new_weight ~ dat$household)

  ## calculate weights "by reference"
  ipf_step_ref(dat$weight, dat$household, targets)
  dat

  ##### multidimensional ipu #####

  ## load data
  factors <- c("time", "sex", "smoker", "day")
  tips <- data.frame(sex=c("Female", "Male", "Male"), day=c("Sun", "Mon", "Tue"),
    time=c("Dinner", "Lunch", "Lunch"), smoker=c("No", "Yes", "No"))
  tips <- tips[factors]

  ## combine factors
  con <- xtabs(~., tips)
  cf <- combine_factors(tips, con)
  cbind(tips, cf)[sample(nrow(tips), 10, replace = TRUE),]

  ## adjust weights
  weight <- rnorm(nrow(tips)) + 5
  adjusted_weight <- ipf_step(weight, cf, con)

  ## check outputs
  con2 <- xtabs(adjusted_weight ~ ., data = tips)
  sum((con - con2)^2)

```

 kishFactor

Kish Factor

Description

Compute the design effect due to unequal weighting.

Usage

```
kishFactor(w, na.rm = FALSE)
```

Arguments

<code>w</code>	a numeric vector with weights
<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.

Details

The factor is computed according to 'Weighting for Unequal P_i', Leslie Kish, Journal of Official Statistics, Vol. 8. No. 2, 1992

$$def f = \sqrt{n} \sum_j w_j^2 / (\sum_j w_j)^2$$

Value

The function will return the kish factor

Author(s)

Alexander Kowarik

Examples

```
kishFactor(rep(1,10))
kishFactor(rlnorm(10))
```

plot.surveysd	<i>Plot surveysd-Objects</i>
---------------	------------------------------

Description

Plot results of `calc.stError()`

Usage

```
## S3 method for class 'surveysd'
plot(
  x,
  variable = x$param$var[1],
  type = c("summary", "grouping"),
  groups = NULL,
  sd.type = c("dot", "ribbon"),
  ...
)
```


Arguments

<code>x</code>	object of class 'surveysd' output of function calc.stError
<code>variable</code>	Name of the variable for which standard errors have been calculated in <code>dat</code>
<code>type</code>	can be either "summary" or "grouping", default value is "summary". For "summary" a barplot is created giving an overview of the number of estimates having the flag <code>smallGroup</code> , <code>cvHigh</code> , both or none of them. For 'grouping' results for point estimate and standard error are plotted for pre defined groups.
<code>groups</code>	If <code>type='grouping'</code> variables must be defined by which the data is grouped. Only 2 levels are supported as of right now. If only one group is defined the higher group will be the estimate over the whole period. Results are plotted for the first argument in <code>groups</code> as well as for the combination of <code>groups[1]</code> and <code>groups[2]</code> .
<code>sd.type</code>	can be either 'ribbon' or 'dot' and is only used if <code>type='grouping'</code> . Default is "dot" For <code>sd.type='dot'</code> point estimates are plotted and flagged if the corresponding standard error and/or the standard error using the mean over k-periods exceeded the value <code>cv.limit</code> (see calc.stError). For <code>sd.type='ribbon'</code> the point estimates including ribbons, defined by point estimate \pm estimated standard error are plotted. The calculated standard errors using the mean over k periods are plotted using less transparency. Results for the higher level (<code>~groups[1]</code>) are coloured grey.
<code>...</code>	additional arguments supplied to plot.

Examples

```
library(surveysd)

set.seed(1234)
eusilc <- demo.eusilc(n = 3, prettyNames = TRUE)

dat_boot <- draw.bootstrap(eusilc, REP = 3, hid = "hid", weights = "pWeight",
                           strata = "region", period = "year")

# calibrate weight for bootstrap replicates
dat_boot_calib <- recalib(dat_boot, conP.var = "gender", conH.var = "region")

# estimate weightedRatio for povmd60 per period
group <- list("gender", "region", c("gender", "region"))
err.est <- calc.stError(dat_boot_calib, var = "povertyRisk",
                        fun = weightedRatio,
                        group = group, period.mean = NULL)

plot(err.est)

# plot results for gender
# dotted line is the result on the national level
plot(err.est, type = "grouping", groups = "gender")
```

```
# plot results for rb090 in each db040
# with standard errors as ribbons
plot(err.est, type = "grouping", groups = c("gender", "region"), sd.type = "ribbon")
```

PointEstimates

Weighted Point Estimates

Description

Predefined functions for weighted point estimates in package `surveysd`.

Usage

```
weightedRatio(x, w)
```

```
weightedSum(x, w)
```

Arguments

x	numeric vector
w	weight vector

Details

Predefined functions are weighted ratio and weighted sum.

Value

Each of the functions return a single numeric value

Examples

```
x <- 1:10
w <- 10:1
weightedRatio(x,w)
x <- 1:10
w <- 10:1
weightedSum(x,w)
```

print.summary.ipf	<i>Print method for IPF calibration summary</i>
-------------------	---

Description

Provides a concise summary of an IPF (Iterative Proportional Fitting) calibration summary object. It extracts the calibration weight from `all_formulas`, computes the Kish factor for the weights, and prints the first 10 rows of any `calib_results_` tables. Useful for a quick overview of calibration results. Additional details can be explored with `str()` or `names()`.

Usage

```
## S3 method for class 'summary.ipf'  
print(x, ...)
```

Arguments

x	An object of class <code>summary.ipf</code> , as returned by summary.ipf .
...	Additional arguments (currently ignored).

Value

The input object x, invisibly (for chaining).

print.surveysd	<i>Print function for surveysd objects</i>
----------------	--

Description

Prints the results of a call to [calc.stError](#). Shows used variables and function, number of point estimates as well as properties of the results.

Usage

```
## S3 method for class 'surveysd'  
print(x, ...)
```

Arguments

x	an object of class 'surveysd'
...	additonal parameters

recalib

*Calibrate weights***Description**

Calibrate weights for bootstrap replicates by using iterative proportional updating to match population totals on various household and personal levels.

Usage

```
recalib(
  dat,
  hid = attr(dat, "hid"),
  weights = attr(dat, "weights"),
  b.rep = attr(dat, "b.rep"),
  period = attr(dat, "period"),
  conP.var = NULL,
  conH.var = NULL,
  conP = NULL,
  conH = NULL,
  epsP = 0.01,
  epsH = 0.02,
  ...
)
```

Arguments

<code>dat</code>	either <code>data.frame</code> or <code>data.table</code> containing the sample survey for various periods.
<code>hid</code>	character specifying the name of the column in <code>dat</code> containing the household ID.
<code>weights</code>	character specifying the name of the column in <code>dat</code> containing the sample weights.
<code>b.rep</code>	character specifying the names of the columns in <code>dat</code> containing bootstrap weights which should be recalibrated
<code>period</code>	character specifying the name of the column in <code>dat</code> containing the sample period.
<code>conP.var</code>	character vector containig person-specific variables to which weights should be calibrated or a list of such character vectors. Contingency tables for the population are calculated per period using weights. If a vector is supplied contingency tables will be calculated for each vector entry. If a list is supplied contingency tables will be calculated for each list entry. See examples for more details.
<code>conH.var</code>	character vector containig household-specific variables to which weights should be calibrated or a list of such character vectors. Contingency tables for the population are calculated per period using weights. If a vector is supplied contingency tables will be calculated for each vector entry. If a list is supplied

	contingency tables will be calculated for each list entry. See examples for more details.
conP	list or (partly) named list defining the constraints on person level. The list elements are contingency tables in array representation with dimnames corresponding to the names of the relevant calibration variables in <code>dat</code> . If a numerical variable is to be calibrated, the respective list element has to be named with the name of that numerical variable. Otherwise the list element should NOT be named.
conH	list or (partly) named list defining the constraints on household level. The list elements are contingency tables in array representation with dimnames corresponding to the names of the relevant calibration variables in <code>dat</code> . If a numerical variable is to be calibrated, the respective list element has to be named with the name of that numerical variable. Otherwise the list element should NOT be named.
epsP	numeric value specifying the convergence limit for <code>conP.var</code> or <code>conP</code> , see ipf() .
epsH	numeric value specifying the convergence limit for <code>conH.var</code> or <code>conH</code> , see ipf() .
...	additional arguments passed on to function ipf() from this package.

Details

`recalib` takes survey data (`dat`) containing the bootstrap replicates generated by [draw.bootstrap](#) and calibrates weights for each bootstrap replication according to population totals for person- or household-specific variables.

`dat` must be household data where household members correspond to multiple rows with the same household identifier. The data should at least contain the following columns:

- Column indicating the sample period;
- Column indicating the household ID;
- Column containing the household sample weights;
- Columns which contain the bootstrap replicates (see output of [draw.bootstrap](#));
- Columns indicating person- or household-specific variables for which sample weight should be adjusted.

For each period and each variable in `conP.var` and/or `conH.var` contingency tables are estimated to get margin totals on personal- and/or household-specific variables in the population.

Afterwards the bootstrap replicates are multiplied with the original sample weight and the resulting product is then adjusted using [ipf\(\)](#) to match the previously calculated contingency tables. In this process the columns of the bootstrap replicates are overwritten by the calibrated weights.

Value

Returns a `data.table` containing the survey data as well as the calibrated weights for the bootstrap replicates. The original bootstrap replicates are overwritten by the calibrated weights. If calibration of a bootstrap replicate does not converge the bootstrap weight is not returned and numeration of the returned bootstrap weights is reduced by one.


```
conH = NULL, verbose = TRUE)
```

```
rescaled.bootstrap
```

Draw bootstrap replicates

Description

Draw bootstrap replicates from survey data using either the rescaled bootstrap for stratified multi-stage sampling, presented by J. Preston (2009) or the Rao-Wu bootstrap by J. N. K. Rao and C. F. J. Wu (1988)

Usage

```
rescaled.bootstrap(
  dat,
  method = c("Preston", "Rao-Wu"),
  REP = 1000,
  strata = "DB050>1",
  cluster = "DB060>DB030",
  fpc = "N.cluster>N.households",
  single.PSU = c("merge", "mean"),
  return.value = c("data", "replicates"),
  run.input.checks = TRUE,
  already.selected = NULL,
  seed = NULL
)
```

Arguments

<code>dat</code>	either data frame or data table containing the survey sample
<code>method</code>	for bootstrap replicates, either "Preston" or "Rao-Wu"
<code>REP</code>	integer indicating the number of bootstraps to be drawn
<code>strata</code>	string specifying the column name in <code>dat</code> that is used for stratification. For multistage sampling multiple column names can be specified by <code>strata=c("strata1","strata2","strata3")</code> or <code>strata=c("strata1>strata2>strata3")</code> . See Details for more information.
<code>cluster</code>	string specifying the column name in <code>dat</code> that is used for clustering. For instance given a household sample the column containing the household ID should be supplied. For multistage sampling multiple column names can be specified by <code>cluster=c("cluster1","cluster2","cluster3")</code> or <code>cluster=c("cluster1>cluster2>cluster3")</code> . See Details for more information.
<code>fpc</code>	string specifying the column name in <code>dat</code> that contains the number of PSUs at the first stage. For multistage sampling the number of PSUs at each stage must be specified by <code>strata=c("fpc1","fpc2","fpc3")</code> or <code>strata=c("fpc1>fpc2>fpc3")</code> .

<code>single.PSU</code>	either "merge" or "mean" defining how single PSUs need to be dealt with. For <code>single.PSU="merge"</code> single PSUs at each stage are merged with the strata or cluster with the next least number of PSUs. If multiple of those exist one will be select via random draw. For <code>single.PSU="mean"</code> single PSUs will get the mean over all bootstrap replicates at the stage which did not contain single PSUs.
<code>return.value</code>	either "data", "replicates" and/or "selection" specifying the return value of the function. For "data" the survey data is returned as <code>class data.table</code> , for "replicates" only the bootstrap replicates are returned as <code>data.table</code> . For "selection" list of <code>data.tables</code> with length of <code>length(strata)</code> is returned containing 1:REP 0-1 columns indicating if a PSU was selected for each sampling stage.
<code>run.input.checks</code>	logical, if TRUE the input will be checked before applying the bootstrap procedure
<code>already.selected</code>	list of <code>data.tables</code> or NULL where each <code>data.table</code> contains columns in <code>cluster</code> , <code>strata</code> and additionally 1:REP columns containing 0-1 values which indicate if a PSU was selected for each bootstrap replicate. Each of the <code>data.tables</code> corresponds to one of the sampling stages. First entry in the list corresponds to the first sampling stage and so on.
<code>seed</code>	integer specifying the seed for the random number generator.

Details

For specifying multistage sampling designs the column names in `strata`, `cluster` and `fpc` need to be separated by ">".

For multistage sampling the strings are read from left to right meaning that the first vector entry or column name before the first ">" is taken as the column for stratification/clustering/number of PSUs at the first and the last vector entry or column after the last ">" is taken as the column for stratification/clustering/number of PSUs at the last stage. If for some stages the sample was not stratified or clustered one must specify this by "1" or "I", e.g. `strata=c("strata1", "I", "strata3")` or `strata=c("strata1>I>strata3")` if there was no stratification at the second stage or `cluster=c("cluster1", "cluster2")` respectively `cluster=c("cluster1>cluster2>I")` if there were no clusters at the last stage.

The number of PSUs at each stage is not calculated internally and must be specified for any sampling design. For single stage sampling using stratification this can usually be done by adding over all sample weights of each PSU by each strata-code.

Spaces in each of the strings will be removed, so if column names contain spaces they should be renamed before calling this procedure!

If `already.selected` is supplied the sampling of bootstrap replicates considers if specific PSUs have already been selected by a previous survey wave. For a specific strata and cluster this could lead to more than $\text{floor}(n/2)$ records selected. In that case records will be de-selected such that $\text{floor}(n/2)$ records, with n as the total number of records, are selected for each strata and cluster. This parameter is mostly used by [draw.bootstrap](#) in order to consider the rotation of the sampling units over time.

Value

returns the complete data set including the bootstrap replicates or just the bootstrap replicates, depending on `return.value="data"` or `return.value="replicates"` respectively.

Author(s)

Johannes Gussenbauer, Eileen Vattheuer, Statistics Austria

References

Preston, J. (2009). Rescaled bootstrap for stratified multistage sampling. *Survey Methodology*. 35. 227-234. Rao, J. N. K., and C. F. J. Wu. (1988). Resampling Inference with Complex Survey Data. *Journal of the American Statistical Association* 83 (401): 231-41.

Examples

```
library(surveysd)
library(data.table)
setDTthreads(1)
set.seed(1234)
eusilc <- demo.eusilc(n = 1, prettyNames = TRUE)

eusilc[, N.households := uniqueN(hid), by = region]
eusilc.bootstrap <- rescaled.bootstrap(eusilc, REP = 10, strata = "region",
                                       cluster = "hid", fpc = "N.households")

eusilc[, new_strata := paste(region, hsize, sep = "_")]
eusilc[, N.households := uniqueN(hid), by = new_strata]
eusilc.bootstrap <- rescaled.bootstrap(eusilc, REP = 10, strata = c("new_strata"),
                                       cluster = "hid", fpc = "N.households")
```

summary.ipf

Generate Summary Output for IPF Calibration

Description

Generates a detailed summary of an Iterative Proportional Fitting (IPF) calibration, providing a complete tool for evaluating the calibration's success and the validity of the resulting weights.

The output is a list of data.tables for a comprehensive evaluation, including:

Calibration Results:

- `calib_results_conP_*` and `calib_results_conH_*`: Key diagnostic tables that compare calibrated margins to population targets and assess the goodness of fit via metrics like `maxFac`.

Data and Diagnostics:

- `weighted_data`: An excerpt of the final dataset with the calculated calibration weights.
- `distribution of the weights`: A statistical overview of the weight distribution (min, max, CV).

Detailed Margin Comparisons:

- conP_*, conH_*, *_adjusted, *_original, *_rel_diff_*: Tables that compare original sample margins, calibrated margins, and population targets, along with their relative differences.

Usage

```
## S3 method for class 'ipf'
summary(object, ...)
```

Arguments

```
object      object of class ipf
...         additional arguments
```

Value

a list of the following outputs

Examples

```
## Not run:
# load data
eusilc <- demo.eusilc(n = 1, prettyNames = TRUE)

# personal constraints
conP1 <- xtabs(pWeight ~ age, data = eusilc)
conP2 <- xtabs(pWeight ~ gender + region, data = eusilc)
conP3 <- xtabs(pWeight*eqIncome ~ gender, data = eusilc)

# household constraints
conH1 <- xtabs(pWeight ~ hsize + region, data = eusilc)

# simple usage -----

calibweights1 <- ipf(
  eusilc,
  conP = list(conP1, conP2, eqIncome = conP3),
  bound = NULL,
  verbose = TRUE
)
output <- summary(calibweights1)
# the output can easily be exported to an Excel file, e.g. with
# library(openxlsx)
# write.xlsx(output, "SummaryIPF.xlsx")

## End(Not run)
```

Index

- * **manip**
 - calc.stError, [2](#)
- * **survey**
 - calc.stError, [2](#)
- calc.stError, [2](#), [25](#), [27](#)
- combine_factors (ipf_step), [22](#)
- computeFrac (computeLinear), [7](#)
- computeLinear, [7](#)
- computeLinearG1 (computeLinear), [7](#)
- computeLinearG1_old (computeLinear), [7](#)
- cpp_mean, [9](#)
- data.table, [14](#)
- demo.eusilc, [10](#)
- draw.bootstrap, [2](#), [3](#), [6](#), [11](#), [29](#), [32](#)
- draw.bootstrap(), [16](#)
- generate.HHID, [15](#)
- geometric_mean_reference (cpp_mean), [9](#)
- get.selection, [16](#)
- get.selection(), [12](#), [13](#)
- ipf, [8](#), [18](#)
- ipf(), [29](#), [30](#)
- ipf_step, [22](#)
- ipf_step_f (ipf_step), [22](#)
- ipf_step_ref (ipf_step), [22](#)
- kishFactor, [23](#)
- laeken::eusilc, [10](#)
- numericalWeighting, [20](#)
- numericalWeighting (computeLinear), [7](#)
- plot.surveysd, [24](#)
- PointEstimates, [26](#)
- print.summary.ipf, [27](#)
- print.surveysd, [27](#)
- recalib, [2–4](#), [6](#), [28](#)
- rescaled.bootstrap, [13](#), [31](#)
- summary.ipf, [27](#), [33](#)
- weightedRatio, [3](#)
- weightedRatio (PointEstimates), [26](#)
- weightedSum, [3](#)
- weightedSum (PointEstimates), [26](#)
- xtabs, [22](#)