

Package ‘tkrplot’

May 26, 2025

Version 0.0-30
Author Luke Tierney <luke-tierney@uiowa.edu>
Description Simple mechanism for placing R graphics in a Tk widget.
Title TK Rplot
Depends R (>= 2.13), grDevices, tcltk
License GPL
Maintainer Luke Tierney <luke-tierney@uiowa.edu>
SystemRequirements Windows or X11
NeedsCompilation yes
Repository CRAN
Date/Publication 2025-05-26 07:20:02 UTC

Contents

TkRplot	1
Index	3

TkRplot	<i>Tk Rplot</i>
---------	-----------------

Description

Placing R graphics in a Tk image.

Usage

```
tkrplot(parent, fun, hscale=1, vscale=1)
tkrreplot(lab, fun = lab$fun, hscale=lab$hscale, vscale=lab$vscale)
tkpersp(x,y,z, theta = 30,phi = 30,expand = 0.5, r = sqrt(3), ...)
.my.tkdev(hscale = 1, vscale = 1)
.make.tkindex()
```

Arguments

parent	parent of widget window
fun	function of no arguments that creates the plot
lab	a Tk Rplot label widget
hscale	horizontal scale factor for image size
vscale	vertical scale factor for image size
x	as for persp
y	as for persp
z	as for persp
theta	as for persp
phi	as for persp
expand	as for persp
r	as for persp
...	additional arguments for persp

Details

The function `tkrplot` creates and returns a Tk label widget containing a Tk image of type Rplot. For now the size is hard-wired. The plot is created by calling `fun` with a special device used create the image.

The function `tkrreplot` calls `fun` to place a new plot in the Rplot widget `lab`.

`tkpersp` is called like `persp` but produces a plot in which some of the parameters of `persp` are controlled graphically.

`.my.tkdev` and `.make.tkindex` are useful for defining new functions like `tkrplot`.

Examples

```
## Not run:
## These cannot be run by examples() but should be OK when pasted
## into an interactive R session with the tcltk package loaded

tt <- tktoplevel()
bb<-1
img <-tkrplot(tt, function() plot(1:20,(1:20)^bb))
f<-function(...) {
  b <- as.numeric(tclvalue("bb"))
  if (b != bb) {
    bb <- b
    tkrreplot(img)
  }
}
s <- tkscale(tt, command=f, from=0.05, to=2.00, variable="bb",
            showvalue=FALSE, resolution=0.05, orient="horiz")
tkpack(img,s)

## End(Not run)
```

Index

* **misc**

- TkRplot, [1](#)
- .make.tkindex (TkRplot), [1](#)
- .my.tkdev (TkRplot), [1](#)
- tkpersp (TkRplot), [1](#)
- TkRplot, [1](#)
- tkrplot (TkRplot), [1](#)
- tkrreplot (TkRplot), [1](#)