

Package ‘BwQuant’

January 20, 2025

Type Package

Title Bandwidth Selectors for Local Linear Quantile Regression

Version 0.1.0

Date 2022-01-31

Depends R (>= 2.6), quantreg, KernSmooth, nleqslv

Description

Bandwidth selectors for local linear quantile regression, including cross-validation and plug-in methods. The local linear quantile regression estimate is also implemented.

Language en-GB

License GPL-2

Encoding UTF-8

Biarch true

NeedsCompilation yes

Author Mercedes Conde-Amboage [aut, cre] (<<https://orcid.org/0000-0003-0306-8142>>),
Cesar Sanchez-Sellero [aut] (<<https://orcid.org/0000-0003-0046-0819>>)

Maintainer Mercedes Conde-Amboage <mercedes.amboage@usc.es>

Repository CRAN

Date/Publication 2022-02-08 16:00:11 UTC

Contents

BwQuant-package	2
bwCV	2
bwPI	3
bwRT	4
bwYJ	5
llqr	6

Index

8

BwQuant-package

*Bandwidth selectors for local linear quantile regression***Description**

The R package BwQuant implements different bandwidth selectors for local linear quantile regression, including selectors based on rule of thumb, plug-in and cross-validation techniques.

Author(s)

Mercedes Conde-Amboage <mercedes.amboage@usc.es> and Cesar Sanchez-Sellero <cesar.sanchez@usc.es>
Maintainer: Mercedes Conde-Amboage <mercedes.amboage@usc.es>

bwCV

*Computing the cross-validation bandwidth proposed by Abberger (1998)***Description**

Function to compute a bandwidth for local linear quantile regression following the cross-validation criteria presented by Abberger (1998).

Usage

```
bwCV(x, y, hseq, tau)
```

Arguments

- | | |
|-------------------|--|
| <code>x</code> | numeric vector of x data. |
| <code>y</code> | numeric vector of y data. This must be the same length as <code>x</code> . |
| <code>hseq</code> | sequence of values where the cross-validation function will be evaluated. |
| <code>tau</code> | the quantile order where the regression function is to be estimated. It must be a number strictly between 0 and 1. |

Details

The cross-validation function is evaluated at each element of `hseq`. Then, the cross-validation selector will be the element of `hseq` that minimizes the cross-validation function.

Value

Returns a number with the chosen bandwidth.

Author(s)

Mercedes Conde-Amboage and Cesar Sanchez-Sellero.

References

- Abberger, K. (1998). Cross-validation in nonparametric quantile regression. *Allgemeines Statistisches Archiv*, 82, 149-161.
- Abberger, K. (2002). Variable data driven bandwidth choice in nonparametric quantile regression. Technical Report.

See Also

The obtained bandwidth can be used in the function [llqr](#) to produce a local linear estimate of the tau-quantile regression function.

Examples

```
set.seed(1234)
x=runif(100)
y=10*(x^4+x^2-x)+rexp(100)
hseq=seq(0.05,0.8,length=21)
tau=0.25
bwCV(x,y,hseq,tau)
```

bwPI

Computing the plug-in bandwidth proposed by Conde-Amboage and Sanchez-Sellero (2018)

Description

Function to compute a bandwidth selector for local linear quantile regression following the plug-in rule proposed in Section 2.2 of Conde-Amboage and Sanchez-Sellero (2018).

Usage

```
bwPI(x, y, tau)
```

Arguments

- | | |
|-----|--|
| x | numeric vector of x data. |
| y | numeric vector of y data. This must be the same length as x. |
| tau | the quantile order where the regression function is to be estimated. It must be a number strictly between 0 and 1. |

Value

Returns a bandwidth for a local linear estimate of the tau-quantile regression function.

Author(s)

Mercedes Conde-Amboage and Cesar Sanchez-Sellero.

References

Conde-Amboage, M. and Sanchez-Sellero, C. (2018). A plug-in bandwidth selector for nonparametric quantile regression. TEST, 28, 423-450. <doi:10.1007/s11749-018-0582-6>.

See Also

The obtained bandwidth can be used in the function [llqr](#) to produce a local linear estimate of the tau-quantile regression function.

Examples

```
set.seed(1234)
x=runif(100)
y=10*(x^4+x^2-x)+rexp(100)
tau=0.25
bwPI(x,y,tau)
```

bwRT

*Computing a bandwidth using a rule of thumb***Description**

Function to compute a bandwidth selector for local linear quantile regression following the rule of thumb presented in Section 2.1 of Conde-Amboage and Sanchez-Sellero (2018).

Usage

```
bwRT(x, y, tau)
```

Arguments

- | | |
|------------------|--|
| <code>x</code> | numeric vector of x data. |
| <code>y</code> | numeric vector of y data. This must be the same length as <code>x</code> . |
| <code>tau</code> | the quantile order where the regression function is to be estimated. It must be a number strictly between 0 and 1. |

Value

Returns a bandwidth for a local linear estimate of the tau-quantile regression function.

Author(s)

Mercedes Conde-Amboage and Cesar Sanchez-Sellero.

References

Conde-Amboage, M. and Sanchez-Sellero, C. (2018). A plug-in bandwidth selector for nonparametric quantile regression. TEST, 28, 423-450. <doi:10.1007/s11749-018-0582-6>.

See Also

The obtained bandwidth can be used in the function [llqr](#) to produce a local linear estimate of the tau-quantile regression function.

Examples

```
set.seed(1234)
x=runif(100)
y=10*(x^4+x^2-x)+rexp(100)
tau=0.25
bwRT(x,y,tau)
```

bwYJ

Computing the plug-in bandwidth proposed by Yu and Jones (1998)

Description

Function to compute a bandwidth selector for local linear quantile regression following the plug-in rule proposed by Yu and Jones (1998).

Usage

```
bwYJ(x, y, tau)
```

Arguments

x	numeric vector of x data.
y	numeric vector of y data. This must be the same length as x.
tau	the quantile order where the regression function is to be estimated. It must be a number strictly between 0 and 1.

Value

Returns a bandwidth for a local linear estimate of the tau-quantile regression function.

Author(s)

Mercedes Conde-Amboage and Cesar Sanchez-Sellero.

References

- Ruppert, D., Sheather, S. J. and Wand, M. P. (1995). An efective bandwidth selector for local least squares regression. *Journal of the American Statistical Association*. 90, 1257-1270.
- Yu, K. and Jones, M. C. (1998). Local linear quantile regression. *Journal of the American Statistical Association*, 93, 228-237.

See Also

The obtained bandwidth can be used in the function [llqr](#) to produce a local linear estimate of the tau-quantile regression function.

Examples

```
set.seed(1234)
x=runif(100)
y=10*(x^4+x^2-x)+rexp(100)
tau=0.25
bwYJ(x,y,tau)
```

[llqr](#)

Fitting a local linear quantile regression model

Description

Function that estimates the quantile regression function using a local linear kernel smoother.

Usage

```
llqr(x, y, tau, t, h)
```

Arguments

x	numeric vector of x data.
y	numeric vector of y data. This must be the same length as x.
tau	the quantile order where the regression function is to be estimated. It must be a number strictly between 0 and 1.
t	the values of x at which the quantile regression model is to be estimated.
h	the bandwidth parameter.

Value

A list with the following components:

x.values	the given points at which the evaluation occurs.
y.values	the estimated values of the quantile regression function at the given x.values.

Author(s)

Mercedes Conde-Amboage and Cesar Sanchez-Sellero.

References

- Fan, J., Hu, T. C. and Truong, Y. K. (1994). Robust nonparametric function estimation. Scandinavian Journal of Statistics, 21, 433-446.
- Yu, K. and Jones, M. C. (1998). Local linear quantile regression. Journal of the American Statistical Association, 93, 228-237.

See Also

The argument *h* with the bandwidth parameter can be fixed to some arbitrary value or chosen by one of the procedures implemented in the functions [bwCV](#), [bwPI](#), [bwRT](#) or [bwYJ](#).

Examples

```
set.seed(1234)
x=runif(100)
y=10*(x^4+x^2-x)+rexp(100)
tau=0.25
h=bwPI(x,y,tau)
t=seq(0,1,length=101)
m=llqr(x,y,tau,t,h)
plot(x,y)
lines(m$x.values,m$y.values)
```

Index

* bandwidth selection

[bwCV](#), [2](#)
[bwPI](#), [3](#)
[bwRT](#), [4](#)
[bwYJ](#), [5](#)
[llqr](#), [6](#)

* local linear quantile regression

[bwCV](#), [2](#)
[bwPI](#), [3](#)
[bwRT](#), [4](#)
[bwYJ](#), [5](#)
[llqr](#), [6](#)

* package

[BwQuant-package](#), [2](#)

[bwCV](#), [2](#), [7](#)
[bwPI](#), [3](#), [7](#)
[BwQuant \(BwQuant-package\)](#), [2](#)
[BwQuant-package](#), [2](#)
[bwRT](#), [4](#), [7](#)
[bwYJ](#), [5](#), [7](#)

[llqr](#), [3–6](#), [6](#)