

# Package ‘CovCorTest’

June 6, 2025

**Title** Statistical Tests for Covariance and Correlation Matrices and  
their Structures

**Version** 1.0.0

**Maintainer** Svenja Jedhoff <jedhoff@statistik.tu-dortmund.de>

**Description** A compilation of tests for hypotheses regarding covariance  
and correlation matrices for one or more groups. The hypothesis can  
be specified through a corresponding hypothesis matrix and a vector or  
by choosing one of the basic hypotheses, while for the structure test,  
only the latter works. Thereby Monte-Carlo and Bootstrap-techniques  
are used, and the respective method must be chosen, and the functions  
provide p-values and mostly also estimators of calculated covariance  
matrices of test statistics. For more details on the methodology, see  
Sattler et al. (2022) <[doi:10.1016/j.jspi.2021.12.001](https://doi.org/10.1016/j.jspi.2021.12.001)>,  
Sattler and Pauly (2024) <[doi:10.1007/s11749-023-00906-6](https://doi.org/10.1007/s11749-023-00906-6)>, and  
Sattler and Dobler (2025) <[doi:10.48550/arXiv.2310.11799](https://arxiv.org/abs/2310.11799)>.

**License** GPL (>= 3)

**Imports** MANOVA.RM, matrixcalc

**Suggests** testthat (>= 3.0.0)

**Config/testthat.edition** 3

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**URL** <https://github.com/sjedhoff/CovCorTest>

**BugReports** <https://github.com/sjedhoff/CovCorTest/issues>

**NeedsCompilation** no

**Author** Paavo Sattler [aut] (ORCID: <<https://orcid.org/0000-0001-8731-0893>>),  
Svenja Jedhoff [cre, aut] (ORCID:  
<<https://orcid.org/0009-0008-2939-9103>>),  
Markus Pauly [ctb] (ORCID: <<https://orcid.org/0000-0002-0976-7190>>),  
Arne C Bathke [ctb] (ORCID: <<https://orcid.org/0000-0002-6260-3726>>),  
Dennis Dobler [ctb] (ORCID: <<https://orcid.org/0000-0002-9040-0854>>)

**Repository** CRAN

**Date/Publication** 2025-06-06 13:30:13 UTC

## Contents

<code>print.CombTest</code> . . . . .	2
<code>print.CovTest</code> . . . . .	2
<code>test_combined</code> . . . . .	3
<code>test_correlation</code> . . . . .	4
<code>test_correlation_structure</code> . . . . .	5
<code>test_covariance</code> . . . . .	6
<code>test_covariance_structure</code> . . . . .	8

## Index

9

`print.CombTest`      *Print function for CombTest object*

### Description

Print function for CombTest object

### Usage

```
## S3 method for class 'CombTest'
print(x, ...)
```

### Arguments

<code>x</code>	an <code>CombTest</code> object
<code>...</code>	additional parameters

### Value

no return, just print

`print.CovTest`      *Print function for CovTest object*

### Description

Print function for CovTest object

### Usage

```
## S3 method for class 'CovTest'
print(x, ...)
```

**Arguments**

- x an [CovTest](#) object
- ... additional parameters

**Value**

no return, just print

test_combined	<i>Combined test for equality of covariance matrices and correlation matrices</i>
---------------	---

**Description**

For two groups a combined test for equality of covariance matrices and equality of correlation matrices between these groups is conducted. Both hypotheses can be rejected or only the larger one, the equality of the covariance matrices

**Usage**

```
test_combined(X, nv = NULL, repetitions = 1000)
```

**Arguments**

- X a list or matrix containing the observation vectors. In case of a list, each matrix in this list is another group, where the observation vectors are the columns. For a matrix, all groups are together in one matrix and nv is used to indicate the group sizes.
- nv vector of group sizes
- repetitions a scalar, indicate the number of runs for the chosen method. The predefined value is 1.000, and the number should not be below 500.

**Value**

an object of the class [CovTest](#).

**Examples**

```
# Load the data
data("EEGwide", package = "MANOVA.RM")

vars <- colnames(EEGwide)[1:6]

# Part the data into six groups of sex and diagnosis
X_list <- list(t(EEGwide[EEGwide$sex=="M" & EEGwide$diagnosis=="AD",vars]),
t(EEGwide[EEGwide$sex=="M" & EEGwide$diagnosis=="MCI",vars]))
```

```
nv <- unlist(lapply(X_list, ncol))
set.seed(31415)
test_combined(X_list, nv)
```

**test\_correlation**      *Test for Correlation Matrices*

## Description

This function conducts statistical tests for hypotheses regarding correlation matrices. Users can either select from predefined hypotheses or provide their own contrast matrix C and vector Xi for custom hypotheses. It supports both bootstrap and Monte Carlo resampling methods to obtain the p-value of the ANOVA-type statistic (ATS).

## Usage

```
test_correlation(
  X,
  nv = NULL,
  C = NULL,
  Xi = NULL,
  hypothesis = NULL,
  method = "BT",
  repetitions = 1000
)
```

## Arguments

X	A list or a matrix containing the observation vectors. If a list, each entry is a group, with observations as columns. If a matrix, all groups are combined, and nv must be used to indicate group sizes.
nv	(Optional) A vector indicating group sizes, needed when X is a combined matrix or for multiple groups.
C	(Optional) A user-defined contrast matrix for testing custom hypotheses. Must match dimensions with Xi.
Xi	(Optional) A numeric vector used in combination with C to specify a custom hypothesis.
hypothesis	A character string describing the null hypothesis. Must be one of "equal-correlated" or "uncorrelated". If supplied, C and Xi are ignored.
method	A character indicating the resampling method: "BT" (Bootstrap) or "MC" (Monte Carlo).
repetitions	Number of repetitions to use for the resampling method (default: 1000, should be $\geq 500$ ).

## Value

An object of class "CovTest".

## References

Sattler, P. and Pauly, M. (2024). Testing hypotheses about correlation matrices in general MANOVA designs. *TEST*, 33(2), 496–516. doi:[10.1007/s11749023009066](https://doi.org/10.1007/s11749023009066)

## Examples

```
# Example with one group:
set.seed(31415)
X <- matrix(rnorm(5 * 100), nrow = 5)
test_correlation(X, hypothesis = "uncorrelated",
                 method = "BT", repetitions = 100)
```

## test\_correlation\_structure

*Test for structure of data's correlation matrix*

## Description

With this function the correlation matrix of data can be checked for one of the predefined structures. Depending on the chosen method a bootstrap, the Taylor-based Monte-Carlo approach or Monte-Carlo-technique is used to calculate the p-value of the Anova-type-statistic(ATS) based on a specified number of runs.

## Usage

```
test_correlation_structure(X, structure, method = "BT", repetitions = 1000)
```

## Arguments

X	a matrix containing the observation vectors as columns (one group)
structure	a character specifying the structure regarding them the correlation matrix should be checked. Options are "Hautoregressive" ("Har"), "diagonal" ("diag"), "Hcom-poundsymmetry" ("Hcs") and "Htoeplitz" ("Hteop").
method	a character, to chose whether bootstrap("BT") or Taylor-based Monte-Carlo-approach("TAY") or Monte-Carlo-technique("MC") is used, while bootstrap is the predefined method.
repetitions	a scalar, indicate the number of runs for the chosen method. The predefined value is 1,000, and the number should not be below 500.

## Value

an object of the class [CovTest](#)

## References

Sattler, P. and Dobler, D. (2025). Testing for patterns and structures in covariance and correlation matrices. *arXiv preprint* <https://arxiv.org/abs/2310.11799>

## Examples

```
# Load the data
data("EEGwide", package = "MANOVA.RM")

# Select only the males with the diagnosis AD
X <- as.matrix(EEGwide[EEGwide$sex == "W" & EEGwide$diagnosis == "AD",
  c("brainrate_temporal", "brainrate_frontal", "brainrate_central",
  "complexity_temporal", "complexity_frontal",
  "complexity_central")])

test_correlation_structure(X = X, structure = "diagonal", method = "MC")
```

**test\_covariance**      *Test for Covariance Matrices*

## Description

This function conducts statistical tests for hypotheses regarding covariance matrices. Users can either select from predefined hypotheses (e.g., equal covariance, equal trace, etc.) or provide their own contrast matrix C and vector Xi for custom hypotheses. It supports both bootstrap and Monte Carlo resampling methods to obtain the p-value of the ANOVA-type statistic (ATS).

## Usage

```
test_covariance(
  X,
  nv = NULL,
  C = NULL,
  Xi = NULL,
  hypothesis = NULL,
  A = NULL,
  method = "MC",
  repetitions = 1000
)
```

## Arguments

- |    |   |
|----|---|
| X  | A list or a matrix containing the observation vectors. If a list, each entry is a group, with observations as columns. If a matrix, all groups are combined, and nv must be used to indicate group sizes. |
| nv | (Optional) A vector indicating group sizes, needed when X is a combined matrix or for multiple groups.  |

C	(Optional) A user-defined contrast matrix for testing custom hypotheses. Must match dimensions with Xi.
Xi	(Optional) A numeric vector used in combination with C to specify a custom hypothesis.
hypothesis	A character specifying one of the predefined hypotheses: <ul style="list-style-type: none"> <li>• "equal" — equal covariance matrices</li> <li>• "equal-trace" — equal traces across groups</li> <li>• "equal-diagonals" — equal variances across groups</li> <li>• "given-trace" — test against a given trace (single group only)</li> <li>• "given-matrix" — test against a given covariance matrix (single group only)</li> <li>• "uncorrelated" — test if variables are uncorrelated (single group only)</li> </ul> If C and Xi are provided, this can be set to NULL.
A	Optional scalar or matrix to define the hypothesis value when hypothesis is "given-trace" (scalar) or "given-matrix" (matrix). Ignored for other hypotheses.
method	A character indicating the resampling method: "BT" (Bootstrap) or "MC" (Monte Carlo).
repetitions	Number of repetitions to use for the resampling method (default: 1000, should be >= 500).

## Value

An object of class [CovTest](#).

## References

Sattler, P., Bathke, A. C., and Pauly, M. (2022). "Testing hypotheses about covariance matrices in general MANOVA designs." *Journal of Statistical Planning and Inference*, 219, 134–146. [doi: 10.1016/j.jspi.2021.12.001](https://doi.org/10.1016/j.jspi.2021.12.001)

## Examples

```
# Load the data
data("EEGwide", package = "MANOVA.RM")

vars <- colnames(EEGwide)[1:6]

X <- t(EEGwide[EEGwide$sex == "M" & EEGwide$diagnosis == "AD", vars])

# Testing the trace
C <- matrix(c(1,0,0,0,0,0,1,0,0,0,0,1,0,0,0,0,1,0,0,1,0,1), nrow = 1, ncol = 21)
Xi <- 2
set.seed(31415)
test_covariance(X = X, nv = NULL, C = C, Xi = Xi, method = "BT",
                 repetitions = 1000)
```

**test\_covariance\_structure***Test for structure of data's covariance matrix*

---

**Description**

This function conducts the test for the covariance matrix of data regarding structures. Depending on the chosen method a bootstrap or Monte-Carlo-technique is used to calculate p-value of the Anova-type-statistic(ATS) based on a specified number of runs.

**Usage**

```
test_covariance_structure(X, structure, method = "BT", repetitions = 1000)
```

**Arguments**

X	a matrix containing the observation vectors as columns (one group only)
structure	a character specifying the structure regarding the covariance matrix should be checked. Options are "autoregressive" ("ar"), "FO-autoregressive" ("FO-ar"), "diagonal" ("diag"), "sphericity" ("spher"), "compoundsymmetry" ("cs") and "toeplitz" ("toep").
method	a character, to chose whether bootstrap("BT") or Monte-Carlo-technique("MC") is used, while bootstrap is the predefined method.
repetitions	a scalar, indicate the number of runs for the chosen method. The predefined value is 1,000, and the number should not be below 500.

**Value**

an object of the class `CovTest`

**References**

Sattler, P. and Dobler, D. (2025). Testing for patterns and structures in covariance and correlation matrices. *arXiv preprint* <https://arxiv.org/abs/2310.11799>

**Examples**

```
# Load the data
data("EEGwide", package = "MANOVA.RM")

# Select only the males with the diagnosis AD
X <- as.matrix(EEGwide[EEGwide$sex == "W" & EEGwide$diagnosis == "AD",
                      c("brainrate_temporal", "brainrate_frontal",
                        "brainrate_central", "complexity_temporal",
                        "complexity_frontal", "complexity_central")])

test_covariance_structure(X = X, structure = "diagonal", method = "MC")
```

# Index

CombTest, 2  
CovTest, 3, 5, 7, 8  
  
print.CombTest, 2  
print.CovTest, 2  
  
test\_combined, 3  
test\_correlation, 4  
test\_correlation\_structure, 5  
test\_covariance, 6  
test\_covariance\_structure, 8