Package 'DiceEval'

January 20, 2025

Title Construction and Evaluation of Metamodels

Version 1.6.1

Date 2023-11-30

Author D. Dupuy and C. Helbert

Maintainer C. Helbert <Celine.Helbert@ec-lyon.fr>

Description Estimation, validation and prediction of models of different types : linear models, additive models, MARS,PolyMARS and Kriging.

License GPL-3

Depends DiceKriging

Suggests gam, mda, polspline

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2023-12-04 15:00:02 UTC

Contents

iceEval-package	 2
ossValidation	 4
ataIRSN5D	 6
IAE	 7
odelComparison	 8
odelFit	 9
odelPredict	 11
enaltyPolyMARS	 12
2	 14
sidualsStudy	 15
ΜΑ	 15
MSE	
epEvolution	 18
stCrossValidation	 19
stIRSN5D	 20

Index

DiceEval-package Metamodels

Description

Construction and evaluation of metamodels.

Package:	DiceEval
Type:	Package
Version:	1.4
Date:	2015-06-15
License:	GPL-3

Details

This package is dedicated to the construction of metamodels. A validation procedure is also proposed using usual criteria (RMSE, MAE etc.) and cross-validation procedure. Moreover, graphical tools help to choose the best value for the penalty parameter of a stepwise or a PolyMARS model. Another routine is dedicated to the comparison of metamodels.

Note

This work was conducted within the frame of the DICE (Deep Inside Computer Experiments) Consortium between ARMINES, Renault, EDF, IRSN, ONERA and TOTAL S.A. (http://emse.dice.fr/).

Functions gam, mars and polymars are required for the construction of metamodels. km provides Kriging models.

Author(s)

D. Dupuy & C. Helbert

References

Dupuy D., Helbert C., Franco J. (2015), DiceDesign and DiceEval: Two R-Packages for Design and Analysis of Computer Experiments, *Journal of Statistical Software*, **65**(11), 1–38, https://www.jstatsoft.org/v65/i11/.

Friedman J. (1991), Multivariate Adaptative Regression Splines (invited paper), *Annals of Statistics*, **10**/1, 1-141.

Hastie T. and Tibshirani R. (1990), Generalized Additive Models, Chapman and Hall, London.

Hastie T., Tibshirani R. and Friedman J. (2001), The Elements of Statistical Learning : Data Mining, Inference and Prediction, *Springer*.

Helbert C. and Dupuy D. (2007-09-26), Retour d'exp?riences sur m?tamod?les : partie th?orique, *Livrable r?dig? dans le cadre du Consortium DICE*.

21

Kooperberg C., Bose S. and Stone C.J. (1997), Polychotomous Regression, *Journal of the American Statistical Association*, **92** Issue 437, 117-127.

3

Rasmussen C.E. and Williams C.K.I. (2006), Gaussian Processes for Machine Learning, *the MIT Press*, www.GaussianProcess.org/gpml.

Stones C., Hansen M.H., Kooperberg C. and Truong Y.K. (1997), Polynomial Splines and their Tensor Products in Extended Linear Modeling, *Annals of Statistics*, **25**/4, 1371-1470.

See Also

modelFit, modelPredict, crossValidation and modelComparison

Different space-filling designs can be found in the DiceDesign package and we refer to the DiceKriging package for the construction of kriging models. This package takes part of a toolbox inplemented during the Dice consortium.

```
## Not run:
rm(list=ls())
# A 2D example
Branin <- function(x1,x2) {</pre>
x1 <- 1/2*(15*x1+5)
x2 <- 15/2*(x2+1)
(x^2 - 5.1/(4*pi^2)*(x1^2) + 5/pi*x1 - 6)^2 + 10*(1 - 1/(8*pi))*cos(x1) + 10
}
# A 2D uniform design with n points in [-1,1]^2
n <- 50
X <- matrix(runif(n*2,-1,1),ncol=2,nrow=n)</pre>
Y \le Branin(X[,1],X[,2])
Z \leq (Y-mean(Y))/sd(Y)
# Construction of a PolyMARS model with a penalty parameter equal to 2
library(polspline)
modPolyMARS <- modelFit(X,Z,type = "PolyMARS",gcv=2.2)</pre>
# Prediction and comparison between the exact function and the predicted one
xtest <- seq(-1, 1, length= 21)</pre>
ytest <- seq(-1, 1, length= 21)</pre>
Zreal <- outer(xtest, ytest, Branin)</pre>
Zreal <- (Zreal-mean(Y))/sd(Y)</pre>
Zpredict <- modelPredict(modPolyMARS,expand.grid(xtest,ytest))</pre>
m <- min(floor(Zreal), floor(Zpredict))</pre>
M <- max(ceiling(Zreal),ceiling(Zpredict))</pre>
persp(xtest, ytest, Zreal, theta = 30, phi = 30, expand = 0.5,
col = "lightblue",main="Branin function",zlim=c(m,M),
ticktype = "detailed")
persp(xtest, ytest, matrix(Zpredict,nrow=length(xtest),
ncol=length(ytest)), theta = 30, phi = 30, expand = 0.5,
col = "lightblue",main="PolyMARS Model",zlab="Ypredict",zlim=c(m,M),
ticktype = "detailed")
```

```
# Comparison of models
modelComparison(X,Y,type=c("Linear", "StepLinear", "PolyMARS", "Kriging"),
formula=Y~X1+X2+X1:X2+I(X1^2)+I(X2^2),penalty=log(dim(X)[1]), gcv=4)
# see also the demonstration example in dimension 5 (source: IRSN)
demo(IRSN5D)
## End(Not run)
```

crossValidation K-fold Cross Validation

Description

This function calculates the predicted values at each point of the design and gives an estimation of criterion using K-fold cross-validation.

Usage

crossValidation(model, K)

Arguments

model	an output of the modelFit function. This argument is the initial model fitted with all the data.
К	the number of groups into which the data should be split to apply cross-validation

Value

A list with the following components:

Ypred	a vector of predicted values obtained using K-fold cross-validation at the points of the design
Q2	a real which is the estimation of the criterion R2 obtained by cross-validation
folds	a list which indicates the partitioning of the data into the folds
RMSE_CV	RMSE by K-fold cross-validation (see more details below)
MAE_CV	MAE by K-fold cross-validation (see more details below)
In the case of a Kriging model, other components to test the robustess of the procedure are proposed:	

theta	the range parameter theta estimated for each fold,
-------	--

trend the trend parameter estimated for each fold,

shape the estimated shape parameter if the covariance structure is of type powerexp.

4

crossValidation

The principle of cross-validation is to split the data into K folds of approximately equal size $A_1A1, ..., A_KAK$. For k = 1 to K, a model $\hat{Y}^{(-k)}$ is fitted from the data $\bigcup_{j \neq k} A_k$ and this model is validated on the fold A_k . Given a criterion of quality L (here, L could be the RMSE or the MAE criterion), the "evaluation" of the model consists in computing :

$$L_{k} = \frac{1}{n/K} \sum_{i \in A_{k}} L\left(y_{i}, Y^{(-k)}(x_{i})\right).$$

The cross-validation criterion is the mean of the K criterion: $L_{\text{CV}} = \frac{1}{K} \sum_{k=1}^{K} L_k$.

The Q2 criterion is defined as: Q2 = R2(Y, Ypred) with Y the response value and Ypred the value fit by cross-validation.

Note

When K is equal to the number of observations, *leave-one-out* cross-validation is performed.

Author(s)

D. Dupuy

See Also

R2, modelFit, MAE, RMSE, foldsComposition, testCrossValidation

```
## Not run:
rm(list=ls())
# A 2D example
Branin <- function(x1,x2) {</pre>
  x1 <- x1*15-5
  x2 <- x2*15
  (x^2 - 5/(4*pi^2)*(x^{1/2}) + 5/pi*x^1 - 6)^2 + 10*(1 - 1/(8*pi))*cos(x^1) + 10
}
# Linear model on 50 points
n <- 50
X <- matrix(runif(n*2),ncol=2,nrow=n)</pre>
Y \leq Branin(X[,1],X[,2])
modLm <- modelFit(X,Y,type = "Linear",formula=Y~X1+X2+X1:X2+I(X1^2)+I(X2^2))</pre>
R2(Y,modLm$model$fitted.values)
crossValidation(modLm,K=10)$Q2
# kriging model : gaussian covariance structure, no trend, no nugget effect
# on 16 points
n <- 16
X <- data.frame(x1=runif(n),x2=runif(n))</pre>
Y <- Branin(X[,1],X[,2])</pre>
mKm <- modelFit(X,Y,type="Kriging",formula=~1, covtype="powexp")</pre>
K <- 10
```

```
out <- crossValidation(mKm, K)
par(mfrow=c(2,2))
plot(c(0,1:K),c(mKm$model@covariance@range.val[1],out$theta[,1]),
    xlab='',ylab='Theta1')
plot(c(0,1:K),c(mKm$model@covariance@range.val[2],out$theta[,2]),
    xlab='',ylab='Theta2')
plot(c(0,1:K),c(mKm$model@covariance@shape.val[1],out$shape[,1]),
    xlab='',ylab='p1',ylim=c(0,2))
plot(c(0,1:K),c(mKm$model@covariance@shape.val[2],out$shape[,2]),
    xlab='',ylab='p2',ylim=c(0,2))
par(mfrow=c(1,1))
## End(Not run)</pre>
```

dataIRSN5D

5D benchmark from nuclear criticality safety assessments

Description

Nuclear criticality safety assessments are based on an optimization process to search for safetypenalizing physical conditions in a given range of parameters of a system involving fissile materials.

In the following examples, the criticality coefficient (namely k-effective or keff) models the nuclear chain reaction trend:

- keff > 1 is an increasing neutrons production leading to an uncontrolled chain reaction potentially having deep consequences on safety,

- keff = 1 means a stable neutrons population as required in nuclear reactors,

- keff < 1 is the safety state required for all unused fissile materials, like for fuel storage.

Besides its fissile materials geometry and composition, the criticality of a system is widely sensitive to physical parameters like water density, geometrical perturbations or structure materials (like concrete) characteristics. Thereby, a typical criticality safety assessment is supposed to verify that k-effective cannot reach the critical value of 1.0 (in practice the limit value used is 0.95) for given hypothesis on these parameters.

The benchmark system is an assembly of four fuel rods contained in a reflecting hull. Regarding criticality safety hypothesis, the main parameters are the uranium enrichment of fuel (namely "e", U235 enrichment, varying in [0.03, 0.07]), the rods assembly geometrical characteristics (namely "p", the pitch between rods, varying in [1.0, 2.0] cm and "l", the length of fuel rods, varying in [10, 60] cm), the water density inside the assembly (namely "b", varying in [0.1, 0.9]), and the hull reflection characteristics (namely "r", reflection coefficient, varying in [0.75, 0.95]).

In this criticality assessment, the MORET (Fernex et al., 2005) Monte Carlo simulator is used to estimate the criticality coefficient of the fuel storage system using these parameters (among other) as numerical input,. The output k-effective is returned as a Gaussian density which standard deviation is setup to be negligible regarding input parameters sensitivity.

Usage

data(dataIRSN5D)

6

MAE

Format

a data frame with 50 observations (lines) and 6 columns. Columns 1 to 5 correspond to the design of experiments for the input variables ("b","e","p","r" and "l") and the last column the value of the output "keff".

Author(s)

Y. Richet

Source

IRSN (Institut de Radioprotection et de Sûreté Nucléaire)

References

Fernex F., Heulers L, Jacquet O., Miss J. and Richet Y. (2005) *The MORET 4B Monte Carlo code* - *New features to treat complex criticality systems*, M&C International Conference on Mathematics and Computation Supercomputing, Reactor Physics and Nuclear and Biological Application, Avignon, 12/09/2005

MAE

Mean Absolute Error

Description

The mean of absolute errors between real values and predictions.

Usage

MAE(Y, Ypred)

Arguments

Y	a real vector with the values of the output
Ypred	a real vector with the predicted values at the same inputs

Value

a real which represents the mean of the absolute errors between the real and the predicted values:

$$MAE = \frac{1}{n} \sum_{i=1}^{n} |Y(x_i) - \hat{Y}(x_i)|$$

where x_i denotes the points of the experimental design, Y the output of the computer code and \hat{Y} the fitted model.

Author(s)

D. Dupuy

See Also

other quality criteia as RMSE and RMA.

Examples

```
X <- seq(-1,1,0.1)
Y <- 3*X + rnorm(length(X),0,0.5)
Ypred <- 3*X
MAE(Y,Ypred)</pre>
```

modelComparison Comparison of different types of metamodels

Description

modelComparison fits different metamodels and returns R2 and RMSE criteria relating to each.

Usage

```
modelComparison(X,Y, type="all",K=10,test=NULL,...)
```

Arguments

Х	a data.frame containing the design of experiments
Υ	a vector containing the response variable
type	a vector containing the type of models to compare. The default value is "all"=c("Linear", "StepLinear", "Additive", "PolyMARS", "MARS", "Kriging")
К	the number of folds for cross-validation (default value is set at 10)
test	a data.frame containing the design and the response of a test set when available, the prediction criteria will be evaluated on the test design (default corresponds to no test set)
	according to the type argument, parameters can be specified (for example, formula and penalty for a stepwise procedure)

Value

A list containing two fields if the argument test equal NULL and three fields otherwise :

Learning	R2 and RMSE criteria evaluated from learning set,
CV	Q2 and RMSE_CV criteria using K-fold cross-validation,
Test	R2 and RMSE criteria on the test set.

A graphical tool to compare the value of the criteria is proposed.

modelFit

Author(s)

D. Dupuy

See Also

modelFit and crossValidation

Examples

```
## Not run:
data(dataIRSN5D)
X <- dataIRSN5D[,1:5]
Y <- dataIRSN5D[,6]
data(testIRSN5D)
library(gam)
library(mda)
library(polspline)
crit <- modelComparison(X,Y, type="all",test=testIRSN5D)
crit2 <- modelComparison(X,Y, type=rep("StepLinear",5),test=testIRSN5D,
penalty=c(1,2,5,10,20),formula=Y~.^2)
## End(Not run)
```

modelFit	Fitting metamodels	
----------	--------------------	--

Description

modelFit is used to fit a metamodel of class lm, gam, mars, polymars or km.

Usage

modelFit (X,Y, type, ...)

Arguments

Х	a data.frame containing the design of experiments
Υ	a vector containing the response variable
type	represents the method used to fit the model:

linear model,
stepwise,
gam,
mars
polymars
kriging model.

• • •

corresponds to the parameter(s) of the model. The list of the needed arguments for each type of models is given below:

"Linear"	formula (see formulaLm),
"StepLinear"	formula
	penalty parameter,
"Additive"	<pre>formula (see formulaAm),</pre>
"MARS"	degree,
"PolyMARS"	gcv criteria.
"Kriging"	formula
	covtype

Value

A list with the following components:

Х	a data frame representing the design of experiments
Y	a vector representing the response
type	the type of metamodel
model	a fitted model of the specified class

and the value of the parameter(s) depending on the fitted model.

Author(s)

D. Dupuy

See Also

modelPredict

```
# A 2D example
Branin <- function(x1,x2) {
    x1 <- x1*15-5
    x2 <- x2*15
    (x2 - 5/(4*pi^2)*(x1^2) + 5/pi*x1 - 6)^2 + 10*(1 - 1/(8*pi))*cos(x1) + 10
}
# a 2D uniform design and the value of the response at these points
X <- matrix(runif(24),ncol=2,nrow=12)
Z <- Branin(X[,1],X[,2])
Y <- (Z-mean(Z))/sd(Z)
# construction of a linear model
modLm <- modelFit(X,Y,type = "Linear",formula=Y~X1+X2+X1:X2+I(X1^2)+I(X2^2))
summary(modLm$model)</pre>
```

modelPredict

```
## Not run:
# construction of a stepwise-selected model
modStep <- modelFit(X,Y,type = "StepLinear",penalty=log(dim(X)[1]),</pre>
formula=Y~X1+X2+X1:X2+I(X1^2)+I(X2^2))
summary(modStep$model)
# construction of an additive model
library(gam)
modAm <- modelFit(X,Y,type = "Additive",formula=Y~s(X1)+s(X2))</pre>
summary(modAm$model)
# construction of a MARS model of degree 2
library(mda)
modMARS <- modelFit(X,Y,type = "MARS",degree=2)</pre>
print(modMARS$model)
# construction of a PolyMARS model with a penalty parameter equal to 1
library(polspline)
modPolyMARS <- modelFit(X,Y,type = "PolyMARS",gcv=1)</pre>
summary(modPolyMARS$model)
# construction of a Kriging model
modKm <- modelFit(X,Y,type = "Kriging")</pre>
str(modKm$model)
## End(Not run)
```

modelPredict Prediction at newdata for a fitted metamodel

Description

modelPredict computes predicted values based on the model given in argument.

Usage

```
modelPredict(model,newdata)
```

Arguments

model	a fitted model obtained from modelFit
newdata	a matrix (or a data frame) which represents the predictor values at which the fitted values will be computed.

Value

a vector of predicted values, obtained by evaluating the model at newdata.

Author(s)

D. Dupuy

See Also

modelFit

Examples

```
X <- seq(-1,1,1=21)
Y <- 3*X + rnorm(21,0,0.5)
# construction of a linear model
modLm <- modelFit(X,Y,type = "Linear",formula="Y~.")</pre>
print(modLm$model$coefficient)
## Not run:
# illustration on a 2-dimensional example
Branin <- function(x1,x2) {</pre>
x1 <- 1/2*(15*x1+5)
x2 <- 15/2*(x2+1)
(x^2 - 5.1/(4*pi^2)*(x^{1}^2) + 5/pi*x^1 - 6)^2 + 10*(1 - 1/(8*pi))*cos(x^1) + 10
}
# A 2D uniform design with 20 points in [-1,1]^2
n <- 20
X <- matrix(runif(n*2,-1,1),ncol=2,nrow=n)</pre>
Y <- Branin(X[,1],X[,2])</pre>
Z \leq (Y-mean(Y))/sd(Y)
# Construction of a Kriging model
mKm <- modelFit(X,Z,type = "Kriging")</pre>
# Prediction and comparison between the exact function and the predicted one
xtest <- seq(-1, 1, length= 21)</pre>
ytest <- seq(-1, 1, length= 21)</pre>
Zreal <- outer(xtest, ytest, Branin)</pre>
Zreal <- (Zreal-mean(Y))/sd(Y)</pre>
Zpredict <- modelPredict(mKm,expand.grid(xtest,ytest))</pre>
z <- abs(Zreal-matrix(Zpredict,nrow=length(xtest),ncol=length(ytest)))</pre>
contour(xtest, xtest, z,30)
points(X,pch=19)
## End(Not run)
```

penaltyPolyMARS Choice of the penalty parameter for a PolyMARS model

Description

This function fits a PolyMARS model for different values of the penalty parameter and compute criteria.

penaltyPolyMARS

Usage

```
penaltyPolyMARS(X,Y,test=NULL,graphic=FALSE,K=10,
Penalty=seq(0,5,by=0.2))
```

Arguments

Х	a data.frame containing the design of experiments
Υ	a vector containing the response variable
test	a data.frame containing the design and the response of a test set when available, the prediction criteria will be computed for the test data (default corresponds to no test set)
graphic	if TRUE the values of the criteria are represented
К	the number of folds for cross-validation (by default, K=10)
Penalty	a vector containing the values of the penalty parameter

Value

A data frame containing

а	the values of the penalty parameter
R2	the R2 criterion evaluted on the learning set
m	the size of the selected model
If a test set is available the last row is	
R2test	the R2 criterion evaluated on the test set
If no test set is available, criteria computed by K-corss-validation are provided:	
Q2	the Q2 evaluated by cross-validation (by default, K=10)
RMSE CV	RMSE computed by cross-validation

Note that the penalty parameter could be chosen by minimizing the value of the RMSE by cross-validation.

Author(s)

D. Dupuy

See Also

modelFit, R2 and crossValidation

```
data(dataIRSN5D)
X <- dataIRSN5D[,1:5]
Y <- dataIRSN5D[,6]
data(testIRSN5D)
library(polspline)
Crit <- penaltyPolyMARS(X,Y,test=testIRSN5D[,-7],graphic=TRUE)</pre>
```

R2

Description

Coefficient of determination \mathbb{R}^2

Usage

R2(Y, Ypred)

Arguments

Y	a real vector with the values of the output
Ypred	a real vector with the predicted values at the same inputs

Value

$$\mathsf{R2} = 1 - \frac{SSE}{SST}$$

where $SSE = \sum_{i=1}^{n} (Y(x_i) - \hat{Y}(x_i)^2)$ is the residual sum of squares and $SST = \sum_{i=1}^{n} (Y(x_i) - \bar{Y})^2$ is the total sum of squares.

Note that the order of the input argument is important.

Author(s)

D. Dupuy

Examples

X <- seq(-1,1,0.1)
Y <- 3*X + rnorm(length(X),0,0.5)
Ypred <- 3*X
print(R2(Y,Ypred))</pre>

residualsStudy Plot residuals

Description

residualsStudy analyzes the residuals of a model: a plot of the residuals against the index, a plot of the residuals against the fitted values, the representation of the density and a normal Q-Q plot.

Usage

```
residualsStudy(model)
```

Arguments

model

a fitted model obtained from modelFit

Author(s)

D. Dupuy

See Also

modelFit and modelPredict

Examples

```
data(dataIRSN5D)
X <- dataIRSN5D[,1:5]
Y <- dataIRSN5D[,6]
library(gam)
modAm <- modelFit(X,Y,type = "Additive",formula=formulaAm(X,Y))
residualsStudy(modAm)</pre>
```

RMA

Relative Maximal Absolute Error

Description

Relative Maximal Absolute Error

Usage

RMA(Y, Ypred)

Arguments

Y	a real vector with the values of the output
Ypred	a real vector with the predicted values at the same inputs

Value

The RMA criterion represents the maximum of errors between exact values and predicted one:

$$RMA = \max_{1 \le i \le n} \frac{|Y(x_i) - \dot{Y}(x_i)|}{\sigma_Y}$$

where Y is the output variable, \hat{Y} is the fitted model and σ_Y denotes the standard deviation of Y. The output of this function is a list with the following components:

max.value	the value of the RMA criterion
max.data	an integer i indicating the data \boldsymbol{x}^i for which the RMA is reached
index	a vector containing the data sorted according to the value of the errors
error	a vector containing the corresponding value of the errors

Author(s)

D. Dupuy

See Also

other validation criteria as MAE or RMSE.

```
Х
      <- seq(-1,1,0.1)
Υ
      <- 3*X + rnorm(length(X),0,0.5)
Ypred <- 3*X
print(RMA(Y,Ypred))
# Illustration on Branin function
Branin <- function(x1,x2) {</pre>
   x1 <- x1*15-5
   x2 <- x2*15
   (x2 - 5/(4*pi^2)*(x1^2) + 5/pi*x1 - 6)^2 + 10*(1 - 1/(8*pi))*cos(x1) + 10
}
X <- matrix(runif(24),ncol=2,nrow=12)</pre>
Z <- Branin(X[,1],X[,2])</pre>
Y \leq (Z-mean(Z))/sd(Z)
# Fitting of a Linear model on the data (X,Y)
modLm <- modelFit(X,Y,type = "Linear",formula=Y~X1+X2+X1:X2+I(X1^2)+I(X2^2))</pre>
# Prediction on a grid
u <- seq(0,1,0.1)
Y_test_real <- Branin(expand.grid(u,u)[,1],expand.grid(u,u)[,2])</pre>
Y_test_pred <- modelPredict(modLm,expand.grid(u,u))</pre>
Y_error <- matrix(abs(Y_test_pred-(Y_test_real-mean(Z))/sd(Z)),length(u),length(u))</pre>
contour(u, u, Y_error,45)
Y_pred <- modelPredict(modLm,X)</pre>
out <- RMA(Y,Y_pred)</pre>
```

RMSE

```
for (i in 1:dim(X)[1]){
    points(X[out$index[i],1],X[out$index[i],2],pch=19,col='red',cex=out$error[i]*10)
}
```

RMSE

Root Mean Squared Error

Description

The root of the Mean Squared Error between the exact value and the predicted one.

Usage

RMSE(Y, Ypred)

Arguments

Y	a real vector with the values of the output
Ypred	a real vector with the predicted values

Value

a real which represents the root of the mean squared error between the target response Y and the fitted one \hat{Y} :

$$\mathsf{RMSE} = \sqrt{\frac{1}{n}\sum_{i=1}^{n} \left(Y\left(x_{i}\right) - \hat{Y}\left(x_{i}\right)\right)^{2}}.$$

Author(s)

D. Dupuy

See Also

other validation criteria as MAE or RMA

```
X <- seq(-1,1,0.1)
Y <- 3*X + rnorm(length(X),0,0.5)
Ypred <- 3*X
print(RMSE(Y,Ypred))
```

stepEvolution

Description

Graphical representation of the selected terms using stepwise procedure for different values of the penalty parameter.

Usage

```
stepEvolution(X,Y,formula,P=1:7,K=10,test=NULL,graphic=TRUE)
```

Arguments

Х	a data.frame containing the design of experiments
Υ	a vector containing the response variable
formula	a formula for the initial model
Ρ	a vector containing different values of the penalty parameter for which a step- wise selected model is fitted
К	the number of folds for the cross-validation procedure
test	an additional data set on which the prediction criteria are evaluated (default cor- responds to no test data set)
graphic	if TRUE the values of the criteria are represented

Value

a list with the different criteria for different values of the penalty parameter. This list contains:

penalty	the values for the penalty parameter
m	size ${\tt m}$ of the selected model for each value in ${\tt P}$
R2	the value of the R2 criterion for each model

According to the value of the test argument, other criteria are calculated:

- a. If a test set is available, R2test contains the value of the R2 criterion on the test set
- b. If no test set is available, the Q2 and the RMSE computed by cross-validation are done.

Note

Plots are also available. A tabular represents the selected terms for each value in P.

The evolution of the R2 criterion, the evolution of the size m of the selected model and criteria on the test set or by K-folds cross-validation are represented.

These graphical tools can be used to select the best value for the penalty parameter.

testCrossValidation

Author(s)

D. Dupuy

See Also

step procedure for linear models.

Examples

```
## Not run:
data(dataIRSN5D)
design <- dataIRSN5D[,1:5]
Y <- dataIRSN5D[,6]
out <- stepEvolution(design,Y,formulaLm(design,Y),P=c(1,2,5,10,20,30))
## End(Not run)
```

testCrossValidation Test the robustess of the cross-validation procedure

Description

This function calculates the estimated K-fold cross-validation for different values of K.

Usage

testCrossValidation(model,Kfold=c(2,5,10,20,30,40,dim(model\$data\$X)[1]),N=10)

Arguments

model	a fitted model from modelFit
Kfold	a vector containing the values to test (default corresponds to 2,5,10,20,30,40 and the number of observations for leave-one-out procedure)
Ν	an integer given the number of times the K-fold cross-validation is performed for each value of K

Value

a matrix of all the values obtained by K-fold cross-validation

Note

For each value of K, the cross-validation procedure is repeated N times in order to get an idea of the dispersion of the Q2 criterion and of the RMSE by K-fold cross-validation.

Author(s)

D. Dupuy

See Also

crossValidation

Examples

```
## Not run:
rm(list=ls())
# A 2D example
Branin <- function(x1,x2) {
    x1 <- x1*15-5
    x2 <- x2*15
    (x2 - 5/(4*pi^2)*(x1^2) + 5/pi*x1 - 6)^2 + 10*(1 - 1/(8*pi))*cos(x1) + 10
}
# a 2D uniform design and the value of the response at these points
n <- 50
X <- matrix(runif(n*2),ncol=2,nrow=n)
Y <- Branin(X[,1],X[,2])
mod <- modelFit(X,Y,type="Linear",formula=formulaLm(X,Y))
out <- testCrossValidation(mod,N=20)
## End(Not run)
```

testIRSN5D A set of test data

Description

These test data correspond to the five-dimensional case provided by the IRSN detailed in dataIRSN5D.

Usage

data(testIRSN5D)

Format

A data frame with 324 rows representing the number of observations and 6 columns: the first five corresponding to the input variables ("b","e","p","r" and "l") and the last to the response Keff.

Source

IRSN (Institut de Radioprotection et de Sûreté Nucléaire)

See Also

dataIRSN5D

20

Index

* datasets dataIRSN5D, 6 testIRSN5D, 20 * models crossValidation, 4 DiceEval-package, 2 MAE, 7modelComparison, 8modelFit,9 modelPredict, 11 penaltyPolyMARS, 12 R2, 14 residualsStudy, 15 RMA, 15 **RMSE**, 17 stepEvolution, 18 testCrossValidation, 19 * package DiceEval-package, 2 crossValidation, 3, 4, 9, 13, 20 dataIRSN5D, 6, 20 DiceEval (DiceEval-package), 2 DiceEval-package, 2 foldsComposition, 5 formulaAm, 10 formulaLm, 10 gam, 2 km, 2

MAE, 4, 5, 7, 16, 17 mars, 2 modelComparison, 3, 8 modelFit, 3, 5, 9, 9, 12, 13, 15 modelPredict, 3, 10, 11, 15

penaltyPolyMARS, 12

polymars, 2

```
R2, 5, 13, 14
residualsStudy, 15
RMA, 8, 15, 17
RMSE, 4, 5, 8, 16, 17
```

stepEvolution, 18

testCrossValidation, 5, 19
testIRSN5D, 20