

# Package ‘GroupComparisons’

January 20, 2025

**Type** Package

**Title** Paired/Unpaired Parametric/Non-Parametric Group Comparisons

**Version** 0.1.0

**Author** Aaron England <aaron.england24@gmail.com>

**Maintainer** Aaron England <aaron.england24@gmail.com>

**Description** Receives two vectors, computes appropriate function for group comparison (i.e., t-test, Mann-Whitney; equality of variances), and reports the findings (mean/median, standard deviation, test statistic, p-value, effect size) in APA format (Fay, M.P., & Proschan, M.A. (2010)<DOI:10.1214/09-SS051>).

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.1.0

**Depends** car

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-10-24 23:00:06 UTC

## Contents

Group_Comparison_Paired . . . . .	2
Group_Comparison_Unpaired . . . . .	2

## Index

4

**Group\_Comparison\_Paired***Paired Parametric/Non-Parametric Group Comparisons***Description**

Receives two vectors, computes appropriate function for paired group comparison (t-test, Mann-Whitney), and reports the findings (mean/median, standard deviation, test statistic, p-value, effect size) in APA format (Field, A. (2013). Discovering statistics using IBM SPSS statistics. New York, NY: SAGE.).

**Usage**

```
Group_Comparison_Paired(vec1, vec2)
```

**Arguments**

vec1	A vector of numbers
vec2	A vector of numbers

**Value**

This function returns a sentence summarizing the findings and reporting them in APA format (effect size included)

**Examples**

```
dt <- mtcars
vector1 <- dt$mpg
vector2 <- dt$hp
Group_Test <- Group_Comparison_Paired(vector1, vector2)
Group_Test
```

**Group\_Comparison\_Unpaired***Unpaired Parametric/Non-Parametric Group Comparisons***Description**

Receives two vectors, computes best function for unpaired group comparison (t-test, Mann-Whitney), and reports the findings (mean/median, standard deviation, test statistic, p-value, effect size) in APA format (Field, A. (2013). Discovering statistics using IBM SPSS statistics. New York, NY: SAGE.).

**Usage**

```
Group_Comparison_Unpaired(vec1, vec2)
```

**Arguments**

vec1	A vector of numbers
vec2	A vector of numbers

**Value**

This function returns a sentence summarizing the findings and reporting them in APA format (effect size included)

**Examples**

```
dt <- mtcars  
vector1 <- dt$mpg  
vector2 <- dt$hp  
Group_Test <- Group_Comparison_Unpaired(vector1, vector2)  
Group_Test
```

# Index

[Group\\_Comparison\\_Paired, 2](#)  
[Group\\_Comparison\\_Unpaired, 2](#)