

Package ‘IRR2FPR’

January 20, 2025

Title Computing False Positive Rate from Inter-Rater Reliability

Version 0.1.1

Maintainer František Bartoš <f.bartos96@gmail.com>

Description

Implements a 'Shiny Item Analysis' module and functions for computing false positive rate and other binary classification metrics from inter-rater reliability based on Bartoš & Martinková (2024)
<[doi:10.1111/bmsp.12343](https://doi.org/10.1111/bmsp.12343)>.

URL <https://github.com/FBartos/IRR2FPR>

BugReports <https://github.com/FBartos/IRR2FPR/issues>

License GPL-3

Encoding UTF-8

Config/ShinyItemAnalysis/module true

Imports shiny, mvtnorm

RoxygenNote 7.2.3

NeedsCompilation no

Author František Bartoš [aut, cre] (<<https://orcid.org/0000-0002-0018-5573>>)

Repository CRAN

Date/Publication 2024-04-24 15:30:12 UTC

Contents

compute_false_negative_rate	2
compute_false_positive_rate	2
compute_proportion_of_correctly_selected	3
compute_true_positive_rate	4
IRR2FPR	4
spearman_brown_formula	5

Index

6

```
compute_false_negative_rate  
Compute the false negative rate
```

Description

Compute the false negative rate based on the inter-rater reliability and the proportion of selected candidates

Usage

```
compute_false_negative_rate(IRR, proportion_selected)
```

Arguments

IRR	The inter-rater reliability
proportion_selected	The proportion of selected candidates

Value

The false negative rate

Examples

```
compute_false_negative_rate(0.75, 0.10)
```

```
compute_false_positive_rate  
Compute the false positive rate
```

Description

Compute the false positive rate based on the inter-rater reliability and the proportion of selected candidates

Usage

```
compute_false_positive_rate(IRR, proportion_selected)
```

Arguments

IRR	The inter-rater reliability
proportion_selected	The proportion of selected candidates

`compute_proportion_of_correctly_selected`

3

Value

The false positive rate

Examples

```
compute_false_positive_rate(0.75, 0.10)
```

`compute_proportion_of_correctly_selected`

Compute the proportion of correctly selected candidates

Description

Compute proportion of correctly selected candidates based on the inter-rater reliability and the proportion of selected candidates

Usage

```
compute_proportion_of_correctly_selected(IRR, proportion_selected)
```

Arguments

`IRR` The inter-rater reliability

`proportion_selected`
 The proportion of selected candidates

Value

The proportion of correctly selected candidates

Examples

```
compute_proportion_of_correctly_selected(0.75, 0.10)
```

`compute_true_positive_rate`
Compute the true positive rate

Description

Compute the true positive rate based on the inter-rater reliability and the proportion of selected candidates

Usage

```
compute_true_positive_rate(IRR, proportion_selected)
```

Arguments

IRR	The inter-rater reliability
proportion_selected	The proportion of selected candidates

Value

The true positive rate

Examples

```
compute_true_positive_rate(0.75, 0.10)
```

IRR2FPR

Interactive Module for Inter-Rater Reliability to False Positive Rate Conversion

Description

This module allows users to convert inter-rater reliability (IRR) to false positive rate (FPR) as described in Bartoš and Martinková (2024).

Author(s)

František Bartoš

References

Bartoš, F., & Martinková, P. (2024). Selecting applicants based on multiple ratings: Using binary classification framework as an alternative to inter-rater reliability. *British Journal of Mathematical and Statistical Psychology.* doi:[10.1111/bmsp.12343](https://doi.org/10.1111/bmsp.12343)

`spearman_brown_formula`

Compute IRR from the Spearman-Brown formula

Description

Compute the inter-rater reliability based on the Spearman-Brown formula

Usage

`spearman_brown_formula(IRR_1, n_raters)`

Arguments

<code>IRR_1</code>	The inter-rater reliability of the first rater
<code>n_raters</code>	The number of raters

Value

The inter-rater reliability

Examples

`spearman_brown_formula(0.5, 3)`

Index

* SIAmodules package

IRR2FPR, [4](#)

compute_false_negative_rate, [2](#)

compute_false_positive_rate, [2](#)

compute_proportion_of_correctly_selected,
[3](#)

compute_true_positive_rate, [4](#)

IRR2FPR, [4](#)

spearman_brown_formula, [5](#)