

# Package ‘ML2Pvae’

January 20, 2025

**Type** Package

**Title** Variational Autoencoder Models for IRT Parameter Estimation

**Version** 1.0.0.1

**Maintainer** Geoffrey Converse <converseg@gmail.com>

**Description** Based on the work of Curi, Converse, Hajewski, and Oliveira (2019) <[doi:10.1109/IJCNN.2019.8852333](https://doi.org/10.1109/IJCNN.2019.8852333)>. This package provides easy-to-use functions which create a variational autoencoder (VAE) to be used for parameter estimation in Item Response Theory (IRT) - namely the Multidimensional Logistic 2-Parameter (ML2P) model. To use a neural network as such, nontrivial modifications to the architecture must be made, such as restricting the nonzero weights in the decoder according to some binary matrix Q. The functions in this package allow for straight-forward construction, training, and evaluation so that minimal knowledge of 'tensorflow' or 'keras' is required.

**Note** The developer version of 'keras' should be used, rather than the CRAN version. The latter will cause tests to fail on an initial run, but work on subsequent tries. To avoid this, use `devtools::install_github(``rstudio/keras")`. The user also must have an installation of 'Python 3'.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Imports** keras (>= 2.3.0), reticulate (>= 1.0), tensorflow (>= 2.2.0), tfprobability (>= 0.11.0)

**RoxygenNote** 7.1.1

**Suggests** knitr, rmarkdown, testthat, R.rsp

**VignetteBuilder** R.rsp

**Depends** R (>= 3.6)

**URL** <https://converseg.github.io>

**SystemRequirements** TensorFlow (<https://www.tensorflow.org>), Keras (<https://keras.io>), TensorFlow Probability (<https://www.tensorflow.org/probability>)

2 .onLoad

**Config/reticulate** list( packages = list( list(package = ``keras'', pip = TRUE), list(package = ``tensorflow'', pip = TRUE), list(package = ``tensorflow-probability'', pip = TRUE) ) )

**NeedsCompilation** no

**Author** Geoffrey Converse [aut, cre, cph],  
Suely Oliveira [ctb, ths],  
Mariana Curi [ctb]

**Repository** CRAN

**Date/Publication** 2022-05-23 08:02:16 UTC

## Contents

.onLoad	2
build_hidden_encoder	3
build_vae_correlated	3
build_vae_independent	5
correlation_matrix	6
diff_true	7
disc_true	7
get_ability_parameter_estimates	8
get_item_parameter_estimates	8
ML2Pvae	9
q_1pl_constraint	9
q_constraint	10
q_matrix	10
responses	11
sampling_correlated	11
sampling_independent	12
theta_true	12
train_model	13
vae_loss_correlated	14
vae_loss_independent	15
validate_inputs	15

**Index** 17

---

.onLoad *Display a message upon loading package*

---

### Description

Display a message upon loading package

### Usage

.onLoad(libnam, pkgname)

**Arguments**

libnam	the library name
pkgname	the package name

---

build\_hidden\_encoder    *Build the encoder for a VAE*

---

**Description**

Build the encoder for a VAE

**Usage**

```
build_hidden_encoder(  
    input_size,  
    layers,  
    activations = rep("sigmoid", length(layers))  
)
```

**Arguments**

input_size	an integer representing the number of items
layers	a list of integers giving the size of each hidden layer
activations	a list of strings, the same length as layers

**Value**

two tensors: the input layer to the VAE and the last hidden layer of the encoder

---

build\_vae\_correlated    *Build a VAE that fits to a normal, full covariance N(m,S) latent distribution*

---

**Description**

Build a VAE that fits to a normal, full covariance N(m,S) latent distribution

**Usage**

```
build_vae_correlated(
  num_items,
  num_skills,
  Q_matrix,
  mean_vector = rep(0, num_skills),
  covariance_matrix = diag(num_skills),
  model_type = 2,
  enc_hid_arch = c(ceiling((num_items + num_skills)/2)),
  hid_enc_activations = rep("sigmoid", length(enc_hid_arch)),
  output_activation = "sigmoid",
  kl_weight = 1,
  learning_rate = 0.001
)
```

**Arguments**

<code>num_items</code>	an integer giving the number of items on the assessment; also the number of nodes in the input/output layers of the VAE
<code>num_skills</code>	an integer giving the number of skills being evaluated; also the dimensionality of the distribution learned by the VAE
<code>Q_matrix</code>	a binary, <code>num_skills</code> by <code>num_items</code> matrix relating the assessment items with skills
<code>mean_vector</code>	a vector of length <code>num_skills</code> specifying the mean of each latent trait; the default of <code>rep(0, num_skills)</code> should almost always be used
<code>covariance_matrix</code>	a symmetric, positive definite, <code>num_skills</code> by <code>num_skills</code> matrix giving the covariance of the latent traits
<code>model_type</code>	either 1 or 2, specifying a 1 parameter (1PL) or 2 parameter (2PL) model; if 1PL, then all decoder weights are fixed to be equal to one
<code>enc_hid_arch</code>	a vector detailing the size of hidden layers in the encoder; the number of hidden layers is determined by the length of this vector
<code>hid_enc_activations</code>	a vector specifying the activation function in each hidden layer in the encoder; must be the same length as <code>enc_hid_arch</code>
<code>output_activation</code>	a string specifying the activation function in the output of the decoder; the ML2P model always used 'sigmoid'
<code>kl_weight</code>	an optional weight for the KL divergence term in the loss function
<code>learning_rate</code>	an optional parameter for the adam optimizer

**Value**

returns three keras models: the encoder, decoder, and vae

## Examples

```

Q <- matrix(c(1,0,1,1,0,1,1,0), nrow = 2, ncol = 4)
cov <- matrix(c(.7,.3,.3,1), nrow = 2, ncol = 2)
models <- build_vae_correlated(4, 2, Q,
                               mean_vector = c(-0.5, 0), covariance_matrix = cov,
                               enc_hid_arch = c(6, 3), hid_enc_activation = c('sigmoid', 'relu'),
                               output_activation = 'tanh',
                               kl_weight = 0.1)
vae <- models[[3]]

```

`build_vae_independent` *Build a VAE that fits to a standard N(0,I) latent distribution with independent latent traits*

## Description

Build a VAE that fits to a standard N(0,I) latent distribution with independent latent traits

## Usage

```

build_vae_independent(
  num_items,
  num_skills,
  Q_matrix,
  model_type = 2,
  enc_hid_arch = c(ceiling((num_items + num_skills)/2)),
  hid_enc_activations = rep("sigmoid", length(enc_hid_arch)),
  output_activation = "sigmoid",
  kl_weight = 1,
  learning_rate = 0.001
)

```

## Arguments

<code>num_items</code>	an integer giving the number of items on the assessment; also the number of nodes in the input/output layers of the VAE
<code>num_skills</code>	an integer giving the number of skills being evaluated; also the dimensionality of the distribution learned by the VAE
<code>Q_matrix</code>	a binary, <code>num_skills</code> by <code>num_items</code> matrix relating the assessment items with skills
<code>model_type</code>	either 1 or 2, specifying a 1 parameter (1PL) or 2 parameter (2PL) model; if 1PL, then all decoder weights are fixed to be equal to one
<code>enc_hid_arch</code>	a vector detailing the size of hidden layers in the encoder; the number of hidden layers is determined by the length of this vector

**hid\_enc\_activations**  
 a vector specifying the activation function in each hidden layer in the encoder;  
 must be the same length as enc\_hid\_arch

**output\_activation**  
 a string specifying the activation function in the output of the decoder; the ML2P  
 model always uses 'sigmoid'

**kl\_weight** an optional weight for the KL divergence term in the loss function

**learning\_rate** an optional parameter for the adam optimizer

### Value

returns three keras models: the encoder, decoder, and vae.

### Examples

```
Q <- matrix(c(1,0,1,1,0,1,1,0), nrow = 2, ncol = 4)
models <- build_vae_independent(4, 2, Q,
                                enc_hid_arch = c(6, 3), hid_enc_activation = c('sigmoid', 'relu'),
                                output_activation = 'tanh', kl_weight = 0.1)
models <- build_vae_independent(4, 2, Q)
vae <- models[[3]]
```

**correlation\_matrix**      *Simulated latent abilities correlation matrix*

### Description

A symmetric positive definite matrix detailing the correlations among three latent traits.

### Usage

`correlation_matrix`

### Format

A data frame with 3 rows and 3 columns

### Source

Generated using the python package SciPy

---

diff_true	<i>Simulated difficulty parameters</i>
-----------	--

---

**Description**

Difficulty parameters for an exam with 30 items.

**Usage**

```
diff_true
```

**Format**

A data frame with 30 rows and one column. Each entry corresponds to the true value of a particular difficulty parameter.

**Source**

Each entry is sampled uniformly from [-3, 3].

---

disc_true	<i>Simulated discrimination parameters</i>
-----------	--

---

**Description**

Difficulty parameters for an exam of 30 items assessing 3 latent abilities.

**Usage**

```
disc_true
```

**Format**

A data frame with 3 rows and 30 columns. Entry [k, i] represents the discrimination parameter between item i and ability k.

**Source**

Each entry is sampled uniformly from [0.25, 1.75]. If an entry in q\_matrix.rda is 0, then so is the corresponding entry in disc\_true.rda.

**get\_ability\_parameter\_estimates**

*Feed forward response sets through the encoder, which outputs student ability estimates*

**Description**

Feed forward response sets through the encoder, which outputs student ability estimates

**Usage**

```
get_ability_parameter_estimates(encoder, responses)
```

**Arguments**

encoder	a trained keras model; should be the encoder returned from either <code>build_vae_independent()</code> or <code>build_vae_correlated</code>
responses	a num_students by num_items matrix of binary responses, as used in training

**Value**

a list where the first entry contains student ability estimates and the second entry holds the variance (or covariance matrix) of those estimates

**Examples**

```
data <- matrix(c(1,1,0,0,1,0,1,1,0,1,1,0), nrow = 3, ncol = 4)
Q <- matrix(c(1,0,1,1,0,1,1,0), nrow = 2, ncol = 4)
models <- build_vae_independent(4, 2, Q, model_type = 2)
encoder <- models[[1]]
ability_parameter_estimates_variances <- get_ability_parameter_estimates(encoder, data)
student_ability_est <- ability_parameter_estimates_variances[[1]]
```

**get\_item\_parameter\_estimates**

*Get trainable variables from the decoder, which serve as item parameter estimates.*

**Description**

Get trainable variables from the decoder, which serve as item parameter estimates.

**Usage**

```
get_item_parameter_estimates(decoder, model_type = 2)
```

## Arguments

decoder	a trained keras model; can either be the decoder or vae returned from <code>build_vae_independent()</code> or <code>build_vae_correlated</code>
model_type	either 1 or 2, specifying a 1 parameter (1PL) or 2 parameter (2PL) model; if 1PL, then only the difficulty parameter estimates (output layer bias) will be returned; if 2PL, then the discrimination parameter estimates (output layer weights) will also be returned

## Value

a list which contains item parameter estimates; the length of this list is equal to `model_type` - the first entry in the list holds the difficulty parameter estimates, and the second entry (if 2PL) contains discrimination parameter estimates

## Examples

```
Q <- matrix(c(1,0,1,1,0,1,1,0), nrow = 2, ncol = 4)
models <- build_vae_independent(4, 2, Q, model_type = 2)
decoder <- models[[2]]
item_parameter_estimates <- get_item_parameter_estimates(decoder, model_type = 2)
difficulty_est <- item_parameter_estimates[[1]]
discrimination_est <- item_parameter_estimates[[2]]
```

## ML2Pvae

*ML2Pvae: A package for creating a VAE whose decoder recovers the parameters of the ML2P model. The encoder can be used to predict the latent skills based on assessment scores.*

## Description

The ML2Pvae package includes functions which build a VAE with the desired architecture, and fits the latent skills to either a standard normal (independent) distribution, or a multivariate normal distribution with a full covariance matrix. Based on the work "Interpretable Variational Autoencoders for Cognitive Models" by Curi, M., Converse, G., Hajewski, J., and Oliveira, S. Found in International Joint Conference on Neural Networks, 2019.

## q\_1pl\_constraint

*A custom kernel constraint function that forces nonzero weights to be equal to one, so the VAE will estimate the 1-parameter logistic model. Nonzero weights are determined by the Q matrix.*

## Description

A custom kernel constraint function that forces nonzero weights to be equal to one, so the VAE will estimate the 1-parameter logistic model. Nonzero weights are determined by the Q matrix.

**Usage**

```
q_1pl_constraint(Q)
```

**Arguments**

*Q* a binary matrix of size num\_skills by num\_items

**Value**

returns a function whose parameters match keras kernel constraint format

*q\_constraint*

*A custom kernel constraint function that restricts weights between the learned distribution and output. Nonzero weights are determined by the Q matrix.*

**Description**

A custom kernel constraint function that restricts weights between the learned distribution and output. Nonzero weights are determined by the Q matrix.

**Usage**

```
q_constraint(Q)
```

**Arguments**

*Q* a binary matrix of size num\_skills by num\_items

**Value**

returns a function whose parameters match keras kernel constraint format

*q\_matrix*

*Simulated Q-matrix*

**Description**

The Q-matrix determines the relation between items and abilities.

**Usage**

```
q_matrix
```

**Format**

A data frame with 3 rows and 30 columns. If entry [k, i] = 1, then item i requires skill k.

**Source**

Generated by sampling each entry from  $\text{Bernoulli}(0.35)$ , but ensures each item assess at least one latent ability

---

responses

*Response data*

---

**Description**

Simulated response sets for 5000 students on an exam with 30 items.

**Usage**

responses

**Format**

A data frame with 30 columns and 5000 rows. Entry  $[j, i]$  is 1 if student  $j$  answers item  $i$  correctly, and 0 otherwise.

**Source**

Generated by sampling from the probability of student success on a given item according to the ML2P model. Model parameters can be found in `diff_true.rda`, `disc_true.rda`, and `theta_true.rda`.

---

sampling\_correlated    *A reparameterization in order to sample from the learned multivariate normal distribution of the VAE*

---

**Description**

A reparameterization in order to sample from the learned multivariate normal distribution of the VAE

**Usage**

`sampling_correlated(arg)`

**Arguments**

`arg`              a layer of tensors representing the mean and log cholesky transform of the covariance matrix

---

sampling_independent	<i>A reparameterization in order to sample from the learned standard normal distribution of the VAE</i>
----------------------	---

---

**Description**

A reparameterization in order to sample from the learned standard normal distribution of the VAE

**Usage**

```
sampling_independent(arg)
```

**Arguments**

arg	a layer of tensors representing the mean and variance
-----	---

---

theta_true	<i>Simulated ability parameters</i>
------------	-------------------------------------

---

**Description**

Three correlated ability parameters for 5000 students.

**Usage**

```
theta_true
```

**Format**

A data frame with 5000 rows and 3 columns. Each row represents a particular student's three latent abilities.

**Source**

Generated by sampling from a 3-dimensional multivariate Gaussian distribution with mean 0 and covariance matrix `correlation_matrix.rda`.

---

train_model	<i>Trains a VAE or autoencoder model. This acts as a wrapper for keras::fit().</i>
-------------	--

---

**Description**

Trains a VAE or autoencoder model. This acts as a wrapper for keras::fit().

**Usage**

```
train_model(
  model,
  train_data,
  num_epochs = 10,
  batch_size = 1,
  validation_split = 0.15,
  shuffle = FALSE,
  verbose = 1
)
```

**Arguments**

model	the keras model to be trained; this should be the vae returned from build_vae_independent() or build_vae_correlated
train_data	training data; this should be a binary num_students by num_items matrix of student responses to an assessment
num_epochs	number of epochs to train for
batch_size	batch size for mini-batch stochastic gradient descent; default is 1, detailing pure SGD; if a larger batch size is used (e.g. 32), then a larger number of epochs should be set (e.g. 50)
validation_split	split percentage to use as validation data
shuffle	whether or not to shuffle data
verbose	verbosity levels; 0 = silent; 1 = progress bar and epoch message; 2 = epoch message

**Value**

a list containing training history; this holds the loss from each epoch which can be plotted

**Examples**

```
data <- matrix(c(1,1,0,0,1,0,1,1,0,1,1,0), nrow = 3, ncol = 4)
Q <- matrix(c(1,0,1,1,0,1,1,0), nrow = 2, ncol = 4)
models <- build_vae_independent(4, 2, Q)
vae <- models[[3]]
```

```
history <- train_model(vae, data, num_epochs = 3, validation_split = 0, verbose = 0)
plot(history)
```

`vae_loss_correlated`    *A custom loss function for a VAE learning a multivariate normal distribution with a full covariance matrix*

## Description

A custom loss function for a VAE learning a multivariate normal distribution with a full covariance matrix

## Usage

```
vae_loss_correlated(
  encoder,
  inv_skill_cov,
  det_skill_cov,
  skill_mean,
  kl_weight,
  rec_dim
)
```

## Arguments

<code>encoder</code>	the encoder model of the VAE, used to obtain <code>z_mean</code> and <code>z_log_cholesky</code> from inputs
<code>inv_skill_cov</code>	a constant tensor matrix of the inverse of the covariance matrix being learned
<code>det_skill_cov</code>	a constant tensor scalar representing the determinant of the covariance matrix being learned
<code>skill_mean</code>	a constant tensor vector representing the means of the latent skills being learned
<code>kl_weight</code>	weight for the KL divergence term
<code>rec_dim</code>	the number of nodes in the input/output of the VAE

## Value

returns a function whose parameters match keras loss format

---

vae_loss_independent	<i>A custom loss function for a VAE learning a standard normal distribution</i>
----------------------	---

---

**Description**

A custom loss function for a VAE learning a standard normal distribution

**Usage**

```
vae_loss_independent(encoder, kl_weight, rec_dim)
```

**Arguments**

encoder	the encoder model of the VAE, used to obtain z_mean and z_log_var from inputs
kl_weight	weight for the KL divergence term
rec_dim	the number of nodes in the input/output of the VAE

**Value**

returns a function whose parameters match keras loss format

---

validate_inputs	<i>Give error messages for invalid inputs in exported functions.</i>
-----------------	--

---

**Description**

Give error messages for invalid inputs in exported functions.

**Usage**

```
validate_inputs(
  num_items,
  num_skills,
  Q_matrix,
  model_type = 2,
  mean_vector = rep(0, num_skills),
  covariance_matrix = diag(num_skills),
  enc_hid_arch = c(ceiling((num_items + num_skills)/2)),
  hid_enc_activations = rep("sigmoid", length(enc_hid_arch)),
  output_activation = "sigmoid",
  kl_weight = 1,
  learning_rate = 0.001
)
```

### Arguments

<code>num_items</code>	the number of items on the assessment; also the number of nodes in the input/output layers of the VAE
<code>num_skills</code>	the number of skills being evaluated; also the size of the distribution learned by the VAE
<code>Q_matrix</code>	a binary, <code>num_skills</code> by <code>num_items</code> matrix relating the assessment items with skills
<code>model_type</code>	either 1 or 2, specifying a 1 parameter (1PL) or 2 parameter (2PL) model
<code>mean_vector</code>	a vector of length <code>num_skills</code> specifying the mean of each latent trait
<code>covariance_matrix</code>	a symmetric, positive definite, <code>num_skills</code> by <code>num_skills</code> , matrix giving the covariance of the latent traits
<code>enc_hid_arch</code>	a vector detailing the number and size of hidden layers in the encoder
<code>hid_enc_activations</code>	a vector specifying the activation function in each hidden layer in the encoder; must be the same length as <code>enc_hid_arch</code>
<code>output_activation</code>	a string specifying the activation function in the output of the decoder; the ML2P model always used 'sigmoid'
<code>kl_weight</code>	an optional weight for the KL divergence term in the loss function
<code>learning_rate</code>	an optional parameter for the adam optimizer

# Index

```
* datasets
    correlation_matrix, 6
    diff_true, 7
    disc_true, 7
    q_matrix, 10
    responses, 11
    theta_true, 12
    .onLoad, 2

    build_hidden_encoder, 3
    build_vae_correlated, 3
    build_vae_independent, 5

    correlation_matrix, 6

    diff_true, 7
    disc_true, 7

    get_ability_parameter_estimates, 8
    get_item_parameter_estimates, 8

    ML2Pvae, 9

    q_1pl_constraint, 9
    q_constraint, 10
    q_matrix, 10

    responses, 11

    sampling_correlated, 11
    sampling_independent, 12

    theta_true, 12
    train_model, 13

    vae_loss_correlated, 14
    vae_loss_independent, 15
    validate_inputs, 15
```