

Package ‘MmcSD’

January 20, 2025

Title Modeling Complex Longitudinal Data in a Quick and Easy Way

Version 1.0.0

Description Matching longitudinal methodology models with complex sampling design. It fits fixed and random effects models and covariance structured models so far. It also provides tools to perform statistical tests considering these specifications as described in : Pacheco, P. H. (2021). ``Modeling complex longitudinal data in R: development of a statistical package.'' <<https://repositorio.ufjf.br/jspui/bitstream/ufjf/13437/1/pedrohenriquedemesquitapacheco.pdf>>.

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Imports dplyr, knitr, magrittr, methods, purrr, rlist, stats, tibble, tidyverse

Depends R (>= 2.10)

Suggests rmarkdown, simstudy, kableExtra, tidyverse

VignetteBuilder knitr

NeedsCompilation no

Author Pedro Pacheco [aut, cre] (<<https://orcid.org/0000-0003-4804-1576>>),
Marcel Vieira [aut] (<<https://orcid.org/0000-0002-0456-380X>>),
Gustavo Silva [aut]

Maintainer Pedro Pacheco <gustavoaeida2002@gmail.com>

Repository CRAN

Date/Publication 2023-03-31 08:10:02 UTC

Contents

cov_mmcSD	2
example_data	3
mmcSD	3
sigmaThetaExpr_viewer	4

summary.mmcSD	5
summary.mmcSD.theta	5

<i>cov_mmcSD</i>	<i>Fit covariance structured longitudinal model.</i>
------------------	--

Description

Responsible for performing the modeling of the model's covariance matrix through the use of covariance structures.

Usage

```
cov_mmcSD(fit, fittingType, sigmaThetaExpr, optimParams)
```

Arguments

<code>fit</code>	A fit model with class 'mmcSD'
<code>fittingType</code>	A character with the fitting function type. See optins above
<code>sigmaThetaExpr</code>	A character with the covariance structure type or a list of expressions
<code>optimParams</code>	A list with configuration for optim function. 'Par' is required.

Value

The fit model with class 'mmcSD.theta'.

Examples

```
fit <- mmcSD(
  score ~ wave + ageg + ecacg + qualifg,
  waves = wave, ids = id,
  weights = weight, stratum = strata, cluster = cluster,
  data = example_data, sigma = "exchangeable"
)
fitTheta_ucm <- cov_mmcSD(fit,
  fittingType = "PML", sigmaThetaExpr = "UCM",
  optimParams = list(par = c(7, 5))
)
```

example_data*A longitudinal example dataset.*

Description

An example dataset containing the individuals scores for certain subject.

Usage

```
example_data
```

Format

A data frame with 6700 rows and 9 variables:

id respondent id
wave wave number
score respondent score
weight sampling weight
strata strata variable
cluster cluster variable
ageg cathegorical age
ecacg educational level
qualifg economic activity

mmcsd*Fit fixed and random effects longitudinal model.*

Description

Estimate the fixed effects of the model, also known as B parameters of the regression,taking into account the sampling plan of the research, and also estimating the covariance matrix of the model considering the estimates of B

Usage

```
mmcsd(formula, waves, ids, weights, stratum, cluster, data, sigma = "identity")
```

Arguments

<code>formula</code>	A formula
<code>waves</code>	a dataframe column or an array
<code>ids</code>	a dataframe column or an array
<code>weights</code>	a dataframe column or an array
<code>stratum</code>	a dataframe column or an array
<code>cluster</code>	a dataframe column or an array
<code>data</code>	A dataframe or tibble
<code>sigma</code>	A character or a square matrix

Value

The fit model with class 'mmcsd'.

Examples

```
fit <- mmcsd(
  score ~ wave + ageg + ecacg + qualifg,
  waves = wave, ids = id,
  weights = weight, stratum = strata, cluster = cluster,
  data = example_data, sigma = "exchangeable"
)
```

sigmaThetaExpr_viewer covariance structure viewer to preview sigmaThetaExpr to be used in 'cov_mmcsd'.

Description

Knowing the difficulty of visualizing the covariance structure, especially when the user chooses to determine his own structure. This function was developed, that allows the user to view the provided structure even before it is evaluated, that is, through mathematics symbolic.

Usage

```
sigmaThetaExpr_viewer(sigmaThetaExpr, numWaves = NULL)
```

Arguments

<code>sigmaThetaExpr</code>	A character with the covariance structure type or a list of expressions
<code>numWaves</code>	An integer with the size of the square matrix to be printed.

Value

Return NULL and print in terminal the sigmaThetaExpr.

Examples

```
sigmaThetaExpr_viewer("UCM", 5)
```

summary.mmc	<i>Summarise the results of 'mmc' fit.</i>
-------------	--

Description

Summarise the results of 'mmc' fit.

Usage

```
## S3 method for class 'mmc'  
summary(object, ...)
```

Arguments

object	A mmc fitted model
...	Additional params passed to summary

Value

Return NULL and print in terminal the results.

Examples

```
fit <- mmc(  
  score ~ wave + ageg + ecacg + qualifg,  
  waves = wave, ids = id,  
  weights = weight, stratum = strata, cluster = cluster,  
  data = example_data, sigma = "exchangeable"  
)  
summary(fit)
```

summary.mmc.theta	<i>Summarise the results of 'cov_mmc' fit.</i>
-------------------	--

Description

Summarise the results of 'cov_mmc' fit.

Usage

```
## S3 method for class 'mmc.theta'  
summary(object, ...)
```

Arguments

- object A mmcسد.theta fitted model
... Additional params passed to summary

Value

Return NULL and print in terminal the results.

Examples

```
fit <- mmcسد(  
  score ~ wave + ageg + ecacg + qualifg,  
  waves = wave, ids = id,  
  weights = weight, stratum = strata, cluster = cluster,  
  data = example_data, sigma = "exchangeable"  
)  
fitTheta_ucm <- cov_mmcسد(fit,  
  fittingType = "PML", sigmaThetaExpr = "UCM",  
  optimParams = list(par = c(7, 5)))  
summary(fitTheta_ucm)
```

Index

- * **datasets**
 - example_data, [3](#)
 - cov_mmcSD, [2](#)
 - example_data, [3](#)
 - mmcSD, [3](#)
 - sigmaThetaExpr_viewer, [4](#)
 - summary.mmcSD, [5](#)
 - summary.mmcSD.theta, [5](#)