

Package ‘NPflow’

January 20, 2025

Type Package

Title Bayesian Nonparametrics for Automatic Gating of Flow-Cytometry Data

Version 0.13.5

Date 2024-01-13

LinkingTo Rcpp, RcppArmadillo

Depends R (>= 3.1), Rcpp (>= 0.12.11), truncnorm

Imports graphics, stats, grDevices, ellipse, fastcluster, ggplot2, pheatmap, reshape2, GGally

Suggests foreach, parallel, doParallel, iterators, microbenchmark

Description Dirichlet process mixture of multivariate normal, skew normal or skew t-distributions modeling oriented towards flow-cytometry data preprocessing applications. Method is detailed in: Hejblum, Alkhassim, Gottardo, Caron & Thiebaut (2019) <[doi:10.1214/18-AOAS1209](https://doi.org/10.1214/18-AOAS1209)>.

License LGPL-3 | file LICENSE

BugReports <https://github.com/sistm/NPflow/issues>

Encoding UTF-8

RoxygenNote 7.3.0

NeedsCompilation yes

Author Boris P Hejblum [aut, cre],
Chariff Alkhassim [aut],
Francois Caron [aut]

Maintainer Boris P Hejblum <boris.hejblum@u-bordeaux.fr>

Repository CRAN

Date/Publication 2024-01-13 10:00:02 UTC

Contents

NPflow-package	3
burn.DPMMclust	4

cluster_est_binder	4
cluster_est_Fmeasure	5
cluster_est_Mbinder_norm	6
cluster_est_pear	7
cytoScatter	8
DPMGibbsN	10
DPMGibbsN_parallel	14
DPMGibbsN_SeqPrior	17
DPMGibbsSkewN	21
DPMGibbsSkewN_parallel	28
DPMGibbsSkewT	32
DPMGibbsSkewT_parallel	37
DPMGibbsSkewT_SeqPrior	41
DPMGibbsSkewT_SeqPrior_parallel	44
DPMpost	48
evalClustLoss	53
Flimited	54
FmeasureC	55
FmeasureC_no0	55
Fmeasure_costC	56
lgamma_mv	57
MAP_sNiW_mmEM	57
MLE_gamma	60
MLE_NiW_mmEM	61
MLE_sNiW	62
MLE_sNiW_mmEM	63
mmNiWpdf	65
mmNiWpdfC	66
mmsNiWlogpdf	67
mmsNiWpdfC	68
mmvnpdfC	69
mmvsnpdfC	70
mmvstpdfC	72
mmvtpdfC	73
mvnlikC	75
mvnnpdf	76
mvnnpdfC	77
mvsnlikC	78
mvsnpdf	79
mvstlikC	80
mvstpdf	81
mvtpdf	82
NuMatParC	83
plot_ConvDPM	83
plot_DPM	84
plot_DPMsn	85
plot_DPMst	86
postProcess.DPMMclust	87

print.summaryDPMMclust	89
priormix	90
rCRP	91
sample_alpha	93
similarityMat	95
similarityMatC	96
similarityMat_nocostC	96
summary.DPMMclust	97
vclust2mcoclustC	99

Index**100**

NPflow-package

*Bayesian Nonparametrics for Automatic Gating of Flow Cytometry data***Description**

Dirichlet process mixture of multivariate normal, skew normal or skew t-distributions modeling oriented towards flow-cytometry data pre-processing applications.

Details

Package: NPflow
Type: Package
Version: 0.13.5
Date: 2024-01-13
License: **LGPL-3**

The main function in this package is [DPMpost](#).

Author(s)

Boris P. Hejblum, Chariff Alkhassim, Francois Caron — Maintainer: Boris P. Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

See Also

Useful links:

- Report bugs at <https://github.com/sistm/NPflow/issues>

burn.DPMMclust *Burning MCMC iterations from a Dirichlet Process Mixture Model.*

Description

Utility function for burning MCMC iteration from a DPMMclust object.

Usage

```
burn.DPMMclust(x, burnin = 0, thin = 1)
```

Arguments

x	a DPMMclust object.
burnin	the number of MCMC iterations to burn (default is 0).
thin	the spacing at which MCMC iterations are kept. Default is 1, i.e. no thinning.

Value

a DPMMclust object minus the burnt iterations

Author(s)

Boris Hejblum

See Also

[summary.DPMMclust](#)

cluster_est_binder *Point estimate of the partition for the Binder loss function*

Description

Get a point estimate of the partition using the Binder loss function.

Usage

```
cluster_est_binder(c, logposterior)
```

Arguments

c	a list of vector of length n. c[[j]][i] is the cluster allocation of observation i=1...n at iteration j=1...N.
logposterior	vector of logposterior corresponding to each partition from c used to break ties when minimizing the cost function

Value

a list:

c_est: a vector of length n. Point estimate of the partition

cost: a vector of length N. cost[j] is the cost associated to partition c[[j]]

similarity: matrix of size n x n. Similarity matrix (see [similarityMat](#))

opt_ind: the index of the optimal partition among the MCMC iterations.

Author(s)

Francois Caron, Boris Hejblum

References

F Caron, YW Teh, TB Murphy, Bayesian nonparametric Plackett-Luce models for the analysis of preferences for college degree programmes, *Annals of Applied Statistics*, 8(2):1145-1181, 2014.

DB Dahl, Model-Based Clustering for Expression Data via a Dirichlet Process Mixture Model, *Bayesian Inference for Gene Expression and Proteomics*, K-A Do, P Muller, M Vannucci (Eds.), Cambridge University Press, 2006.

See Also

[similarityMat](#) [similarityMatC](#)

cluster_est_Fmeasure *Point estimate of the partition using the F-measure as the cost function.*

Description

Get a point estimate of the partition using the F-measure as the cost function.

Usage

```
cluster_est_Fmeasure(c, logposterior)
```

Arguments

c a list of vector of length n. c[[j]][i] is the cluster allocation of observation i=1...n at iteration j=1...N.

logposterior a vector of logposterior corresponding to each partition from c used to break ties when minimizing the cost function

Value

a list:

- c_est: a vector of length n. Point estimate of the partition
- cost: a vector of length N. cost[j] is the cost associated to partition c[[j]]
- similarity: matrix of size n x n. Similarity matrix (see [similarityMat](#))
- opt_ind: the index of the optimal partition among the MCMC iterations.

Author(s)

Francois Caron, Boris Hejblum

See Also

[similarityMat](#)

cluster_est_Mbinder_norm

Point estimate of the partition using a modified Binder loss function

Description

Get a point estimate of the partition using a modified Binder loss function for Gaussian components

Usage

```
cluster_est_Mbinder_norm(c, Mu, Sigma, lambda = 0, a = 1, b = a, logposterior)
```

Arguments

- c a list of vector of length n. c[[j]][i] is the cluster allocation of observation i=1...n at iteration j=1...N.
- Mu is a list of length n composed of p x 1 matrices. Where 1 is the maximum number of components per partition.
- Sigma is list of length n composed of arrays containing a maximum of 1 p x p covariance matrices.
- lambda is a nonnegative tuning parameter allowing further control over the distance function. Default is 0.
- a nonnegative constant seen as the unit cost for pairwise misclassification. Default is 1.
- b nonnegative constant seen as the unit cost for the other kind of pairwise misclassification. Default is 1.
- logposterior vector of logposterior corresponding to each partition from c used to break ties when minimizing the cost function

Details

Note that the current implementation only allows Gaussian components.

The modified Binder loss function takes into account the distance between mixture components using #'the Bhattacharyya distance.

Value

a list:

- c_est: a vector of length n. Point estimate of the partition
- cost: a vector of length N. cost[j] is the cost associated to partition c[[j]]
- similarity: matrix of size n x n. Similarity matrix (see [similarityMat](#))
- opt_ind: the index of the optimal partition among the MCMC iterations.

Author(s)

Chariff Alkhassim

References

JW Lau, PJ Green, Bayesian Model-Based Clustering Procedures, *Journal of Computational and Graphical Statistics*, 16(3):526-558, 2007.

DA Binder, Bayesian cluster analysis, *Biometrika* 65(1):31-38, 1978.

See Also

[similarityMat](#) [similarityMatC](#) [similarityMat_nocostC](#)

cluster_est_pear	Gets a point estimate of the partition using posterior expected adjusted Rand index (PEAR)
------------------	--

Description

Gets a point estimate of the partition using posterior expected adjusted Rand index (PEAR)

Usage

```
cluster_est_pear(c)
```

Arguments

- c a list of vector of length n. c[[j]][i] is the cluster allocation of observation i=1...n at iteration j=1...N.

Value

a list:

- c_est: a vector of length n. Point estimate of the partition
- pear: a vector of length N. pear[j] is the posterior expected adjusted Rand index associated to partition c[[j]]
- similarity: matrix of size n x n. Similarity matrix (see [similarityMat](#))
- opt_ind: the index of the optimal partition among the MCMC iterations.

Author(s)

Chariff Alkhassim

References

A. Fritsch, K. Ickstadt. Improved Criteria for Clustering Based on the Posterior Similarity Matrix, in Bayesian Analysis, Vol.4 : p.367-392 (2009)

See Also

[similarityMat](#) [similarityMatC](#)

cytoScatter

Scatterplot of flow cytometry data

Description

Scatterplot of flow cytometry data

Usage

```
cytoScatter(
  cytomatrix,
  dims2plot = c(1, 2),
  gating = NULL,
  scale_log = FALSE,
  xlim = NULL,
  ylim = NULL,
  gg.add = list(theme())
)
```

Arguments

cytometryx	a $p \times n$ data matrix, of n cell observations measured over p markers.
dims2plot	a vector of length at least 2, indicating of the dimensions to be plotted. Default is <code>c(1, 2)</code> .
gating	an optional vector of length n indicating a known gating of the cells to be displayed. Default is <code>NULL</code> in which case no gating is displayed.
scale_log	a logical Flag indicating whether the data should be plotted on the log scale. Default is <code>FALSE</code> .
xlim	a vector of length 2 to specify the x-axis limits. Only used if <code>dims2plot</code> is of length 2Default is the data range.
ylim	a vector of length 2 to specify the y-axis limits. Only used if <code>dims2plot</code> is of length 2. Default is the data range.
gg.add	A list of instructions to add to the <code>ggplot2</code> instruction (see gg-add). Default is <code>list(theme())</code> , which adds nothing. to the plot.

Examples

```

rm(list=ls())
#Number of data
n <- 500
#n <- 2000
set.seed(1234)
#set.seed(123)
#set.seed(4321)

# Sample data
m <- matrix(nrow=2, ncol=4, c(-1, 1, 1.5, 2, 2, -2, -1.5, -2))
p <- c(0.2, 0.1, 0.4, 0.3) # frequence des clusters

sdev <- array(dim=c(2,2,4))
sdev[, ,1] <- matrix(nrow=2, ncol=2, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=2, ncol=2, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=2, ncol=2, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)
c <- rep(0,n)
z <- matrix(0, nrow=2, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- m[, c[k]] + sdev[, , c[k]]%*%matrix(rnorm(2, mean = 0, sd = 1), nrow=2, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}
cytoScatter(z)

```

DPMGibbsN*Slice Sampling of the Dirichlet Process Mixture Model with a prior on alpha*

Description

Slice Sampling of the Dirichlet Process Mixture Model with a prior on alpha

Usage

```
DPMGibbsN(
  z,
  hyperG0,
  a = 1e-04,
  b = 1e-04,
  N,
  doPlot = TRUE,
  nbclust_init = 30,
  plotevery = N/10,
  diagVar = TRUE,
  use_variance_hypervprior = TRUE,
  verbose = TRUE,
  ...
)
```

Arguments

<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>hyperG0</code>	prior mixing distribution.
<code>a</code>	shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is <code>0.0001</code> .
<code>b</code>	scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is <code>0.0001</code> . If <code>0</code> , then the concentration is fixed set to <code>a</code> .
<code>N</code>	number of MCMC iterations.
<code>doPlot</code>	logical flag indicating whether to plot MCMC iteration or not. Default to <code>TRUE</code> .
<code>nbclust_init</code>	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
<code>plotevery</code>	an integer indicating the interval between plotted iterations when <code>doPlot</code> is <code>TRUE</code> .
<code>diagVar</code>	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is <code>TRUE</code> (diagonal variance).

use_variance_hypervprior	logical flag indicating whether a hyperprior is added for the variance parameter. Default is TRUE which decrease the impact of the variance prior on the posterior. FALSE is useful for using an informative prior.
verbose	logical flag indicating whether partition info is written in the console at each MCMC iteration.
...	additional arguments to be passed to plot_DPM . Only used if doPlot is TRUE.

Value

a object of class DPMclust with the following attributes:

mcmc_partitions:	a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.
alpha:	a vector of length N. cost[j] is the cost associated to partition c[[j]]
listU_mu:	a list of length N containing the matrices of mean vectors for all the mixture components at each MCMC iteration
listU_Sigma:	a list of length N containing the arrays of covariances matrices for all the mixture components at each MCMC iteration
U_SS_list:	a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
weights_list:	a list of length N containing the logposterior values at each MCMC iterations
logposterior_list:	a list of length N containing the logposterior values at each MCMC iterations
data:	the data matrix d x n with d dimensions in rows and n observations in columns.
nb_mcmcit:	the number of MCMC iterations
clust_distrib:	the parametric distribution of the mixture component - "gaussian"
hyperG0:	the prior on the cluster location

Author(s)

Boris Hejblum

Examples

```
rm(list=ls())
#Number of data
n <- 500
d <- 4
#n <- 2000
set.seed(1234)
#set.seed(123)
#set.seed(4321)

# Sample data
m <- matrix(nrow=d, ncol=4, c(-1, 1, 1.5, 2, 2, -2, -1.5, -2))
```

```

p <- c(0.2, 0.1, 0.4, 0.3) # frequence des clusters

sdev <- array(dim=c(d,d,4))
sdev[, ,1] <- 0.3*diag(d)
sdev[, ,2] <- c(0.1, 0.3)*diag(d)
sdev[, ,3] <- matrix(nrow=d, ncol=d, 0.15)
diag(sdev[, ,3]) <- 0.3
sdev[, ,4] <- 0.3*diag(d)
c <- rep(0,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- m[, c[k]] + sdev[, , c[k]]%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# Set parameters of G0
hyperG0 <- list()
hyperG0[["mu"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["nu"]] <- d+2
hyperG0[["lambda"]] <- diag(d)/10

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

# Number of iterations
N <- 30

# do some plots
doPlot <- TRUE
nbclust_init <- 30

## Data
#####
library(ggplot2)
p <- (ggplot(data.frame("X"=z[,1], "Y"=z[,2]), aes(x=X, y=Y))
      + geom_point()
      + ggtitle("Toy example Data"))
p

## alpha priors plots
#####
prioralpha <- data.frame("alpha"=rgamma(n=5000, shape=a, scale=1/b),
                           "distribution" =factor(rep("prior", 5000),
                           levels=c("prior", "posterior")))
p <- (ggplot(prioralpha, aes(x=alpha))
      + geom_histogram(aes(y=..density..),
                      colour="black", fill="white", bins=30)

```

```

+ geom_density(alpha=.6, fill="red", color=NA)
+ ggtitle(paste("Prior distribution on alpha: Gamma(", a,
               ", ", b, ",")\n", sep=""))
+ theme_bw()
)
p

if(interactive()){
# Gibbs sampler for Dirichlet Process Mixtures
#####
MCMCsample <- DPMGibbsN(z, hyperG0, a, b, N=500, doPlot, nbclust_init, plotevery=100,
                           gg.add=list(theme_bw(),
                           guides(shape=guide_legend(override.aes = list(fill="grey45")))),
                           diagVar=FALSE)

plot_ConvDPM(MCMCsample, from=2)

s <- summary(MCMCsample, burnin = 200, thin=2, posterior_approx=FALSE,
lossFn = "MBinderN")

F <- FmeasureC(pred=s$point_estim$c_est, ref=c)

postalpha <- data.frame("alpha"=MCMCsample$alpha[50:500],
                       "distribution" = factor(rep("posterior",500-49),
                       levels=c("prior", "posterior")))
p <- (ggplot(postalpha, aes(x=alpha))
      + geom_histogram(aes(y=..density..), binwidth=.1,
                      colour="black", fill="white")
      + geom_density(alpha=.2, fill="blue")
      + ggtitle("Posterior distribution of alpha\n")
      # Ignore NA values for mean
      # Overlay with transparent density plot
      + geom_vline(aes(xintercept=mean(alpha, na.rm=TRUE)),
                   color="red", linetype="dashed", size=1)
)
p

p <- (ggplot(drop=FALSE, alpha=.6)
      + geom_density(aes(x=alpha, fill=distribution),
                    color=NA, alpha=.6,
                    data=prioralpha)
      #+ geom_density(aes(x=alpha, fill=distribution),
      #               color=NA, alpha=.6,
      #               data=postalpha)
      + ggtitle("Prior and posterior distributions of alpha\n")
      + scale_fill_discrete(drop=FALSE)
      + theme_bw()
      + xlim(0,10)
      + ylim(0, 1.3)
)
p

```

```

}

# k-means comparison
#####
plot(x=z[1,], y=z[2,], col=kmeans(t(z), centers=4)$cluster,
      xlab = "d = 1", ylab= "d = 2", main="k-means with K=4 clusters")

KM <- kmeans(t(z), centers=4)
dataKM <- data.frame("X"=z[1,], "Y"=z[2,],
                      "Cluster"=as.character(KM$cluster))
dataCenters <- data.frame("X"=KM$centers[,1],
                           "Y"=KM$centers[,2],
                           "Cluster"=rownames(KM$centers))

p <- (ggplot(dataKM)
       + geom_point(aes(x=X, y=Y, col=Cluster))
       + geom_point(aes(x=X, y=Y, fill=Cluster, order=Cluster),
                     data=dataCenters, shape=22, size=5)
       + scale_colour_discrete(name="Cluster")
       + ggtitle("K-means with K=4 clusters\n"))
p

```

DPMGibbsN_parallel

*Slice Sampling of the Dirichlet Process Mixture Model with a prior on alpha***Description**

Slice Sampling of the Dirichlet Process Mixture Model with a prior on alpha

Usage

```
DPMGibbsN_parallel(
  Ncpus,
  type_connec,
  z,
  hyperG0,
  a = 1e-04,
  b = 1e-04,
  N,
  doPlot = TRUE,
  nbclust_init = 30,
  plotevery = N/10,
```

```

diagVar = TRUE,
use_variance_hypervior = TRUE,
verbose = TRUE,
monitorfile = "",
...
)

```

Arguments

Ncpus	the number of processors available
type_connec	The type of connection between the processors. Supported cluster types are "SOCK", "FORK", "MPI", and "NWS". See also makeCluster .
z	data matrix d x n with d dimensions in rows and n observations in columns.
hyperG0	prior mixing distribution.
a	shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001.
b	scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001. If 0, then the concentration is fixed set to a.
N	number of MCMC iterations.
doPlot	logical flag indicating whether to plot MCMC iteration or not. Default to TRUE.
nbclust_init	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
plotevery	an integer indicating the interval between plotted iterations when doPlot is TRUE.
diagVar	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is TRUE (diagonal variance).
use_variance_hypervior	logical flag indicating whether a hyperprior is added for the variance parameter. Default is TRUE which decrease the impact of the variance prior on the posterior. FALSE is useful for using an informative prior.
verbose	logical flag indicating whether partition info is written in the console at each MCMC iteration.
monitorfile	a writable connections or a character string naming a file to write into, to monitor the progress of the analysis. Default is "" which is no monitoring. See Details.
...	additional arguments to be passed to plot_DPM . Only used if doPlot is TRUE.

Value

a object of class DPMclust with the following attributes:

mcmc_partitions:

a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.

alpha:

a vector of length N. cost[j] is the cost associated to partition c[[j]]

listU_mu: a list of length N containing the matrices of mean vectors for all the mixture components at each MCMC iteration
 listU_Sigma: a list of length N containing the arrays of covariances matrices for all the mixture components at each MCMC iteration
 U_SS_list: a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
 weights_list: a list of length N containing the logposterior values at each MCMC iterations
 logposterior_list:
 data: the data matrix d x n with d dimensions in rows and n observations in columns
 nb_mcmcitr: the number of MCMC iterations
 clust_distrib: the parametric distribution of the mixture component - "gaussian"
 hyperG0: the prior on the cluster location

Author(s)

Boris Hejblum

See Also

[DPMGibbsN](#)

Examples

```

# Scaling up: ----
rm(list=ls())
#Number of data
n <- 2000
set.seed(1234)

# Sample data
d <- 3
nclust <- 5
m <- matrix(nrow=d, ncol=nclust, runif(d*nclust)*8)
# p: cluster probabilities
p <- runif(nclust)
p <- p/sum(p)

# Covariance matrix of the clusters
sdev <- array(dim=c(d, d, nclust))
for (j in 1:nclust){
  sdev[, , j] <- matrix(NA, nrow=d, ncol=d)
  diag(sdev[, , j]) <- abs(rnorm(n=d, mean=0.3, sd=0.1))
  sdev[, , j][lower.tri(sdev[, , j], diag = FALSE)] <- rnorm(n=d*(d-1)/2,
  mean=0, sd=0.05)
  sdev[, , j][upper.tri(sdev[, , j], diag = FALSE)] <- (sdev[, , j][
    lower.tri(sdev[, , j], diag = FALSE)])
}
c <- rep(0, n)

```

```

z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- m[, c[k]] + sdev[, , c[k]]%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# hyperprior on the Scale parameter of DPM
a <- 0.001
b <- 0.001

# Number of iterations
N <- 25

# do some plots
doPlot <- TRUE

# Set parameters of G0
hyperG0 <- list()
hyperG0[["mu"]] <- rep(0, d)
hyperG0[["kappa"]] <- 0.01
hyperG0[["nu"]] <- d + 2
hyperG0[["lambda"]] <- diag(d)/10

nbclust_init <- 30

if(interactive()){
  library(doParallel)
  MCMCsample <- DPMGibbsN_parallel(Ncpus=2, type_connec="FORK", z, hyperG0, a, b,
                                      N=1000, doPlot=FALSE, nbclust_init=30,
                                      plotevery=100, gg.add=list(ggplot2::theme_bw(),
                                      ggplot2::guides(shape =
                                      ggplot2::guide_legend(override.aes = list(fill="grey45")))),
                                      diagVar=FALSE)
}

```

Description

Slice Sampling of Dirichlet Process Mixture of Gaussian distributions

Usage

```
DPMGibbsN_SeqPrior(
  z,
```

```

prior_inform,
hyperG0,
N,
nbclust_init,
add.vagueprior = TRUE,
weightnoninfo = NULL,
doPlot = TRUE,
plotevery = N/10,
diagVar = TRUE,
verbose = TRUE,
...
)

```

Arguments

<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>prior_inform</code>	an informative prior such as the approximation computed by <code>summary.DPMMclust</code> .
<code>hyperG0</code>	a non informative prior component for the mixing distribution. Only used if <code>add.vagueprior</code> is TRUE.
<code>N</code>	number of MCMC iterations.
<code>nbclust_init</code>	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
<code>add.vagueprior</code>	logical flag indicating whether a non informative component should be added to the informative prior. Default is TRUE.
<code>weightnoninfo</code>	a real between 0 and 1 giving the weights of the non informative component in the prior.
<code>doPlot</code>	logical flag indicating whether to plot MCMC iteration or not. Default to TRUE.
<code>plotevery</code>	an integer indicating the interval between plotted iterations when <code>doPlot</code> is TRUE.
<code>diagVar</code>	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is TRUE (diagonal variance).
<code>verbose</code>	logical flag indicating whether partition info is written in the console at each MCMC iteration.
<code>...</code>	additional arguments to be passed to <code>plot_DPM</code> . Only used if <code>doPlot</code> is TRUE.

Value

a object of class `DPMclust` with the following attributes:

<code>mcmc_partitions</code> :	a list of length N . Each element <code>mcmc_partitions[n]</code> is a vector of length n giving the partition of the n observations.
<code>alpha</code> :	a vector of length N . <code>cost[j]</code> is the cost associated to partition <code>c[[j]]</code>
<code>listU_mu</code> :	a list of length N containing the matrices of mean vectors for all the mixture components at each MCMC iteration

listU_Sigma: a list of length N containing the arrays of covariances matrices for all the mixture components at each MCMC iteration
 U_SS_list: a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
 weights_list:
 logposterior_list: a list of length N containing the logposterior values at each MCMC iterations
 data: the data matrix d x n with d dimensions in rows and n observations in columns.
 nb_mcmcitr: the number of MCMC iterations
 clust_distrib: the parametric distribution of the mixture component - "gaussian"
 hyperG0: the prior on the cluster location

Author(s)

Boris Hejblum, Chariff Alkhassim

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

See Also

[postProcess.DPMMclust](#) [DPMGibbsN](#)

Examples

```

rm(list=ls())
library(NPflow)
#Number of data
n <- 1500
# Sample data
#m <- matrix(nrow=2, ncol=4, c(-1, 1, 1.5, 2, 2, -2, 0.5, -2))
m <- matrix(nrow=2, ncol=4, c(-.8, .7, .5, .7, .5, -.7, -.5, -.7))
p <- c(0.2, 0.1, 0.4, 0.3) # frequence des clusters

sdev <- array(dim=c(2,2,4))
sdev[, ,1] <- matrix(nrow=2, ncol=2, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=2, ncol=2, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=2, ncol=2, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)
c <- rep(0,n)
z <- matrix(0, nrow=2, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- m[, c[k]] + sdev[, , c[k]]%*%matrix(rnorm(2, mean = 0, sd = 1), nrow=2, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}
  
```

```

}

d<-2
# Set parameters of G0
hyperG0 <- list()
hyperG0[["mu"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["nu"]] <- d+2
hyperG0[["lambda"]] <- diag(d)/10

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

# Number of iterations
N <- 30

# do some plots
doPlot <- TRUE
nbclust_init <- 20

## Data
#####
library(ggplot2)
p <- (ggplot(data.frame("X"=z[,1], "Y"=z[,2]), aes(x=X, y=Y))
      + geom_point()
      + ggtitle("Toy example Data"))
p

if(interactive()){
  # Gibbs sampler for Dirichlet Process Mixtures
#####

MCMCsample <- DPMGibbsN(z, hyperG0, a, b, N=1500, doPlot, nbclust_init, plotevery=200,
                           gg.add=list(theme_bw(),
                           guides(shape=guide_legend(override.aes = list(fill="grey45")))),
                           diagVar=FALSE)

s <- summary(MCMCsample, posterior_approx=TRUE, burnin = 1000, thin=5)
F1 <- FmeasureC(pred=s$point_estim$c_est, ref=c)
F1

MCMCsample2 <- DPMGibbsN_SeqPrior(z, prior_inform=s$param_posterior,
                                      hyperG0, N=1500,
                                      add.vagueprior = TRUE,
                                      doPlot=TRUE, plotevery=100,
                                      nbclust_init=nbclust_init,
                                      gg.add=list(theme_bw(),
                                      guides(shape=guide_legend(override.aes = list(fill="grey45")))),
```

```

diagVar=FALSE)

s2 <- summary(MCMCsamp2, burnin = 500, thin=5)
F2 <- FmeasureC(pred=s2$point_estim$c_est, ref=c)
F2
}

```

DPMGibbsSkewN

*Slice Sampling of Dirichlet Process Mixture of skew normal distributions***Description**

Slice Sampling of Dirichlet Process Mixture of skew normal distributions

Usage

```

DPMGibbsSkewN(
  z,
  hyperG0,
  a = 1e-04,
  b = 1e-04,
  N,
  doPlot = TRUE,
  nbclust_init = 30,
  plotevery = N/10,
  diagVar = TRUE,
  use_variance_hypervprior = TRUE,
  verbose = TRUE,
  ...
)

```

Arguments

- | | |
|---------------------|---|
| z | data matrix d x n with d dimensions in rows and n observations in columns. |
| hyperG0 | prior mixing distribution. |
| a | shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001. |
| b | scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001. If 0, then the concentration is fixed set to a. |
| N | number of MCMC iterations. |
| doPlot | logical flag indicating whether to plot MCMC iteration or not. Default to TRUE. |
| nbclust_init | number of clusters at initialization. Default to 30 (or less if there are less than 30 observations). |

plotevery	an integer indicating the interval between plotted iterations when doPlot is TRUE.
diagVar	logical flag indicating whether the variance of a cluster is a diagonal matrix. Default is FALSE (full matrix).
use_variance_hypervprior	logical flag indicating whether a hyperprior is added for the variance parameter. Default is TRUE which decrease the impact of the variance prior on the posterior. FALSE is useful for using an informative prior.
verbose	logical flag indicating whether partition info is written in the console at each MCMC iteration.
...	additional arguments to be passed to <code>plot_DPMsn</code> . Only used if doPlot is TRUE.

Value

a object of class DPMclust with the following attributes:

mcmc_partitions:	a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.
alpha:	a vector of length N. cost[j] is the cost associated to partition c[[j]]
U_SS_list:	a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
weights_list:	a list of length N containing the logposterior values at each MCMC iterations
logposterior_list:	a list of length N containing the logposterior values at each MCMC iterations
data:	the data matrix d x n with d dimensions in rows and n observations in columns
nb_mcmcitr:	the number of MCMC iterations
clust_distrib:	the parametric distribution of the mixture component - "skewnorm"
hyperG0:	the prior on the cluster location

Author(s)

Boris Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

Examples

```
rm(list=ls())
#Number of data
n <- 1000
```

```

set.seed(123)

d <- 2
ncl <- 4

# Sample data

sdev <- array(dim=c(d,d,ncl))

#xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1, 1.5, 1, 1.5, -2, -2, -2))
xi <- matrix(nrow=d, ncol=ncl, c(-0.5, 0, 0.5, 0, 0.5, -1, -1, 1))
##xi <- matrix(nrow=d, ncol=ncl, c(-0.3, 0, 0.5, 0.5, 0.5, -1.2, -1, 1))
psi <- matrix(nrow=d, ncol=4, c(0.4, -0.6, 0.8, 0, 0.3, -0.7, -0.3, -1.2))
p <- c(0.2, 0.1, 0.4, 0.3) # frequence des clusters
sdev[, ,1] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=d, ncol=d, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=d, ncol=d, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)

c <- rep(0,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- xi[, c[k]] + psi[, c[k]]*abs(rnorm(1)) + sdev[, , c[k]]%*%matrix(rnorm(d, mean = 0,
    sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# Set parameters of G0
hyperG0 <- list()
hyperG0[["b_xi"]] <- rep(0,d)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.0001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d + 1
hyperG0[["lambda"]] <- diag(d)

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

# do some plots
doPlot <- TRUE
nbclust_init <- 30

## Data
#####
library(ggplot2)
p <- (ggplot(data.frame("X"=z[,1], "Y"=z[,2]), aes(x=X, y=Y))

```

```

+ geom_point()
+ ggtitle("Simple example in 2d data")
+xlab("D1")
+ylab("D2")
+theme_bw())
p

c2plot <- factor(c)
levels(c2plot) <- c("3", "2", "4", "1")
pp <- (ggplot(data.frame("X"=z[1,], "Y"=z[2,], "Cluster"=as.character(c2plot)))
+ geom_point(aes(x=X, y=Y, colour=Cluster, fill=Cluster))
+ ggtitle("Slightly overlapping skew-normal simulation\n")
+ xlab("D1")
+ ylab("D2")
+ theme_bw()
+ scale_colour_discrete(guide=guide_legend(override.aes = list(size = 6, shape=22))))
pp

## alpha priors plots
#####
prioralpha <- data.frame("alpha"=rgamma(n=5000, shape=a, scale=1/b),
                           "distribution" =factor(rep("prior",5000),
                           levels=c("prior", "posterior")))
p <- (ggplot(prioralpha, aes(x=alpha))
+ geom_histogram(aes(y=..density..),
colour="black", fill="white")
+ geom_density(alpha=.2, fill="red")
+ ggtitle(paste("Prior distribution on alpha: Gamma(", a,
", ", b, ")\\n", sep=""))
)
p

if(interactive()){
# Gibbs sampler for Dirichlet Process Mixtures
#####

MCMCsample_sn <- DPMGibbsSkewN(z, hyperG0, a, b, N=2500,
                                    doPlot, nbclust_init, plotevery=200,
                                    gg.add=list(theme_bw(),
                                    guides(shape=guide_legend(override.aes = list(fill="grey45")))),
                                    diagVar=FALSE)

s <- summary(MCMCsample_sn, burnin = 2000, thin=10)
#cluster_est_binder(MCMCsample_sn$mcmc_partitions[1000:1500])
print(s)
plot(s)
#plot_ConvDPM(MCMCsample_sn, from=2)
}

```

```

# k-means

plot(x=z[1,], y=z[2,], col=kmeans(t(z), centers=4)$cluster,
      xlab = "d = 1", ylab= "d = 2", main="k-means with K=4 clusters")

KM <- kmeans(t(z), centers=4)
KMclust <- factor(KM$cluster)
levels(KMclust) <- c("2", "4", "1", "3")
dataKM <- data.frame("X"=z[1,], "Y"=z[2,],
                      "Cluster"=as.character(KMclust))
dataCenters <- data.frame("X"=KM$centers[,1],
                           "Y"=KM$centers[,2],
                           "Cluster"=c("2", "4", "1", "3"))

p <- (ggplot(dataKM)
      + geom_point(aes(x=X, y=Y, col=Cluster))
      + geom_point(aes(x=X, y=Y, fill=Cluster, order=Cluster),
                    data=dataCenters, shape=22, size=5)
      + scale_colour_discrete(name="Cluster",
                              guide=guide_legend(override.aes=list(size=6, shape=22)))
      + ggtitle("K-means with K=4 clusters\n")
      + theme_bw()
)
p

postalpha <- data.frame("alpha"=MCMCsample_sn$alpha[501:1000],
                        "distribution" = factor(rep("posterior",1000-500),
                        levels=c("prior", "posterior")))

postK <- data.frame("K"sapply(lapply(postalpha$alpha, "["),
                         function(x){sum(x/(x+0:(1000-1))))}))

p <- (ggplot(postalpha, aes(x=alpha))
      + geom_histogram(aes(y=..density..), binwidth=.1,
                      colour="black", fill="white")
      + geom_density(alpha=.2, fill="blue")
      + ggtitle("Posterior distribution of alpha\n")
      # Ignore NA values for mean
      # Overlay with transparent density plot
      + geom_vline(aes(xintercept=mean(alpha, na.rm=T)),
                    color="red", linetype="dashed", size=1)
)
p

p <- (ggplot(postK, aes(x=K))
      + geom_histogram(aes(y=..density..),
                      colour="black", fill="white")
      + geom_density(alpha=.2, fill="blue")
      + ggtitle("Posterior distribution of predicted K\n")
      # Ignore NA values for mean

```

```

# Overlay with transparent density plot
+ geom_vline(aes(xintercept=mean(K, na.rm=T)),
             color="red", linetype="dashed", size=1)
#+ scale_x_continuous(breaks=c(0:6)*2, minor_breaks=c(0:6)*2+1)
+ scale_x_continuous(breaks=c(1:12))
)
p

p <- (ggplot(drop=FALSE, alpha=.6)
+ geom_density(aes(x=alpha, fill=distribution),
              color=NA, alpha=.6,
              data=postalpha)
+ geom_density(aes(x=alpha, fill=distribution),
              color=NA, alpha=.6,
              data=prioralpha)
+ ggtitle("Prior and posterior distributions of alpha\n")
+ scale_fill_discrete(drop=FALSE)
+ theme_bw()
+ xlim(0,100)
)
p

#Skew Normal
n=100000
xi <- 0
d <- 0.995
alpha <- d/sqrt(1-d^2)
z <- rtruncnorm(n,a=0, b=Inf)
e <- rnorm(n, mean = 0, sd = 1)
x <- d*z + sqrt(1-d^2)*e
o <- 1
y <- xi+o*x
nu=1.3
w <- rgamma(n,scale=nu/2, shape=nu/2)
yy <- xi+o*x/w
snd <- data.frame("Y"=y,"YY"=yy)
p <- (ggplot(snd)+geom_density(aes(x=Y), fill="blue", alpha=.2)
+ theme_bw()
+ ylab("Density")
+ ggtitle("Y~SN(0,1,10)\n")
+ xlim(-1,6)
+ ylim(0,0.8)
)
p

p <- (ggplot(snd)+geom_density(aes(x=YY), fill="blue", alpha=.2)
+ theme_bw()
+ ylab("Density")
+ ggtitle("Y~ST(0,1,10,1.3)\n")
+ xlim(-2,40)
+ ylim(0,0.8)
)
p

```

```

p <- (ggplot(snd)
+ geom_density(aes(x=Y, fill="blue"), alpha=.2)
+ geom_density(aes(x=YY, fill="red"), alpha=.2)
+ theme_bw()
+ theme(legend.text = element_text(size = 13), legend.position="bottom")
+ ylab("Density")
+ xlim(-2,40)
+ ylim(0,0.8)
+ scale_fill_manual(name="", labels=c("Y~SN(0,1,10)", "Y~ST(0,1,10,1.3)"),
guide="legend", values=c("blue", "red"))
)
p

#Variations
n=100000
xi <- -1
d <- 0.995
alpha <- d/sqrt(1-d^2)
z <- rtruncnorm(n,a=0, b=Inf)
e <- rnorm(n, mean = 0, sd = 1)
x <- d*z + sqrt(1-d^2)*e
snd <- data.frame("X"=x)
p <- (ggplot(snd)+geom_density(aes(x=X), fill="blue", alpha=.2)
+ theme_bw()
+ ylab("Density")
+ ggtitle("X~SN(10)\n")
+ xlim(-1.5,4)
+ ylim(0,1.6)
)
p

o <- 0.5
y <- xi+o*x
snd <- data.frame("Y"=y)
p <- (ggplot(snd)+geom_density(aes(x=Y), fill="blue", alpha=.2)
+ theme_bw()
+ ylab("Density")
+ ggtitle("Y~SN(-1,1,10)\n")
+ xlim(-1.5,4)
+ ylim(0,1.6)
)
p

#Simple toy example
#####
n <- 500
set.seed(12345)

```

```

d <- 2
ncl <- 4

# Sample data

sdev <- array(dim=c(d,d,ncl))

xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1, 1.5, 1, 1.5, -2, -2, -2))
psi <- matrix(nrow=d, ncol=4, c(0.4, -0.6, 0.8, 0, 0.3, -0.7, -0.3, -1.2))
p <- c(0.2, 0.1, 0.4, 0.3) # frequence des clusters
sdev[, ,1] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=d, ncol=d, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=d, ncol=d, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)

#' # Set parameters of G0
hyperG0 <- list()
hyperG0[["b_xi"]] <- rep(0,d)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.0001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d + 1
hyperG0[["lambda"]] <- diag(d)

c <- rep(0,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- xi[, c[k]] + psi[, c[k]]*abs(rnorm(1)) + sdev[, , c[k]]%*%matrix(rnorm(d, mean = 0,
    sd = 1), nrow=d, ncol=1)
  cat(k, "/", n, " observations simulated\n", sep="")
}
MCMCsample_sn_sep <- DPMGibbsSkewN(z, hyperG0, a, b, N=600,
  doPlot, nbclust_init, plotevery=100,
  gg.add=list(theme_bw(),
  guides(shape=guide_legend	override.aes = list(fill="grey45"))),
  diagVar=TRUE)

s <- summary(MCMCsample_sn, burnin = 400)

}

```

Description

If the `monitorfile` argument is a character string naming a file to write into, in the case of a new file that does not exist yet, such a new file will be created. A line is written at each MCMC iteration.

Usage

```
DPMGibbsSkewN_parallel(
  Ncpus,
  type_connec,
  z,
  hyperG0,
  a = 1e-04,
  b = 1e-04,
  N,
  doPlot = FALSE,
  nbclust_init = 30,
  plotevery = N/10,
  diagVar = TRUE,
  use_variance_hyperprior = TRUE,
  verbose = FALSE,
  monitorfile = "",
  ...
)
```

Arguments

<code>Ncpus</code>	the number of processors available
<code>type_connec</code>	The type of connection between the processors. Supported cluster types are "SOCK", "FORK", "MPI", and "NWS". See also makeCluster .
<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>hyperG0</code>	prior mixing distribution.
<code>a</code>	shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is <code>0.0001</code> .
<code>b</code>	scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is <code>0.0001</code> . If θ , then the concentration is fixed set to <code>a</code> .
<code>N</code>	number of MCMC iterations.
<code>doPlot</code>	logical flag indicating whether to plot MCMC iteration or not. Default to <code>TRUE</code> .
<code>nbclust_init</code>	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
<code>plotevery</code>	an integer indicating the interval between plotted iterations when <code>doPlot</code> is <code>TRUE</code> .
<code>diagVar</code>	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is <code>TRUE</code> (diagonal variance).

<code>use_variance_hyperprior</code>	logical flag indicating whether a hyperprior is added for the variance parameter. Default is TRUE which decrease the impact of the variance prior on the posterior. FALSE is useful for using an informative prior.
<code>verbose</code>	logical flag indicating whether partition info is written in the console at each MCMC iteration.
<code>monitorfile</code>	a writable connections or a character string naming a file to write into, to monitor the progress of the analysis. Default is "" which is no monitoring. See Details.
...	additional arguments to be passed to plot_DPM . Only used if doPlot is TRUE.

Value

a object of class `DPMclust` with the following attributes:

<code>mcmc_partitions</code> :	a list of length N. Each element <code>mcmc_partitions[n]</code> is a vector of length n giving the partition of the n observations.
<code>alpha</code> :	a vector of length N. <code>cost[j]</code> is the cost associated to partition <code>c[[j]]</code>
<code>U_SS_list</code> :	a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
<code>weights_list</code> :	
<code>logposterior_list</code> :	a list of length N containing the logposterior values at each MCMC iterations
<code>data</code> :	the data matrix d x n with d dimensions in rows and n observations in columns
<code>nb_mcmcitr</code> :	the number of MCMC iterations
<code>clust_distrib</code> :	the parametric distribution of the mixture component - "skewnorm"
<code>hyperG0</code> :	the prior on the cluster location

Author(s)

Boris Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

Examples

```
rm(list=ls())
#Number of data
n <- 2000
set.seed(1234)

d <- 4
```

```

ncl <- 5

# Sample data

sdev <- array(dim=c(d,d,ncl))

xi <- matrix(nrow=d, ncol=ncl, c(runif(n=d*ncl,min=0,max=3)))
psi <- matrix(nrow=d, ncol=ncl, c(runif(n=d*ncl,min=-1,max=1)))
p <- runif(n=ncl)
p <- p/sum(p)
sdev0 <- diag(runif(n=d, min=0.05, max=0.6))
for (j in 1:ncl){
  sdev[, ,j] <- invwishrnd(n = d+2, lambda = sdev0)
}

c <- rep(0,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- xi[, c[k]] + psi[, c[k]]*abs(rnorm(1)) + sdev[, , c[k]]%*%matrix(rnorm(d, mean = 0,
                                                                                     sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# Set parameters of G0
hyperG0 <- list()
hyperG0[["b_xi"]] <- rep(0,d)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d + 1
hyperG0[["lambda"]] <- diag(d)/10

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

# do some plots
doPlot <- TRUE
nbclust_init <- 30

z <- z*200
## Data
#####
library(ggplot2)
p <- (ggplot(data.frame("X"=z[,1], "Y"=z[,2]), aes(x=X, y=Y))
      + geom_point()
      + ggtitle("Simple example in 2d data")
      + xlab("D1")
      + ylab("D2"))

```

```

+theme_bw())
p

## alpha priors plots
#####
prioralpha <- data.frame("alpha"=rgamma(n=5000, shape=a, scale=1/b),
                           "distribution" =factor(rep("prior",5000),
                           levels=c("prior", "posterior")))
p <- (ggplot(prioralpha, aes(x=alpha))
      + geom_histogram(aes(y=..density..),
                      colour="black", fill="white")
      + geom_density(alpha=.2, fill="red")
      + ggtitle(paste("Prior distribution on alpha: Gamma(", a,
                     ", ", b, ",")\n", sep=""))
      )
p

# Gibbs sampler for Dirichlet Process Mixtures
#####
if(interactive()){
  MCMCsamp_sn_par <- DPMGibbsSkewN_parallel(Ncpus=parallel::detectCores()-1,
                                                type_connec="SOCK", z, hyperG0,
                                                a, b, N=5000, doPlot, nbclust_init,
                                                plotevery=25, gg.add=list(theme_bw(),
                                                guides(shape=guide_legend(override.aes = list(fill="grey45")))))
  plot_ConvDPM(MCMCsamp_sn_par, from=2)
}

```

DPMGibbsSkewT

*Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions***Description**

Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions

Usage

```
DPMGibbsSkewT(
  z,
  hyperG0,
  a = 1e-04,
  b = 1e-04,
```

```

N,
doPlot = TRUE,
nbclust_init = 30,
plotevery = N/10,
diagVar = TRUE,
use_variance_hyperprior = TRUE,
verbose = TRUE,
...
)

```

Arguments

<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>hyperG0</code>	parameters of the prior mixing distribution in a <code>list</code> with the following named components: <ul style="list-style-type: none"> • "<code>b_xi</code>": a vector of length d with the mean location prior parameter. Can be set as the empirical mean of the data in an Empirical Bayes fashion. • "<code>b_psi</code>": a vector of length d with the skewness location prior parameter. Can be set as 0 a priori. • "<code>kappa • "<code>D_xi</code>": hyperprior controlling the information in ξ (the larger the less information is carried). 100 is a reasonable value, based on Fruhwirth-Schnatter et al., Biostatistics, 2010. • "<code>D_psi</code>": hyperprior controlling the information in ψ (the larger the less information is carried). 100 is a reasonable value, based on Fruhwirth-Schnatter et al., Biostatistics, 2010 • "<code>nu</code>": a prior number on the degrees of freedom of the t component that must be strictly greater than d. Can be set as $d + 1$ for instance. • "<code>lambda</code>": a $d \times d$ symmetric definitive positive matrix part of the inverse-Wishart component of the prior on the variance matrix. Can be set as the diagonal of empirical variance of the data in an Empirical Bayes fashion divided by a factor 3 according to Fruhwirth-Schnatter et al., Biostatistics, 2010. </code>
<code>a</code>	shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001.
<code>b</code>	scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001. If 0, then the concentration is fixed set to <code>a</code> .
<code>N</code>	number of MCMC iterations.
<code>doPlot</code>	logical flag indicating whether to plot MCMC iteration or not. Default to TRUE.
<code>nbclust_init</code>	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
<code>plotevery</code>	an integer indicating the interval between plotted iterations when <code>doPlot</code> is TRUE.

diagVar	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is TRUE (diagonal variance).
use_variance_hypervprior	logical flag indicating whether a hyperprior is added for the variance parameter. Default is TRUE which decrease the impact of the variance prior on the posterior. FALSE is useful for using an informative prior.
verbose	logical flag indicating whether partition info is written in the console at each MCMC iteration.
...	additional arguments to be passed to <code>plot_DPMst</code> . Only used if doPlot is TRUE.

Value

a object of class DPMclust with the following attributes:

mcmc_partitions:	a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.
alpha:	a vector of length N. cost[j] is the cost associated to partition c[[j]]
U_SS_list:	a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
weights_list:	a list of length N containing the weights of each mixture component for each MCMC iterations
logposterior_list:	a list of length N containing the logposterior values at each MCMC iterations
data:	the data matrix d x n with d dimensions in rows and n observations in columns
nb_mcmcit:	the number of MCMC iterations
clust_distrib:	the parametric distribution of the mixture component - "skewt"
hyperG0:	the prior on the cluster location

Author(s)

Boris Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

Fruhwirth-Schnatter S, Pyne S, Bayesian inference for finite mixtures of univariate and multivariate skew-normal and skew-t distributions, *Biostatistics*, 2010.

Examples

```

rm(list=ls())

#Number of data
n <- 2000
set.seed(4321)

d <- 2
ncl <- 4

# Sample data
library(truncnorm)

sdev <- array(dim=c(d,d,ncl))

#xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1.5, 1.5, 1.5, 2, -2.5, -2.5, -3))
#xi <- matrix(nrow=d, ncol=ncl, c(-0.5, 0, 0.5, 0, 0.5, -1, -1, 1))
xi <- matrix(nrow=d, ncol=ncl, c(-0.2, 0.5, 2.4, 0.4, 0.6, -1.3, -0.9, -2.7))
psi <- matrix(nrow=d, ncol=4, c(0.3, -0.7, -0.8, 0, 0.3, -0.7, 0.2, 0.9))
nu <- c(100,25,8,5)
p <- c(0.15, 0.05, 0.5, 0.3) # frequence des clusters
sdev[, ,1] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=d, ncol=d, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=d, ncol=d, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)

c <- rep(0,n)
w <- rep(1,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  w[k] <- rgamma(1, shape=nu[c[k]]/2, rate=nu[c[k]]/2)
  z[,k] <- xi[, c[k]] + psi[, c[k]]*rtruncnorm(n=1, a=0, b=Inf, mean=0, sd=1/sqrt(w[k])) +
    (sdev[, , c[k]]/sqrt(w[k]))%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# Set parameters of G0
hyperG0 <- list()
hyperG0[["b_xi"]] <- rowMeans(z)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d+1
hyperG0[["lambda"]] <- diag(apply(z,MARGIN=1, FUN=var))/3

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

```

```

## Data
#####
library(ggplot2)
p <- (ggplot(data.frame("X"=z[1,], "Y"=z[2,]), aes(x=X, y=Y))
      + geom_point()
      #+ ggtitle("Simple example in 2d data")
      +xlab("D1")
      +ylab("D2")
      +theme_bw())
p #pdf(height=8.5, width=8.5)

c2plot <- factor(c)
levels(c2plot) <- c("4", "1", "3", "2")
pp <- (ggplot(data.frame("X"=z[1,], "Y"=z[2,], "Cluster"=as.character(c2plot)))
       + geom_point(aes(x=X, y=Y, colour=Cluster, fill=Cluster))
       #+ ggtitle("Slightly overlapping skew-normal simulation\n")
       + xlab("D1")
       + ylab("D2")
       + theme_bw()
       + scale_colour_discrete(guide=guide_legend(override.aes = list(size = 6, shape=22))))
pp #pdf(height=7, width=7.5)

## alpha priors plots
#####
prioralpha <- data.frame("alpha"=rgamma(n=5000, shape=a, scale=1/b),
                           "distribution" =factor(rep("prior",5000),
                           levels=c("prior", "posterior")))
p <- (ggplot(prioralpha, aes(x=alpha))
      + geom_histogram(aes(y=..density..),
                      colour="black", fill="white")
      + geom_density(alpha=.2, fill="red")
      + ggtitle(paste("Prior distribution on alpha: Gamma(", a,
                     ", ", b, ", )\n", sep=""))
      )
p

if(interactive()){
  # Gibbs sampler for Dirichlet Process Mixtures
  #####
  MCMCsample_st <- DPMGibbsSkewT(z, hyperG0, a, b, N=1500,
                                      doPlot=TRUE, nbclust_init=30, plotevery=100,
                                      diagVar=FALSE)
  s <- summary(MCMCsample_st, burnin = 1000, thin=10, lossFn = "Binder")
  print(s)
  plot(s, hm=TRUE) #pdf(height=8.5, width=10.5) #png(height=700, width=720)
  plot_ConvDPM(MCMCsample_st, from=2)
  #cluster_est_binder(MCMCsample_st$mcmc_partitions[900:1000])
}

```

```
}
```

DPMGibbsSkewT_parallel

Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions

Description

Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions

Usage

```
DPMGibbsSkewT_parallel(
  Ncpus,
  type_connec,
  z,
  hyperG0,
  a = 1e-04,
  b = 1e-04,
  N,
  doPlot = FALSE,
  nbclust_init = 30,
  plotevery = N/10,
  diagVar = TRUE,
  use_variance_hyperprior = TRUE,
  verbose = FALSE,
  monitorfile = "",
  ...
)
```

Arguments

Ncpus	the number of processors available
type_connec	The type of connection between the processors. Supported cluster types are "PSOCK", "FORK", "SOCK", "MPI", and "NWS". See also makeCluster .
z	data matrix d x n with d dimensions in rows and n observations in columns.
hyperG0	prior mixing distribution.
a	shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001.
b	scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001. If 0, then the concentration is fixed set to a.
N	number of MCMC iterations.

doPlot	logical flag indicating whether to plot MCMC iteration or not. Default to TRUE.
nbclust_init	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
plotevery	an integer indicating the interval between plotted iterations when doPlot is TRUE.
diagVar	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is TRUE (diagonal variance).
use_variance_hypervprior	logical flag indicating whether a hyperprior is added for the variance parameter. Default is TRUE which decrease the impact of the variance prior on the posterior. FALSE is useful for using an informative prior.
verbose	logical flag indicating whether partition info is written in the console at each MCMC iteration.
monitorfile	a writable connections or a character string naming a file to write into, to monitor the progress of the analysis. Default is "" which is no monitoring. See Details.
...	additional arguments to be passed to plot_DPMst . Only used if doPlot is TRUE.

Value

a object of class DPMclust with the following attributes:

mcmc_partitions:	a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.
alpha:	a vector of length N. cost[j] is the cost associated to partition c[[j]]
U_SS_list:	a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
weights_list:	a list of length N containing the weights of each mixture component for each MCMC iterations
logposterior_list:	a list of length N containing the logposterior values at each MCMC iterations
data:	the data matrix d x n with d dimensions in rows and n observations in columns
nb_mcmcit:	the number of MCMC iterations
clust_distrib:	the parametric distribution of the mixture component - "skewt"
hyperG0:	the prior on the cluster location

Author(s)

Boris Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

Examples

```

rm(list=ls())

#Number of data
n <- 2000
set.seed(123)
#set.seed(4321)

d <- 2
ncl <- 4

# Sample data

sdev <- array(dim=c(d,d,ncl))

xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1, 1.5, 1, 1.5, -2, -2, -2))
psi <- matrix(nrow=d, ncol=4, c(0.4, -0.6, 0.8, 0, 0.3, -0.7, -0.3, -0.8))
p <- c(0.2, 0.1, 0.4, 0.3) # frequence des clusters
sdev[, ,1] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=d, ncol=d, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=d, ncol=d, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)

c <- rep(0,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  z[,k] <- (xi[, c[k]]
    + psi[, c[k]]*abs(rnorm(1))
    + sdev[, , c[k]]%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1))
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# Set parameters of G0
hyperG0 <- list()
hyperG0[["b_xi"]] <- rep(0,d)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d + 1
hyperG0[["lambda"]] <- diag(d)

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

# do some plots
doPlot <- TRUE
nbclust_init <- 30

```

```

## Data
#####
library(ggplot2)
p <- (ggplot(data.frame("X"=z[1,], "Y"=z[2,]), aes(x=X, y=Y))
      + geom_point()
      + ggtitle("Simple example in 2d data")
      + xlab("D1")
      + ylab("D2")
      + theme_bw())
p

c2plot <- factor(c)
levels(c2plot) <- c("3", "2", "4", "1")
pp <- (ggplot(data.frame("X"=z[1,], "Y"=z[2,], "Cluster"=as.character(c2plot)))
       + geom_point(aes(x=X, y=Y, colour=Cluster, fill=Cluster))
       + ggtitle("Slightly overlapping skew-normal simulation\n")
       + xlab("D1")
       + ylab("D2")
       + theme_bw()
       + scale_colour_discrete(guide=guide_legend(override.aes = list(size = 6, shape=22))))
pp

## alpha priors plots
#####
prioralpha <- data.frame("alpha"=rgamma(n=5000, shape=a, scale=1/b),
                           "distribution" =factor(rep("prior",5000),
                           levels=c("prior", "posterior")))
p <- (ggplot(prioralpha, aes(x=alpha))
      + geom_histogram(aes(y=..density..),
                      colour="black", fill="white")
      + geom_density(alpha=.2, fill="red")
      + ggtitle(paste("Prior distribution on alpha: Gamma(", a,
                     ", ", b, ")\n", sep=""))
      )
p

if(interactive()){
# Gibbs sampler for Dirichlet Process Mixtures
#####
MCMCsample_st <- DPMGibbsSkewT(z, hyperG0, a, b, N=2000,
                                    doPlot, nbclust_init, plotevery=100, gg.add=list(theme_bw(),
                                    guides(shape=guide_legend(override.aes = list(fill="grey45")))),
                                    diagVar=FALSE)
s <- summary(MCMCsample_st, burnin = 350)
print(s)
plot(s)
plot_ConvDPM(MCMCsample_st, from=2)
cluster_est_binder(MCMCsample_st$mcmc_partitions[1500:2000])
}

```

```
}
```

DPMGibbsSkewT_SeqPrior

Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions

Description

Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions

Usage

```
DPMGibbsSkewT_SeqPrior(
  z,
  prior_inform,
  hyperG0,
  N,
  nbclust_init,
  add.vagueprior = TRUE,
  weightnoninfo = NULL,
  doPlot = TRUE,
  plotevery = N/10,
  diagVar = TRUE,
  verbose = TRUE,
  ...
)
```

Arguments

<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>prior_inform</code>	an informative prior such as the approximation computed by <code>summary.DPMMclust</code> .
<code>hyperG0</code>	prior mixing distribution.
<code>N</code>	number of MCMC iterations.
<code>nbclust_init</code>	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
<code>add.vagueprior</code>	logical flag indicating whether a non informative component should be added to the informative prior. Default is TRUE.
<code>weightnoninfo</code>	a real between 0 and 1 giving the weights of the non informative component in the prior.
<code>doPlot</code>	logical flag indicating whether to plot MCMC iteration or not. Default to TRUE.

plotevery	an integer indicating the interval between plotted iterations when doPlot is TRUE.
diagVar	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is TRUE (diagonal variance).
verbose	logical flag indicating whether partition info is written in the console at each MCMC iteration.
...	additional arguments to be passed to <code>plot_DPM</code> . Only used if doPlot is TRUE.

Value

a object of class DPMclust with the following attributes:

mcmc_partitions:	a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.
alpha:	a vector of length N. cost[j] is the cost associated to partition c[[j]]
U_SS_list:	a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
weights_list:	a list of length N containing the weights of each mixture component for each MCMC iterations
logposterior_list:	a list of length N containing the logposterior values at each MCMC iterations
data:	the data matrix d x n with d dimensions in rows and n observations in columns
nb_mcmcit:	the number of MCMC iterations
clust_distrib:	the parametric distribution of the mixture component - "skewt"
hyperG0:	the prior on the cluster location

Author(s)

Boris Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

Examples

```
rm(list=ls())
#Number of data
n <- 2000
set.seed(123)
```

```

d <- 2
ncl <- 4

# Sample data

sdev <- array(dim=c(d,d,ncl))

xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1, 1.5, 1, 1.5, -2, -2, -2))
psi <- matrix(nrow=d, ncol=4, c(0.4, -0.6, 0.8, 0, 0.3, -0.7, -0.3, -0.8))
nu <- c(100,15,8,5)
p <- c(0.15, 0.05, 0.5, 0.3) # frequence des clusters
sdev[, ,1] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=d, ncol=d, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=d, ncol=d, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)

c <- rep(0,n)
w <- rep(1,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  w[k] <- rgamma(1, shape=nu[c[k]]/2, rate=nu[c[k]]/2)
  z[,k] <- xi[, c[k]] + psi[, c[k]]*rtruncnorm(n=1, a=0, b=Inf, mean=0, sd=1/sqrt(w[k])) +
    (sdev[, ,c[k]]/sqrt(w[k]))%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# Set parameters of G0
hyperG0 <- list()
hyperG0[["b_xi"]] <- rowMeans(z)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d+1
hyperG0[["lambda"]] <- diag(apply(z,MARGIN=1, FUN=var))/3

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

# do some plots
nbclust_init <- 30

## Plot Data
library(ggplot2)
q <- (ggplot(data.frame("X"=z[,1], "Y"=z[,2]), aes(x=X, y=Y))
  + geom_point()
  + ggtitle("Simple example in 2d data")
  + xlab("D1")
  + ylab("D2")
  + theme_bw())

```

```

q

if(interactive()){
  MCMCsample_st <- DPMGibbsSkewT(z, hyperG0, a, b, N=2000,
                                    doPlot=TRUE, plotevery=250,
                                    nbclust_init, diagVar=FALSE,
                                    gg.add=list(theme_bw(),
                                                guides(shape=guide_legend(override.aes = list(fill="grey45")))))
  s <- summary(MCMCsample_st, burnin = 1500, thin=2, posterior_approx=TRUE)
  F <- FmeasureC(pred=s$point_estim$c_est, ref=c)

  for(k in 1:n){
    c[k] = which(rmultinom(n=1, size=1, prob=p)!0)
    w[k] <- rgamma(1, shape=nu[c[k]]/2, rate=nu[c[k]]/2)
    z[,k] <- xi[, c[k]] + psi[, c[k]]*rtruncnorm(n=1, a=0, b=Inf, mean=0, sd=1/sqrt(w[k])) +
      (sdev[, , c[k]]/sqrt(w[k]))%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
    cat(k, "/", n, " observations simulated\n", sep="")
  }
  MCMCsample_st2 <- DPMGibbsSkewT_SeqPrior(z, prior=s$param_posterior,
                                              hyperG0, N=2000,
                                              doPlot=TRUE, plotevery=100,
                                              nbclust_init, diagVar=FALSE,
                                              gg.add=list(theme_bw(),
                                                          guides(shape=guide_legend(override.aes = list(fill="grey45")))))
  s2 <- summary(MCMCsample_st2, burnin = 1500, thin=5)
  F2 <- FmeasureC(pred=s2$point_estim$c_est, ref=c)

  # MCMCsample_st2_par <- DPMGibbsSkewT_SeqPrior_parallel(Ncpus= 2, type_connec="SOCK",
  #                                                       z, prior_inform=s$param_posterior,
  #                                                       hyperG0, N=2000,
  #                                                       doPlot=TRUE, plotevery=50,
  #                                                       nbclust_init, diagVar=FALSE,
  #                                                       gg.add=list(theme_bw(),
  #                                                       guides(shape=guide_legend(override.aes = list(fill="grey45"))))
  # )
}

```

DPMGibbsSkewT_SeqPrior_parallel

Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions

Description

Slice Sampling of Dirichlet Process Mixture of skew Student's t-distributions

Usage

DPMGibbsSkewT_SeqPrior_parallel(

```

Ncpus,
type_connec,
z,
prior_inform,
hyperG0,
N,
nbclust_init,
add.vagueprior = TRUE,
weightnoninfo = NULL,
doPlot = FALSE,
plotevery = N/10,
diagVar = TRUE,
verbose = TRUE,
monitorfile = "",
...
)

```

Arguments

<code>Ncpus</code>	the number of processors available
<code>type_connec</code>	The type of connection between the processors. Supported cluster types are "SOCK", "FORK", "MPI", and "NWS". See also makeCluster .
<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>prior_inform</code>	an informative prior such as the approximation computed by summary.DPMMclust .
<code>hyperG0</code>	prior mixing distribution.
<code>N</code>	number of MCMC iterations.
<code>nbclust_init</code>	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
<code>add.vagueprior</code>	logical flag indicating whether a non informative component should be added to the informative prior. Default is TRUE.
<code>weightnoninfo</code>	a real between 0 and 1 giving the weights of the non informative component in the prior.
<code>doPlot</code>	logical flag indicating whether to plot MCMC iteration or not. Default to TRUE.
<code>plotevery</code>	an integer indicating the interval between plotted iterations when <code>doPlot</code> is TRUE.
<code>diagVar</code>	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is TRUE (diagonal variance).
<code>verbose</code>	logical flag indicating whether partition info is written in the console at each MCMC iteration.
<code>monitorfile</code>	a writable connections or a character string naming a file to write into, to monitor the progress of the analysis. Default is "" which is no monitoring. See Details.
<code>...</code>	additional arguments to be passed to plot_DPM . Only used if <code>doPlot</code> is TRUE.

Value

a object of class DPMclust with the following attributes:

mcmc_partitions:

a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.

alpha: a vector of length N. cost[j] is the cost associated to partition c[[j]]

U_SS_list: a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration

weights_list: a list of length N containing the logposterior values at each MCMC iterations

logposterior_list:

a list of length N containing the logposterior values at each MCMC iterations

data: the data matrix d x n with d dimensions in rows and n observations in columns

nb_mcmcitr: the number of MCMC iterations

clust_distrib: the parametric distribution of the mixture component - "skewt"

hyperG0: the prior on the cluster location

Author(s)

Boris Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

Examples

```
rm(list=ls())

#Number of data
n <- 2000
set.seed(123)

d <- 2
ncl <- 4

# Sample data

sdev <- array(dim=c(d,d,ncl))

#xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1.5, 1.5, 1.5, 2, -2.5, -2.5, -3))
#psi <- matrix(nrow=d, ncol=4, c(0.4, -0.6, 0.8, 0, 0.3, -0.7, -0.3, -0.8))
xi <- matrix(nrow=d, ncol=ncl, c(-0.2, 0.5, 2.4, 0.4, 0.6, -1.3, -0.9, -2.7))
psi <- matrix(nrow=d, ncol=4, c(0.3, -0.7, -0.8, 0, 0.3, -0.7, 0.2, 0.9))
```



```

s <- summary(MCMCsample_st, burnin = 1500, thin=5, posterior_approx=TRUE)
F <- FmeasureC(pred=s$point_estim$c_est, ref=c)

for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  w[k] <- rgamma(1, shape=nu[c[k]]/2, rate=nu[c[k]]/2)
  z[,k] <- xi[, c[k]] + psi[, c[k]]*truncnorm(n=1, a=0, b=Inf, mean=0, sd=1/sqrt(w[k])) +
    (sdev[, , c[k]]/sqrt(w[k]))%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}
MCMCsample_st2 <- DPMGibbsSkewT_SeqPrior_parallel(Ncpus=2, type_connec="SOCK",
  z, prior_inform=s$param_posterior,
  hyperG0, N=3000,
  doPlot=TRUE, plotevery=100,
  nbclust_init, diagVar=FALSE, verbose=FALSE,
  gg.add=list(theme_bw(),
    guides(shape=guide_legend(override.aes = list(fill="grey45")))))
s2 <- summary(MCMCsample_st2, burnin = 2000, thin=5)
F2 <- FmeasureC(pred=s2$point_estim$c_est, ref=c)
}

```

DPMpost

Posterior estimation for Dirichlet process mixture of multivariate (potentially skew) distributions models

Description

Partially collapse slice Gibbs sampling for Dirichlet process mixture of multivariate normal, skew normal or skew t distributions.

Usage

```
DPMpost(
  data,
  hyperG0,
  a = 1e-04,
  b = 1e-04,
  N,
  doPlot = TRUE,
  nbclust_init = 30,
  plotevery = floor(N/10),
  diagVar = TRUE,
  verbose = TRUE,
  distrib = c("gaussian", "skewnorm", "skewt"),
  ncores = 1,
  type_connec = "SOCK",
  informPrior = NULL,
```

```

  ...
)
```

Arguments

data	data matrix d x n with d dimensions in rows and n observations in columns.
hyperG0	prior mixing distribution.
a	shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001.
b	scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001. If 0, then the concentration is fixed set to a.
N	number of MCMC iterations.
doPlot	logical flag indicating whether to plot MCMC iteration or not. Default to TRUE.
nbclust_init	number of clusters at initialization. Default to 30 (or less if there are less than 30 observations).
plotevery	an integer indicating the interval between plotted iterations when doPlot is TRUE.
diagVar	logical flag indicating whether the variance of each cluster is estimated as a diagonal matrix, or as a full matrix. Default is TRUE (diagonal variance).
verbose	logical flag indicating whether partition info is written in the console at each MCMC iteration.
distrib	the distribution used for the clustering. Current possibilities are "gaussian", "skewnorm" and "skewt".
ncores	number of cores to use.
type_connec	The type of connection between the processors. Supported cluster types are "SOCK", "FORK", "MPI", and "NWS". See also makeCluster .
informPrior	an optional informative prior such as the approximation computed by summary.DPMMclust .
...	additional arguments to be passed to plot_DPM . Only used if doPlot is TRUE.

Details

This function is a wrapper around the following functions: [DPMGibbsN](#), [DPMGibbsN_parallel](#), [DPMGibbsN_SeqPrior](#), [DPMGibbsSkewN](#), [DPMGibbsSkewN_parallel](#), [DPMGibbsSkewT](#), [DPMGibbsSkewT_parallel](#), [DPMGibbsSkewT_SeqPrior](#), [DPMGibbsSkewT_SeqPrior_parallel](#).

Value

a object of class DPMMclust with the following attributes:

mcmc_partitions:

a list of length N. Each element mcmc_partitions[n] is a vector of length n giving the partition of the n observations.

alpha:

a vector of length N. cost[j] is the cost associated to partition c[[j]]

U_SS_list: a list of length N containing the lists of sufficient statistics for all the mixture components at each MCMC iteration
 weights_list: a list of length N containing the weights of each mixture component for each MCMC iterations
 logposterior_list: a list of length N containing the logposterior values at each MCMC iterations
 data: the data matrix d x n with d dimensions in rows and n observations in columns
 nb_mcmcitr: the number of MCMC iterations
 clust_distrib: the parametric distribution of the mixture component
 hyperG0: the prior on the cluster location

Author(s)

Boris Hejblum

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

See Also

[summary.DPMMclust](#)

Examples

```

#rm(list=ls())
set.seed(123)

# Exemple in 2 dimensions with skew-t distributions

# Generate data:
n <- 2000 # number of data points
d <- 2 # dimensions
ncl <- 4 # number of true clusters
sdev <- array(dim=c(d,d,ncl))
xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1.5, 1.5, 1.5, 2, -2.5, -2.5, -3))
psi <- matrix(nrow=d, ncol=4, c(0.3, -0.7, -0.8, 0, 0.3, -0.7, 0.2, 0.9))
nu <- c(100,25,8,5)
proba <- c(0.15, 0.05, 0.5, 0.3) # cluster frequencies
sdev[, ,1] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=d, ncol=d, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.2))
sdev[, ,4] <- .3*diag(2)
c <- rep(0,n)
w <- rep(1,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  xi[, k] = rskewt(d, mu=psi[, k], sdev=sdev[, ,k], nu=nu[k])
  w[k] = rdirichlet(1, proba)
  z[, k] = xi %*% w[k]
}
  
```

```

c[k] = which(rmultinom(n=1, size=1, proba)!=0)
w[k] <- rgamma(1, shape=nu[c[k]]/2, rate=nu[c[k]]/2)
z[,k] <- xi[, c[k]] + psi[, c[k]]*rtruncnorm(n=1, a=0, b=Inf, mean=0, sd=1/sqrt(w[k])) +
(sdev[, , c[k]]/sqrt(w[k]))%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
}

# Define hyperprior
hyperG0 <- list()
hyperG0[["b_xi"]] <- rowMeans(z)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d+1
hyperG0[["lambda"]] <- diag(apply(z,MARGIN=1, FUN=var))/3

if(interactive()){
# Plot data
cytoScatter(z)

# Estimate posterior
MCMCsample_st <- DPMpost(data=z, hyperG0=hyperG0, N=2000,
distrib="skewt",
gg.add=list(ggplot2::theme_bw(),
ggplot2::guides(shape=ggplot2::guide_legend	override.aes = list(fill="grey45"))))

s <- summary(MCMCsample_st, burnin = 1600, thin=5, lossFn = "Binder")
s
plot(s)
#plot(s, hm=TRUE) # this can take a few sec...

# more data plotting:
library(ggplot2)
p <- (ggplot(data.frame("X"=z[,1], "Y"=z[,2]), aes(x=X, y=Y))
+ geom_point()
+ ggtitle("Unsupervised data")
+ xlab("D1")
+ ylab("D2")
+ theme_bw())
)
p

c2plot <- factor(c)
levels(c2plot) <- c("4", "1", "3", "2")
pp <- (ggplot(data.frame("X"=z[,1], "Y"=z[,2], "Cluster"=as.character(c2plot)))
+ geom_point(aes(x=X, y=Y, colour=Cluster, fill=Cluster))
+ ggtitle("True clusters")
+ xlab("D1")
+ ylab("D2")
+ theme_bw())
+ scale_colour_discrete(guide=guide_legend	override.aes = list(size = 6, shape=22)))

```

```

)
pp
}

# Exemple in 2 dimensions with Gaussian distributions

set.seed(1234)

# Generate data
n <- 2000 # number of data points
d <- 2 # dimensions
ncl <- 4 # number of true clusters
m <- matrix(nrow=2, ncol=4, c(-1, 1, 1.5, 2, 2, -2, -1.5, -2)) # cluster means
sdev <- array(dim=c(2, 2, 4)) # cluster standard-deviations
sdev[, ,1] <- matrix(nrow=2, ncol=2, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=2, ncol=2, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=2, ncol=2, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)
proba <- c(0.15, 0.05, 0.5, 0.3) # cluster frequencies
c <- rep(0,n)
z <- matrix(0, nrow=2, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=proba)!=0)
  z[,k] <- m[, c[k]] + sdev[, , c[k]]%*%matrix(rnorm(2, mean = 0, sd = 1), nrow=2, ncol=1)
}

# Define hyperprior
hyperG0 <- list()
hyperG0[["mu"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["nu"]] <- d+2
hyperG0[["lambda"]] <- diag(d)

if(interactive()){
  # Plot data
  cytoScatter(z)

  # Estimate posterior
  MCMCsample_n <- DPMpost(data=z, hyperG0=hyperG0, N=2000,
    distrib="gaussian", diagVar=FALSE,
    gg.add=list(ggplot2::theme_bw(),
      ggplot2::guides(shape=ggplot2::guide_legend	override.aes = list(fill="grey45")))))
}
s <- summary(MCMCsample_n, burnin = 1500, thin=5, lossFn = "Binder")
s
plot(s)
#plot(s, hm=TRUE) # this can take a few sec...

```

```

# more data plotting:
library(ggplot2)
p <- (ggplot(data.frame("X"=z[1,], "Y"=z[2,]), aes(x=X, y=Y))
      + geom_point()
      + ggtitle("Unsupervised data")
      + xlab("D1")
      + ylab("D2")
      + theme_bw())
)
p

c2plot <- factor(c)
levels(c2plot) <- c("4", "1", "3", "2")
pp <- (ggplot(data.frame("X"=z[1,], "Y"=z[2,], "Cluster"=as.character(c2plot)))
       + geom_point(aes(x=X, y=Y, colour=Cluster, fill=Cluster))
       #+ ggtitle("Slightly overlapping skew-normal simulation\n")
       + xlab("D1")
       + ylab("D2")
       + theme_bw())
       + scale_colour_discrete(guide=guide_legend(override.aes = list(size = 6, shape=22)))
       + ggtitle("True clusters")
)
pp
}

```

evalClustLoss*ELoss of a partition point estimate compared to a gold standard***Description**

Evaluate the loss of a point estimate of the partition compared to a gold standard according to a given loss function

Usage

```
evalClustLoss(c, gs, lossFn = "F-measure", a = 1, b = 1)
```

Arguments

c	vector of length n containing the estimated partition of the n observations.
gs	vector of length n containing the gold standard partition of the n observations.
lossFn	character string specifying the loss function to be used. Either "F-measure" or "Binder" (see Details). Default is "F-measure".
a	only relevant if lossFn is "Binder". Penalty for wrong co-clustering in c compared to gs. Defaults is 1.
b	only relevant if lossFn is "Binder". Penalty for missed co-clustering in c compared to gs. Defaults is 1.

Details

The cost of a point estimate partition is calculated using either a pairwise coincidence loss function (Binder), or 1-Fmeasure (F-measure).

Value

the cost of the point estimate c in regard of the gold standard gs for a given loss function.

Author(s)

Boris Hejblum

References

J.W. Lau & P.J. Green. Bayesian Model-Based Clustering Procedures, Journal of Computational and Graphical Statistics, 16(3): 526-558, 2007.

D. B. Dahl. Model-Based Clustering for Expression Data via a Dirichlet Process Mixture Model, in Bayesian Inference for Gene Expression and Proteomics, K.-A. Do, P. Muller, M. Vannucci (Eds.), Cambridge University Press, 2006.

See Also

[similarityMat](#), [cluster_est_binder](#)

Flimited

Compute a limited F-measure

Description

A limited version of F-measure that only takes into account small clusters

Usage

`Flimited(n_small_clst, pred, ref)`

Arguments

<code>n_small_clst</code>	an integer for limit size of the small cluster
<code>pred</code>	vector of a predicted partition
<code>ref</code>	vector of a reference partition

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209> <arXiv: 1702.04407> <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

Examples

```
pred <- c(rep(1, 5),rep(2, 8),rep(3,10))
ref <- c(rep(1, 5),rep(c(2,3), 4),rep(c(3,2),5))
FmeasureC(pred, ref)
Flimited(6, pred, ref)
```

FmeasureC

*C++ implementation of the F-measure computation***Description**

C++ implementation of the F-measure computation

Usage

```
FmeasureC(pred, ref)
```

Arguments

pred	vector of a predicted partition
ref	vector of a reference partition

Examples

```
pred <- c(1,1,2,3,2,3)
ref <- c(2,2,1,1,1,3)
FmeasureC(pred, ref)
```

FmeasureC_no0

*C++ implementation of the F-measure computation without the reference class 0***Description**

Aghaeepour in FlowCAP 1 ignore the reference class labeled "0"

Usage

```
FmeasureC_no0(pred, ref)
```

Arguments

pred	vector of a predicted partition
ref	vector of a reference partition

References

N Aghaeepour, G Finak, H Hoos, TR Mosmann, RR Brinkman, R Gottardo, RH Scheuermann, Critical assessment of automated flow cytometry data analysis techniques, *Nature Methods*, 10(3):228-38, 2013.

Examples

```
library(NPflow)
pred <- c(1,1,2,3,2,3)
ref <- c(2,2,0,0,0,3)
FmeasureC(pred, ref)
FmeasureC_no0(pred, ref)
```

Fmeasure_costC

Multiple cost computations with the F-measure as the loss function

Description

C++ implementation of multiple cost computations with the F-measure as the loss function using the Armadillo library

Usage

```
Fmeasure_costC(c)
```

Arguments

c	a matrix where each column is one MCMC partition
---	--

Value

a list with the following elements:

Fmeas:	TODO
cost:	TODO

Examples

```
library(NPflow)
c <- list(c(1,1,2,3,2,3), c(1,1,1,2,3,3),c(2,2,1,1,1,1))
#Fmeasure_costC(sapply(c, "["))

if(interactive()){
c2 <- list()
for(i in 1:100){
  c2 <- c(c2, list(rmultinom(n=1, size=2000, prob=rexp(n=2000))))
}
Fmeasure_costC(sapply(c2, "["))
```

```
}
```

lgamma_mv

*Multivariate log gamma function***Description**

Multivariate log gamma function

Usage

```
lgamma_mv(x, p)
```

Arguments

x	strictly positive real number
p	integer

MAP_sNiW_mmEM

*EM MAP for mixture of sNiW***Description**

Maximum A Posteriori (MAP) estimation of mixture of Normal inverse Wishart distributed observations with an EM algorithm

Usage

```
MAP_sNiW_mmEM(
  xi_list,
  psi_list,
  S_list,
  hyperG0,
  init = NULL,
  K,
  maxit = 100,
  tol = 0.1,
  doPlot = TRUE,
  verbose = TRUE
)
MAP_sNiW_mmEM_weighted(
  xi_list,
  psi_list,
```

```

S_list,
obsweight_list,
hyperG0,
K,
maxit = 100,
tol = 0.1,
doPlot = TRUE,
verbose = TRUE
)

MAP_sNiW_mmEM_vague(
xi_list,
psi_list,
S_list,
hyperG0,
K = 10,
maxit = 100,
tol = 0.1,
doPlot = TRUE,
verbose = TRUE
)

```

Arguments

<code>xi_list</code>	a list of length n, each element is a vector of size d containing the argument xi of the corresponding allocated cluster.
<code>psi_list</code>	a list of length n, each element is a vector of size d containing the argument psi of the corresponding allocated cluster.
<code>S_list</code>	a list of length n, each element is a matrix of size d x d containing the argument S of the corresponding allocated cluster.
<code>hyperG0</code>	prior mixing distribution used if <code>init</code> is NULL.
<code>init</code>	a list for initializing the algorithm with the following elements: <code>b_xi</code> , <code>b_psi</code> , <code>lambda</code> , <code>B</code> , <code>nu</code> . Default is NULL in which case the initialization of the algorithm is random.
<code>K</code>	integer giving the number of mixture components.
<code>maxit</code>	integer giving the maximum number of iteration for the EM algorithm. Default is 100.
<code>tol</code>	real number giving the tolerance for the stopping of the EM algorithm. Default is 0.1.
<code>doPlot</code>	a logical flag indicating whether the algorithm progression should be plotted. Default is TRUE.
<code>verbose</code>	logical flag indicating whether plot should be drawn. Default is TRUE.
<code>obsweight_list</code>	a list of length n where each element is a vector of weights for each sampled cluster at each MCMC iterations.

Details

MAP_sNiW_mmEM provides an estimation for the MAP of mixtures of Normal inverse Wishart distributed observations. MAP_sNiW_mmEM_vague provides an estimates incorporating a vague component in the mixture. MAP_sNiW_mmEM_weighted provides a weighted version of the algorithm.

Author(s)

Boris Hejblum, Chariff Alkhassim

Examples

```

set.seed(1234)
hyperG0 <- list()
hyperG0$b_xi <- c(0.3, -1.5)
hyperG0$b_psi <- c(0, 0)
hyperG0$kappa <- 0.001
hyperG0$D_xi <- 100
hyperG0$D_psi <- 100
hyperG0$nu <- 20
hyperG0$lambda <- diag(c(0.25,0.35))

hyperG0 <- list()
hyperG0$b_xi <- c(1, -1.5)
hyperG0$b_psi <- c(0, 0)
hyperG0$kappa <- 0.1
hyperG0$D_xi <- 1
hyperG0$D_psi <- 1
hyperG0$nu <- 2
hyperG0$lambda <- diag(c(0.25,0.35))

xi_list <- list()
psi_list <- list()
S_list <- list()
w_list <- list()

for(k in 1:200){
  NNiW <- rNNiW(hyperG0, diagVar=FALSE)
  xi_list[[k]] <- NNiW[["xi"]]
  psi_list[[k]] <- NNiW[["psi"]]
  S_list[[k]] <- NNiW[["S"]]
  w_list [[k]] <- 0.75
}

hyperG02 <- list()
hyperG02$b_xi <- c(-1, 2)
hyperG02$b_psi <- c(-0.1, 0.5)
hyperG02$kappa <- 0.1
hyperG02$D_xi <- 1
hyperG02$D_psi <- 1
hyperG02$nu <- 4
hyperG02$lambda <- 0.5*diag(2)

```

```

for(k in 201:400){
  NNIW <- rNNIW(hyperG02, diagVar=FALSE)
  xi_list[[k]] <- NNIW[["xi"]]
  psi_list[[k]] <- NNIW[["psi"]]
  S_list[[k]] <- NNIW[["S"]]
  w_list [[k]] <- 0.25
}

map <- MAP_sNiW_mmEM(xi_list, psi_list, S_list, hyperG0, K=2, tol=0.1)

```

MLE_gamma*MLE for Gamma distribution***Description**

Maximum likelihood estimation of Gamma distributed observations distribution parameters

Usage

```
MLE_gamma(g)
```

Arguments

g a list of Gamma distributed observation.

Examples

```

g_list <- list()
for(i in 1:1000{
  g_list <- c(g_list, rgamma(1, shape=100, rate=5))
}

mle <- MLE_gamma(g_list)
mle

```

<code>MLE_NiW_mmEM</code>	<i>EM MLE for mixture of NiW</i>
---------------------------	----------------------------------

Description

Maximum likelihood estimation of mixture of Normal inverse Wishart distributed observations with an EM algorithm

Usage

```
MLE_NiW_mmEM(
  mu_list,
  S_list,
  hyperG0,
  K,
  maxit = 100,
  tol = 0.1,
  doPlot = TRUE
)
```

Arguments

<code>mu_list</code>	a list of length N whose elements are observed vectors of length d of the mean parameters.
<code>S_list</code>	a list of length N whose elements are observed variance-covariance matrices of dimension d x d.
<code>hyperG0</code>	prior mixing distribution used for randomly initializing the algorithm.
<code>K</code>	integer giving the number of mixture components.
<code>maxit</code>	integer giving the maximum number of iteration for the EM algorithm. Default is 100.
<code>tol</code>	real number giving the tolerance for the stopping of the EM algorithm. Default is 0.1.
<code>doPlot</code>	a logical flag indicating whether the algorithm progression should be plotted. Default is TRUE.

Examples

```
set.seed(123)
U_mu <- list()
U_Sigma <- list()
U_nu<-list()
U_kappa<-list()

d <- 2
hyperG0 <- list()
hyperG0[["mu"]] <- rep(1,d)
```

```

hyperG0[["kappa"]] <- 0.01
hyperG0[["nu"]] <- d+1
hyperG0[["lambda"]] <- diag(d)

for(k in 1:200){

  NiW <- rNiW(hyperG0, diagVar=FALSE)
  U_mu[[k]] <- NiW[["mu"]]
  U_Sigma[[k]] <- NiW[["S"]]
}

hyperG02 <- list()
hyperG02[["mu"]] <- rep(2,d)
hyperG02[["kappa"]] <- 1
hyperG02[["nu"]] <- d+10
hyperG02[["lambda"]] <- diag(d)/10

for(k in 201:400){

  NiW <- rNiW(hyperG02, diagVar=FALSE)
  U_mu[[k]] <- NiW[["mu"]]
  U_Sigma[[k]] <- NiW[["S"]]
}

mle <- MLE_NiW_mmEM( U_mu, U_Sigma, hyperG0, K=2)

hyperG0[["mu"]]
hyperG02[["mu"]]
mle$U_mu

hyperG0[["lambda"]]
hyperG02[["lambda"]]
mle$U_lambda

hyperG0[["nu"]]
hyperG02[["nu"]]
mle$U_nu

hyperG0[["kappa"]]
hyperG02[["kappa"]]
mle$U_kappa

```

Description

Maximum likelihood estimation of Normal inverse Wishart distributed observations

Usage

```
MLE_sNiW(xi_list, psi_list, S_list, doPlot = TRUE)
```

Arguments

xi_list	a list of length N whose elements are observed vectors of length d of the mean parameters xi.
psi_list	a list of length N whose elements are observed vectors of length d of the skew parameters psi.
S_list	a list of length N whose elements are observed variance-covariance matrices of dimension d x d.
doPlot	a logical flag indicating whether the algorithm progression should be plotted. Default is TRUE.

Author(s)

Boris Hejblum, Chariff Alkhassim

Examples

```
hyperG0 <- list()
hyperG0$b_xi <- c(0.3, -1.5)
hyperG0$b_psi <- c(0, 0)
hyperG0$kappa <- 0.001
hyperG0$D_xi <- 100
hyperG0$D_psi <- 100
hyperG0$nu <- 35
hyperG0$lambda <- diag(c(0.25, 0.35))

xi_list <- list()
psi_list <- list()
S_list <- list()
for(k in 1:1000){
  NNiW <- rNNiW(hyperG0, diagVar=FALSE)
  xi_list[[k]] <- NNiW[["xi"]]
  psi_list[[k]] <- NNiW[["psi"]]
  S_list[[k]] <- NNiW[["S"]]
}
mle <- MLE_sNiW(xi_list, psi_list, S_list)
mle
```

Description

Maximum likelihood estimation of mixture of Normal inverse Wishart distributed observations with an EM algorithm

Usage

```
MLE_sNiW_mmEM(
  xi_list,
  psi_list,
  S_list,
  hyperG0,
  K,
  init = NULL,
  maxit = 100,
  tol = 0.1,
  doPlot = TRUE,
  verbose = TRUE
)
```

Arguments

xi_list	a list of length N whose elements are observed vectors of length d of the mean parameters xi.
psi_list	a list of length N whose elements are observed vectors of length d of the skew parameters psi.
S_list	a list of length N whose elements are observed variance-covariance matrices of dimension d x d.
hyperG0	prior mixing distribution used if init is NULL.
K	integer giving the number of mixture components.
init	a list for initializing the algorithm with the following elements: b_xi, b_psi, lambda, B, nu. Default is NULL in which case the initialization of the algorithm is random.
maxit	integer giving the maximum number of iteration for the EM algorithm. Default is 100.
tol	real number giving the tolerance for the stopping of the EM algorithm. Default is 0.1.
doPlot	a logical flag indicating whether the algorithm progression should be plotted. Default is TRUE.
verbose	logical flag indicating whether plot should be drawn. Default is TRUE.

Author(s)

Boris Hejblum, Chariff Alkhassim

Examples

```
set.seed(1234)
hyperG0 <- list()
hyperG0$b_xi <- c(0.3, -1.5)
hyperG0$b_psi <- c(0, 0)
hyperG0$kappa <- 0.001
```

```

hyperG0$D_xi <- 100
hyperG0$D_psi <- 100
hyperG0$nu <- 3
hyperG0$lambda <- diag(c(0.25,0.35))

xi_list <- list()
psi_list <- list()
S_list <- list()
for(k in 1:200){
  NNiW <- rNNiW(hyperG0, diagVar=FALSE)
  xi_list[[k]] <- NNiW[["xi"]]
  psi_list[[k]] <- NNiW[["psi"]]
  S_list[[k]] <- NNiW[["S"]]
}

hyperG02 <- list()
hyperG02$b_xi <- c(-1, 2)
hyperG02$b_psi <- c(-0.1, 0.5)
hyperG02$kappa <- 0.001
hyperG02$D_xi <- 10
hyperG02$D_psi <- 10
hyperG02$nu <- 3
hyperG02$lambda <- 0.5*diag(2)

for(k in 201:400){
  NNiW <- rNNiW(hyperG02, diagVar=FALSE)
  xi_list[[k]] <- NNiW[["xi"]]
  psi_list[[k]] <- NNiW[["psi"]]
  S_list[[k]] <- NNiW[["S"]]
}

mle <- MLE_sNiW_mmEM(xi_list, psi_list, S_list, hyperG0, K=2)

```

mmNiWpdf

multivariate Normal inverse Wishart probability density function for multiple inputs

Description

multivariate Normal inverse Wishart probability density function for multiple inputs

Usage

```
mmNiWpdf(mu, Sigma, U_mu0, U_kappa0, U_nu0, U_lambda0, Log = TRUE)
```

Arguments

mu	data matrix of dimension p x n, p being the dimension of the data and n the number of data points, where each column is an observed mean vector.
----	--

Sigma	list of length n of observed variance-covariance matrices, each of dimensions p x p.
U_mu0	mean vectors matrix of dimension p x K, K being the number of distributions for which the density probability has to be evaluated
U_kappa0	vector of length K of scale parameters.
U_nu0	vector of length K of degree of freedom parameters.
U_lambda0	list of length K of variance-covariance matrices, each of dimensions p x p.
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

Value

matrix of densities of dimension K x n

mmNiWpdfC

C++ implementation of multivariate Normal inverse Wishart probability density function for multiple inputs

Description

C++ implementation of multivariate Normal inverse Wishart probability density function for multiple inputs

Usage

```
mmNiWpdfC(Mu, Sigma, U_Mu0, U_Kappa0, U_Nu0, U_Sigma0, Log = TRUE)
```

Arguments

Mu	data matrix of dimension p x n, p being the dimension of the data and n the number of data points, where each column is an observed mean vector.
Sigma	list of length n of observed variance-covariance matrices, each of dimensions p x p.
U_Mu0	mean vectors matrix of dimension p x K, K being the number of distributions for which the density probability has to be evaluated
U_Kappa0	vector of length K of scale parameters.
U_Nu0	vector of length K of degree of freedom parameters.
U_Sigma0	list of length K of variance-covariance matrices, each of dimensions p x p.
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

Value

matrix of densities of dimension K x n

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209>. <arXiv: 1702.04407>. <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

mmsNiWlogpdf	<i>Probability density function of multiple structured Normal inverse Wishart</i>
--------------	---

Description

Probability density function of structured Normal inverse Wishart (sNiW) for multiple inputs, on the log scale.

Usage

```
mmsNiWlogpdf(U_xi, U_psi, U_Sigma, U_xi0, U_psi0, U_B0, U_Sigma0, U_df0)
```

Arguments

U_xi	a list of length n of observed mean vectors, each of dimension p
U_psi	a list of length n of observed skew vectors of dimension p
U_Sigma	a list of length n of observed covariance matrices, each of dimension p x p
U_xi0	a list of length K of mean vector parameters for sNiW, each of dimension p
U_psi0	a list of length K of mean vector parameters for sNiW, each of dimension p
U_B0	a list of length K of structuring matrix parameters for sNiW, each of dimension 2 x 2
U_Sigma0	a list of length K of covariance matrix parameters for sNiW, each of dimension p x p
U_df0	a list of length K of degrees of freedom parameters for sNiW, each of dimension p x p

Examples

```
hyperG0 <- list()
hyperG0$b_xi <- c(-1.6983129, -0.4819131)
hyperG0$b_psi <- c(-0.0641866, -0.7606068)
hyperG0$kappa <- 0.001
hyperG0$D_xi <- 16.951313
hyperG0$D_psi <- 1.255192
hyperG0$\nu <- 27.67656
hyperG0$\lambda <- matrix(c(2.3397761, -0.3975259, -0.3975259, 1.9601773), ncol=2)

xi_list <- list()
psi_list <- list()
```

```

S_list <- list()
for(k in 1:1000{
  NNiW <- rNNiW(hyperG0, diagVar=FALSE)
  xi_list[[k]] <- NNiW[["xi"]]
  psi_list[[k]] <- NNiW[["psi"]]
  S_list[[k]] <- NNiW[["S"]]
}
mmsNiWlogpdf(U_xi=xi_list, U_psi=psi_list, U_Sigma=S_list,
               U_xi0=list(hyperG0$b_xi), U_psi0=list(hyperG0$b_psi) ,
               U_B0=list(diag(c(hyperG0$D_xi, hyperG0$D_psi))) ,
               U_Sigma0=list(hyperG0$lambda), U_df0=list(hyperG0$nu))

hyperG0 <- list()
hyperG0$b_xi <- c(-1.6983129)
hyperG0$b_psi <- c(-0.0641866)
hyperG0$kappa <- 0.001
hyperG0$D_xi <- 16.951313
hyperG0$D_psi <- 1.255192
hyperG0$nu <- 27.67656
hyperG0$lambda <- matrix(c(2.3397761), ncol=1)
#'xi_list <- list()
psi_list <- list()
S_list <- list()
for(k in 1:1000{
  NNiW <- rNNiW(hyperG0, diagVar=FALSE)
  xi_list[[k]] <- NNiW[["xi"]]
  psi_list[[k]] <- NNiW[["psi"]]
  S_list[[k]] <- NNiW[["S"]]
}
mmsNiWlogpdf(U_xi=xi_list, U_psi=psi_list, U_Sigma=S_list,
               U_xi0=list(hyperG0$b_xi), U_psi0=list(hyperG0$b_psi) ,
               U_B0=list(diag(c(hyperG0$D_xi, hyperG0$D_psi))) ,
               U_Sigma0=list(hyperG0$lambda), U_df0=list(hyperG0$nu))

```

mmsNiWpdfC

C++ implementation of multivariate structured Normal inverse Wishart probability density function for multiple inputs

Description

C++ implementation of multivariate structured Normal inverse Wishart probability density function for multiple inputs

Usage

```
mmsNiWpdfC(xi, psi, Sigma, U_xi0, U_psi0, U_B0, U_Sigma0, U_df0, Log = TRUE)
```

Arguments

<code>x1</code>	data matrix of dimensions $p \times n$ where columns contain the observed mean vectors.
<code>psi</code>	data matrix of dimensions $p \times n$ where columns contain the observed skew parameter vectors.
<code>Sigma</code>	list of length n of observed variance-covariance matrices, each of dimensions $p \times p$.
<code>U_xi0</code>	mean vectors matrix of dimension $p \times K$, K being the number of distributions for which the density probability has to be evaluated.
<code>U_psi0</code>	skew parameter vectors matrix of dimension $p \times K$.
<code>U_B0</code>	list of length K of structured scale matrices, each of dimensions $p \times p$.
<code>U_Sigma0</code>	list of length K of variance-covariance matrices, each of dimensions $p \times p$.
<code>U_df0</code>	vector of length K of degree of freedom parameters.
<code>Log</code>	logical flag for returning the log of the probability density function. Defaults is TRUE.

Value

matrix of densities of dimension $K \times n$

References

Hejblum BP, Alkhassim C, Gottardo R, Caron F and Thiebaut R (2019) Sequential Dirichlet Process Mixtures of Multivariate Skew t-distributions for Model-based Clustering of Flow Cytometry Data. *The Annals of Applied Statistics*, 13(1): 638-660. <doi: 10.1214/18-AOAS1209>. <arXiv: 1702.04407>. <https://arxiv.org/abs/1702.04407> doi:10.1214/18AOAS1209

`mmvnpdfC`

C++ implementation of multivariate Normal probability density function for multiple inputs

Description

C++ implementation of multivariate Normal probability density function for multiple inputs

Usage

```
mmvnpdfC(x, mean, varcovM, Log = TRUE)
```

Arguments

x	data matrix of dimension p x n, p being the dimension of the data and n the number of data points.
mean	mean vectors matrix of dimension p x K, K being the number of distributions for which the density probability has to be evaluated.
varcovM	list of length K of variance-covariance matrices, each of dimensions p x p.
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

Value

matrix of densities of dimension K x n.

Examples

```
if(require(microbenchmark)){
  library(microbenchmark)
  microbenchmark(mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE),
    mvnpdfC(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE),
    mmvnpdfC(x=matrix(1.96), mean=matrix(0), varcovM=list(diag(1)), Log=FALSE),
    times=1000L)
  microbenchmark(mvnpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1), mean=c(-0.2, 0.3),
    varcovM=matrix(c(2, 0.2, 0.2, 2), ncol=2), Log=FALSE),
    mvnpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1), mean=c(-0.2, 0.3),
    varcovM=matrix(c(2, 0.2, 0.2, 2), ncol=2), Log=FALSE),
    mmvnpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
      mean=matrix(c(-0.2, 0.3), nrow=2, ncol=1),
      varcovM=list(matrix(c(2, 0.2, 0.2, 2), ncol=2)), Log=FALSE),
    times=1000L)
  microbenchmark(mvnpdf(x=matrix(c(rep(1.96,2),rep(0,2)), nrow=2, ncol=2),
    mean=list(c(0,0),c(-1,-1), c(1.5,1.5)),
    varcovM=list(diag(2),10*diag(2), 20*diag(2)), Log=FALSE),
    mmvnpdfC(matrix(c(rep(1.96,2),rep(0,2)), nrow=2, ncol=2),
      mean=matrix(c(0,0,-1,-1, 1.5,1.5), nrow=2, ncol=3),
      varcovM=list(diag(2),10*diag(2), 20*diag(2)), Log=FALSE),
    times=1000L)
} else{
  cat("package 'microbenchmark' not available\n")
}
```

mmvsnpdfC

C++ implementation of multivariate skew Normal probability density function for multiple inputs

Description

C++ implementation of multivariate skew Normal probability density function for multiple inputs

Usage

```
mmvsnpdfC(x, xi, psi, sigma, Log = TRUE)
```

Arguments

x	data matrix of dimension p x n, p being the dimension of the data and n the number of data points.
xi	mean vectors matrix of dimension p x K, K being the number of distributions for which the density probability has to be evaluated.
psi	skew parameter vectors matrix of dimension p x K.
sigma	list of length K of variance-covariance matrices, each of dimensions p x p.
Log	logical flag for returning the log of the probability density function. Default is TRUE.

Value

matrix of densities of dimension K x n.

Author(s)

Boris Hejblum

Examples

```
mmvsnpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
            xi=matrix(c(0, 0)), psi=matrix(c(1, 1),ncol=1), sigma=list(diag(2)), Log=FALSE
)
mmvsnpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
            xi=matrix(c(0, 0)), psi=matrix(c(1, 1),ncol=1), sigma=list(diag(2)))
if(require(microbenchmark)){
  library(microbenchmark)
  microbenchmark(mvsnpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1), xi=c(0, 0), psi=c(1, 1),
                         sigma=diag(2), Log=FALSE),
                 mmvsnpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1), xi=matrix(c(0, 0)),
                            psi=matrix(c(1, 1),ncol=1), sigma=list(diag(2)), Log=FALSE),
                 times=1000L
  )
  microbenchmark(mvsnpdf(x=matrix(c(rep(1.96,2),rep(0,2)), nrow=2, ncol=2),
                         xi=list(c(0,0),c(-1,-1), c(1.5,1.5)),
                         psi=list(c(0.1,0.1),c(-0.1,-1), c(0.5,-1.5)),
                         sigma=list(diag(2),10*diag(2), 20*diag(2)), Log=FALSE),
                 mmvsnpdfC(matrix(c(rep(1.96,2),rep(0,2)), nrow=2, ncol=2),
                           xi=matrix(c(0,0,-1,-1, 1.5,1.5), nrow=2, ncol=3),
                           psi=matrix(c(0.1,0.1,-0.1,-1, 0.5,-1.5), nrow=2, ncol=3),
                           sigma=list(diag(2),10*diag(2), 20*diag(2)), Log=FALSE),
                 times=1000L)
} else{
  cat("package 'microbenchmark' not available\n")
```

{}

mmvstpdfC*C++ implementation of multivariate Normal probability density function for multiple inputs***Description**

C++ implementation of multivariate Normal probability density function for multiple inputs

Usage

```
mmvstpdfC(x, xi, psi, sigma, df, Log = TRUE)
```

Arguments

x	data matrix of dimension p x n, p being the dimension of the data and n the number of data points.
xi	mean vectors matrix of dimension p x K, K being the number of distributions for which the density probability has to be evaluated.
psi	skew parameter vectors matrix of dimension p x K.
sigma	list of length K of variance-covariance matrices, each of dimensions p x p.
df	vector of length K of degree of freedom parameters.
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

Value

matrix of densities of dimension K x n.

Author(s)

Boris Hejblum

Examples

```
mmvstpdfC(x = matrix(c(3.399890,-5.936962), ncol=1), xi=matrix(c(0.2528859,-2.4234067)),
psi=matrix(c(11.20536,-12.51052), ncol=1),
sigma=list(matrix(c(0.2134011, -0.0382573, -0.0382573, 0.2660086), ncol=2)),
df=c(7.784106)
)
mvstpdf(x = matrix(c(3.399890,-5.936962), ncol=1), xi=c(0.2528859,-2.4234067),
psi=c(11.20536,-12.51052),
sigma=matrix(c(0.2134011, -0.0382573, -0.0382573, 0.2660086), ncol=2),
df=c(7.784106)
)
```

```

#skew-normal limit
mmvsnpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
            xi=matrix(c(0, 0)), psi=matrix(c(1, 1),ncol=1), sigma=list(diag(2))
            )
mvstpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
         xi=c(0, 0), psi=c(1, 1), sigma=diag(2),
         df=100000000
         )
mmvstpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
            xi=matrix(c(0, 0)), psi=matrix(c(1, 1),ncol=1), sigma=list(diag(2)),
            df=100000000
            )

#non-skewed limit
mmvtpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
            mean=matrix(c(0, 0)), varcovM=list(diag(2)),
            df=10
            )
mmvstpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
            xi=matrix(c(0, 0)), psi=matrix(c(0, 0),ncol=1), sigma=list(diag(2)),
            df=10
            )

if(require(microbenchmark)){
  library(microbenchmark)
  microbenchmark(mvstpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
                        xi=c(0, 0), psi=c(1, 1),
                        sigma=diag(2), df=10),
                 mmvstpdfC(x=matrix(rep(1.96,2), nrow=2, ncol=1),
                            xi=matrix(c(0, 0)), psi=matrix(c(1, 1),ncol=1),
                            sigma=list(diag(2)), df=10),
                 times=1000L)
} else{
  cat("package 'microbenchmark' not available\n")
}

```

mmvtpdfC

C++ implementation of multivariate Normal probability density function for multiple inputs

Description

C++ implementation of multivariate Normal probability density function for multiple inputs

Usage

```
mmvtpdfC(x, mean, varcovM, df, Log = TRUE)
```

Arguments

<code>x</code>	data matrix of dimension $p \times n$, p being the dimension of the data and n the number of data points.
<code>mean</code>	mean vectors matrix of dimension $p \times K$, K being the number of distributions for which the density probability has to be evaluated.
<code>varcovM</code>	list of length K of variance-covariance matrices, each of dimensions $p \times p$.
<code>df</code>	vector of length K of degree of freedom parameters.
<code>Log</code>	logical flag for returning the log of the probability density function. Defaults is TRUE.

Value

matrix of densities of dimension $K \times n$.

Author(s)

Boris Hejblum

Examples

```

mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE)
mvtcdf(x=matrix(1.96), mean=0, varcovM=diag(1), df=10000000, Log=FALSE)
mmvtpdfC(x=matrix(1.96), mean=matrix(0), varcovM=list(diag(1)), df=10000000, Log=FALSE)

mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1))
mvtcdf(x=matrix(1.96), mean=0, varcovM=diag(1), df=10000000)
mmvtpdfC(x=matrix(1.96), mean=matrix(0), varcovM=list(diag(1)), df=10000000)

mvtcdf(x=matrix(1.96), mean=0, varcovM=diag(1), df=10)
mmvtpdfC(x=matrix(1.96), mean=matrix(0), varcovM=list(diag(1)), df=10)

if(require(microbenchmark)){
  library(microbenchmark)
  microbenchmark(mvtcdf(x=matrix(1.96), mean=0, varcovM=diag(1), df=1, Log=FALSE),
    mmvtpdfC(x=matrix(1.96), mean=matrix(0), varcovM=list(diag(1)),
      df=c(1), Log=FALSE),
    times=10000L)
} else{
  cat("package 'microbenchmark' not available\n")
}

```

mvnlikC*C++ implementation of multivariate Normal probability density function for multiple inputs***Description**

C++ implementation of multivariate Normal probability density function for multiple inputs

Usage

```
mvnlikC(x, c, clustval, mu, sigma, loglik = TRUE)
```

Arguments

x	data matrix of dimension p x n, p being the dimension of the data and n the number of data points
c	integer vector of cluster allocations with values from 1 to K
clustval	vector of unique values from c in the order corresponding to the storage of cluster parameters in xi, psi, and varcovM
mu	mean vectors matrix of dimension p x K, K being the number of clusters
sigma	list of length K of variance-covariance matrices, each of dimensions p x p.
loglik	logical flag or returning the log-likelihood instead of the likelihood. Default is TRUE.

Value

a list:

"indiv":	vector of likelihood of length n;
"clust":	vector of likelihood of length K;
"total":	total (log)-likelihood;

Author(s)

Boris Hejblum

mvnpdf*multivariate-Normal probability density function***Description**

multivariate-Normal probability density function

Usage

```
mvnpdf(x, mean, varcovM, Log = TRUE)
```

Arguments

x	p x n data matrix with n the number of observations and p the number of dimensions
mean	mean vector or list of mean vectors (either a vector, a matrix or a list)
varcovM	variance-covariance matrix or list of variance-covariance matrices (either a matrix or a list)
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

Author(s)

Boris P. Hejblum

See Also

[mvnpdf](#), [mmvnpdfC](#)

Examples

```
mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE)
dnorm(1.96)

mvnpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
       mean=c(0, 0), varcovM=diag(2), Log=FALSE
     )
```

mvnpdfC*C++ implementation of multivariate normal probability density function for multiple inputs*

Description

Based on the implementation from Nino Hardt and Dicko Ahmadou https://gallery.rcpp.org/articles/dmvnorm_arma/ (accessed in August 2014)

Usage

```
mvnpdfC(x, mean, varcovM, Log = TRUE)
```

Arguments

x	data matrix
mean	mean vector
varcovM	variance covariance matrix
Log	logical flag for returning the log of the probability density function. Default is TRUE

Value

vector of densities

Author(s)

Boris P. Hejblum

Examples

```
mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE)
mvnpdfC(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE)
mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1))
mvnpdfC(x=matrix(1.96), mean=0, varcovM=diag(1))

if(require(microbenchmark)){
  library(microbenchmark)
  microbenchmark(dnorm(1.96),
    mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE),
    mvnpdfC(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE),
    times=10000L)
} else{
  cat("package 'microbenchmark' not available\n")
}
```

mvsnlikC*C++ implementation of multivariate skew normal likelihood function
for multiple inputs***Description**

C++ implementation of multivariate skew normal likelihood function for multiple inputs

Usage

```
mvsnlikC(x, c, clustval, xi, psi, sigma, loglik = TRUE)
```

Arguments

<code>x</code>	data matrix of dimension p x n, p being the dimension of the data and n the number of data points
<code>c</code>	integer vector of cluster allocations with values from 1 to K
<code>clustval</code>	vector of unique values from c in the order corresponding to the storage of cluster parameters in <code>xi</code> , <code>psi</code> , and <code>sigma</code>
<code>xi</code>	mean vectors matrix of dimension p x K, K being the number of clusters
<code>psi</code>	skew parameter vectors matrix of dimension p x K
<code>sigma</code>	list of length K of variance-covariance matrices, each of dimensions p x p.
<code>loglik</code>	logical flag or returning the log-likelihood instead of the likelihood. Default is TRUE.

Value

a list:

- "`indiv`": vector of likelihood of length n;
- "`clust`": vector of likelihood of length K;
- "`total`": total (log)-likelihood;

Author(s)

Boris Hejblum

mvsnpdf*multivariate Skew-Normal probability density function***Description**

multivariate Skew-Normal probability density function

Usage

```
mvsnpdf(x, xi, sigma, psi, Log = TRUE)
```

Arguments

x	p x n data matrix with n the number of observations and p the number of dimensions
xi	mean vector or list of mean vectors (either a vector, a matrix or a list)
sigma	variance-covariance matrix or list of variance-covariance matrices (either a matrix or a list)
psi	skew parameter vector or list of skew parameter vectors (either a vector, a matrix or a list)
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

See Also

[mvnpdf](#), [mmvsnpdfC](#)

Examples

```
mvnpdf(x=matrix(1.96), mean=0, varcovM=diag(1), Log=FALSE)
dnorm(1.96)
mvsnpdf(x=matrix(rep(1.96,1), nrow=1, ncol=1),
         xi=c(0), psi=c(0), sigma=diag(1),
         Log=FALSE
)
mvsnpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
         xi=c(0, 0), psi=c(1, 1), sigma=diag(2)
)
N=50000#00
Yn <- rnorm(n=N, mean=0, sd=1)

Z <- rtruncnorm(n=N, a=0, b=Inf, mean=0, sd=1)
eps <- rnorm(n=N, mean=0, sd=1)
psi <- 10
Ysn <- psi*Z + eps
```

```

nu <- 1.5
W <- rgamma(n=N, shape=nu/2, rate=nu/2)
Yst=Ysn/sqrt(W)

library(reshape2)
library(ggplot2)
data2plot <- melt(cbind.data.frame(Ysn, Yst))
#pdf(file="ExSNST.pdf", height=5, width=4)
p <- (ggplot(data=data2plot)
+ geom_density(aes(x=value, fill=variable, alpha=variable), col="black")#, lwd=1.1)
+ theme_bw()
+ xlim(-15,100)
+ theme(legend.position="bottom")
+ scale_fill_manual(values=alpha(c("#F8766D", "#00B0F6"),c(0.2,0.45)),
  name = " ",
  labels=c("Y~SN(0,1,10)", "Y~ST(0,1,10,1.5)"))
)
+ scale_alpha_manual(guide=FALSE, values=c(0.25, 0.45))
+ xlab("Y")
+ ylim(0,0.08)
+ ylab("Density")
+ guides(fill = guide_legend(override.aes = list(colour = NULL)))
+ theme(legend.key = element_rect(colour = "black"))
)
p
#dev.off()

```

mvstlikC

C++ implementation of multivariate skew t likelihood function for multiple inputs

Description

C++ implementation of multivariate skew t likelihood function for multiple inputs

Usage

```
mvstlikC(x, c, clustval, xi, psi, sigma, df, loglik = TRUE)
```

Arguments

- | | |
|----------|--|
| x | data matrix of dimension p x n, p being the dimension of the data and n the number of data points |
| c | integer vector of cluster allocations with values from 1 to K |
| clustval | vector of unique values from c in the order corresponding to the storage of cluster parameters in xi, psi, and sigma |
| xi | mean vectors matrix of dimension p x K, K being the number of clusters |

psi	skew parameter vectors matrix of dimension p x K
sigma	list of length K of variance-covariance matrices, each of dimensions p x p.
df	vector of length K of degree of freedom parameters.
loglik	logical flag or returning the log-likelihood instead of the likelihood. Default is TRUE.

Value

a list:

"indiv":	vector of likelihood of length n;
"clust":	vector of likelihood of length K;
"total":	total (log)-likelihood;

Author(s)

Boris Hejblum

mvstpdf

multivariate skew-t probability density function

Description

multivariate skew-t probability density function

Usage

```
mvstpdf(x, xi, sigma, psi, df, Log = TRUE)
```

Arguments

x	p x n data matrix with n the number of observations and p the number of dimensions
xi	mean vector or list of mean vectors (either a vector, a matrix or a list)
sigma	variance-covariance matrix or list of variance-covariance matrices (either a matrix or a list)
psi	skew parameter vector or list of skew parameter vectors (either a vector, a matrix or a list)
df	a numeric vector or a list of the degrees of freedom (either a vector or a list)
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

See Also

[mvtpdf](#), [mvsnpdf](#), [mmvstpdfC](#), [mvstlikC](#)

Examples

```
mvstpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
         xi=c(0, 0), psi=c(1, 1), sigma=diag(2),
         df=100000000, Log=FALSE
)
mvsnpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
         xi=c(0, 0), psi=c(1, 1), sigma=diag(2),
         Log=FALSE
)
mvstpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
         xi=c(0, 0), psi=c(1, 1), sigma=diag(2),
         df=100000000
)
mvsnpdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
         xi=c(0, 0), psi=c(1, 1), sigma=diag(2)
)
```

mvtpdf

multivariate Student's t-distribution probability density function

Description

multivariate Student's t-distribution probability density function

Usage

```
mvtpdf(x, mean, varcovM, df, Log = TRUE)
```

Arguments

x	$p \times n$ data matrix with n the number of observations and p the number of dimensions
mean	mean vector or list of mean vectors (either a vector, a matrix or a list)
varcovM	variance-covariance matrix or list of variance-covariance matrices (either a matrix or a list)
df	a numeric vector or a list of the degrees of freedom (either a vector or a list)
Log	logical flag for returning the log of the probability density function. Defaults is TRUE.

Examples

```
mvtpdf(x=matrix(1.96), mean=0, varcovM=diag(1), df=100000000)
mvpdf(x=matrix(1.96), mean=0, varcovM=diag(1))

mvtpdf(x=matrix(1.96), mean=0, varcovM=diag(1), df=10)
```

```
mvtcdf(x=matrix(rep(1.96,2), nrow=2, ncol=1),
        mean=c(0, 0), varcovM=diag(2), df=10
)
```

NuMatParC

*C++ implementation of similarity matrix computation using pre-computed distances***Description**

C++ implementation of similarity matrix computation using pre-computed distances

Usage

```
NuMatParC(c, d)
```

Arguments

- c an MCMC partitions of length n.
- d a symmetric n x n matrix containing distances between each group distributions.

Author(s)

Boris Hejblum, Chariff Alkhassim

Examples

```
c <- c(1,1,2,3,2,3)
d <- matrix(runif(length(c)^2),length(c))
NuMatParC(c,d)
```

plot_ConvDPM

*Convergence diagnostic plots***Description**

Convergence diagnostic plots

Usage

```
plot_ConvDPM(
  MCMCsamp,
  from = 1,
  to = length(MCMCsamp$logposterior_list),
  shift = 0,
  thin = 1,
  ...
)
```

Arguments

MCMCsamp	a DPMclust or summaryDPMclust object.
from	the MCMC iteration from which the plot should start. Default is 1.
to	the MCMC iteration up until which the plot should stop. Default is 1.
shift	a number of initial iterations not to be displayed. Default is 0.
thin	integer giving the spacing at which MCMC iterations are kept. Default is 1, i.e. no thinning.
...	further arguments passed to or from other methods

plot_DPM*Plot of a Dirichlet process mixture of gaussian distribution partition***Description**

Plot of a Dirichlet process mixture of gaussian distribution partition

Usage

```
plot_DPM(
  z,
  U_mu = NULL,
  U_Sigma = NULL,
  m,
  c,
  i,
  alpha = "?",
  U_SS = NULL,
  dims2plot = 1:nrow(z),
  ellipses = ifelse(length(dims2plot) < 3, TRUE, FALSE),
  gg.add = list(theme())
)
```

Arguments

<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>U_mu</code>	either a list or a matrix containing the current estimates of mean vectors of length d for each cluster. Default is <code>NULL</code> in which case <code>U_SS</code> has to be provided.
<code>U_Sigma</code>	either a list or an array containing the $d \times d$ current estimates for covariance matrix of each cluster. Default is <code>NULL</code> in which case <code>U_SS</code> has to be provided.
<code>m</code>	vector of length n containing the number of observations currently assigned to each clusters.
<code>c</code>	allocation vector of length n indicating which observation belongs to which clusters.
<code>i</code>	current MCMC iteration number.
<code>alpha</code>	current value of the DP concentration parameter.
<code>U_SS</code>	a list containing " <code>mu</code> " and " <code>S</code> ". Default is <code>NULL</code> in which case <code>U_mu</code> and <code>U_Sigma</code> have to be provided.
<code>dims2plot</code>	index vector, subset of $1:d$ indicating which dimensions should be drawn. Default is all of them.
<code>ellipses</code>	a logical flag indicating whether ellipses should be drawn around clusters. Default is <code>TRUE</code> if only 2 dimensions are plotted, <code>FALSE</code> otherwise.
<code>gg.add</code>	a list of instructions to add to the <code>ggplot2</code> instruction (see gg-add). Default is <code>list(theme())</code> , which adds nothing to the plot.

Author(s)

Boris Hejblum

`plot_DPMsn`

Plot of a Dirichlet process mixture of skew normal distribution partition

Description

Plot of a Dirichlet process mixture of skew normal distribution partition

Usage

```
plot_DPMsn(
  z,
  c,
  i = "",
  alpha = "?",
  U_SS,
  dims2plot = 1:nrow(z),
  ellipses = ifelse(length(dims2plot) < 3, TRUE, FALSE),
  gg.add = list(theme()),
  nbsim_dens = 1000
)
```

Arguments

<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>c</code>	allocation vector of length n indicating which observation belongs to which clusters.
<code>i</code>	current MCMC iteration number.
<code>alpha</code>	current value of the DP concentration parameter.
<code>U_SS</code>	a list containing " <code>xi</code> ", " <code>psi</code> ", " <code>S</code> ", and " <code>df</code> ".
<code>dims2plot</code>	index vector, subset of <code>1:d</code> indicating which dimensions should be drawn. Default is all of them.
<code>ellipses</code>	a logical flag indicating whether ellipses should be drawn around clusters. Default is <code>TRUE</code> if only 2 dimensions are plotted, <code>FALSE</code> otherwise.
<code>gg.add</code>	A list of instructions to add to the <code>ggplot2</code> instruction (see gg-add). Default is <code>list(theme())</code> , which adds nothing to the plot.
<code>nbsim_dens</code>	number of simulated points used for computing clusters density contours in 2D plots. Default is <code>1000</code> points.

Author(s)

Boris Hejblum

`plot_DPMst`

Plot of a Dirichlet process mixture of skew t-distribution partition

Description

Plot of a Dirichlet process mixture of skew t-distribution partition

Usage

```
plot_DPMst(
  z,
  c,
  i = "",
  alpha = "?",
  U_SS,
  dims2plot = 1:nrow(z),
  ellipses = ifelse(length(dims2plot) < 3, TRUE, FALSE),
  gg.add = list(theme()),
  nbsim_dens = 1000,
  nice = FALSE
)
```

Arguments

<code>z</code>	data matrix $d \times n$ with d dimensions in rows and n observations in columns.
<code>c</code>	allocation vector of length n indicating which observation belongs to which clusters.
<code>i</code>	current MCMC iteration number.
<code>alpha</code>	current value of the DP concentration parameter.
<code>U_SS</code>	a list containing " <code>xi</code> ", " <code>psi</code> ", " <code>S</code> ", and " <code>df</code> ".
<code>dims2plot</code>	index vector, subset of <code>1:d</code> indicating which dimensions should be drawn. Default is all of them.
<code>ellipses</code>	a logical flag indicating whether ellipses should be drawn around clusters. Default is <code>TRUE</code> if only 2 dimensions are plotted, <code>FALSE</code> otherwise.
<code>gg.add</code>	A list of instructions to add to the <code>ggplot2</code> instruction (see gg-add). Default is <code>list(theme())</code> , which adds nothing to the plot.
<code>nbsim_dens</code>	number of simulated points used for computing clusters density contours in 2D plots. Default is <code>1000</code> points.
<code>nice</code>	logical flag changing the plot looks. Default is <code>FALSE</code> .

Author(s)

Boris Hejblum

`postProcess.DPMMclust` *Post-processing Dirichlet Process Mixture Models results to get a mixture distribution of the posterior locations*

Description

Post-processing Dirichlet Process Mixture Models results to get a mixture distribution of the posterior locations

Usage

```
postProcess.DPMMclust(
  x,
  burnin = 0,
  thin = 1,
  gs = NULL,
  lossFn = "F-measure",
  K = 10,
  ...
)
```

Arguments

x	a DPMMclust object.
burnin	integer giving the number of MCMC iterations to burn (defaults is half)
thin	integer giving the spacing at which MCMC iterations are kept. Default is 1, i.e. no thinning.
gs	optional vector of length n containing the gold standard partition of the n observations to compare to the point estimate.
lossFn	character string specifying the loss function to be used. Either "F-measure" or "Binder" (see Details). Default is "F-measure".
K	integer giving the number of mixture components. Default is 10.
...	further arguments passed to or from other methods

Details

The cost of a point estimate partition is calculated using either a pairwise coincidence loss function (Binder), or 1-Fmeasure (F-measure).

Value

a list:

burnin:	an integer passing along the burnin argument
thin:	an integer passing along the thin argument
lossFn:	a character string passing along the lossFn argument
point_estim:	
loss:	
index_estim:	

Author(s)

Boris Hejblum

See Also

[similarityMat](#) [summary.DPMMclust](#)

print.summaryDPMMclust

Methods for a summary of a DPMMclust object

Description

Methods for a summary of a DPMMclust object

Usage

```
## S3 method for class 'summaryDPMMclust'  
print(x, ...)  
  
## S3 method for class 'summaryDPMMclust'  
plot(  
  x,  
  hm = FALSE,  
  nbsim_densities = 5000,  
  hm_subsample = NULL,  
  hm_order_by_clust = TRUE,  
  gg.add = list(theme_bw()),  
  ...  
)
```

Arguments

x	a summaryDPMMclust object.
...	further arguments passed to or from other methods
hm	logical flag to plot the heatmap of the similarity matrix. Default is FALSE.
nbsim_densities	the number of simulated observations to be used to plot the density lines of the clusters in the point estimate partition plot
hm_subsample	a integer designating the number of observations to use when plotting the heatmap. Used only if hm is TRUE. #Default is NULL in which no subsampling is done and all observations are plotted.
hm_order_by_clust	logical flag indicating whether observations should be ordered according to the point estimate first. Used only if hm is TRUE. Default is TRUE.
gg.add	a list of instructions to add to the ggplot2 instruction (see gg-add). Default is list(theme()), which adds nothing to the plot.

Author(s)

Boris Hejblum

Description

Construction of an Empirical based prior

Usage

```
priormix(sDPMclust, nu0add = 5)
```

Arguments

- | | |
|-----------|--|
| sDPMclust | an object of class <code>summary.DPMMclust</code> |
| nu0add | an additional value integer added to hyperprior parameter nu (increase to avoid non positive definite matrix sampling) |

See Also

`summary.DPMMclust`

Examples

```
rm(list=ls())

#Number of data
n <- 2000
set.seed(123)
#set.seed(4321)

d <- 2
ncl <- 4

# Sample data

sdev <- array(dim=c(d,d,ncl))

xi <- matrix(nrow=d, ncol=ncl, c(-1.5, 1.5, 1.5, 1.5, 2, -2.5, -2.5, -3))
#xi <- matrix(nrow=d, ncol=ncl, c(-0.5, 0, 0.5, 0, 0.5, -1, -1, 1))
psi <- matrix(nrow=d, ncol=4, c(0.4, -0.6, 0.8, 0, 0.3, -0.7, -0.3, -0.8))
nu <- c(100,15,8,5)
p <- c(0.15, 0.05, 0.5, 0.3) # frequence des clusters
sdev[, ,1] <- matrix(nrow=d, ncol=d, c(0.3, 0, 0, 0.3))
sdev[, ,2] <- matrix(nrow=d, ncol=d, c(0.1, 0, 0, 0.3))
sdev[, ,3] <- matrix(nrow=d, ncol=d, c(0.3, 0.15, 0.15, 0.3))
sdev[, ,4] <- .3*diag(2)
```

```

c <- rep(0,n)
w <- rep(1,n)
z <- matrix(0, nrow=d, ncol=n)
for(k in 1:n){
  c[k] = which(rmultinom(n=1, size=1, prob=p)!=0)
  w[k] <- rgamma(1, shape=nu[c[k]]/2, rate=nu[c[k]]/2)
  z[,k] <- xi[, c[k]] + psi[, c[k]]*truncnorm(n=1, a=0, b=Inf, mean=0, sd=1/sqrt(w[k])) +
    (sdev[, , c[k]]/sqrt(w[k]))%*%matrix(rnorm(d, mean = 0, sd = 1), nrow=d, ncol=1)
  #cat(k, "/", n, " observations simulated\n", sep="")
}

# Set parameters of G0
hyperG0 <- list()
hyperG0[["b_xi"]] <- rowMeans(z)
hyperG0[["b_psi"]] <- rep(0,d)
hyperG0[["kappa"]] <- 0.001
hyperG0[["D_xi"]] <- 100
hyperG0[["D_psi"]] <- 100
hyperG0[["nu"]] <- d+1
hyperG0[["lambda"]] <- diag(apply(z,MARGIN=1, FUN=var))/3

# hyperprior on the Scale parameter of DPM
a <- 0.0001
b <- 0.0001

nbclust_init <- 30

if(interactive()){
  MCMCsample_st <- DPMGibbsSkewT(z, hyperG0, a, b, N=2000, doPlot=FALSE,
                                     nbclust_init, diagVar=FALSE)
  s <- summary(MCMCsample_st, burnin = 1500, thin=5, posterior_approx=TRUE)
  pmix <- priormix(s)
}

```

Description

Generating cluster data from the Chinese Restaurant Process

Usage

```
rCRP(n = 1000, alpha = 2, hyperG0, verbose = TRUE)
```

Arguments

n	number of observations
alpha	concentration parameter

hyperG0	base distribution hyperparameter
verbose	logical flag indicating whether info is written in the console.

Examples

```

rm(list=ls())

d=2
hyperG0 <- list()
hyperG0[["NNiW"]] <- list()
hyperG0[["NNiW"]][["b_xi"]] <- rep(0,d)
hyperG0[["NNiW"]][["b_psi"]] <- rep(0,d)
hyperG0[["NNiW"]][["D_xi"]] <- 100
hyperG0[["NNiW"]][["D_psi"]] <- 8
hyperG0[["NNiW"]][["nu"]] <- d+1
hyperG0[["NNiW"]][["lambda"]] <- diag(c(1,1))

hyperG0[["scale"]] <- list()

set.seed(4321)
N <- 200
alph <- runif(n=1,0.2,2)
GvHD_sims <- rCRP(n=2*N, alpha=alph, hyperG0=hyperG0)
library(ggplot2)
q <- (ggplot(data=cbind.data.frame("D1"=GvHD_sims$data[1,],
                                    "D2"=GvHD_sims$data[2,],
                                    "Cluster"=GvHD_sims$cluster),
              aes(x=D1, y=D2))
      + geom_point(aes(colour=Cluster), alpha=0.6)
      + theme_bw()
      )
q
#q + stat_density2d(alpha=0.15, geom="polygon")

if(interactive()){
  MCMCy1 <- DPMGibbsSkewT(z=GvHD_sims$data[,1:N],
                             hyperG0$NNiW, a=0.0001, b=0.0001, N=5000,
                             doPlot=TRUE, nbclust_init=64, plotevery=500,
                             gg.add=list(theme_bw()), diagVar=FALSE)
  s1 <- summary(MCMCy1, burnin=4000, thin=5,
                 posterior_approx=TRUE)
  F1 <- FmeasureC(ref=GvHD_sims$cluster[1:N], pred=s1$point_estim$c_est)

  # s <- summary(MCMCy1, burnin=4000, thin=5,
  #               posterior_approx=TRUE, K=1)
  # s2 <- summary(MCMCy1, burnin=4000, thin=5,
  #               posterior_approx=TRUE, K=2)
  # MCMCy2_seqPost<- DPMGibbsSkewT(z=GvHD_sims$data[, (N+1):(2*N)],
  #                                   hyperG0=s1$param_post$parameters,
  #                                   a=s1$param_post$alpha_param$shape,
  #                                   b=s1$param_post$alpha_param$rate,
  #                                   N=5000, doPlot=TRUE, nbclust_init=64, plotevery=500,
  #
}

```

```

#                                     gg.add=list(theme_bw()), diagVar=FALSE)

MCMCy2_seqPost <- DPMGibbsSkewT_SeqPrior(z=GvHD_sims$data[, (N+1):(2*N)],
                                             prior=s1$param_post, hyperG0=hyperG0$NNiW, , N=1000,
                                             doPlot=TRUE, nbclust_init=10, plotevery=100,
                                             gg.add=list(theme_bw()), diagVar=FALSE)
s2_seqPost <- summary(MCMCy2_seqPost, burnin=600, thin=2)
F2_seqPost <- FmeasureC(ref=GvHD_sims$cluster[(N+1):(2*N)], pred=s2_seqPost$point_estim$c_est)

MCMCy2 <- DPMGibbsSkewT(z=GvHD_sims$data[, (N+1):(2*N)],
                           hyperG0$NNiW, a=0.0001, b=0.0001, N=5000,
                           doPlot=TRUE, nbclust_init=64, plotevery=500,
                           gg.add=list(theme_bw()), diagVar=FALSE)
s2 <- summary(MCMCy2, burnin=4000, thin=5)
F2 <- FmeasureC(ref=GvHD_sims$cluster[(N+1):(2*N)], pred=s2$point_estim$c_est)

MCMCtot <- DPMGibbsSkewT(z=GvHD_sims$data,
                            hyperG0$NNiW, a=0.0001, b=0.0001, N=5000,
                            doPlot=TRUE, nbclust_init=10, plotevery=500,
                            gg.add=list(theme_bw()), diagVar=FALSE)
stot <- summary(MCMCtot, burnin=4000, thin=5)
F2tot <- FmeasureC(ref=GvHD_sims$cluster[(N+1):(2*N)], pred=stot$point_estim$c_est[(N+1):(2*N)])

c(F1, F2, F2_seqPost, F2tot)
}

```

sample_alpha*Sampler for the concentration parameter of a Dirichlet process***Description**

Sampler updating the concentration parameter of a Dirichlet process given the number of observations and a Gamma(a, b) prior, following the augmentation strategy of West, and of Escobar and West.

Usage

```
sample_alpha(alpha_old, n, K, a = 1e-04, b = 1e-04)
```

Arguments

alpha_old	the current value of alpha
n	the number of data points
K	current number of cluster
a	shape hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001.
b	scale hyperparameter of the Gamma prior on the concentration parameter of the Dirichlet Process. Default is 0.0001. If 0 then the concentration is fixed and this function returns a.

Details

A Gamma prior is used.

References

M West, Hyperparameter estimation in Dirichlet process mixture models, Technical Report, Duke University, 1992.

MD Escobar, M West, Bayesian Density Estimation and Inference Using Mixtures *Journal of the American Statistical Association*, 90(430):577-588, 1995.

Examples

```
#Test with a fixed K
#####
alpha_init <- 1000
N <- 10000
#n=500
n=10000
K <- 80
a <- 0.0001
b <- a
alphas <- numeric(N)
alphas[1] <- alpha_init
for (i in 2:N){
  alphas[i] <- sample_alpha(alpha_old = alphas[i-1], n=n, K=K, a=a, b=b)
}

postalphas <- alphas[floor(N/2):N]
alphaMMSE <- mean(postalphas)
alphaMAP <- density(postalphas)$x[which.max(density(postalphas)$y)]

expK <- sum(alphaMMSE/(alphaMMSE+0:(n-1)))
round(expK)

prioralpha <- data.frame("alpha"=rgamma(n=5000, a,1/b),
                           "distribution" =factor(rep("prior",5000),
                           levels=c("prior", "posterior")))

library(ggplot2)
p <- (ggplot(prioralpha, aes(x=alpha))
      + geom_histogram(aes(y=..density..),
                      colour="black", fill="white")
      + geom_density(alpha=.2, fill="red")
      + ggtitle(paste("Prior distribution on alpha: Gamma(", a,
                     ", ", b, ")"))
      )
p

postalpha.df <- data.frame("alpha"=postalphas,
```

```

    "distribution" = factor(rep("posterior",length(postalphas)),
                           levels=c("prior", "posterior")))
p <- (ggplot(postalpha.df, aes(x=alpha))
      + geom_histogram(aes(y=..density..), binwidth=.1,
                       colour="black", fill="white")
      + geom_density(alpha=.2, fill="blue")
      + ggtitle("Posterior distribution of alpha\n")
      # Ignore NA values for mean
      # Overlay with transparent density plot
      + geom_vline(aes(xintercept=mean(alpha, na.rm=TRUE)),
                   color="red", linetype="dashed", size=1)
      )
p

```

similarityMat*Computes the co-clustering (or similarity) matrix***Description**

Computes the co-clustering (or similarity) matrix

Usage

```
similarityMat(c, step = 1)
```

Arguments

- c a list of vector of length n. c[[j]][i] is the cluster allocation of observation i=1...n at iteration j=1...N.
- step provide co-clustering every step iterations. Default is 1.

Value

A matrix of size n x n whose term [i,j] is the proportion of MCMC iterations where observation i and observations j are allocated to the same cluster.

Author(s)

Boris Hejblum

similarityMatC *C++ implementation*

Description

C++ implementation

Usage

`similarityMatC(cc)`

Arguments

`cc` a matrix whose columns each represents a (MCMC) partition

Examples

```
c <- list(c(1,1,2,3,2,3), c(1,1,1,2,3,3),c(2,2,1,1,1,1))
similarityMatC(sapply(c, "["))

c2 <- list()
for(i in 1:10){
  c2 <- c(c2, list(rmultinom(n=1, size=200, prob=rexp(n=200))))
}
similarityMatC(sapply(c2, "["))
```

similarityMat_nocostC *C++ implementation*

Description

C++ implementation

Usage

`similarityMat_nocostC(cc)`

Arguments

`cc` a matrix whose columns each represents a ()MCMC partition

Examples

```
c <- list(c(1,1,2,3,2,3), c(1,1,1,2,3,3),c(2,2,1,1,1,1))
similarityMat_nocostC(sapply(c, "["))

c2 <- list()
for(i in 1:10){
  c2 <- c(c2, list(rmultinom(n=1, size=1000, prob=rexp(n=1000))))
}

c3 <- sapply(c2, "[")

if(require(microbenchmark)){
  library(microbenchmark)
  microbenchmark(similarityMat(c3), similarityMat_nocostC(c3), times=2L)
} else{
  cat("package 'microbenchmark' not available\n")
}
```

summary.DPMMclust

Summarizing Dirichlet Process Mixture Models

Description

Summary methods for DPMMclust objects.

Usage

```
## S3 method for class 'DPMMclust'
summary(
  object,
  burnin = 0,
  thin = 1,
  gs = NULL,
  lossFn = "Binder",
  posterior_approx = FALSE,
  ...
)
```

Arguments

<code>object</code>	a DPMMclust object.
<code>burnin</code>	integer giving the number of MCMC iterations to burn (defaults is half)
<code>thin</code>	integer giving the spacing at which MCMC iterations are kept. Default is 1, i.e. no thinning.
<code>gs</code>	optional vector of length n containing the gold standard partition of the n observations to compare to the point estimate

lossFn character string specifying the loss function to be used. Either "F-measure" or "Binder" (see Details). Default is "Binder".
posterior_approx logical flag whether a parametric approximation of the posterior should be computed. Default is FALSE
... further arguments passed to or from other methods

Details

The cost of a point estimate partition is calculated using either a pairwise coincidence loss function (Binder), or 1-Fmeasure (F-measure).

The number of retained sampled partitions is $m = (N - \text{burnin})/\text{thin}$

Value

a list containing the following elements:

nb_mcmcit: an integer giving the value of m , the number of retained sampled partitions, i.e. $(N - \text{burnin})/\text{thin}$
burnin: an integer passing along the `burnin` argument
thin: an integer passing along the `thin` argument
lossFn: a character string passing along the `lossFn` argument
clust_distrib: a character string passing along the `clust_distrib` argument
point_estim: a list containing:
 c_est: a vector of length n containing the point estimated clustering for each observations
 cost: a vector of length m containing the cost of each sampled partition
 Fmeas: if `lossFn` is 'F-measure', the $m \times m$ matrix of total F-measures for each pair of sampled partitions
 opt_ind: the index of the point estimate partition among the m sampled
 loss: the loss for the point estimate. NA if `lossFn` is not 'Binder'
 param_posterior: a list containing the parametric approximation of the posterior, suitable to be plugged in as prior for a new MCMC algorithm run
 mcmc_partitions: a list containing the m sampled partitions
 alpha: a vector of length m with the values of the alpha DP parameter
 index_estim: the index of the point estimate partition among the m sampled
 hyperG0: a list passing along the prior, i.e. the `hyperG0` argument
 logposterior_list: a list of length m containing the logposterior and its decomposition, for each sampled partition
 U_SS_list: a list of length m containing the lists of sufficient statistics for all the mixture components, for each sampled partition
 data: a $d \times n$ matrix containing the clustered data

Author(s)

Boris Hejblum

See Also

[similarityMat](#) [similarityMatC](#)

vclust2mcoclustC *C++ implementation*

Description

C++ implementation

Usage

`vclust2mcoclustC(c)`

Arguments

`c` is an MCMC partition

Author(s)

Chariff Alkhassim

Examples

```
cc <- c(1,1,2,3,2,3)
vclust2mcoclustC(cc)
```

Index

burn.DPMMclust, 4
cluster_est_binder, 4, 54
cluster_est_Fmeasure, 5
cluster_est_Mbinder_norm, 6
cluster_est_pear, 7
connections, 15, 30, 38, 45
cytoScatter, 8
DPMGibbsN, 10, 16, 19, 49
DPMGibbsN_parallel, 14, 49
DPMGibbsN_SeqPrior, 17, 49
DPMGibbsSkewN, 21, 49
DPMGibbsSkewN_parallel, 28, 49
DPMGibbsSkewT, 32, 49
DPMGibbsSkewT_parallel, 37, 49
DPMGibbsSkewT_SeqPrior, 41, 49
DPMGibbsSkewT_SeqPrior_parallel, 44, 49
DPMpost, 3, 48
evalClustLoss, 53
Flimited, 54
Fmeasure_costC, 56
FmeasureC, 55
FmeasureC_no0, 55
lgamma_mv, 57
makeCluster, 15, 29, 37, 45, 49
MAP_sNiW_mmEM, 57
MAP_sNiW_mmEM_vague (MAP_sNiW_mmEM), 57
MAP_sNiW_mmEM_weighted (MAP_sNiW_mmEM),
57
MLE_gamma, 60
MLE_NiW_mmEM, 61
MLE_sNiW, 62
MLE_sNiW_mmEM, 63
mmNiWpdf, 65
mmNiWpdfC, 66
mmsNiWlogpdf, 67
mmsNiWpdfC, 68
mmvnpdfC, 69, 76
mmvsnpdfC, 70, 79
mmvstpdfC, 72, 81
mmvtpdfC, 73
mvnlikC, 75
mvnpdf, 76, 76, 79
mvnpdfC, 77
mvsnlikC, 78
mvsnpdf, 79, 81
mvstlikC, 80, 81
mvstpdf, 81
mvtpdf, 81, 82
NPflow (NPflow-package), 3
NPflow-package, 3
NuMatParC, 83
plot.summaryDPMMclust
 (print.summaryDPMMclust), 89
plot_ConvDPM, 83
plot_DPM, 11, 15, 18, 30, 42, 45, 49, 84
plot_DPMsn, 22, 85
plot_DPMst, 34, 38, 86
postProcess.DPMMclust, 19, 87
print.summaryDPMMclust, 89
priormix, 90
rCRP, 91
sample_alpha, 93
similarityMat, 5–8, 54, 88, 95, 99
similarityMat_nocostC, 7, 96
similarityMatC, 5, 7, 8, 96, 99
summary.DPMMclust, 4, 50, 88, 97
summaryDPMMclust
 (print.summaryDPMMclust), 89
vclust2mcoclustC, 99