

# Package ‘apdesign’

October 12, 2022

**Title** An Implementation of the Additive Polynomial Design Matrix

**Version** 1.0.0

**Description** An implementation of the additive polynomial (AP) design matrix. It constructs and appends an AP design matrix to a data frame for use with longitudinal data subject to seasonality.

**Depends** R (>= 3.2.3)

**License** GPL-3

**LazyData** true

**Imports** Matrix (>= 1.2)

**RoxygenNote** 5.0.1

**Suggests** testthat

**NeedsCompilation** no

**Author** Tyler Matta [aut, cre],  
Quinn Lathrop [ctb],  
Yeow Meng Thum [ctb]

**Maintainer** Tyler Matta <tyler.matta@gmail.com>

**Repository** CRAN

**Date/Publication** 2016-11-15 07:16:42

## R topics documented:

apdesign . . . . .	2
apdesign_i . . . . .	3
indv_change . . . . .	4
mean_change . . . . .	4
<b>Index</b>	<b>5</b>

---

apdesign	<i>apdesign: AP coding apdesign returns a data frame with additive polynomial coding</i>
----------	------------------------------------------------------------------------------------------

---

## Description

apdesign: AP coding apdesign returns a data frame with additive polynomial coding

## Usage

```
apdesign(data, id_var, time_var, center_time, cycle_var, center_cycle,
        max_degree = c(1, 1))
```

## Arguments

data	A data frame.
id_var	A character that indicates the subject identifier in data.
time_var	A character that indicates the within-cycle time indicator in data.
center_time	A numeric specifying the within-cycle time to center on.
cycle_var	A character that indicates the cycle indicator in data.
center_cycle	A numeric specifying the cycle to center on.
max_degree	A vector of numerics specifying the highest degree for each polynomial.

## Value

Output will be a data frame.

## Examples

```
id <- c(rep(1,10), rep(2, 10))
y <- c(c(10, 15, 21, 20, 23, 25, 27, 25, 28, 29),
      c(12, 16, 18, 20, 20, 22, 28, 27, 29, 31))
time <- c(c(0.2, 0.5, 0.7), c(0.3, 0.6, 0.75, 0.89), c(0.1, 0.3, 0.8),
         c(0.3, 0.6, 0.7, 0.85), c(0.2, 0.7, 0.79), c(0.2, 0.5, 0.75))
cycle <- c(rep(1, 3), rep(2, 4), rep(3, 3), rep(1, 4), rep(2, 3), rep(3, 3))
df <- data.frame(id, y, time, cycle)
apdesign(data = df, id = "id", time_var = "time", cycle_var = "cycle",
        center_cycle = 1, center_time = 0, max_degree = c(2,1))
```

---

apdesign_i	<i>apdesign_i: AP coding for a single subject</i>
------------	---------------------------------------------------

---

## Description

apdesign\_i: AP coding for a single subject

## Usage

```
apdesign_i(data, cycle_var, center_cycle, time_var, center_time,  
          max_degree = c(1, 1), matrices = FALSE)
```

## Arguments

data	A data frame.
cycle_var	A character that indicates the cycle indicator in data.
center_cycle	A numeric specifying the cycle to center on.
time_var	A character that indicates the within-cycle time indicator in data.
center_time	A numeric specifying the within-cycle time to center on.
max_degree	A vector of numerics specifying the highest degree for each polynomial.
matrices	If TRUE, will print the AP, D1 and D2 matrices.

## Value

Output will be a matrix.

## Examples

```
y <- c(10, 15, 21, 20, 23, 25, 27, 25, 28, 29)  
time <- c(c(0.2, 0.5, 0.7), c(0.3, 0.6, 0.75, 0.89), c(0.1, 0.3, 0.8))  
cycle <- c(rep(1, 3), rep(2, 4), rep(3, 3))  
df <- data.frame(y, time, cycle)  
apdesign_i(data = df, time_var = "time", cycle_var = "cycle",  
          center_cycle = 1, center_time = 0, max_degree = c(2,1))
```

---

 indiv\_change

*Repeated measures data over three years*


---

### Description

A dataset of longitudinal responses of 36 study participants over a three years span.

### Usage

indv\_change

### Format

A data frame with 234 observations and 5 variables:

**id** subject identifier

**cycle** cycle number

**cycle\_time** time since the start of the cycle, in weeks

**start\_time** time since the start of the study, in weeks

**response** outcome measure

---

 mean\_change

*Data for a single time trend over three years*


---

### Description

A dataset of mean responses of study participants over a three years span.

### Usage

mean\_change

### Format

A data frame with 9 observations and 4 variables:

**cycle** cycle number

**cycle\_time** time since the start of the cycle, in weeks

**start\_time** time since the start of the study, in weeks

**response** outcome measure

# Index

## \* datasets

indv\_change, 4

mean\_change, 4

apdesign, 2

apdesign\_i, 3

indv\_change, 4

mean\_change, 4