

# Package ‘fTrading’

October 13, 2022

**Title** Rmetrics - Trading and Rebalancing Financial Instruments

**Date** 2017-11-12

**Version** 3042.79

**Author** Diethelm Wuertz [aut],  
Tobias Setz [cre],  
Yohan Chalabi [ctb]

**Maintainer** Tobias Setz <tobias.setz@live.com>

**Description** A collection of functions for trading and rebalancing financial instruments. It implements various technical indicators to analyse time series such as moving averages or stochastic oscillators.

**Depends** R (>= 2.15.1), timeDate, timeSeries, fBasics

**Imports** graphics, stats

**Suggests** methods, RUnit, tcltk

**LazyData** yes

**License** GPL (>= 2)

**URL** <http://www.rmetrics.org>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2017-11-15 22:37:38 UTC

## R topics documented:

|                             |   |
|-----------------------------|---|
| fTrading-package . . . . .  | 2 |
| BenchmarkAnalysis . . . . . | 3 |
| RollingAnalysis . . . . .   | 6 |
| TechnicalAnalysis . . . . . | 7 |

**Index**

11

## Description

The Rmetrics "fTrading" package is a collection of functions for trading and rebalancing financial instruments.

## Details

|             |                                                                 |
|-------------|-----------------------------------------------------------------|
| Package:    | fTrading                                                        |
| Type:       | Package                                                         |
| Version:    | R 3.0.1                                                         |
| Date:       | 2014                                                            |
| License:    | GPL Version 2 or later                                          |
| Copyright:  | (c) 1999-2014 Rmetrics Association                              |
| Repository: | R-FORGE                                                         |
| URL:        | <a href="https://www.rmetrics.org">https://www.rmetrics.org</a> |

## Content

### *Utility Functions:*

|                |                            |
|----------------|----------------------------|
| emaTA          | Exponential Moving Average |
| biasTA         | Bias Indicator             |
| medpriceTA     | Medium Price Indicator     |
| typicalpriceTA | Typical Price Indicator    |
| wcloseTA       | Weighted Close Indicator   |
| rocTA          | Rate of Change             |
| oscTA          | Oscillator Indicator       |

### *Oscillator Indicators:*

|        |                     |
|--------|---------------------|
| momTA  | Momentum Indicator  |
| macdTA | MACD Indicator      |
| cdsTA  | MACD Signal Line    |
| cdoTA  | MACD Oscillator     |
| vohlTA | High/Low Volatility |
| vorTA  | Volatility Ratio    |

  

|              |                        |
|--------------|------------------------|
| stochasticTA | Stochastics Oscillator |
|--------------|------------------------|

|       |                         |
|-------|-------------------------|
| fPkTA | Fast Percent K          |
| fPdTA | Fast Percent D          |
| spdTA | Slow Percent D          |
| apdTA | Averaged Percent D      |
| wprTA | William's Percent R     |
| rsiTA | Relative Strength Index |

*S-Plus Like Moving Averages:*

|      |                                       |
|------|---------------------------------------|
| SMA  | Simple Moving Average                 |
| EWMA | Exponentially Weighted Moving Average |

**About Rmetrics:**

The fTrading Rmetrics package is written for educational support in teaching "Computational Finance and Financial Engineering" and licensed under the GPL.

**Description**

A collection and description of utility and benchmark functions for the analysis of financial markets. The collection provides a set of functions for the computation of returns, for the display of price charts, and for benchmark measurements.

The functions are:

|               |                                       |
|---------------|---------------------------------------|
| ohlcPlot      | Plots open–high–low–close bar charts, |
| sharpeRatio   | Computes Sharpe Ratio,                |
| sterlingRatio | Computes Sterling Ratio,              |
| maxDrawDown   | Computes maximum drawdown.            |

**Usage**

```
ohlcPlot(x, xlim = NULL, ylim = NULL, xlab = "Time", ylab, col = par("col"),
bg = par("bg"), axes = TRUE, frame.plot = axes, ann = par("ann"),
main = NULL, date = c("calendar", "julian"), format = "%Y-%m-%d",
origin = "1899-12-30", ...)

sharpeRatio(x, r = 0, scale = sqrt(250))
sterlingRatio(x)

maxDrawDown(x)
```

## Arguments

date, format, origin  
     [ohlcPlot] -  
     date elements,  
     date, a string indicating the type of x axis annotation. Default is calendar dates.  
     format, a string indicating the format of the x axis annotation if date == "calendar".  
     For details see [format.POSIXct](#).  
     origin an R object specifying the origin of the Julian dates if date == "calendar".  
     Defaults to 1899-12-30 (Popular spreadsheet programs internally also use Julian  
     dates with this origin).  
  
 r  
     [sharpeRatio] -  
     the risk free rate. Default corresponds to using portfolio returns not in excess of  
     the riskless return.  
  
 scale  
     [sharpeRatio] -  
     a scale factor. Default corresponds to an annualization when working with daily  
     financial time series data.  
  
 x  
     a numeric vector of prices. For ohlcPlot a multivariate time series object of  
     class `mts` is required.  
  
 xlim, ylim, xlab, ylab, col, bg, axes, frame.plot, ann, main  
     [ohlcPlot] -  
     graphical arguments, see [plot](#), [plot.default](#) and [par](#).  
  
 ...  
     [ohlcPlot] -  
     further graphical arguments passed to [plot.window](#), [title](#), [axis](#), and [box](#).

## Details

### Open–High–Low–Close Chart:

Within an open–high–low–close bar chart, each bar represents price information for the time interval between the open and the close price. The left tick for each bar indicates the open price for the time interval. The right tick indicates the closing price for the time interval. The vertical length of the bar represents the price range for the time interval. The time scale of x must be in Julian dates (days since the origin).

[tseries:plotOHLC]

### Sharpe and Sterling Ratios:

The Sharpe ratio is defined as a portfolio's mean return in excess of the riskless return divided by the portfolio's standard deviation. In finance the Sharpe Ratio represents a measure of the portfolio's risk-adjusted (excess) return. The Sterling ratio is defined as a portfolio's overall return divided by the portfolio's maximum drawdown statistic. In finance the Sterling Ratio represents a measure of the portfolio's risk-adjusted return.

[tseries:sharpe]

### Maximum Drawdown:

The maximum drawdown or maximum loss statistic is defined as the maximum value drop after one of the peaks of  $x$ . For financial instruments the maximum drawdown represents the worst investment loss for a buy-and-hold strategy invested in  $x$ .

[tseries:maxdrawdown]

### Get Returns:

The function computes the return series given a financial security price series. The price series may be an object of class `numeric` or a time series object. This includes objects of classes "`ts`", "`its`" and/or "`timeSeries`".

### Value

`ohlcPlot`

creates an Open-High-Low-Close chart.

`sharpeRatio`

`sterlingRatio`

return the Sharpe or Sterling ratio, a numeric value.

`maxDrawDown`

returns a list containing the following three components: `maxDrawDown`, double representing the max drawdown or max loss statistic; `from`, the index (or vector of indices) where the maximum drawdown period starts; `to`, the index (or vector of indices) where the max drawdown period ends.

### Author(s)

Adrian Trapletti for the `ohlcPlot,*Ratio` and `maxDrawDown` functions,  
Diethelm Wuertz for the Rmetrics R-port.

### Examples

```
## ohlcPlot -
# Plot OHLC for SP500
# ohlcPlot(x, ylab = "price", main = instrument)

## sharpeRatio -
# Sharpe Ratio for DAX and FTSE:
data(EuStockMarkets)
dax = log(EuStockMarkets[, "DAX"])
ftse = log(EuStockMarkets[, "FTSE"])
# Ratios:
sharpeRatio(dax)
sharpeRatio(ftse)

## maxDrawDown -
data(EuStockMarkets)
dax = log(EuStockMarkets[, "DAX"])
mdd = maxDrawDown(dax)
mdd
# Plot DAX:
plot(dax)
```

```

grid()
segments(time(dax)[mdd$from], dax[mdd$from],
          time(dax)[mdd$to], dax[mdd$from])
segments(time(dax)[mdd$from], dax[mdd$to],
          time(dax)[mdd$to], dax[mdd$to])
mid = time(dax)[(mdd$from + mdd$to)/2]
arrows(mid, dax[mdd$from], mid, dax[mdd$to], col = 2)
title(main = "DAX: Max Drawdown")

```

**RollingAnalysis***Rolling Analysis***Description**

A collection and description of functions to perform a rolling analysis. A rolling analysis is often required in building trading models.

The functions are:

|                |                                      |
|----------------|--------------------------------------|
| <b>rollFun</b> | Rolling or moving sample statistics, |
| <b>rollVar</b> | Rolling or moving sample variance.   |

**Usage**

```
rollFun(x, n, trim = TRUE, na.rm = FALSE, FUN, ...)
```

```
rollVar(x, n = 9, trim = TRUE, unbiased = TRUE, na.rm = FALSE)
```

**Arguments**

|                 |                                                                                                                                                                         |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>FUN</b>      | the rolling function, arguments to this function can be passed through the ... argument.                                                                                |
| <b>n</b>        | an integer specifying the number of periods or terms to use in each rolling/moving sample.                                                                              |
| <b>na.rm</b>    | a logical flag: if TRUE, missing values in x will be removed before computation. The default is FALSE.                                                                  |
| <b>trim</b>     | a logical flag: if TRUE, the first n-1 missing values in the returned object will be removed; if FALSE, they will be saved in the returned object. The default is TRUE. |
| <b>unbiased</b> | a logical flag. If TRUE, the unbiased sample variance will be returned. The default is TRUE.                                                                            |
| <b>x</b>        | an univariate <code>timeSeries</code> object or a numeric vector.                                                                                                       |
| <b>...</b>      | additional arguments to be passed.                                                                                                                                      |

**Value**

The functions return a `timeSeries` object or a numeric vector, depending on the argument `x`.

`rollMax` returns the rolling sample maximum,  
`rollMin` returns the rolling sample minimum,  
`rollMean` returns the rolling sample mean, and  
`rollVar` returns the biased/unbiased rolling sample variance.

Note, that the function `rollFun` always returns a numeric vector, independent of the argument `x`.

If you like to operate for `x` with rectangular objects, you have to call the functions columnwise within a loop.

**Author(s)**

Diethelm Wuertz for the Rmetrics R-port.

**See Also**

[var](#).

**Examples**

```
## Rolling Analysis:
x = (1:10)^2
x
trim = c(TRUE, TRUE, FALSE, FALSE)
na.rm = c(TRUE, FALSE, TRUE, FALSE)
for (i in 1:4)
  rollFun(x, 5, trim[i], na.rm[i], FUN = min)
for (i in 1:4)
  rollFun(x, 5, trim[i], na.rm[i], FUN = max)
for (i in 1:4)
  rollVar(x, 5, trim[i], unbiased = TRUE, na.rm[i])
for (i in 1:4)
  rollVar(x, 5, trim[i], unbiased = FALSE, na.rm[i])
```

**Description**

A collection and description of functions for the technical analysis of stock markets. The collection provides a set of the most common technical indicators.

Utility Functions:

|                         |                             |
|-------------------------|-----------------------------|
| <code>emaTA</code>      | Exponential Moving Average, |
| <code>biasTA</code>     | Bias Indicator,             |
| <code>medpriceTA</code> | Medium Price Indicator,     |

|                             |                           |
|-----------------------------|---------------------------|
| <code>typicalpriceTA</code> | Typical Price Indicator,  |
| <code>wcloseTA</code>       | Weighted Close Indicator, |
| <code>rocTA</code>          | Rate of Change,           |
| <code>oscTA</code>          | Oscillator Indicator.     |

Oscillator Indicators:

|                     |                      |
|---------------------|----------------------|
| <code>momTA</code>  | Momentum Indicator,  |
| <code>macdTA</code> | MACD Indicator,      |
| <code>cdsTA</code>  | MACD Signal Line,    |
| <code>cdoTA</code>  | MACD Oscillator,     |
| <code>vohlTA</code> | High/Low Volatility, |
| <code>vorTA</code>  | Volatility Ratio.    |

|                           |                          |
|---------------------------|--------------------------|
| <code>stochasticTA</code> | Stochastics Oscillator,  |
| <code>fpkTA</code>        | Fast Percent K,          |
| <code>fpdTA</code>        | Fast Percent D,          |
| <code>spdTA</code>        | Slow Percent D,          |
| <code>apdTA</code>        | Averaged Percent D,      |
| <code>wprTA</code>        | William's Percent R,     |
| <code>rsiTA</code>        | Relative Strength Index. |

S-Plus Like Moving Averages:

|                   |                                        |
|-------------------|----------------------------------------|
| <code>SMA</code>  | Simple Moving Average,                 |
| <code>EWMA</code> | Exponentially Weighted Moving Average. |

## Usage

```

emaTA(x, lambda, startup = 0)
biasTA(x, lag)
medpriceTA(high, low)
typicalpriceTA(high, low, close)
wcloseTA(high, low, close)
rocTA(x, lag)
oscTA(x, lag1 = 25, lag2 = 65)

momTA(x, lag)
macdTA(x, lag1, lag2)
cdsTA(x, lag1 = 12, lag2 = 26, lag3 = 9)
cdoTA(x, lag1 = 12, lag2 = 26, lag3 = 9)
vohlTA(high, low)
vorTA(high, low)

stochasticTA(close, high, low, lag1 = 5, lag2 = 3, lag3 = 5,
            type = c("fast", "slow"))
fpkTA(close, high, low, lag)

```

```

fpdTA(close, high, low, lag1, lag2)
spdTA(close, high, low, lag1, lag2, lag3)
apdTA(close, high, low, lag1, lag2, lag3, lag4)
wprTA(close, high, low, lag)
rsiTIA(close, lag)

SMA(x, n = 5)
EWMA(x, lambda, startup = 0)

```

## Arguments

|                             |                                                                                                                                                                                                                         |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| lag, lag1, lag2, lag3, lag4 |                                                                                                                                                                                                                         |
|                             | integer values, time lags.                                                                                                                                                                                              |
| n                           | [SMA] -                                                                                                                                                                                                                 |
|                             | an integer value, time lag.                                                                                                                                                                                             |
| lambda                      | [emaTA][EWMA] -                                                                                                                                                                                                         |
|                             | a numeric value between zero and one giving the decay length of the exponential moving average. If an integer value greater than one is given, lambda is used as a lag of "n" periods to calculate the decay parameter. |
| startup                     | [emaTA][EWMA] -                                                                                                                                                                                                         |
|                             | an integer value, the startup position of the exponential moving average, by default 0.                                                                                                                                 |
| type                        | [stochasticTA] -                                                                                                                                                                                                        |
|                             | a character string, either "fast" or "slow" characterizing the type of the percent K and percent D indicator. By default type="fast"                                                                                    |
| x, high, low, close         |                                                                                                                                                                                                                         |
|                             | a numeric vector of prices, either opening, closing, or high and low values. For ohlcPlot a multivariate time series object of class mts.                                                                               |

## Value

\*TA

The technical Indicators return the following numeric vectors (or matrix):

emaTA returns the Exponential Moving Average, EMA  
 biasTA returns the EMA-Bias,  
 medpriceTA returns the Medium Price,  
 typicalpriceTA returns the Typical Price,  
 wcloseTA returns the Weighted Closing Price,  
 rocTA returns the Rate of Change Indicator,  
 oscTA returns the EMA Oscillator Indicator,  
 momTA returns the Momentum Oscillator,

macdTA returns the MACD Oscillator,  
 cdsTA returns the MACD Signal Line,  
 cdo returns the MACD Oscillator,  
 vohlTA returns the High/Low Volatility Oscillator,

`vorTA` returns Volatility Ratio Oscillator,

`stochasticTA` returns a 2-column matrix with percent K and D Indicator,  
`fpkTA` returns the Fast Percent-K Stochastics Indicator,  
`fpdTA` returns the Fast Percent-D Stochastics Indicator,  
`spdTA` returns the Slow Percent-D Stochastics Indicator,  
`apdTA` returns the Averaged Percent-D Stochastics Indicator,  
`wprTA` returns the Williams Percent-R Stochastics Indicator,  
`rsiTA` returns the Relative Strength Index Stochastics Indicator.

### Author(s)

Diethelm Wuertz for the Rmetrics R-port.

### Examples

```
## data -
# Load MSFT Data:
x = MSFT
colnames(x)
x = x[, "Close"]
head(x)

## emaTA -
# Exponential Moving Average:
y = emaTA(x, lambda = 9)
seriesPlot(x)
lines(y, col = "red")
```

# Index

- \* **math**
  - BenchmarkAnalysis, 3
  - RollingAnalysis, 6
  - TechnicalAnalysis, 7
- \* **package**
  - fTrading-package, 2
- acceltaTA (TechnicalAnalysis), 7
- adiTA (TechnicalAnalysis), 7
- adoscillatorTA (TechnicalAnalysis), 7
- apdTA (TechnicalAnalysis), 7
- axis, 4
- BenchmarkAnalysis, 3
- biasTA (TechnicalAnalysis), 7
- bollingerTA (TechnicalAnalysis), 7
- box, 4
- cdoTA (TechnicalAnalysis), 7
- cdsTA (TechnicalAnalysis), 7
- chaikinoTA (TechnicalAnalysis), 7
- chaikinvTA (TechnicalAnalysis), 7
- emaTA (TechnicalAnalysis), 7
- EWMA (TechnicalAnalysis), 7
- format.POSIXct, 4
- fpdTA (TechnicalAnalysis), 7
- fpkTA (TechnicalAnalysis), 7
- fTrading (fTrading-package), 2
- fTrading-package, 2
- garmanklassTA (TechnicalAnalysis), 7
- macdTA (TechnicalAnalysis), 7
- maxDrawDown (BenchmarkAnalysis), 3
- medpriceTA (TechnicalAnalysis), 7
- momTA (TechnicalAnalysis), 7
- nviTA (TechnicalAnalysis), 7
- obvTA (TechnicalAnalysis), 7
- ohlcPlot (BenchmarkAnalysis), 3
- oscTA (TechnicalAnalysis), 7
- par, 4
- plot, 4
- plot.default, 4
- plot.window, 4
- pviTA (TechnicalAnalysis), 7
- pvtrendTA (TechnicalAnalysis), 7
- rocTA (TechnicalAnalysis), 7
- rollFun (RollingAnalysis), 6
- RollingAnalysis, 6
- rollVar (RollingAnalysis), 6
- rsiTA (TechnicalAnalysis), 7
- sharpeRatio (BenchmarkAnalysis), 3
- SMA (TechnicalAnalysis), 7
- spdTA (TechnicalAnalysis), 7
- sterlingRatio (BenchmarkAnalysis), 3
- stochasticTA (TechnicalAnalysis), 7
- TechnicalAnalysis, 7
- title, 4
- typicalpriceTA (TechnicalAnalysis), 7
- var, 7
- vohlTA (TechnicalAnalysis), 7
- vorTA (TechnicalAnalysis), 7
- wcloseTA (TechnicalAnalysis), 7
- williamsadTA (TechnicalAnalysis), 7
- williamsrTA (TechnicalAnalysis), 7
- wprTA (TechnicalAnalysis), 7