

Package ‘gamCopula’

April 2, 2025

Type Package

Title Generalized Additive Models for Bivariate Conditional Dependence Structures and Vine Copulas

Version 0.0-8

Encoding UTF-8

Date 2025-04-02

Maintainer Thibault Vatter <thibault.vatter@gmail.com>

Depends R (>= 3.1.0)

Imports graphics, stats, utils, VineCopula (>= 2.0.0), mgcv, MASS, gsl, numDeriv, methods, copula, igraph (>= 1.0.0), parallel, foreach, doParallel

Description Implementation of various inference and simulation tools to apply generalized additive models to bivariate dependence structures and non-simplified vine copulas.

License GPL-3

LazyLoad yes

BugReports <https://github.com/tvatter/gamCopula/issues>

URL <https://github.com/tvatter/gamCopula>

RoxygenNote 7.3.2

NeedsCompilation no

Author Thomas Nagler [aut],
Thibault Vatter [aut, cre]

Repository CRAN

Date/Publication 2025-04-02 12:30:07 UTC

Contents

gamCopula-package	2
AIC.gamBiCop	8

BIC.gamBiCop	9
BiCopEta2Par	10
BiCopPar2Eta	11
condBiCopSim	12
dim.gamVine	14
EDF	15
formula.gamBiCop	15
gamBiCop	16
gamBiCop-class	16
gamBiCopCDF	17
gamBiCopFit	19
gamBiCopPDF	23
gamBiCopPredict	25
gamBiCopSelect	27
gamBiCopSimulate	30
gamVine	32
gamVine-class	33
gamVineCopSelect	33
gamVineFamily	38
gamVineNormalize	38
gamVinePDF	39
gamVineSeqFit	42
gamVineSimulate	46
gamVineStructureSelect	48
logLik.gamBiCop	51
nobs.gamBiCop	52
plot.gamBiCop	52
plot.gamVine	53
RVM2GVC	53
summary.gamBiCop	54
summary.gamVine	55

Index	56
--------------	-----------

gamCopula-package

gamCopula: Generalized Additive Models for Bivariate Conditional Dependence Structures and Vine Copulas

Description

This package implements inference and simulation tools to apply generalized additive models to bivariate dependence structures and vine copulas.

Details

More details can be found in Vatter and Chavez-Demoulin (2015) and Vatter and Nagler (2016).

```
Package: gamCopula
Type: Package
Version: 0.0-8
Date: 2025-04-02
License: GPL-3
```

Author(s)

Thibault Vatter and Thomas Nagler

Maintainer: Thibault Vatter <thibault.vatter@gmail.com>

References

- Aas, K., C. Czado, A. Frigessi, and H. Bakken (2009) Pair-copula constructions of multiple dependence. *Insurance: Mathematics and Economics*, 44(2), 182–198.
- Brechmann, E. C., C. Czado, and K. Aas (2012) Truncated regular vines in high dimensions with applications to financial data. *Canadian Journal of Statistics*, 40(1), 68–85.
- Dissmann, J. F., E. C. Brechmann, C. Czado, and D. Kurowicka (2013) Selecting and estimating regular vine copulae and application to financial returns. *Computational Statistics & Data Analysis*, 59(1), 52–69.
- Vatter, T. and V. Chavez-Demoulin (2015) Generalized Additive Models for Conditional Dependence Structures. *Journal of Multivariate Analysis*, 141, 147–167.
- Vatter, T. and T. Nagler (2016) Generalized additive models for non-simplified pair-copula constructions. <https://arxiv.org/abs/1608.01593>
- Wood, S. N. (2004) Stable and efficient multiple smoothing parameter estimation for generalized additive models. *Journal of the American Statistical Association*, 99, 673–686.
- Wood, S. N. (2006) Generalized Additive Models: an introduction with R. Chapman and Hall/CRC.

See Also

The present package heavily relies on the **mgcv** and **VineCopula** packages, as it basically extends and mixes both of them.

Examples

```
##### A gamBiCop example
require(copula)
require(mgcv)
set.seed(0)

## Simulation parameters (sample size, correlation between covariates,
## Gaussian copula family)
n <- 5e2
rho <- 0.5
fam <- 1

### A calibration surface depending on three variables
```

```

eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)
### Display the calibration surface
par(mfrow = c(1, 3), pty = "s", mar = c(1, 1, 4, 1))
u <- seq(0, 1, length.out = 100)
sel <- matrix(c(1, 1, 2, 2, 3, 3), ncol = 2)
jet.colors <- colorRamp(c(
  "#00007F", "blue", "#007FFF", "cyan", "#7FFF7F",
  "yellow", "#FF7F00", "red", "#7F0000"
))
jet <- function(x) {
  rgb(jet.colors(exp(x / 3) / (1 + exp(x / 3))),
    maxColorValue = 255
  )
}
for (k in 1:3) {
  tmp <- outer(u, u, function(x, y) {
    eta0 + calib.surf[[sel[k, 1]]](x) + calib.surf[[sel[k, 2]]](y)
  })
  persp(u, u, tmp,
    border = NA, theta = 60, phi = 30, zlab = "",
    col = matrix(jet(tmp), nrow = 100),
    xlab = paste("X", sel[k, 1], sep = ""),
    ylab = paste("X", sel[k, 2], sep = ""),
    main = paste("eta0+f", sel[k, 1],
      "(X", sel[k, 1], ") +f", sel[k, 2],
      "(X", sel[k, 2], ")",
      sep = ""
    )
  )
}
### 3-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 3),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)

```

```

X <- rMvdc(n, covariates.distr)
### U in [0,1]x[0,1] with copula parameter depending on X
U <- condBiCopSim(fam, function(x1, x2, x3) {
  eta0 + sum(mapply(function(f, x) {
    f(x)
  }, calib.surf, c(x1, x2, x3)))
}, X[, 1:3], par2 = 6, return.par = TRUE)
### Merge U and X
data <- data.frame(U$data, X)
names(data) <- c(paste("u", 1:2, sep = ""), paste("x", 1:3, sep = ""))
### Display the data
dev.off()
plot(data[, "u1"], data[, "u2"], xlab = "U1", ylab = "U2")
### Model fit with a basis size (arguably) too small
### and unpenalized cubic spines
pen <- FALSE
basis0 <- c(3, 4, 4)
formula <- ~ s(x1, k = basis0[1], bs = "cr", fx = !pen) +
  s(x2, k = basis0[2], bs = "cr", fx = !pen) +
  s(x3, k = basis0[3], bs = "cr", fx = !pen)
system.time(fit0 <- gamBiCopFit(data, formula, fam))
### Model fit with a better basis size and penalized cubic splines (via min GCV)
pen <- TRUE
basis1 <- c(3, 10, 10)
formula <- ~ s(x1, k = basis1[1], bs = "cr", fx = !pen) +
  s(x2, k = basis1[2], bs = "cr", fx = !pen) +
  s(x3, k = basis1[3], bs = "cr", fx = !pen)
system.time(fit1 <- gamBiCopFit(data, formula, fam))
### Extract the gamBiCop objects and show various methods
(res <- sapply(list(fit0, fit1), function(fit) {
  fit$res
}))
metds <- list("logLik" = logLik, "AIC" = AIC, "BIC" = BIC, "EDF" = EDF)
lapply(res, function(x) sapply(metds, function(f) f(x)))
### Comparison between fitted, true smooth and spline approximation for each
### true smooth function for the two basis sizes
fitted <- lapply(res, function(x) {
  gamBiCopPredict(x, data.frame(x1 = u, x2 = u, x3 = u),
    type = "terms"
  )$calib
})
true <- vector("list", 3)
for (i in 1:3) {
  y <- eta0 + calib.surf[[i]](u)
  true[[i]]$true <- y - eta0
  temp <- gam(y ~ s(u, k = basis0[i], bs = "cr", fx = TRUE))
  true[[i]]$approx <- predict.gam(temp, type = "terms")
  temp <- gam(y ~ s(u, k = basis1[i], bs = "cr", fx = FALSE))
  true[[i]]$approx2 <- predict.gam(temp, type = "terms")
}
### Display results
par(mfrow = c(1, 3), pty = "s")
yy <- range(true, fitted)

```

```

yy[1] <- yy[1] * 1.5
for (k in 1:3) {
  plot(u, true[[k]]$true,
    type = "l", ylim = yy,
    xlab = paste("Covariate", k), ylab = paste("Smooth", k)
  )
  lines(u, true[[k]]$approx, col = "red", lty = 2)
  lines(u, fitted[[1]][, k], col = "red")
  lines(u, fitted[[2]][, k], col = "green")
  lines(u, true[[k]]$approx2, col = "green", lty = 2)
  legend("bottomleft",
    cex = 0.6, lty = c(1, 1, 2, 1, 2),
    c("True", "Fitted", "Appox 1", "Fitted 2", "Approx 2"),
    col = c("black", "red", "red", "green", "green")
  )
}
##### A gamVine example
set.seed(0)
### Simulation parameters
## Sample size
n <- 1e3
## Copula families
familyset <- c(1:2, 301:304, 401:404)
## Define a 4-dimensional R-vine tree structure matrix
d <- 4
Matrix <- c(2, 3, 4, 1, 0, 3, 4, 1, 0, 0, 4, 1, 0, 0, 0, 1)
Matrix <- matrix(Matrix, d, d)
nnames <- paste("X", 1:d, sep = "")
### A function factory
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)
### Create the model
## Define gam-vine model list
count <- 1
model <- vector(mode = "list", length = d * (d - 1) / 2)
sel <- seq(d, d^2 - d, by = d)

```

```

## First tree
for (i in 1:(d - 1)) {
  # Select a copula family
  family <- sample(familyset, 1)
  model[[count]]$family <- family
  # Use the canonical link and a randomly generated parameter
  if (is.element(family, c(1, 2))) {
    model[[count]]$par <- tanh(rnorm(1) / 2)
    if (family == 2) {
      model[[count]]$par2 <- 2 + exp(rnorm(1))
    }
  } else {
    if (is.element(family, c(401:404))) {
      rr <- rnorm(1)
      model[[count]]$par <- sign(rr) * (1 + abs(rr))
    } else {
      model[[count]]$par <- rnorm(1)
    }
    model[[count]]$par2 <- 0
  }
  count <- count + 1
}
## A dummy dataset
data <- data.frame(u1 = runif(1e2), u2 = runif(1e2), matrix(runif(1e2 * d), 1e2, d))
## Trees 2 to (d-1)
for (j in 2:(d - 1)) {
  for (i in 1:(d - j)) {
    # Select a copula family
    family <- sample(familyset, 1)
    # Select the conditiong set and create a model formula
    cond <- nnames[sort(Matrix[(d - j + 2):d, i])]
    tmpform <- paste("~", paste(paste("s(", cond, ", k=10, bs='cr')",
      sep = ""))
    ), collapse = " + ")
    l <- length(cond)
    temp <- sample(3, l, replace = TRUE)
    # Spline approximation of the true function
    m <- 1e2
    x <- matrix(seq(0, 1, length.out = m), nrow = m, ncol = 1)
    if (l != 1) {
      tmp.fct <- paste("function(x){eta0+", 
        paste(sapply(1:l, function(x) {
          paste("calib.surf[[" , temp[x], "]](x[[" , x, "]])",
          sep = ""
        })
      )), collapse = "+"), "}",
      sep = ""
    }
    tmp.fct <- eval(parse(text = tmp.fct))
    x <- eval(parse(text = paste0("expand.grid(",
      paste0(rep("x", 1), collapse = ","), ","),
      collapse = ""))
  )))
}
```

```

y <- apply(x, 1, tmp.fct)
} else {
  tmp.fct <- function(x) eta0 + calib.surf[[temp]](x)
  colnames(x) <- cond
  y <- tmp.fct(x)
}
# Estimate the gam model
form <- as.formula(paste0("y", tmpform))
dd <- data.frame(y, x)
names(dd) <- c("y", cond)
b <- gam(form, data = dd)
# plot(x[,1],(y-fitted(b))/y)
# Create a dummy gamBiCop object
tmp <- gamBiCopFit(data = data, formula = form, family = 1, n.iters = 1)$res
# Update the copula family and the model coefficients
attr(tmp, "model")$coefficients <- coefficients(b)
attr(tmp, "model")$smooth <- b$smooth
attr(tmp, "family") <- family
if (family == 2) {
  attr(tmp, "par2") <- 2 + exp(rnorm(1))
}
model[[count]] <- tmp
count <- count + 1
}
}
## Create the gamVineCopula object
GVC <- gamVine(Matrix = Matrix, model = model, names = nnames)
print(GVC)
#
## Not run:
### Simulate and fit the model
sim <- gamVineSimulate(n, GVC)
fitGVC <- gamVineSeqFit(sim, GVC, verbose = TRUE)
fitGVC2 <- gamVineCopSelect(sim, Matrix, verbose = TRUE)
### Plot the results
par(mfrow = c(3, 4))
plot(GVC, ylim = c(-2.5, 2.5))
plot(fitGVC, ylim = c(-2.5, 2.5))
plot(fitGVC2, ylim = c(-2.5, 2.5))

## End(Not run)

```

Description

Function calculating Akaike's 'An Information Criterion' (AIC) for an object of the class `gamBiCop` (note that the models are usually fitted by penalized likelihood maximization).

Usage

```
## S4 method for signature 'gamBiCop'  
AIC(object, ..., k = 2)
```

Arguments

- | | |
|--------|--|
| object | An object of the class gamBiCop . |
| ... | un-used in this class |
| k | numeric, the penalty per parameter to be used; the default k = 2 is the classical AIC. |

Value

A numeric value with the corresponding AIC.

See Also

[AIC](#) and [BIC](#).

BIC.gamBiCop

Schwarz's Bayesian Information Criterion for a gamBiCop Object

Description

Function calculating the Schwarz's Bayesian Information Criterion (BIC) for an object of the class [gamBiCop](#) (note that the models are usually fitted by penalized likelihood maximization).

Usage

```
## S4 method for signature 'gamBiCop'  
BIC(object, ...)
```

Arguments

- | | |
|--------|---|
| object | An object of the class gamBiCop . |
| ... | un-used in this class |

Value

A numeric value with the corresponding BIC.

See Also

[AIC](#) and [BIC](#).

BiCopEta2Par*Copula Parameter of a Bivariate Copula for a Given Value of the Calibration Function*

Description

Computes the (first) copula parameter of a bivariate copula for a given value of the calibration function (eta).

Usage

```
BiCopEta2Par(family, eta)
```

Arguments

family	A copula family: 1 Gaussian, 2 Student t, 301 Double Clayton type I (standard and rotated 90 degrees), 302 Double Clayton type II (standard and rotated 270 degrees), 303 Double Clayton type III (survival and rotated 90 degrees), 304 Double Clayton type IV (survival and rotated 270 degrees), 401 Double Gumbel type I (standard and rotated 90 degrees), 402 Double Gumbel type II (standard and rotated 270 degrees), 403 Double Gumbel type III (survival and rotated 90 degrees), 404 Double Gumbel type IV (survival and rotated 270 degrees).
eta	The calibration function.

Value

The value of the first copula parameter, depending on the copula parameter and family as:

- 1 Gaussian, $f(x) = \tanh(x/2)$
- 2 Student t, $f(x) = \tanh(x/2)$
- 301 Double Clayton type I (standard and rotated 90 degrees), $f(x) = x$
- 302 Double Clayton type II (standard and rotated 270 degrees), $f(x) = x$
- 303 Double Clayton type III (survival and rotated 90 degrees), $f(x) = x$
- 304 Double Clayton type IV (survival and rotated 270 degrees), $f(x) = x$
- 401 Double Gumbel type I (standard and rotated 90 degrees), $f(x) = x*(1+abs(x))/abs(x)$
- 402 Double Gumbel type II (standard and rotated 270 degrees), $f(x) = x*(1+abs(x))/abs(x)$
- 403 Double Gumbel type III (survival and rotated 90 degrees), $f(x) = x*(1+abs(x))/abs(x)$
- 404 Double Gumbel type IV (survival and rotated 270 degrees) $f(x) = x*(1+abs(x))/abs(x)$.

See Also

[BiCopPar2Eta](#), [BiCopPar2Tau](#), and [BiCopTau2Par](#) from the **VineCopula** package.

BiCopPar2Eta	<i>Calibration Function of a Bivariate Copula for a Given Parameter's Value</i>
--------------	---

Description

Computes the calibration function (eta) of a bivariate copula for a given value of the (first) copula parameter.

Usage

```
BiCopPar2Eta(family, par)
```

Arguments

family	A copula family: 1 Gaussian, 2 Student t, 301 Double Clayton type I (standard and rotated 90 degrees), 302 Double Clayton type II (standard and rotated 270 degrees), 303 Double Clayton type III (survival and rotated 90 degrees), 304 Double Clayton type IV (survival and rotated 270 degrees), 401 Double Gumbel type I (standard and rotated 90 degrees), 402 Double Gumbel type II (standard and rotated 270 degrees), 403 Double Gumbel type III (survival and rotated 90 degrees), 404 Double Gumbel type IV (survival and rotated 270 degrees).
par	The (first) copula parameter

Value

The value of the calibration function, depending on the copula parameter and family as:

- 1 Gaussian, $f(x) = 2 * \text{atanh}(x)$
- 2 Student t, $f(x) = 2 * \text{atanh}(x)$
- 301 Double Clayton type I (standard and rotated 90 degrees), $f(x) = x$
- 302 Double Clayton type II (standard and rotated 270 degrees), $f(x) = x$
- 303 Double Clayton type III (survival and rotated 90 degrees), $f(x) = x$
- 304 Double Clayton type IV (survival and rotated 270 degrees), $f(x) = x$
- 401 Double Gumbel type I (standard and rotated 90 degrees), $f(x) = x * (1 - 1 / \text{abs}(x))$
- 402 Double Gumbel type II (standard and rotated 270 degrees), $f(x) = x * (1 - 1 / \text{abs}(x))$
- 403 Double Gumbel type III (survival and rotated 90 degrees), $f(x) = x * (1 - 1 / \text{abs}(x))$
- 404 Double Gumbel type IV (survival and rotated 270 degrees) $f(x) = x * (1 - 1 / \text{abs}(x))$.

See Also

[BiCopEta2Par](#), [BiCopPar2Tau](#), and [BiCopTau2Par](#) from the **VineCopula** package.

condBiCopSim*Simulation from a Conditional Bivariate Copula*

Description

Simulates from a conditional bivariate copula, where each copula parameter takes a different value, depending on the calibration function and covariates.

Usage

```
condBiCopSim(family, calib.fnc, X, par2 = 0, return.par = TRUE, tau = TRUE)
```

Arguments

<code>family</code>	family A copula family: 1 Gaussian, 2 Student t, 3 Clayton, 4 Gumbel, 5 Frank, 13 Survival Clayton, 14 Survival Gumbel, 23 Rotated (90 degrees) Clayton, 24 Rotated (90 degrees) Gumbel, 33 Rotated (270 degrees) Clayton and 34 Rotated (270 degrees) Gumbel.
<code>calib.fnc</code>	A calibration function.
<code>X</code>	A vector (if <code>calib.fnc</code> takes a single argument) or matrix (if <code>calib.fnc</code> takes multiple arguments) of covariates values.
<code>par2</code>	The second copula parameter (for the Student t), default <code>par2 = 0</code> .
<code>return.par</code>	Should the parameter (and calibration function) be returned as well (default <code>return.par = TRUE</code>)?
<code>tau</code>	Should the calibration function (and the model) be specified for the copula parameter or Kendall's tau (default <code>tau = TRUE</code>)?

Value

If `return.par = TRUE`, then the function returns a list with:

- `data`, a matrix with two columns containing the simulated data,
- `par`, a vector containing the values of the copula parameter,
- and `eta`, a vector containing the values of the calibration function.

If `return.par = FALSE`, then the function simply returns `data`, a matrix with two columns containing the simulated data.

See Also

[gamBiCopFit](#) and [gamBiCopSimulate](#).

Examples

```

require(copula)
set.seed(0)

## Simulation parameters (sample size, correlation between covariates,
## Gaussian copula family)
n <- 2e2
rho <- 0.5
fam <- 1

## A calibration surface depending on three variables
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)

## Display the calibration surface
par(mfrow = c(1, 3), pty = "s", mar = c(1, 1, 4, 1))
u <- seq(0, 1, length.out = 100)
sel <- matrix(c(1, 1, 2, 2, 3, 3), ncol = 2)
jet.colors <- colorRamp(c(
  "#00007F", "blue", "#007FFF", "cyan", "#7FFF7F",
  "yellow", "#FF7F00", "red", "#7F0000"
))
jet <- function(x) rgb(jet.colors(exp(x / 3) / (1 + exp(x / 3))), maxColorValue = 255
)
for (k in 1:3) {
  tmp <- outer(u, u, function(x, y)
    eta0 + calib.surf[[sel[k, 1]]](x) + calib.surf[[sel[k, 2]]](y))
  persp(u, u, tmp,
    border = NA, theta = 60, phi = 30, zlab = "",
    col = matrix(jet(tmp), nrow = 100),
    xlab = paste("X", sel[k, 1], sep = ""),
    ylab = paste("X", sel[k, 2], sep = ""),
    main = paste("eta0+f", sel[k, 1],

```

```

    "(X", sel[k, 1], ") +f", sel[k, 2],
    "(X", sel[k, 2], ")",
    sep = ""
  )
)
}

## 3-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 3),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)
X <- rMvdc(n, covariates.distr)

## U in [0,1]x[0,1] with copula parameter depending on X
U <- condBiCopSim(fam, function(x1, x2, x3) {
  eta0 + sum(mapply(function(f, x)
    f(x), calib.surf, c(x1, x2, x3)))
}, X[, 1:3], par2 = 6, return.par = TRUE)

## Merge U and X
data <- data.frame(U$data, X)
names(data) <- c(paste("u", 1:2, sep = ""), paste("x", 1:3, sep = ""))

## Display the data
dev.off()
plot(data[, "u1"], data[, "u2"], xlab = "U1", ylab = "U2")

```

dim.gamVine*Dimension of an Object of the Class **gamVine*****Description**

Retrieve the dimension of an object of the class **gamVine**.

Usage

```
## S4 method for signature 'gamVine'
dim(x)
```

Arguments

x An object of the class **gamVine**.

Value

Dimension of the **gamVine** object.

See Also

gamVine.

EDF*Equivalent Degrees of Freedom for an Object of the Class gamBiCop*

Description

Function calculating the Equivalent Degrees of Freedom (EDF) for a `gamBiCop` object. It basically sums the edf of the `gamObject` for each smooth component.

Usage

```
EDF(object)
```

Arguments

`object` An object of the class `gamBiCop`.

Value

Estimated degrees of freedom for each smooth component.

formula.gamBiCop*Model Formula of the gamBiCop Object*

Description

Extracts the `gam` formula from an object of the class `gamBiCop`. This function is a wrapper to `formula.gam` from the `mgcv` package.

Usage

```
## S4 method for signature 'gamBiCop'  
formula(x, ...)
```

Arguments

`x` An object of the class `gamBiCop`.
`...` un-used in this class

See Also

`formula.gam` function from the `mgcv` package.

gamBiCop*Construction of a gamBiCop Class Object***Description**

Constructs an object of the class [gamBiCop](#).

Usage

```
gamBiCop(family, model, par2 = 0, tau = TRUE)
```

Arguments

<code>family</code>	A copula family: 1 Gaussian, 2 Student t, 5 Frank, 301 Double Clayton type I (standard and rotated 90 degrees), 302 Double Clayton type II (standard and rotated 270 degrees), 303 Double Clayton type III (survival and rotated 90 degrees), 304 Double Clayton type IV (survival and rotated 270 degrees), 401 Double Gumbel type I (standard and rotated 90 degrees), 402 Double Gumbel type II (standard and rotated 270 degrees), 403 Double Gumbel type III (survival and rotated 90 degrees), 404 Double Gumbel type IV (survival and rotated 270 degrees).
<code>model</code>	A gamObject as return by the gam function from the mgcv package.
<code>par2</code>	Second parameter for the Student t-copula.
<code>tau</code>	FALSE for a calibration function specified for the Copula parameter or TRUE (default) for a calibration function specified for Kendall's tau.

Value

An object of the class [gamBiCop](#).

See Also

[gamBiCop](#), [gamBiCopFit](#), [gamBiCopPredict](#) and [gamBiCopSimulate](#).

gamBiCop-class*The gamBiCop Class***Description**

`gamBiCop` is an S4 class to store a Generalized Additive Model for bivariate copula a parameter or Kendall's tau. Objects can be created by calls of the form `new("gamBiCop", ...)`, or by function [gamBiCop](#).

Slots

family A copula family: 1 Gaussian, 2 Student t, 5 Frank, 301 Double Clayton type I (standard and rotated 90 degrees), 302 Double Clayton type II (standard and rotated 270 degrees), 303 Double Clayton type III (survival and rotated 90 degrees), 304 Double Clayton type IV (survival and rotated 270 degrees), 401 Double Gumbel type I (standard and rotated 90 degrees), 402 Double Gumbel type II (standard and rotated 270 degrees), 403 Double Gumbel type III (survival and rotated 90 degrees), 404 Double Gumbel type IV (survival and rotated 270 degrees).

model A `gamObject` as return by the `gam` function from the `mgcv` package.

par2 Second parameter for the Studen t-copula.

tau FALSE (default) for a calibration fonction specified for the Copula parameter or TRUE for a calibration function specified for Kendall's tau.

See Also

`gamBiCopFit`, `gamBiCopPredict` and `gamBiCopSimulate`.

`gamBiCopCDF`

Conditional distribution function of a Generalized Additive model for the copula parameter or Kendall's tau

Description

This function returns the distribution function of a bivariate conditional copula, where either the copula parameter or the Kendall's tau is modeled as a function of the covariates.

Usage

```
gamBiCopCDF(object, newdata = NULL)
```

Arguments

- | | |
|----------------|---|
| object | <code>gamBiCop-class</code> object. |
| newdata | (Same as in <code>predict.gam</code> from the <code>mgcv</code> package) A matrix or data frame containing the values of the model covariates at which predictions are required. If this is not provided then the distribution corresponding to the original data are returned. If newdata is provided then it should contain all the variables needed for prediction: a warning is generated if not. |

Value

The conditional density.

See Also

`gamBiCop` and `gamBiCopPredict`.

Examples

```

require(copula)
set.seed(0)

## Simulation parameters (sample size, correlation between covariates,
## Gaussian copula family)
n <- 2e2
rho <- 0.5
fam <- 1

## A calibration surface depending on three variables
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)

## 3-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 3),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)
X <- rmvdc(n, covariates.distr)
colnames(X) <- paste("x", 1:3, sep = "")

## U in [0,1]x[0,1] with copula parameter depending on X
U <- condBiCopSim(fam, function(x1, x2, x3) {
  eta0 + sum(mapply(function(f, x)
    f(x), calib.surf, c(x1, x2, x3)))
}, X[, 1:3], par2 = 6, return.par = TRUE)

## Merge U and X
data <- data.frame(U$data, X)
names(data) <- c(paste("u", 1:2, sep = ""), paste("x", 1:3, sep = ""))

## Model fit with penalized cubic splines (via min GCV)
basis <- c(3, 10, 10)
formula <- ~ s(x1, k = basis[1], bs = "cr") +

```

```

  s(x2, k = basis[2], bs = "cr") +
  s(x3, k = basis[3], bs = "cr")
system.time(fit <- gamBiCopFit(data, formula, fam))

## Evaluate the conditional density
gamBiCopCDF(fit$res)

```

gamBiCopFit

Maximum penalized likelihood estimation of a Generalized Additive model for the copula parameter or Kendall's tau.

Description

This function estimates the parameter(s) of a Generalized Additive model (gam) for the copula parameter or Kendall's tau. It solves the maximum penalized likelihood estimation for the copula families supported in this package by reformulating each Newton-Raphson iteration as a generalized ridge regression, which is solved using the [mgcv](#) package.

Usage

```

gamBiCopFit(
  data,
  formula = ~1,
  family = 1,
  tau = TRUE,
  method = "FS",
  tol.rel = 0.001,
  n.iters = 10,
  verbose = FALSE,
  ...
)

```

Arguments

data	A list, data frame or matrix containing the model responses, (u1,u2) in [0,1]x[0,1], and covariates required by the formula.
formula	A gam formula (see gam , formula.gam and gam.models from mgcv).
family	A copula family: 1 Gaussian, 2 Student t, 5 Frank, 301 Double Clayton type I (standard and rotated 90 degrees), 302 Double Clayton type II (standard and rotated 270 degrees), 303 Double Clayton type III (survival and rotated 90 degrees), 304 Double Clayton type IV (survival and rotated 270 degrees), 401 Double Gumbel type I (standard and rotated 90 degrees), 402 Double Gumbel type II (standard and rotated 270 degrees), 403 Double Gumbel type III (survival and rotated 90 degrees), 404 Double Gumbel type IV (survival and rotated 270 degrees).
tau	FALSE (default) for a calibration function specified for the Copula parameter or TRUE for a calibration function specified for Kendall's tau.

method	'NR' for Newton-Raphson and 'FS' for Fisher-scoring (default).
tol.rel	Relative tolerance for 'FS'/'NR' algorithm.
n.iters	Maximal number of iterations for 'FS'/'NR' algorithm.
verbose	TRUE if informations should be printed during the estimation and FALSE (default) for a silent version.
...	Additional parameters to be passed to gam from mgcv .

Value

`gamBiCopFit` returns a list consisting of

res	S4 gamBiCop-class object.
method	'FS' for Fisher-scoring (default) and 'NR' for Newton-Raphson.
tol.rel	relative tolerance for 'FS'/'NR' algorithm.
n.iters	maximal number of iterations for 'FS'/'NR' algorithm.
trace	the estimation procedure's trace.
conv	0 if the algorithm converged and 1 otherwise.

See Also

[gamBiCop](#) and [gamBiCopSimulate](#).

Examples

```

require(copula)
require(mgcv)
set.seed(0)

## Simulation parameters (sample size, correlation between covariates,
## Gaussian copula family)
n <- 5e2
rho <- 0.5
fam <- 1

## A calibration surface depending on three variables
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
)

```

```

calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
  Tm <- (Tf - Ti) / 2
  a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
  return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
}

## Display the calibration surface
par(mfrow = c(1, 3), pty = "s", mar = c(1, 1, 4, 1))
u <- seq(0, 1, length.out = 100)
sel <- matrix(c(1, 1, 2, 2, 3, 3), ncol = 2)
jet.colors <- colorRamp(c(
  "#00007F", "blue", "#007FFF", "cyan", "#7FFF7F",
  "yellow", "#FF7F00", "red", "#7F0000"
))
jet <- function(x) rgb(jet.colors(exp(x / 3) / (1 + exp(x / 3))),
  maxColorValue = 255
)
for (k in 1:3) {
  tmp <- outer(u, u, function(x, y)
    eta0 + calib.surf[[sel[k, 1]]](x) + calib.surf[[sel[k, 2]]](y))
  persp(u, u, tmp,
    border = NA, theta = 60, phi = 30, zlab = "",
    col = matrix(jet(tmp), nrow = 100),
    xlab = paste("X", sel[k, 1], sep = ""),
    ylab = paste("X", sel[k, 2], sep = ""),
    main = paste("eta0+f", sel[k, 1],
      "(X", sel[k, 1], ") +f", sel[k, 2],
      "(X", sel[k, 2], ")",
      sep = ""
    )
  )
}
}

## 3-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 3),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)
X <- rmvdc(n, covariates.distr)

## U in [0,1]x[0,1] with copula parameter depending on X
U <- condBiCopSim(fam, function(x1, x2, x3) {
  eta0 + sum(mapply(function(f, x)
    f(x), calib.surf, c(x1, x2, x3)))
}, X[, 1:3], par2 = 6, return.par = TRUE)

## Merge U and X
data <- data.frame(U$data, X)
names(data) <- c(paste("u", 1:2, sep = ""), paste("x", 1:3, sep = ""))

## Display the data
dev.off()

```

```

plot(data[, "u1"], data[, "u2"], xlab = "U1", ylab = "U2")

## Model fit with a basis size (arguably) too small
## and unpenalized cubic splines
pen <- FALSE
basis0 <- c(3, 4, 4)
formula <- ~ s(x1, k = basis0[1], bs = "cr", fx = !pen) +
  s(x2, k = basis0[2], bs = "cr", fx = !pen) +
  s(x3, k = basis0[3], bs = "cr", fx = !pen)
system.time(fit0 <- gamBiCopFit(data, formula, fam))

## Model fit with a better basis size and penalized cubic splines (via min GCV)
pen <- TRUE
basis1 <- c(3, 10, 10)
formula <- ~ s(x1, k = basis1[1], bs = "cr", fx = !pen) +
  s(x2, k = basis1[2], bs = "cr", fx = !pen) +
  s(x3, k = basis1[3], bs = "cr", fx = !pen)
system.time(fit1 <- gamBiCopFit(data, formula, fam))

## Extract the gamBiCop objects and show various methods
(res <- sapply(list(fit0, fit1), function(fit) {
  fit$res
})))
metds <- list("logLik" = logLik, "AIC" = AIC, "BIC" = BIC, "EDF" = EDF)
lapply(res, function(x) sapply(metds, function(f) f(x)))

## Comparison between fitted, true smooth and spline approximation for each
## true smooth function for the two basis sizes
fitted <- lapply(res, function(x) gamBiCopPredict(x, data.frame(x1 = u, x2 = u, x3 = u),
  type = "terms"
 )$calib)
true <- vector("list", 3)
for (i in 1:3) {
  y <- eta0 + calib.surf[[i]](u)
  true[[i]]$true <- y - eta0
  temp <- gam(y ~ s(u, k = basis0[i], bs = "cr", fx = TRUE))
  true[[i]]$approx <- predict.gam(temp, type = "terms")
  temp <- gam(y ~ s(u, k = basis1[i], bs = "cr", fx = FALSE))
  true[[i]]$approx2 <- predict.gam(temp, type = "terms")
}
## Display results
par(mfrow = c(1, 3), pty = "s")
yy <- range(true, fitted)
yy[1] <- yy[1] * 1.5
for (k in 1:3) {
  plot(u, true[[k]]$true,
    type = "l", ylim = yy,
    xlab = paste("Covariate", k), ylab = paste("Smooth", k)
  )
  lines(u, true[[k]]$approx, col = "red", lty = 2)
  lines(u, fitted[[1]][, k], col = "red")
}

```

```

lines(u, fitted[[2]][, k], col = "green")
lines(u, true[[k]]$approx2, col = "green", lty = 2)
legend("bottomleft",
       cex = 0.6, lty = c(1, 1, 2, 1, 2),
       c("True", "Fitted", "Appox 1", "Fitted 2", "Approx 2"),
       col = c("black", "red", "red", "green", "green"))
)
}

```

gamBiCopPDF

Conditional density function of a Generalized Additive model for the copula parameter or Kendall's tau

Description

This function returns the density of a bivariate conditional copula, where either the copula parameter or the Kendall's tau is modeled as a function of the covariates.

Usage

```
gamBiCopPDF(object, newdata = NULL)
```

Arguments

object	gamBiCop-class object.
newdata	(Same as in predict.gam from the mgcv package) A matrix or data frame containing the values of the model covariates at which predictions are required, along with two columns named “u1” and “u2”. If this is not provided then the density corresponding to the original data are returned. If newdata is provided then it should contain all the variables needed for prediction: a warning is generated if not.

Value

The conditional density.

See Also

[gamBiCop](#) and [gamBiCopPredict](#).

Examples

```

require(copula)
set.seed(0)

## Simulation parameters (sample size, correlation between covariates,
## Gaussian copula family)
n <- 2e2
rho <- 0.5

```

```

fam <- 1

## A calibration surface depending on three variables
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)))
      - cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)

## 3-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 3),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)
X <- rmvdc(n, covariates.distr)
colnames(X) <- paste("x", 1:3, sep = "")

## U in [0,1]x[0,1] with copula parameter depending on X
U <- condBiCopSim(fam, function(x1, x2, x3) {
  eta0 + sum(mapply(function(f, x)
    f(x), calib.surf, c(x1, x2, x3)))
}, X[, 1:3], par2 = 6, return.par = TRUE)

## Merge U and X
data <- data.frame(U$data, X)
names(data) <- c(paste("u", 1:2, sep = ""), paste("x", 1:3, sep = ""))

## Model fit with penalized cubic splines (via min GCV)
basis <- c(3, 10, 10)
formula <- ~ s(x1, k = basis[1], bs = "cr") +
  s(x2, k = basis[2], bs = "cr") +
  s(x3, k = basis[3], bs = "cr")
system.time(fit <- gamBiCopFit(data, formula, fam))

## Evaluate the conditional density
gamBiCopPDF(fit$res)

```

gamBiCopPredict	<i>Predict method of a Generalized Additive model for the copula parameter or Kendall's tau</i>
-----------------	---

Description

Predict method of a Generalized Additive model for the copula parameter or Kendall's tau

Usage

```
gamBiCopPredict(
  object,
  newdata = NULL,
  target = "calib",
  alpha = 0,
  type = "link"
)
```

Arguments

object	<code>gamBiCop-class</code> object.
newdata	(Same as in <code>predict.gam</code> from the <code>mgcv</code> package) A matrix or data frame containing the values of the model covariates at which predictions are required. If this is not provided then predictions corresponding to the original data are returned. If newdata is provided then it should contain all the variables needed for prediction: a warning is generated if not.
target	Either 'calib', 'par' or 'tau' or a combination of those. 'calib' (default) corresponds to the calibration function, 'par' to the copula parameter and 'tau' to Kendall's tau.
alpha	In (0,1) to return the corresponding confidence interval.
type	(Similar as in <code>predict.gam</code> from the <code>mgcv</code> package, only active for type = 'calib'). When this has the value 'link' (default), the calibration function is returned. When type = 'terms' each component of the linear predictor is returned separately (possibly with standard errors): this includes parametric model components, followed by each smooth component, but excludes any offset and any intercept. When type = 'lpmatrix' then a matrix is returned which yields the values of the linear predictor (minus any offset) when post-multiplied by the parameter vector (in this case alpha is ignored).

Value

If target = 'calib', then a list with 1 item calib. If target = 'par', target = 'tau' or target = c('par', 'tau'), then a list with 2, 2 or 3 items, namely calib and par, tau and par, or calib, tau and par.

If alpha is in (0,1), then additional items of the list are calib.CI as well as e.g. par.CI and/or tau.CI depending on the value of target.

Otherwise, if `type = 'lpmatrix'` (only active for `type = 'calib'`), then a matrix is returned which will give a vector of linear predictor values (minus any offset) at the supplied covariate values, when applied to the model coefficient vector (similar as `predict.gam` from the `mgcv`).

See Also

`gamBiCop` and `gamBiCopFit`.

Examples

```

require(copula)
set.seed(0)

## Simulation parameters (sample size, correlation between covariates,
## Clayton copula family)
n <- 5e2
rho <- 0.5
fam <- 1

## A calibration surface depending on three variables
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)

## 3-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 3),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)
X <- rmvdc(n, covariates.distr)
colnames(X) <- paste("x", 1:3, sep = "")

## U in [0,1]x[0,1] with copula parameter depending on X
U <- condBiCopSim(fam, function(x1, x2, x3) {
  eta0 + sum(mapply(function(f, x)
    f(x), calib.surf, c(x1, x2, x3)))
}
)
```

```

}, X[, 1:3], par2 = 6, return.par = TRUE)

## Merge U and X
data <- data.frame(U$data, X)
names(data) <- c(paste("u", 1:2, sep = ""), paste("x", 1:3, sep = ""))

## Model fit with penalized cubic splines (via min GCV)
basis <- c(3, 10, 10)
formula <- ~ s(x1, k = basis[1], bs = "cr") +
  s(x2, k = basis[2], bs = "cr") +
  s(x3, k = basis[3], bs = "cr")
system.time(fit <- gamBiCopFit(data, formula, fam))

## Extract the gamBiCop objects and show various methods
(res <- fit$res)
EDF(res)
pred <- gamBiCopPredict(fit$res, X, target = c("calib", "par", "tau"))

```

gamBiCopSelect

Selection and Maximum penalized likelihood estimation of a Generalized Additive model (gam) for the copula parameter or Kendall's tau.

Description

This function selects an appropriate bivariate copula family for given bivariate copula data using one of a range of methods. The corresponding parameter estimates are obtained by maximum penalized likelihood estimation, where each Newton-Raphson iteration is reformulated as a generalized ridge regression solved using the [mgcv](#) package.

Usage

```

gamBiCopSelect(
  udata,
  lin.covs = NULL,
  smooth.covs = NULL,
  familyset = NA,
  rotations = TRUE,
  familycrit = "AIC",
  level = 0.05,
  edf = 1.5,
  tau = TRUE,
  method = "FS",
  tol.rel = 0.001,
  n.iters = 10,
  parallel = FALSE,
  verbose = FALSE,
  select.once = TRUE,
  ...
)

```

Arguments

<code>udata</code>	A matrix or data frame containing the model responses, (u1,u2) in [0,1]x[0,1]
<code>lin.covs</code>	A matrix or data frame containing the parametric (i.e., linear) covariates.
<code>smooth.covs</code>	A matrix or data frame containing the non-parametric (i.e., smooth) covariates.
<code>familyset</code>	(Similar to <code>BiCopSelect</code> from the <code>VineCopula</code> package) Vector of bivariate copula families to select from. If <code>familyset</code> = NA (default), selection among all possible families is performed. Coding of bivariate copula families: 1 Gaussian, 2 Student t, 5 Frank, 301 Double Clayton type I (standard and rotated 90 degrees), 302 Double Clayton type II (standard and rotated 270 degrees), 303 Double Clayton type III (survival and rotated 90 degrees), 304 Double Clayton type IV (survival and rotated 270 degrees), 401 Double Gumbel type I (standard and rotated 90 degrees), 402 Double Gumbel type II (standard and rotated 270 degrees), 403 Double Gumbel type III (survival and rotated 90 degrees), 404 Double Gumbel type IV (survival and rotated 270 degrees).
<code>rotations</code>	If TRUE, all rotations of the families in <code>familyset</code> are included.
<code>familycrit</code>	Character indicating the criterion for bivariate copula selection. Possible choices: <code>familycrit</code> = 'AIC' (default) or 'BIC', as in <code>BiCopSelect</code> from the <code>VineCopula</code> package.
<code>level</code>	Numerical; significance level of the test for removing individual predictors (default: <code>level</code> = 0.05).
<code>edf</code>	Numerical; if the estimated EDF for individual predictors is smaller than <code>edf</code> but the predictor is still significant, then it is set as linear (default: <code>edf</code> = 1.5).
<code>tau</code>	FALSE for a calibration function specified for the Copula parameter or TRUE (default) for a calibration function specified for Kendall's tau.
<code>method</code>	'FS' for Fisher-scoring (default) and 'NR' for Newton-Raphson.
<code>tol.rel</code>	Relative tolerance for 'FS'/'NR' algorithm.
<code>n.iters</code>	Maximal number of iterations for 'FS'/'NR' algorithm.
<code>parallel</code>	TRUE for a parallel estimation across copula families.
<code>verbose</code>	TRUE prints informations during the estimation.
<code>select.once</code>	if TRUE the GAM structure is only selected once, for the family that appears first in <code>familyset</code> .
<code>...</code>	Additional parameters to be passed to <code>gam</code>

Value

`gamBiCopFit` returns a list consisting of

<code>res</code>	S4 <code>gamBiCop-class</code> object.
<code>method</code>	'FS' for Fisher-scoring and 'NR' for Newton-Raphson.
<code>tol.rel</code>	relative tolerance for 'FS'/'NR' algorithm.
<code>n.iters</code>	maximal number of iterations for 'FS'/'NR' algorithm.
<code>trace</code>	the estimation procedure's trace.
<code>conv</code>	0 if the algorithm converged and 1 otherwise.

See Also

[gamBiCop](#) and [gamBiCopFit](#).

Examples

```

require(copula)
set.seed(0)

## Simulation parameters (sample size, correlation between covariates,
## Student copula with 4 degrees of freedom)
n <- 5e2
rho <- 0.9
fam <- 2
par2 <- 4

## A calibration surface depending on four variables
eta0 <- 1
calib.surf <- list(
  calib.lin <- function(t, Ti = 0, Tf = 1, b = 2) {
    return(-2 + 4 * t)
  },
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)

## 6-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 6),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)
X <- rmvdc(n, covariates.distr)
colnames(X) <- paste("x", 1:6, sep = "")

## U in [0,1]x[0,1] depending on the four first columns of X
U <- condBiCopSim(fam, function(x1, x2, x3, x4) {
  eta0 + sum(mapply(function(f, x)
    f(x), calib.surf, c(x1, x2, x3, x4)))
}, X[, 1:4], par2 = 4, return.par = TRUE)

```

```

## Not run:
## Selection using AIC (about 30sec on single core)
## Use parallel = TRUE to speed-up....
system.time(best <- gamBiCopSelect(U$data, smooth.covs = X))
print(best$res)
EDF(best$res) ## The first function is linear
## Plot only the smooth component
par(mfrow = c(2, 2))
plot(best$res)

## End(Not run)

```

gamBiCopSimulate *Simulate from [gamBiCop-class](#) object*

Description

Simulate from [gamBiCop-class](#) object

Usage

```

gamBiCopSimulate(
  object,
  newdata = NULL,
  N = NULL,
  return.calib = FALSE,
  return.par = FALSE,
  return.tau = FALSE
)

```

Arguments

object	gamBiCop-class object.
newdata	(same as in predict.gam from the mgcv package) A matrix or data frame containing the values of the model covariates at which simulations are required. If this is not provided then simulations corresponding to the original data are returned.
N	sample size.
return.calib	should the calibration function (TRUE) be returned or not (FALSE)?
return.par	should the copula parameter (TRUE) be returned or not (FALSE)?
return.tau	should the Kendall's tau (TRUE) be returned or not (FALSE)?

Value

A list with 1 item data. When N is smaller or larger than the newdata's number of rows (or the number of rows in the original data if newdata is not provided), then N observations are sampled uniformly (with replacement) among the row of newdata (or the rows of the original data if newdata is not provided).

If `return.calib = TRUE`, `return.par = TRUE` and/or `return.tau = TRUE`, then the list also contains respectively items `calib`, `par` and/or `tau`.

Examples

```
require(copula)
set.seed(1)

## Simulation parameters (sample size, correlation between covariates,
## Gaussian copula family)
n <- 5e2
rho <- 0.5
fam <- 1

## A calibration surface depending on three variables
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)

## 3-dimensional matrix X of covariates
covariates.distr <- mvdc(normalCopula(rho, dim = 3),
  c("unif"), list(list(min = 0, max = 1)),
  marginsIdentical = TRUE
)
X <- rmvdc(n, covariates.distr)
colnames(X) <- paste("x", 1:3, sep = "")

## U in [0,1]x[0,1] with copula parameter depending on X
U <- condBiCopSim(fam, function(x1, x2, x3) {
  eta0 + sum(mapply(function(f, x)
```

```

f(x), calib.surf, c(x1, x2, x3)))
}, X[, 1:3], par2 = 6, return.par = TRUE)

## Merge U and X
data <- data.frame(U$data, X)
names(data) <- c(paste("u", 1:2, sep = ""), paste("x", 1:3, sep = "))

## Model fit with penalized cubic splines (via min GCV)
basis <- c(3, 10, 10)
formula <- ~ s(x1, k = basis[1], bs = "cr") +
  s(x2, k = basis[2], bs = "cr") +
  s(x3, k = basis[3], bs = "cr")
system.time(fit <- gamBiCopFit(data, formula, fam))

## Extract the gamBiCop objects and show various methods
(res <- fit$res)
EDF(res)
sim <- gamBiCopSimulate(fit$res, X)

```

gamVine*Construction of a gamVine Class Object***Description**

Constructs an object of the class [gamVine](#).

Usage

```
gamVine(Matrix, model, names = NA, covariates = NA)
```

Arguments

<code>Matrix</code>	lower triangular d x d matrix that defines the tree structure.
<code>model</code>	list containing d x (d-1)/2 lists with three numeric items (family, par and par2) and/or objects of the class gamBiCop .
<code>names</code>	vector of d names.
<code>covariates</code>	vector of names for the covariates.

Value

An object of the class [gamVine](#).

See Also

[gamVine](#), [RVineMatrix](#), [gamBiCop](#) [gamVineSeqFit](#), [gamVineCopSelect](#), [gamVineStructureSelect](#) and [gamVineSimulate](#).

gamVine-class*The gamVine Class*

Description

gamVine is an S4 class to store a conditional and potentially non-simplified pair-copula construction. Objects can be created by calls of the form `new("gamVine", ...)`, or by function [gamVine](#).

Slots

`Matrix` Lower triangular $d \times d$ matrix that defines the tree structure.

`model` list containing $d \times (d-1)/2$ lists with three numeric items (`family`, `par` and `par2`) and/or [gamBiCop](#) objects.

`names` vector of d names.

`covariates` vector of names for the exogenous covariates.

See Also

[gamVine](#), [RVineMatrix](#), [gamBiCop](#) [gamVineSeqFit](#), [gamVineCopSelect](#), [gamVineStructureSelect](#) and [gamVineSimulate](#).

gamVineCopSelect

Sequential pair-copula selection and maximum penalized likelihood estimation of a GAM-Vine model.

Description

This function select the copula family and estimates the parameter(s) of a Generalized Additive model (GAM) Vine model, where GAMs for individual edges are specified either for the copula parameter or Kendall's tau. It solves the maximum penalized likelihood estimation for the copula families supported in this package by reformulating each Newton-Raphson iteration as a generalized ridge regression, which is solved using the [mgcv](#) package.

Usage

```
gamVineCopSelect(
  data,
  Matrix,
  lin.covs = NULL,
  smooth.covs = NULL,
  simplified = FALSE,
  familyset = NA,
  rotations = TRUE,
  familycrit = "AIC",
```

```

level = 0.05,
trunclevel = NA,
tau = TRUE,
method = "FS",
tol.rel = 0.001,
n.iters = 10,
parallel = FALSE,
verbose = FALSE,
select.once = TRUE,
...
)

```

Arguments

<code>data</code>	A matrix or data frame containing the data in $[0,1]^d$.
<code>Matrix</code>	Lower triangular $d \times d$ matrix that defines the R-vine tree structure.
<code>lin.covs</code>	A matrix or data frame containing the parametric (i.e., linear) covariates (default: <code>lin.covs = NULL</code>).
<code>smooth.covs</code>	A matrix or data frame containing the non-parametric (i.e., smooth) covariates (default: <code>smooth.covs = NULL</code>).
<code>simplified</code>	If <code>TRUE</code> , then a simplified vine is fitted (which is possible only if there are exogenous covariates). If <code>FALSE</code> (default), then a non-simplified vine is fitted.
<code>familyset</code>	An integer vector of pair-copula families to select from (the independence copula MUST NOT be specified in this vector unless one wants to fit an independence vine!). The vector has to include at least one pair-copula family that allows for positive and one that allows for negative dependence. Not listed copula families might be included to better handle limit cases. If <code>familyset = NA</code> (default), selection among all possible families is performed. Coding of pair-copula families: 1 Gaussian, 2 Student t, 3 Clayton, 4 Gumbel, 13 Survival Clayton, 14 Survival Gumbel, 23 Rotated (90 degrees) Clayton, 24 Rotated (90 degrees) Gumbel, 33 Rotated (270 degrees) Clayton and 34 Rotated (270 degrees) Gumbel.
<code>rotations</code>	If <code>TRUE</code> , all rotations of the families in <code>familyset</code> are included.
<code>familycrit</code>	Character indicating the criterion for bivariate copula selection. Possible choices: <code>familycrit = 'AIC'</code> (default) or <code>'BIC'</code> , as in BiCopSelect from the VineCopula package.
<code>level</code>	Numerical; Passed to gamBiCopSelect , it is the significance level of the test for removing individual predictors (default: <code>level = 0.05</code>) for each conditional pair-copula.
<code>trunclevel</code>	Integer; level of truncation.
<code>tau</code>	<code>TRUE</code> (default) for a calibration function specified for Kendall's tau or <code>FALSE</code> for a calibration function specified for the Copula parameter.
<code>method</code>	'NR' for Newton-Raphson and 'FS' for Fisher-scoring (default).
<code>tol.rel</code>	Relative tolerance for 'FS'/'NR' algorithm.
<code>n.iters</code>	Maximal number of iterations for 'FS'/'NR' algorithm.

parallel	TRUE (default) for parallel selection of copula family at each edge or FALSE for the sequential version. for the Copula parameter.
verbose	TRUE if informations should be printed during the estimation and FALSE (default) for a silent version. from mgcv .
select.once	if TRUE the GAM structure is only selected once, for the family that appears first in familyset.
...	Additional parameters to be passed to gam from mgcv .

Value

`gamVineCopSelect` returns a [gamVine-class](#) object.

See Also

[gamVineSeqFit](#), [gamVineStructureSelect](#), [gamVine-class](#), [gamVineSimulate](#) and [gamBiCopFit](#).

Examples

```
require(mgcv)
set.seed(0)

## Simulation parameters
# Sample size
n <- 1e3
# Copula families
familyset <- c(1:2, 301:304, 401:404)
# Define a 4-dimensional R-vine tree structure matrix
d <- 4
Matrix <- c(2, 3, 4, 1, 0, 3, 4, 1, 0, 0, 4, 1, 0, 0, 0, 1)
Matrix <- matrix(Matrix, d, d)
nnames <- paste("X", 1:d, sep = "")

## A function factory
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)) -
      cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)
```

```

)
## Create the model
# Define gam-vine model list
count <- 1
model <- vector(mode = "list", length = d * (d - 1) / 2)
sel <- seq(d, d^2 - d, by = d)

# First tree
for (i in 1:(d - 1)) {
  # Select a copula family
  family <- sample(familyset, 1)
  model[[count]]$family <- family

  # Use the canonical link and a randomly generated parameter
  if (is.element(family, c(1, 2))) {
    model[[count]]$par <- tanh(rnorm(1) / 2)
    if (family == 2) {
      model[[count]]$par2 <- 2 + exp(rnorm(1))
    }
  } else {
    if (is.element(family, c(401:404))) {
      rr <- rnorm(1)
      model[[count]]$par <- sign(rr) * (1 + abs(rr))
    } else {
      model[[count]]$par <- rnorm(1)
    }
    model[[count]]$par2 <- 0
  }
  count <- count + 1
}

# A dummy dataset
data <- data.frame(u1 = runif(1e2), u2 = runif(1e2), matrix(runif(1e2 * d), 1e2, d))

# Trees 2 to (d-1)
for (j in 2:(d - 1)) {
  for (i in 1:(d - j)) {
    # Select a copula family
    family <- sample(familyset, 1)

    # Select the conditioning set and create a model formula
    cond <- nnames[sort(Matrix[(d - j + 2):d, i])]
    tmpform <- paste("~", paste(paste("s(", cond, ", k=10, bs='cr')",
      sep = ""))
    ), collapse = " + "))
    l <- length(cond)
    temp <- sample(3, l, replace = TRUE)

    # Spline approximation of the true function
    m <- 1e2
    x <- matrix(seq(0, 1, length.out = m), nrow = m, ncol = 1)
    if (l != 1) {

```

```

tmp.fct <- paste("function(x){eta0 +",
  paste(sapply(1:l, function(x)
    paste("calib.surf[[" , temp[x], "]](x[[" , x, "]])",
      sep = ""),
    ), collapse = "+"), "}",
  sep = ""
)
tmp.fct <- eval(parse(text = tmp.fct))
x <- eval(parse(text = paste0("expand.grid(", 
  paste0(rep("x", l), collapse = ","), ",",
  collapse = ""))
))
y <- apply(x, 1, tmp.fct)
} else {
  tmp.fct <- function(x) eta0 + calib.surf[[temp]](x)
  colnames(x) <- cond
  y <- tmp.fct(x)
}

# Estimate the gam model
form <- as.formula(paste0("y", tmpform))
dd <- data.frame(y, x)
names(dd) <- c("y", cond)
b <- gam(form, data = dd)
# plot(x[,1],(y-fitted(b))/y)

# Create a dummy gamBiCop object
tmp <- gamBiCopFit(data = data, formula = form, family = 1, n.iters = 1)$res

# Update the copula family and the model coefficients
attr(tmp, "model")$coefficients <- coefficients(b)
attr(tmp, "model")$smooth <- b$smooth
attr(tmp, "family") <- family
if (family == 2) {
  attr(tmp, "par2") <- 2 + exp(rnorm(1))
}
model[[count]] <- tmp
count <- count + 1
}
}

# Create the gamVineCopula object
GVC <- gamVine(Matrix = Matrix, model = model, names = nnames)
print(GVC)
## Not run:
## Simulate and fit the model
sim <- gamVineSimulate(n, GVC)
fitGVC <- gamVineSeqFit(sim, GVC, verbose = TRUE)
fitGVC2 <- gamVineCopSelect(sim, Matrix, verbose = TRUE)

## Plot the results
par(mfrow = c(3, 4))
plot(GVC, ylim = c(-2.5, 2.5))

```

```
plot(fitGVC, ylim = c(-2.5, 2.5))
plot(fitGVC2, ylim = c(-2.5, 2.5))
## End(Not run)
```

gamVineFamily*Family Matrix of an Object of the Class gamVine***Description**

Return the matrix of copula family (see [gamBiCop](#)) corresponding to the model list in the [gamVine](#) object.

Usage

```
gamVineFamily(GVC)
```

Arguments

GVC An object of the class [gamVine](#).

Value

Matrix of copula families corresponding to the model list in the [gamVine](#) object.

See Also

[gamVine](#).

gamVineNormalize*Normalize an Object of the Class gamVine***Description**

Change the R-vine matrix in the natural order, i.e. with d:1 on the diagonal

Usage

```
gamVineNormalize(GVC)
```

Arguments

GVC An object of the class [gamVine](#).

Value

The normalized `gamVine` object.

See Also

`gamVine`.

`gamVinePDF`

Conditional density function of a gamVine

Description

This function returns the density of a conditional pair-copula constructions, where either the copula parameters or the Kendall's taus are modeled as a function of the covariates.

Usage

```
gamVinePDF(object, data)
```

Arguments

- | | |
|--------|---|
| object | <code>gamVine-class</code> object. |
| data | (Same as in <code>predict.gam</code> from the <code>mgcv</code> package) A matrix or data frame containing the values of the model covariates at which predictions are required, along with a number of additional columns corresponding to the variables in the pair copula decomposition. |

Value

The conditional density.

See Also

`gamVine`, `gamVineCopSelect`, `gamVineStructureSelect`, `gamVine-class`, `gamVineSimulate` and `gamBiCopFit`.

Examples

```
require(mgcv)
set.seed(0)

## Simulation parameters
# Sample size
n <- 1e3
# Copula families
familyset <- c(1:2, 301:304, 401:404)
# Define a 4-dimensional R-vine tree structure matrix
d <- 4
```

```

Matrix <- c(2, 3, 4, 1, 0, 3, 4, 1, 0, 0, 4, 1, 0, 0, 0, 1)
Matrix <- matrix(Matrix, d, d)
nnames <- paste("X", 1:d, sep = "")

## A function factory
eta0 <- 1
calib.surf <- list(
  calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
    Tm <- (Tf - Ti) / 2
    a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
    return(a + b * (t - Tm)^2)
  },
  calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
    a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
      cos(2 * f * pi * (Tf - Ti)))
      - cos(2 * f * pi * Ti)))
    return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
  },
  calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
    Tm <- (Tf - Ti) / 2
    a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
    return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
  }
)

## Create the model
# Define gam-vine model list
count <- 1
model <- vector(mode = "list", length = d * (d - 1) / 2)
sel <- seq(d, d^2 - d, by = d)

# First tree
for (i in 1:(d - 1)) {
  # Select a copula family
  family <- sample(familyset, 1)
  model[[count]]$family <- family

  # Use the canonical link and a randomly generated parameter
  if (is.element(family, c(1, 2))) {
    model[[count]]$par <- tanh(rnorm(1) / 2)
    if (family == 2) {
      model[[count]]$par2 <- 2 + exp(rnorm(1))
    }
  } else {
    if (is.element(family, c(401:404))) {
      rr <- rnorm(1)
      model[[count]]$par <- sign(rr) * (1 + abs(rr))
    } else {
      model[[count]]$par <- rnorm(1)
    }
    model[[count]]$par2 <- 0
  }
  count <- count + 1
}

```

```

}

# A dummy dataset
data <- data.frame(u1 = runif(1e2), u2 = runif(1e2), matrix(runif(1e2 * d), 1e2, d))

# Trees 2 to (d-1)
for (j in 2:(d - 1)) {
  for (i in 1:(d - j)) {
    # Select a copula family
    family <- sample(familyset, 1)

    # Select the conditiong set and create a model formula
    cond <- nnames[sort(Matrix[(d - j + 2):d, i])]

    tmpform <- paste("~", paste(paste("s(", cond, ", k=10, bs='cr')",
      sep = ""),
      ), collapse = " + "))

    l <- length(cond)
    temp <- sample(3, l, replace = TRUE)

    # Spline approximation of the true function
    m <- 1e2
    x <- matrix(seq(0, 1, length.out = m), nrow = m, ncol = 1)
    if (l != 1) {
      tmp.fct <- paste("function(x){eta0 +",
        paste(sapply(1:l, function(x)
          paste("calib.surf[[" , temp[x], "]](x[[" , x, "]])",
            sep = ""),
          )), collapse = "+"),
        "}",
        sep = "")
    }

    tmp.fct <- eval(parse(text = tmp.fct))
    x <- eval(parse(text = paste0("expand.grid(",
      paste0(rep("x", l), collapse = ","), ",",
      collapse = ""))
      )))
    y <- apply(x, 1, tmp.fct)
  } else {
    tmp.fct <- function(x) eta0 + calib.surf[[temp]](x)
    colnames(x) <- cond
    y <- tmp.fct(x)
  }

  # Estimate the gam model
  form <- as.formula(paste0("y", tmpform))
  dd <- data.frame(y, x)
  names(dd) <- c("y", cond)
  b <- gam(form, data = dd)
  # plot(x[,1],(y-fitted(b))/y)

  # Create a dummy gamBiCop object
  tmp <- gamBiCopFit(data = data, formula = form, family = 1, n.iters = 1)$res

  # Update the copula family and the model coefficients
}

```

```

attr(tmp, "model")$coefficients <- coefficients(b)
attr(tmp, "model")$smooth <- b$smooth
attr(tmp, "family") <- family
if (family == 2) {
  attr(tmp, "par2") <- 2 + exp(rnorm(1))
}
model[[count]] <- tmp
count <- count + 1
}
}

# Create the gamVineCopula object
GVC <- gamVine(Matrix = Matrix, model = model, names = nnames)
print(GVC)
## Not run:
## Simulate and fit the model
sim <- gamVineSimulate(n, GVC)
fitGVC <- gamVineSeqFit(sim, GVC, verbose = TRUE)
fitGVC2 <- gamVineCopSelect(sim, Matrix, verbose = TRUE)
(gamVinePDF(GVC, sim[1:10, ]))

## Plot the results
dev.off()
par(mfrow = c(3, 4))
plot(GVC, ylim = c(-2.5, 2.5))

plot(fitGVC, ylim = c(-2.5, 2.5))

plot(fitGVC2, ylim = c(-2.5, 2.5))

## End(Not run)

```

gamVineSeqFit

Sequential maximum penalized likelihood estimation of a GAM-Vine model.

Description

This function estimates the parameter(s) of a Generalized Additive model (GAM) Vine model, where GAMs for individual edges are specified either for the copula parameter or Kendall's tau. It solves the maximum penalized likelihood estimation for the copula families supported in this package by reformulating each Newton-Raphson iteration as a generalized ridge regression, which is solved using the [mgcv](#) package.

Usage

```
gamVineSeqFit(
  data,
  GVC,
```

```

covariates = NA,
method = "FS",
tol.rel = 0.001,
n.iters = 10,
verbose = FALSE,
...
)

```

Arguments

data	A matrix or data frame containing the data in [0,1] ^d .
GVC	A gamVine object.
covariates	Vector of names for the covariates.
method	'NR' for Newton-Raphson and 'FS' for Fisher-scoring (default).
tol.rel	Relative tolerance for 'FS'/'NR' algorithm.
n.iters	Maximal number of iterations for 'FS'/'NR' algorithm.
verbose	TRUE if informations should be printed during the estimation and FALSE (default) for a silent version.
...	Additional parameters to be passed to gam from mgcv .

Value

`gamVineSeqFit` returns a [gamVine](#) object.

See Also

[gamVineCopSelect](#) and [gamVineStructureSelect](#)
[gamVineCopSelect](#),[gamVineStructureSelect](#), [gamVine-class](#), [gamVineSimulate](#) and [gamBiCopFit](#).

Examples

```

require(mgcv)
set.seed(0)

## Simulation parameters
# Sample size
n <- 1e3
# Copula families
familyset <- c(1:2, 301:304, 401:404)
# Define a 4-dimensional R-vine tree structure matrix
d <- 4
Matrix <- c(2, 3, 4, 1, 0, 3, 4, 1, 0, 0, 4, 1, 0, 0, 0, 1)
Matrix <- matrix(Matrix, d, d)
nnames <- paste("X", 1:d, sep = "")

## A function factory
eta0 <- 1
calib.surf <- list(

```

```

calib.quad <- function(t, Ti = 0, Tf = 1, b = 8) {
  Tm <- (Tf - Ti) / 2
  a <- -(b / 3) * (Tf^2 - 3 * Tf * Tm + 3 * Tm^2)
  return(a + b * (t - Tm)^2)
},
calib.sin <- function(t, Ti = 0, Tf = 1, b = 1, f = 1) {
  a <- b * (1 - 2 * Tf * pi / (f * Tf * pi +
    cos(2 * f * pi * (Tf - Ti))
    - cos(2 * f * pi * Ti)))
  return((a + b) / 2 + (b - a) * sin(2 * f * pi * (t - Ti)) / 2)
},
calib.exp <- function(t, Ti = 0, Tf = 1, b = 2, s = Tf / 8) {
  Tm <- (Tf - Ti) / 2
  a <- (b * s * sqrt(2 * pi) / Tf) * (pnorm(0, Tm, s) - pnorm(Tf, Tm, s))
  return(a + b * exp(-(t - Tm)^2 / (2 * s^2)))
}
)

## Create the model
# Define gam-vine model list
count <- 1
model <- vector(mode = "list", length = d * (d - 1) / 2)
sel <- seq(d, d^2 - d, by = d)

# First tree
for (i in 1:(d - 1)) {
  # Select a copula family
  family <- sample(familyset, 1)
  model[[count]]$family <- family

  # Use the canonical link and a randomly generated parameter
  if (is.element(family, c(1, 2))) {
    model[[count]]$par <- tanh(rnorm(1) / 2)
    if (family == 2) {
      model[[count]]$par2 <- 2 + exp(rnorm(1))
    }
  } else {
    if (is.element(family, c(401:404))) {
      rr <- rnorm(1)
      model[[count]]$par <- sign(rr) * (1 + abs(rr))
    } else {
      model[[count]]$par <- rnorm(1)
    }
    model[[count]]$par2 <- 0
  }
  count <- count + 1
}

# A dummy dataset
data <- data.frame(u1 = runif(1e2), u2 = runif(1e2), matrix(runif(1e2 * d), 1e2, d))

# Trees 2 to (d-1)
for (j in 2:(d - 1)) {

```

```

for (i in 1:(d - j)) {
  # Select a copula family
  family <- sample(familyset, 1)

  # Select the conditioning set and create a model formula
  cond <- nnames[sort(Matrix[(d - j + 2):d, i])]
  tmpform <- paste("~", paste(paste("s(", cond, ", k=10, bs='cr')",
    sep = ""))
  ), collapse = " + ")
  l <- length(cond)
  temp <- sample(3, l, replace = TRUE)

  # Spline approximation of the true function
  m <- 1e2
  x <- matrix(seq(0, 1, length.out = m), nrow = m, ncol = 1)
  if (l != 1) {
    tmp.fct <- paste("function(x){eta0 +",
      paste(sapply(1:l, function(x)
        paste("calib.surf[[", temp[x], "]](x[, x, ])",",
          sep = ""))
      ), collapse = "+"), "}",
      sep = ""
    )
    tmp.fct <- eval(parse(text = tmp.fct))
    x <- eval(parse(text = paste0("expand.grid(",
      paste0(rep("x", 1), collapse = ", "), ",",
      collapse = ""))
    )))
    y <- apply(x, 1, tmp.fct)
  } else {
    tmp.fct <- function(x) eta0 + calib.surf[[temp]](x)
    colnames(x) <- cond
    y <- tmp.fct(x)
  }

  # Estimate the gam model
  form <- as.formula(paste0("y", tmpform))
  dd <- data.frame(y, x)
  names(dd) <- c("y", cond)
  b <- gam(form, data = dd)
  # plot(x[,1],(y-fitted(b))/y)

  # Create a dummy gamBiCop object
  tmp <- gamBiCopFit(data = data, formula = form, family = 1, n.iters = 1)$res

  # Update the copula family and the model coefficients
  attr(tmp, "model")$coefficients <- coefficients(b)
  attr(tmp, "model")$smooth <- b$smooth
  attr(tmp, "family") <- family
  if (family == 2) {
    attr(tmp, "par2") <- 2 + exp(rnorm(1))
  }
  model[[count]] <- tmp
}

```

```

        count <- count + 1
    }
}

# Create the gamVineCopula object
GVC <- gamVine(Matrix = Matrix, model = model, names = nnames)
print(GVC)
## Not run:
## Simulate and fit the model
sim <- gamVineSimulate(n, GVC)
fitGVC <- gamVineSeqFit(sim, GVC, verbose = TRUE)
fitGVC2 <- gamVineCopSelect(sim, Matrix, verbose = TRUE)
(gamVinePDF(GVC, sim[1:10, ]))

## Plot the results
dev.off()
par(mfrow = c(3, 4))
plot(GVC, ylim = c(-2.5, 2.5))

plot(fitGVC, ylim = c(-2.5, 2.5))

plot(fitGVC2, ylim = c(-2.5, 2.5))

## End(Not run)

```

gamVineSimulate *Simulation from a [gamVine-class](#) object*

Description

Simulation from a [gamVine-class](#) object

Usage

```
gamVineSimulate(n, GVC, U = NULL, newdata = NULL)
```

Arguments

n	number of d-dimensional observations to simulate.
GVC	A gamVine object.
U	If not NULL, U is an (N,d)-matrix of U[0,1] random variates to be transformed to the copula sample.
newdata	If not NULL, which is mandatory when the attribute covariates from GVC is not NA, newdata is a data frame containing the values of the model covariates at which simulations are required.

Value

A matrix of data simulated from the given `gamVine` object.

Examples

```
require(VineCopula)

## Example adapted from RVineSim

## Define 5-dimensional R-vine tree structure matrix
Matrix <- c(
  5, 2, 3, 1, 4,
  0, 2, 3, 4, 1,
  0, 0, 3, 4, 1,
  0, 0, 0, 4, 1,
  0, 0, 0, 0, 1
)
Matrix <- matrix(Matrix, 5, 5)

## Define R-vine pair-copula family matrix
family <- c(
  0, 1, 3, 4, 4,
  0, 0, 3, 4, 1,
  0, 0, 0, 4, 1,
  0, 0, 0, 0, 3,
  0, 0, 0, 0, 0
)
family <- matrix(family, 5, 5)

## Define R-vine pair-copula parameter matrix
par <- c(
  0, 0.2, 0.9, 1.5, 3.9,
  0, 0, 1.1, 1.6, 0.9,
  0, 0, 0, 1.9, 0.5,
  0, 0, 0, 0, 4.8,
  0, 0, 0, 0, 0
)
par <- matrix(par, 5, 5)

## Define second R-vine pair-copula parameter matrix
par2 <- matrix(0, 5, 5)

## Define RVineMatrix object
RVM <- RVineMatrix(
  Matrix = Matrix, family = family,
  par = par, par2 = par2,
  names = c("V1", "V2", "V3", "V4", "V5")
)

## Convert to gamVine object
GVC <- RVM2GVC(RVM)
```

```

## U[0,1] random variates to be transformed to the copula sample
n <- 1e2
d <- 5
U <- matrix(runif(n * d), nrow = n)

## The output of gamVineSimulate correspond to that of RVineSim
sampleRVM <- RVineSim(n, RVM, U)
sampleGVC <- gamVineSimulate(n, GVC, U)
all.equal(sampleRVM, sampleGVC)

## Fit the two models and compare the estimated parameter
fitRVM <- RVM2GVC(RVineSeqEst(sampleRVM, RVM))
fitGVC <- gamVineSeqFit(sampleGVC, GVC)
all.equal(
  simplify2array(attr(fitRVM, "model")),
  simplify2array(attr(fitGVC, "model"))
)

```

gamVineStructureSelect

Structure selection and estimation of a GAM-Vine model.

Description

This function select the structure and estimates the parameter(s) of a Generalized Additive model (GAM) Vine model, where GAMs for individual edges are specified either for the copula parameter or Kendall's tau. It solves the maximum penalized likelihood estimation for the copula families supported in this package by reformulating each Newton-Raphson iteration as a generalized ridge regression, which is solved using the [mgcv](#) package.

Usage

```

gamVineStructureSelect(
  udata,
  lin.covs = NULL,
  smooth.covs = NULL,
  simplified = TRUE,
  type = 0,
  familyset = NA,
  rotations = TRUE,
  familycrit = "AIC",
  treecrit = "tau",
  level = 0.05,
  trunclevel = NA,
  tau = TRUE,
  method = "FS",
  tol.rel = 0.001,
  n.iters = 10,

```

```

    parallel = FALSE,
    verbose = FALSE,
    select.once = TRUE
)

```

Arguments

udata	A matrix or data frame containing the data in $[0,1]^d$.
lin.covs	A matrix or data frame containing the parametric (i.e., linear) covariates (default: <code>lin.covs = NULL</code>).
smooth.covs	A matrix or data frame containing the non-parametric (i.e., smooth) covariates (default: <code>smooth.covs = NULL</code>).
simplified	If <code>TRUE</code> (default), then a simplified vine is fitted (which is possible only if there are exogenous covariates). If <code>FALSE</code> , then a non-simplified vine is fitted.
type	<code>type = 0</code> (default) for a R-Vine and <code>type = 1</code> for a C-Vine.
familyset	An integer vector of pair-copula families to select from (the independence copula MUST NOT be specified in this vector unless one wants to fit an independence vine!). Not listed copula families might be included to better handle limit cases. If <code>familyset = NA</code> (default), selection among all possible families is performed. Coding of pair-copula families: 1 Gaussian, 2 Student t, 5 Frank, 301 Double Clayton type I (standard and rotated 90 degrees), 302 Double Clayton type II (standard and rotated 270 degrees), 303 Double Clayton type III (survival and rotated 90 degrees), 304 Double Clayton type IV (survival and rotated 270 degrees), 401 Double Gumbel type I (standard and rotated 90 degrees), 402 Double Gumbel type II (standard and rotated 270 degrees), 403 Double Gumbel type III (survival and rotated 90 degrees), 404 Double Gumbel type IV (survival and rotated 270 degrees).
rotations	If <code>TRUE</code> , all rotations of the families in <code>familyset</code> are included.
familycrit	Character indicating the criterion for bivariate copula selection. Possible choices: <code>familycrit = 'AIC'</code> (default) or <code>'BIC'</code> , as in BiCopSelect from the VineCopula package.
treecrit	Character indicating how pairs are selected in each tree. <code>treecrit = "tau"</code> uses the maximum spanning tree of the Kendall's tau (i.e., the tree of maximal overall dependence), <code>treecrit = "rho"</code> uses the Spearman's rho.
level	Numerical; Passed to gamBiCopSelect , it is the significance level of the test for removing individual predictors (default: <code>level = 0.05</code>) for each conditional pair-copula.
trunclevel	Integer; level of truncation.
tau	<code>TRUE</code> (default) for a calibration function specified for Kendall's tau or <code>FALSE</code> for a calibration function specified for the Copula parameter.
method	'NR' for Newton-Raphson and 'FS' for Fisher-scoring (default).
tol.rel	Relative tolerance for 'FS'/'NR' algorithm.
n.iters	Maximal number of iterations for 'FS'/'NR' algorithm.
parallel	<code>TRUE</code> (default) for parallel selection of copula family at each edge or <code>FALSE</code> for the sequential version. for the Copula parameter.

verbose	TRUE if informations should be printed during the estimation and FALSE (default) for a silent version. from mgcv .
select.once	if TRUE the GAM structure is only selected once, for the family that appears first in <code>familyset</code> .

Value

`gamVineSeqFit` returns a [gamVine-class](#) object.

See Also

[gamVineSeqFit](#), [gamVineCopSelect](#), [gamVine-class](#), [gamVineSimulate](#) and [gamBiCopSelect](#).

Examples

```
require(VineCopula)
set.seed(0)

## An example with a 3-dimensional GAM-Vine

# Sample size
n <- 1e3

# Define a R-vine tree structure matrix
d <- 3
Matrix <- c(2, 3, 1, 0, 3, 1, 0, 0, 1)
Matrix <- matrix(Matrix, d, d)
nnames <- paste("x", 1:d, sep = "")

# Copula families for each edge
fam <- c(301, 401, 1)

# Parameters for the first tree (two unconditional copulas)
par <- c(1, 2)

# Pre-allocate the GAM-Vine model list
count <- 1
model <- vector(mode = "list", length = d * (d - 1) / 2)

# The first tree contains only the two unconditional copulas
for (i in 1:(d - 1)) {
  model[[count]] <- list(family = fam[count], par = par[count], par2 = 0)
  count <- count + 1
}

# The second tree contains a unique conditional copula
# In this first example, we take a linear calibration function (10*x-5)

# Set-up a dummy dataset
tmp <- data.frame(u1 = runif(1e2), u2 = runif(1e2), x1 = runif(1e2))
```

```

# Set-up an arbitrary linear model for the calibration function
model[[count]] <- gamBiCopFit(tmp, ~x1, fam[count])$res

# Update the coefficients of the model
attr(model[[count]], "model")$coefficients <- c(-5, 10)

# Define gamVine object
GVC <- gamVine(Matrix = Matrix, model = model, names = nnames)
GVC
## Not run:
# Simulate new data
simData <- data.frame(gamVineSimulate(n, GVC))
colnames(simData) <- nnames

# Fit data using sequential estimation assuming true model known
summary(fitGVC <- gamVineSeqFit(simData, GVC))

# Fit data using structure selection and sequential estimation
summary(fitGVC2 <- gamVineStructureSelect(simData, simplified = FALSE))

## End(Not run)

```

logLik.gamBiCop*Extract the Log-likelihood from a gamBiCop Object***Description**

Function to extract the log-likelihood from an object of the class [gamBiCop](#) (note that the models are usually fitted by penalized likelihood maximization). This function is used by [AIC](#) and [BIC](#).

Usage

```
## S4 method for signature 'gamBiCop'
logLik(object, ...)
```

Arguments

<code>object</code>	An object of the class gamBiCop .
<code>...</code>	un-used in this class

Value

Standard `logLik` object: see [logLik](#).

See Also

[AIC](#) and [BIC](#).

`nobs.gamBiCop`*Extract the Number of Observations from gamBiCop Object***Description**

Extract the number of 'observations' from a model fit. This is principally intended to be used in computing the BIC (see [AIC](#)).

Usage

```
## S4 method for signature 'gamBiCop'
nobs(object, ...)
```

Arguments

<code>object</code>	An object of the class gamBiCop .
<code>...</code>	un-used in this class

Value

A single number, normally an integer.

See Also

[AIC](#) and [BIC](#).

`plot.gamBiCop`*Plot a gamBiCop Object***Description**

Plot from an object of the class [gamBiCop](#). The function is based on (see [plot.gam](#) from [mgcv](#)).

Usage

```
## S4 method for signature 'gamBiCop,ANY'
plot(x, y, ...)
```

Arguments

<code>x</code>	An object of the class gamBiCop .
<code>y</code>	Not used with this class.
<code>...</code>	additional arguments to be passed to plot.gam .

Value

This function simply generates plots.

See Also

[plot.gam](#) from [mgcv](#)).

plot.gamVine

Plot an Object of the Class gamVine

Description

Plot an object of the class [gamVine](#). The function is based on (see [plot.gam](#) from [mgcv](#)).

Usage

```
## S4 method for signature 'gamVine,ANY'  
plot(x, y, ...)
```

Arguments

- | | |
|-----|---|
| x | An object of the class gamVine . |
| y | Not used with this class. |
| ... | additional arguments to be passed to plot.gam . |

Value

This function simply generates plots.

See Also

[plot.gam](#) from [mgcv](#)).

RVM2GVC

*Transform an Object of the Class R-Vine into an Object of the Class
gamVine*

Description

Transform an object of the class [RVineMatrix](#) into an object of the class [gamVine](#).

Usage

```
RVM2GVC(RVM)
```

Arguments

RVM An object of the class [RVineMatrix](#).

Value

An object of the class [gamVine](#).

See Also

[RVineMatrix](#) and [gamVine](#).

summary.gamBiCop *Summary for a gamBiCop Object*

Description

Takes a [gamBiCop](#) object and produces various useful summaries from it.

Usage

```
## S4 method for signature 'gamBiCop'
summary(object, ...)
```

Arguments

object An object of the class [gamBiCop](#).
... unused in this class

Value

A useful summary (see [summary.gam](#) from [mgcv](#) for more details).

See Also

[summary.gam](#) from [mgcv](#)

`summary.gamVine` *Summary for an Object of the Class `gamVine`*

Description

Takes an object of the class `gamVine` and produces various useful summaries from it.

Usage

```
## S4 method for signature 'gamVine'  
summary(object, ...)
```

Arguments

<code>object</code>	An object of the class <code>gamVine</code> .
<code>...</code>	unused in this class

Value

A useful summary (see `summary.gam` from `mgcv` for more details).

See Also

`summary.gam` from `mgcv`

Index

AIC, 9, 51, 52
AIC, gamBiCop-method (AIC.gamBiCop), 8
AIC.gamBiCop, 8

BIC, 9, 51, 52
BIC, gamBiCop-method (BIC.gamBiCop), 9
BIC.gamBiCop, 9
BiCopEta2Par, 10, 11
BiCopPar2Eta, 10, 11
BiCopPar2Tau, 10, 11
BiCopSelect, 28, 34, 49
BiCopTau2Par, 10, 11

condBiCopSim, 12

dim, gamVine-method (dim.gamVine), 14
dim.gamVine, 14

EDF, 15

formula, gamBiCop-method
 (formula.gamBiCop), 15
formula.gam, 15, 19
formula.gamBiCop, 15

gam, 15–17, 19, 20, 28, 35, 43
gam.models, 19
gamBiCop, 8, 9, 15, 16, 16, 17, 20, 23, 26, 29,
 32, 33, 38, 51, 52, 54
gamBiCop-class, 16, 30
gamBiCopCDF, 17
gamBiCopFit, 12, 16, 17, 19, 26, 29, 35, 39, 43
gamBiCopPDF, 23
gamBiCopPredict, 16, 17, 23, 25
gamBiCopSelect, 27, 34, 49, 50
gamBiCopSimulate, 12, 16, 17, 20, 30
gamCopula (gamCopula-package), 2
gamCopula-package, 2
gamCopula.package (gamCopula-package), 2
gamObject, 15–17

gamVine, 14, 32, 32, 33, 38, 39, 43, 46, 47,
 53–55
gamVine-class, 33, 46
gamVineCopSelect, 32, 33, 33, 39, 43, 50
gamVineFamily, 38
gamVineNormalize, 38
gamVinePDF, 39
gamVineSeqFit, 32, 33, 35, 42, 50
gamVineSimulate, 32, 33, 35, 39, 43, 46, 50
gamVineStructureSelect, 32, 33, 35, 39, 43,
 48

logLik, 51
logLik, gamBiCop-method
 (logLik.gamBiCop), 51
logLik.gamBiCop, 51

mgcv, 15–17, 19, 20, 23, 25–27, 30, 33, 35, 39,
 42, 43, 48, 50, 52–55

nobs, gamBiCop-method (nobs.gamBiCop), 52
nobs.gamBiCop, 52

plot, gamBiCop, ANY-method
 (plot.gamBiCop), 52
plot, gamVine, ANY-method (plot.gamVine),
 53
plot.gam, 52, 53
plot.gamBiCop, 52
plot.gamVine, 53
predict.gam, 17, 23, 25, 26, 30, 39

RVineMatrix, 32, 33, 53, 54
RVM2GVC, 53

summary, gamBiCop-method
 (summary.gamBiCop), 54
summary, gamVine-method
 (summary.gamVine), 55
summary.gam, 54, 55
summary.gamBiCop, 54

`summary.gamVine`, [55](#)
`VineCopula`, [28](#), [34](#), [49](#)