

Package ‘ggiraphExtra’

October 13, 2022

Type Package

Title Make Interactive 'ggplot2'. Extension to 'ggplot2' and 'ggiraph'

Version 0.3.0

Maintainer Keon-Woong Moon <cardiomoon@gmail.com>

URL <https://github.com/cardiomoon/ggiraphExtra>

Depends R (>= 2.10)

Imports ggplot2 (>= 2.2.0), ggiraph (>= 0.3.2), scales, reshape2,
plyr, mycor, ppcor, grid, mgcv, sjlabelled, sjmisc, stringr,
tidyR, purrr, dplyr, magrittr, RColorBrewer

Suggests TH.data, ggforce, webshot, ztable, moonBook, maps, gcookbook,
knitr, rmarkdown, testthat

Description

Collection of functions to enhance 'ggplot2' and 'ggiraph'. Provides functions for exploratory plots.
All plot can be a 'static' plot or an 'interactive' plot using 'ggiraph'.

License GPL-3

Encoding UTF-8

LazyData true

RoxxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Keon-Woong Moon [aut, cre]

Repository CRAN

Date/Publication 2020-10-06 07:00:02 UTC

R topics documented:

addLabelDf	3
browsers	3
coord_radar	4
getMapping	4

ggAncova	5
ggArea	6
ggBar	7
ggBoxplot	8
ggCaterpillar	9
ggChoropleth	10
ggCLE	11
ggCor	12
ggDensity	14
ggDonut	15
ggDot	16
ggEffect	18
ggErrorBar	19
ggHeatmap	20
ggHSD	22
ggPair	23
ggPie	24
ggPieDonut	25
ggPoints	26
ggPredict	28
ggRadar	29
ggRose	30
ggSpine	31
ggViolin	33
makeEq	34
model2df	35
myscale	35
myscale2	36
newColName	36
num2cut	37
num2factorDf	37
p2chr	38
palette2colors	38
pastecolon	38
pastecomma	39
rescale_df	39
rose	40
subcolors	40
summarySE	41
taco	41
theme_clean	42
theme_clean2	42
unselectNumeric	43

addLabelDf*Add value labels to the data.frame*

Description

Add value labels to the data.frame

Usage

```
addLabelDf(data, mapping = NULL)
```

Arguments

data	A data.frame
mapping	Set of aesthetic mappings created by aes or aes_.

browsers*Browser market share 2011*

Description

A phony dataset measuring browser market share

Usage

```
browsers
```

Format

A data.frame with 12 rows and 3 columns

browser browser

version browser version

share market share, in percentage

coord_radar

The radar coordinate system is a modification of polar coordinate system, commonly used for radar chart

Description

The radar coordinate system is a modification of polar coordinate system, commonly used for radar chart

Usage

```
coord_radar(theta = "x", start = 0, direction = 1)
```

Arguments

theta	variable to map angle to (x or y)
start	offset of starting point from 12 o'clock in radians
direction	1, clockwise; -1, counterclockwise

getMapping

extract variable name from mapping, aes

Description

extract variable name from mapping, aes

Usage

```
getMapping(mapping, varname)
```

Arguments

mapping	aesthetic mapping
varname	variable name to extract

Value

variable name in character

Examples

```
require(ggplot2)
mapping=aes(colour=sex)
mapping=aes(x=c(Sepal.Length,Sepal.Width,Petal.Length,Petal.Width))
getMapping(mapping,"colour")
getMapping(mapping,"x")
```

ggAncova

Make an interactive plot for an ANCOVA model

Description

Make an interactive plot for an ANCOVA model

Usage

```
ggAncova(x, ...)

## Default S3 method:
ggAncova(x, mapping, use.label = TRUE, use.labels = TRUE, ...)

## S3 method for class 'formula'
ggAncova(x, data, ...)

## S3 method for class 'lm'
ggAncova(x, label = NULL, digits = 1, interactive = FALSE, ...)
```

Arguments

x	an object
...	additional arguments passed to the generic function
mapping	Set of aesthetic mappings created by aes or aes_.
use.label	Logical. Whether or not use column label in case of labelled data
use.labels	Logical. Whether or not use value labels in case of labelled data
data	a data.frame
label	A character string of column name be assigned to the label
digits	An integer indicating the number of decimal places
interactive	A logical value. If TRUE, an interactive plot will be returned

Methods (by class)

- **default:** Make an interactive plot for an ANCOVA model
- **formula:** Make an interactive plot for an ANCOVA model
- **lm:** Make an interactive plot for an ANCOVA model

Examples

```
require(moonBook)
require(ggplot2)
require(ggiraph)
ggAncova(radial,aes(age,NTAV,color=sex),interactive=TRUE)
fit=lm(NTAV~age+HBP,data=radial)
```

```
ggAncova(fit,interactive=TRUE)
ggAncova(NTAV~age+DM,data=radial)
```

ggArea*Draw an interactive area plot***Description**

Draw an interactive area plot

Usage

```
ggArea(
  data,
  mapping,
  position = "stack",
  palette = "Blues",
  reverse = TRUE,
  alpha = 0.4,
  size = 0.3,
  use.label = TRUE,
  use.labels = TRUE
)
```

Arguments

<code>data</code>	A <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>position</code>	Either "stack" or "fill"
<code>palette</code>	A character string indicating the color palette
<code>reverse</code>	If true, reverse palette colors
<code>alpha</code>	Transparency
<code>size</code>	Line size
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data

Value

An area plot

Examples

```
require(gcookbook)
require(ggplot2)
ggArea(uspopage,aes(x=Year,y=Thousands,fill=AgeGroup))
ggArea(uspopage,aes(x=Year,y=Thousands,fill=AgeGroup),position="fill")
```

ggBar	<i>Draw an interactive barplot</i>
-------	------------------------------------

Description

Draw an interactive barplot

Usage

```
ggBar(  
  data,  
  mapping,  
  stat = "count",  
  position = "stack",  
  palette = NULL,  
  horizontal = FALSE,  
  yangle = 0,  
  xangle = 0,  
  maxylev = 6,  
  addlabel = FALSE,  
  labelsize = 5,  
  polar = FALSE,  
  reverse = FALSE,  
  use.label = TRUE,  
  use.labels = TRUE,  
  interactive = FALSE,  
  ...  
)
```

Arguments

data	A data.frame
mapping	Set of aesthetic mappings created by aes or aes_.
stat	The statistical transformation to use on the data for this layer, as a string c("count","identity")
position	Position adjustment. One of the c("fill","stack","dodge")
palette	A character string indicating the color palette
horizontal	A logical value. If TRUE,a horizontal bar plot will be returned
yangle	An integer. The value will be used adjust the angle of axis.text.y
xangle	An integer. The value will be used adjust the angle of axis.text.x
maxylev	integer indicating threshold of unique value to be treated as a categorical variable
addlabel	A logical value. If TRUE, label will be added to the plot
labelsize	label size
polar	A logical value. If TRUE, coord_polar() function will be added

<code>reverse</code>	If true, reverse palette colors
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned
<code>...</code>	other arguments passed on to geom_bar_interactive.

Value

An interactive barplot

Examples

```
require(moonBook)
require(ggplot2)
require(ggiraph)
require(plyr)
ggBar(acs,aes(x=Dx,fill=smoking),interactive=TRUE,width=1,colour="white",size=0.2,polar=TRUE)
ggBar(acs,aes(x=Dx,fill=smoking),position="fill",addlabel=TRUE,horizontal=TRUE,width=0.5)
ggBar(acs,aes(x=Dx,fill=smoking),position="dodge",interactive=TRUE,addlabel=TRUE)
ggBar(acs,aes(x=Dx,fill=smoking),position="fill",addlabel=TRUE)
ggBar(rose,aes(x=Month,fill=group,y=value),stat="identity",polar=TRUE,palette="Reds",width=1,
      color="black",size=0.1,reverse=TRUE,interactive=TRUE)
```

ggBoxplot

Draw boxplots of a data.frame

Description

Draw boxplots of a data.frame

Usage

```
ggBoxplot(
  data,
  mapping = NULL,
  rescale = FALSE,
  horizontal = FALSE,
  interactive = FALSE,
  addMean = TRUE,
  position = 0.9,
  use.label = TRUE,
  use.labels = TRUE,
  ...
)
```

Arguments

data	a data.frame
mapping	Set of aesthetic mappings created by aes or aes_.
rescale	if true, rescale the data.frame
horizontal	if true, horizontal boxplots will be made
interactive	A logical value. If TRUE, an interactive plot will be returned
addMean	Whether add mean point on the plot
position	An integer. Uses as argument of position_dodge()
use.label	Logical. Whether or not use column label in case of labelled data
use.labels	Logical. Whether or not use value labels in case of labelled data
...	other arguments passed on to geom_boxplot_interactive

Examples

```
require(ggplot2)
require(ggiraph)
require(reshape2)
ggBoxplot(mtcars, rescale=TRUE)
ggBoxplot(mtcars, aes(x=c(mpg, cyl, disp, hp, drat), color=am), rescale=TRUE)
ggBoxplot(mtcars, aes(x=c(mpg, cyl, disp, hp, drat)), rescale=TRUE)
ggBoxplot(mtcars, rescale=TRUE, interactive=TRUE)
ggBoxplot(mtcars, horizontal=TRUE, interactive=TRUE)
```

ggCatepillar

Make an interactive catepillar plot

Description

Make an interactive catepillar plot

Usage

```
ggCatepillar(
  data,
  mapping,
  errorbar = "se",
  interactive = FALSE,
  digits = 1,
  flip = FALSE,
  use.label = TRUE,
  use.labels = TRUE
)
```

Arguments

<code>data</code>	a data.frame
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>errorbar</code>	which value is displayed with errorbar : "se" or "sd"
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned
<code>digits</code>	An integer indicating the number of decimal places
<code>flip</code>	Logical. If TRUE, <code>coord_flip()</code> function is used to make a horizontal plot
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data

Value

An interactive caterpillar plot

Examples

```
require(moonBook)
require(ggiraph)
require(ggplot2)
ggCaterpillar(acs,aes(Dx,age,color=HBP))
ggCaterpillar(acs,aes(c(Dx,sex),age,color=HBP),interactive=TRUE,flip=TRUE,use.labels=FALSE)
ggCaterpillar(acs,aes(age,height,color=sex),errorbar=FALSE,interactive=TRUE)
```

`ggChoropleth`

Draw an interactive choropleth map

Description

Draw an interactive choropleth map

Usage

```
ggChoropleth(
  data,
  mapping,
  map,
  palette = "OrRd",
  reverse = FALSE,
  color = "grey50",
  title = "",
  digits = 1,
  interactive = FALSE,
  ...
)
```

Arguments

data	a data.frame
mapping	Set of aesthetic mappings created by aes or aes_. Passed on geom_map_interactive. Required mappings are map_id and fill. Possible mapping is facet.
map	a map maybe a result of map_data()
palette	A palette name used for discrete fill var, Default value is "OrRd"
reverse	If true, reverse palette colors
color	A name of color of polygon, Default value is "grey50"
title	A title
digits	An integer indicating the number of decimal places
interactive	Logical. If positive an interactive map will be made
...	other arguments passed on to geom_map_interactive

Examples

```
#crimes <- data.frame(state = tolower(rownames(USArrests)), USArrests)
#require(ggplot2)
#require(ggiraph)
#require(maps)
#require(mapproj)
#require(reshape2)
#require(RColorBrewer)
#states_map <- map_data("state")
#ggChoropleth(crimes,aes(fill=Murder, map_id=state),map=states_map,interactive=TRUE)
#ggChoropleth(crimes,aes(fill=c(Murder,Rape), map_id=state),map=states_map,interactive=TRUE)
#ggChoropleth(crimes,aes(map_id=state),map=states_map,palette="OrRd",interactive=TRUE)
```

ggCLE

Draw a cleveland dot plot

Description

Draw a cleveland dot plot

Usage

```
ggCLE(
  data,
  mapping,
  reorderByX = TRUE,
  no = NULL,
  start = 0.99,
  interactive = FALSE,
  decreasing = TRUE,
  use.label = TRUE,
```

```
use.labels = TRUE,
...
)
```

Arguments

data	a data.frame
mapping	Set of aesthetic mappings created by aes or aes_.
reorderByX	If true, the data is reordered by x variable
no	Number of data be drawn in plot
start	start point of x axis as ratio to minimum x variable
interactive	A logical value. If TRUE, an interactive plot will be returned
decreasing	Should the sort order be increasing or decreasing?
use.label	Logical. Whether or not use column label in case of labelled data
use.labels	Logical. Whether or not use value labels in case of labelled data
...	other arguments passed on to geom_point_interactive

Examples

```
require(ggplot2)
require(ggiraph)
ggCLE(data=mtcars,aes(x=mpg),decreasing=FALSE,interactive=TRUE)
ggCLE(data=mtcars,aes(x=mpg,color=am,facet=am),interactive=TRUE)
if(requireNamespace("gcookbook",quietly=TRUE)){
  require(gcookbook)
  ggCLE(data=tophitters2001,aes(x=avg,y=name,color=lg,facet=lg),no=30,interactive=TRUE)
}
```

ggCor

Draw a heatmap of correlation test

Description

Draw a heatmap of correlation test

Usage

```
ggCor(
  data,
  what = 1,
  label = 0,
  colors = NULL,
  title = TRUE,
  mode = 2,
  digits = 2,
```

```

interactive = FALSE,
yreverse = TRUE,
xangle = 45,
yangle = 0,
use.label = FALSE,
...
)

```

Arguments

data	A data.frame
what	if 1, correlation, if 2, partial correlation, if 3, semi-partial correlation
label	if 0, no label(default), if 1, use r value as label, if 2, use r value with significant mark as label
colors	colors for low, mid and high correlation values
title	if true, add title to the heatmap
mode	1 or 2
digits	The number of decimal place
interactive	A logical value. If TRUE, an interactive plot will be returned
yreverse	If true, reverse y axis
xangle	x-axis text angle
yangle	y-axis text angle
use.label	Logical whether or not use label in case of labelled data
...	further arguments to be passed to cor.test

Examples

```

require(mycor)
require(ggplot2)
require(ggiraph)
require(ppcor)
ggCor(iris,digits=3,label=3)
ggCor(iris,what=3,digits=3,label=3)
ggCor(iris,label=3,interactive=TRUE)
ggCor(mtcars,interactive=TRUE)
ggCor(mtcars,mode=2,interactive=TRUE)
ggCor(iris,method="pearson",interactive=TRUE)

```

ggDensity*Make a density plot with histogram*

Description

Make a density plot with histogram

Usage

```
ggDensity(
  data,
  mapping,
  linecolor = "red",
  addhist = TRUE,
  use.label = TRUE,
  use.labels = TRUE
)
```

Arguments

<code>data</code>	a <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>linecolor</code>	Color of density curve
<code>addhist</code>	Whether add histogram or not
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data

Examples

```
require(ggplot2)
require(moonBook)
ggDensity(acs,aes(x=age))
ggDensity(acs,aes(x=age,color=sex,fill=sex),addhist=FALSE)
ggDensity(acs,aes(x=age,color=sex,fill=sex))
ggDensity(acs,aes(x=age,fill=sex),addhist=FALSE)
ggDensity(acs,aes(x=age,color=sex))
```

ggDonut*Draw a Donut plot*

Description

Draw a Donut plot

Usage

```
ggDonut(  
  data,  
  mapping,  
  addDonutLabel = TRUE,  
  showRatio = TRUE,  
  polar = TRUE,  
  labelposition = 1,  
  labelsize = 3,  
  title = "",  
  use.label = TRUE,  
  use.labels = TRUE,  
  alpha = 0.7,  
  interactive = FALSE,  
  palette = NULL,  
  reverse = FALSE,  
  xmin = 3,  
  xmax = 4,  
  start = 3 * pi/2,  
  direction = 1,  
  colour = "white",  
  explode = NULL,  
  explodePos = 0.5,  
  ...  
)
```

Arguments

<code>data</code>	A <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>addDonutLabel</code>	A logical value. If TRUE, labels are added to the Donuts
<code>showRatio</code>	A logical value. If TRUE, Ratios are added to the DonutLabels
<code>polar</code>	A logical value. If TRUE, <code>coord_polar()</code> function will be added
<code>labelposition</code>	A number indicating the label position
<code>labelsize</code>	label size. default value is 3
<code>title</code>	Plot title
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data

use.labels	Logical. Whether or not use value labels in case of labelled data
alpha	transparency of geom_rect
interactive	A logical value. If TRUE, an interactive plot will be returned
palette	A character string indicating the color palette
reverse	If true, reverse palette colors
xmin	minimum x position
xmax	maximum x position
start	offset of starting point from 12 o'clock in radians
direction	1, clockwise; -1, counterclockwise
colour	colour of geom_rect
explode	number of donuts to explode
explodePos	explode position
...	further arguments to be passed to geom_rect_interactive

Value

An interactive Pie and Donut plot

Examples

```
require(ggplot2)
require(ggiraph)
require(plyr)
ggDonut(browsers,aes(donuts=version,count=share))
ggDonut(browsers,aes(donuts=version,count=share),palette="Reds",explode=c(2,4,6),labelposition=0)
```

ggDot

Draw a Wilkinson dot plot

Description

Draw a Wilkinson dot plot

Usage

```
ggDot(
  data,
  mapping,
  stackdir = "center",
  binaxis = "y",
  binwidth = 0.5,
  method = "dotdensity",
  position = 0.2,
  boxwidth = 0.25,
```

```

  boxfill = NULL,
  use.label = TRUE,
  use.labels = TRUE,
  ...
)

```

Arguments

<code>data</code>	a <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>stackdir</code>	which direction to stack the dots. "up" (default), "down", "center", "centerhole" (centered, but with dots aligned)
<code>binaxis</code>	The axis to bin along, "x" (default) or "y"
<code>binwidth</code>	When method is "dotdensity", this specifies maximum bin width. When method is "histodot", this specifies bin width. Defaults to 1/30 of the range of the data
<code>method</code>	"dotdensity" (default) for dot-density binning, or "histodot" for fixed bin widths (like <code>stat_bin</code>)
<code>position</code>	Position adjustment. If 0, no adjustment.
<code>boxwidth</code>	The width of boxplot
<code>boxfill</code>	Fill color of boxplot
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data
...	other arguments passed on to <code>geom_dotplot</code>

Examples

```

require(ggplot2)
if(requireNamespace("gcookbook", quietly=TRUE)){ # for data heightweight
  require(gcookbook)
  ggDot(heightweight, aes(sex, heightIn, fill=sex), boxfill="white", binwidth=0.4)
  ggDot(heightweight, aes(heightIn))
  ggDot(heightweight, aes(x=heightIn, fill=sex))
}
require(moonBook) #for use data radial
ggDot(radial, aes(x=sex, y=height, fill=sex), boxfill="white", position=0, binwidth=1, boxwidth=1)
ggDot(radial, aes(x=height, fill=sex), binwidth=1)
ggDot(acs, aes(x=sex, y=age, color=sex))
ggDot(acs, aes(x=Dx, y=age, color=Dx))

```

ggEffect	<i>Visualize the effect of interaction between two continuous independent variables on a response variable</i>
----------	--

Description

Visualize the effect of interaction between two continuous independent variables on a response variable

Usage

```
ggEffect(x, ...)

## Default S3 method:
ggEffect(x, mapping, use.label = TRUE, use.labels = TRUE, ...)

## S3 method for class 'formula'
ggEffect(x, data, ...)

## S3 method for class 'lm'
ggEffect(
  x,
  no = 1,
  probs = c(0.1, 0.5, 0.9),
  point = TRUE,
  xvalue = NULL,
  digits = 2,
  use.rownames = FALSE,
  interactive = FALSE,
  ...
)
```

Arguments

x	Object to ggEffect
...	additional arguments passed to the generic function
mapping	Set of aesthetic mappings created by aes or aes_.
use.label	Logical. Whether or not use column label in case of labelled data
use.labels	Logical. Whether or not use value labels in case of labelled data
data	A data.frame
no	an integer
probs	A vector of probability weights for obtaining the elements of the vector being sampled. Default value is c(0.10,0.5,0.90)
point	A logical value. If TRUE, draw points

xvalue	A numeric vector
digits	An integer indicating the number of decimal places
use.rownames	If TRUE, use rownames in label
interactive	A logical value. If TRUE, an interactive plot will be returned

Value

An interactive plot showing interaction

Methods (by class)

- **default:** Visualize the effect of interaction between two continuous independent variables on a response variable
- **formula:** Visualize the effect of interaction between two continuous independent variables on a response variable
- **lm:** Visualize the effect of interaction between two continuous independent variables on a response variable

Examples

```
require(ggplot2)
require(ggiraph)
ggEffect(mtcars,aes(x=wt,y=mpg,color=hp))
ggEffect(mtcars,aes(x=wt,y=mpg,color=hp),interactive=TRUE)
require(moonBook)
ggEffect(acs,aes(x=height,y=weight,color=smoking))
ggEffect(acs,aes(x=height,y=weight,color=smoking),interactive=TRUE)
require(ggplot2)
require(ggiraph)
require(moonBook)
ggEffect(NTAV~age*smoking,data=radial)
require(moonBook)
require(ggplot2)
require(ggiraph)
fit=lm(age~sex*smoking,data=acs)
ggEffect(fit,interactive=TRUE)
ggEffect(radial,aes(x=age,y=NTAV,color=smoking))
ggEffect(radial,aes(x=age,y=NTAV,color=smoking),interactive=TRUE)
```

Description

Make an interactive bar plot with error bar

Usage

```
ggErrorBar(
  data,
  mapping,
  interactive = FALSE,
  digits = 1,
  mode = 2,
  errorbar = "se",
  use.label = TRUE,
  use.labels = TRUE
)
```

Arguments

<code>data</code>	A <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>interactive</code>	A logical value. If <code>TRUE</code> , an interactive plot will be returned
<code>digits</code>	An integer indicating the number of decimal places
<code>mode</code>	if 2, two-sided error bar will be displayed, if 1 one-sided errorbar will be displayed
<code>errorbar</code>	which value is displayed with <code>errorbar</code> :"se" or "sd"
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data

Value

An interactive caterpillar plot

Examples

```
require(ggplot2)
require(ggiraph)
ggErrorBar(mpg,aes(x=drv,y=cty))
ggErrorBar(mpg,aes(x=drv,y=hwy,color=cyl),mode=1,interactive=TRUE,errorbar="sd")
```

`ggHeatmap`

Make an interactive Heatmap

Description

Make an interactive Heatmap

Usage

```
ggHeatmap(
  data,
  mapping,
  stat = "count",
  palette = "Blues",
  reverse = FALSE,
  addlabel = FALSE,
  polar = FALSE,
  interactive = FALSE,
  yangle = 0,
  color = "grey50",
  size = 0.1,
  use.label = TRUE,
  use.labels = TRUE,
  ...
)
```

Arguments

<code>data</code>	A <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>stat</code>	The statistical transformation to use on the data for this layer, as a string c("count", "identity")
<code>palette</code>	A palette name used for discrete fill var, Default value is "Blues"
<code>reverse</code>	If true, reverse palette colors
<code>addlabel</code>	A logical value. If TRUE, label will be added to the plot
<code>polar</code>	A logical value. If TRUE, <code>coord_polar()</code> function will be added
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned
<code>yangle</code>	A integer. The value will be used adjust the angle of <code>axis.text.y</code>
<code>color</code>	Color argument passed on to <code>geom_rect_interactive</code> .
<code>size</code>	Size argument passed on to <code>geom_rect_interactive</code> .
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data
<code>...</code>	other arguments passed on to <code>geom_rect_interactive</code> .

Value

An interactive barplot

Examples

```
require(moonBook)
require(ggplot2)
require(ggiraph)
require(sjmisc)
```

```
ggHeatmap(acs,aes(x=Dx,y=smoking),addlabel=TRUE,interactive=TRUE)
ggHeatmap(acs,aes(x=sex,y=Dx,fill=age),addlabel=TRUE,interactive=TRUE)
ggHeatmap(rose,aes(x=Month,y=group,fill=value),stat="identity",addlabel=TRUE)
ggHeatmap(rose,aes(x=Month,y=group,fill=value),addlabel=TRUE)
ggHeatmap(taco,aes(x=AgeGroup,y=Filling,fill=Rating,facet=ShellType),color="grey50",stat="identity")
```

ggHSD*Draw Tukey Honest Significant Differences plot***Description**

Draw Tukey Honest Significant Differences plot

Usage

```
ggHSD(tukey, no = 1, digits = 2, interactive = FALSE)
```

Arguments

<code>tukey</code>	A object of class "TukeyHSD", the result of TukeyHSD()
<code>no</code>	An integer specify the order of list
<code>digits</code>	integer indicating the number of decimal places
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned

Value

A (interactive) ggplot

Examples

```
require(ggplot2)
fm1 <- aov(breaks ~ wool + tension, data = warpbreaks)
result=TukeyHSD(fm1, "tension", ordered = TRUE)
str(result)
ggHSD(result)
ggHSD(result,interactive=TRUE)
```

ggPair *Make an interactive scatter and line plot*

Description

Make an interactive scatter and line plot

Usage

```
ggPair(  
  data,  
  mapping = NULL,  
  rescale = FALSE,  
  idcolor = TRUE,  
  horizontal = FALSE,  
  use.label = FALSE,  
  use.labels = TRUE,  
  includeFactor = TRUE,  
  includeAll = FALSE,  
  interactive = FALSE  
)
```

Arguments

data	a data.frame
mapping	Set of aesthetic mappings created by aes or aes_.
rescale	if true, rescale the data.frame
idcolor	Logical. If TRUE, row numbers uses as a color variable
horizontal	Logical. If TRUE, coord_flip() function is used to make a horizontal plot
use.label	Logical. Whether or not use column label in case of labelled data
use.labels	Logical. Whether or not use value labels in case of labelled data
includeFactor	Logical. Whether or not include factor variables
includeAll	Logical. Whether or not include all variables
interactive	Logical. If TRUE, an interactive plot using girafe() function will be returned

Examples

```
require(ggplot2)  
require(ggiraph)  
require(sjmisc)  
require(moonBook)  
ggPair(iris,rescale=TRUE,horizontal=TRUE)  
ggPair(acs,aes(colour=smoking),horizontal=TRUE,rescale=TRUE)  
ggPair(radial,aes(color=male),horizontal=TRUE,rescale=TRUE)  
ggPair(mtcars,vertical=TRUE,rescale=TRUE)
```

```
ggPair(iris,rescale=TRUE,horizontal=TRUE,interactive=TRUE)
ggPair(iris,aes(color=Species),rescale=TRUE,interactive=TRUE)
ggPair(iris,aes(x=c(Sepal.Length,Sepal.Width),color=Species),horizontal=TRUE,interactive=TRUE)
```

ggPie*Draw a pie plot***Description**

Draw a pie plot

Usage

```
ggPie(
  data,
  mapping,
  addPieLabel = TRUE,
  showRatioPie = TRUE,
  showRatioPieAbove10 = TRUE,
  title = "",
  labelposition = 1,
  polar = TRUE,
  use.label = TRUE,
  use.labels = TRUE,
  interactive = FALSE
)
```

Arguments

data	A data.frame
mapping	Set of aesthetic mappings created by aes or aes_.
addPieLabel	A logical value. If TRUE, labels are added to the Pies
showRatioPie	A logical value. If TRUE, Ratios are added to the PieLabels
showRatioPieAbove10	A logical value. If TRUE, labels are added to the Pies with ratio above 10.
title	Plot title
labelposition	A number indicating the label position
polar	A logical value. If TRUE, coord_polar() function will be added
use.label	Logical. Whether or not use column label in case of labelled data
use.labels	Logical. Whether or not use value labels in case of labelled data
interactive	A logical value. If TRUE, an interactive plot will be returned

Value

An interactive pie plot

Examples

```
require(ggplot2)
require(ggiraph)
require(plyr)
require(moonBook)
ggPie(data=browsers,aes(pies=browser,count=share))
ggPie(data=acs,aes(pies=Dx))
```

ggPieDonut *Draw a Pie and Donut plot*

Description

Draw a Pie and Donut plot

Usage

```
ggPieDonut(
  data,
  mapping,
  addPieLabel = TRUE,
  addDonutLabel = TRUE,
  showRatioDonut = TRUE,
  showRatioPie = TRUE,
  showRatioPieAbove10 = TRUE,
  title = "",
  labelposition = 1,
  polar = TRUE,
  use.label = TRUE,
  use.labels = TRUE,
  interactive = FALSE
)
```

Arguments

data	A data.frame
mapping	Set of aesthetic mappings created by aes or aes_.
addPieLabel	A logical value. If TRUE, labels are added to the Pies
addDonutLabel	A logical value. If TRUE, labels are added to the Donuts
showRatioDonut	A logical value. If TRUE, Ratios are added to the DonutLabels
showRatioPie	A logical value. If TRUE, Ratios are added to the PieLabels
showRatioPieAbove10	A logical value. If TRUE, labels are added to the Pies with ratio above 10.
title	Plot title
labelposition	A number indicating the label position

polar	A logical value. If TRUE, coord_polar() function will be added
use.label	Logical. Whether or not use column label in case of labelled data
use.labels	Logical. Whether or not use value labels in case of labelled data
interactive	A logical value. If TRUE, an interactive plot will be returned

Value

An interactive Pie and Donut plot

Examples

```
require(ggplot2)
require(ggiraph)
require(plyr)
require(moonBook)
ggPieDonut(acs,aes(pies=Dx,donuts=smoking))
ggPieDonut(acs,aes(pies=smoking))
ggPieDonut(browsers,aes(pies=browser,donuts=version,count=share))
ggPieDonut(browsers,aes(x=c(browser,version),y=share),interactive=TRUE)
```

ggPoints

Make an interactive scatterplot with regression line(s)

Description

Make an interactive scatterplot with regression line(s)

Usage

```
ggPoints(
  data,
  mapping,
  smooth = TRUE,
  se = TRUE,
  method = "auto",
  formula = y ~ x,
  fullrange = FALSE,
  level = 0.95,
  use.count = FALSE,
  maxfactorno = 6,
  digits = 2,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  use.label = TRUE,
  use.labels = TRUE,
  tooltip = NULL,
```

```
  interactive = FALSE,
  ...
)
```

Arguments

<code>data</code>	a data.frame
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>smooth</code>	Logical. Add regression lines to the scatter plot
<code>se</code>	Logical. display confidence interval around linear regression? (TRUE by default)
<code>method</code>	smoothing method (function) to use, eg. "lm", "glm", "gam", "loess", "rlm"
<code>formula</code>	formula to use in smoothing function, eg. $y \sim x$, $y \sim \text{poly}(x, 2)$, $y \sim \log(x)$
<code>fullrange</code>	should the fit span the full range of the plot, or just the data
<code>level</code>	level of confidence interval to use (0.95 by default)
<code>use.count</code>	Logical. If true use <code>geom_count</code> instead of <code>geom_point_interactive</code>
<code>maxfactorno</code>	An integer. Maximum unique number of a numeric vector treated as a factor
<code>digits</code>	integer indicating the number of decimal places
<code>title</code>	The text for plot title
<code>subtitle</code>	The text for plot subtitle
<code>caption</code>	The text for plot caption
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data
<code>tooltip</code>	A character string of column name be included in tooltip. Default value is NULL
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned
<code>...</code>	other arguments passed on to <code>geom_point</code>

Examples

```
require(ggplot2)
require(ggiraph)
require(plyr)
ggPoints(aes(x=wt,y=mpg,fill=am),data=mtcars)
ggPoints(aes(x=wt,y=mpg),data=mtcars)
ggPoints(aes(x=wt,y=mpg,fill=am),data=mtcars,method="lm",interactive=TRUE)
ggPoints(aes(x=wt,y=mpg,color=am),data=mtcars,interactive=TRUE)
```

ggPredict*Visualize predictions from the multiple regression models.***Description**

Visualize predictions from the multiple regression models.

Usage

```
ggPredict(
  fit,
  colorn = 4,
  point = NULL,
  jitter = NULL,
  se = FALSE,
  show.summary = FALSE,
  colorAsFactor = FALSE,
  digits = 2,
  interactive = FALSE,
  ...
)
```

Arguments

<code>fit</code>	a model object for which prediction is desired.
<code>colorn</code>	Integer. Number of subgroups of color variables.
<code>point</code>	Logical. Whether or not draw each point
<code>jitter</code>	Logical. Whether or not jitter points
<code>se</code>	Logical. Whether or not draw se
<code>show.summary</code>	Logical. Whether or not show summary
<code>colorAsFactor</code>	Logical. Whether or not treat color variable as categorical variable
<code>digits</code>	An integer indicating the number of decimal places
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned
<code>...</code>	additional arguments affecting the predictions produced.

Examples

```
require(moonBook)
require(ggplot2)
require(ggiraph)
require(plyr)
fit=lm(NTAV~age*weight,data=radial)
fit=lm(NTAV~age*weight*DM,data=radial)
fit=lm(NTAV~age+DM,data=radial)
ggPredict(fit,interactive=TRUE)
```

```

require(TH.data)
fit=glm(cens~pnodes*horTh,data=GBSG2,family=binomial)
ggPredict(fit,se=TRUE)
fit1=glm(cens~pnodes*age,data=GBSG2,family=binomial)
ggPredict(fit1)
ggPredict(fit1,colorn=100,jitter=FALSE,interactive=TRUE)
fit2=glm(cens~pnodes*age*horTh,data=GBSG2,family=binomial)
ggPredict(fit2,colorn=100,jitter=FALSE,interactive=TRUE)

```

ggRadar

*Draw a radar chart***Description**

Draw a radar chart

Usage

```

ggRadar(
  data,
  mapping = NULL,
  rescale = TRUE,
  legend.position = "top",
  colour = "red",
  alpha = 0.3,
  size = 3,
  ylim = NULL,
  scales = "fixed",
  use.label = FALSE,
  interactive = FALSE,
  ...
)

```

Arguments

<code>data</code>	A <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>rescale</code>	A logical value. If <code>TRUE</code> , all continuous variables in the <code>data.frame</code> are rescaled.
<code>legend.position</code>	Legend position. One of <code>c("top","bottom","left","right","none")</code>
<code>colour</code>	A name of color to be assigned as a color variable
<code>alpha</code>	Any numbers from 0 (transparent) to 1 (opaque)
<code>size</code>	Point size
<code>ylim</code>	A numeric vector of length 2, giving the y coordinates ranges.
<code>scales</code>	should Scales be fixed ("fixed", the default), free ("free"), or free in one dimension ("free_x", "free_y")

<code>use.label</code>	Logical. Whether or not use column label
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned
<code>...</code>	other arguments passed on to geom_point

Value

An interactive radar plot

Examples

```
require(ggplot2)
require(ggiraph)
require(plyr)
require(reshape2)
require(moonBook)
require(sjmisc)
ggRadar(data=iris,aes(group=Species))
ggRadar(data=mtcars,interactive=TRUE)
ggRadar(data=mtcars,aes(colour=am,facet=cyl),interactive=TRUE)
ggRadar(data=acs,aes(colour=Dx,facet=Dx))
ggRadar(iris,aes(x=c(Sepal.Length,Sepal.Width,Petal.Length,Petal.Width)))
```

`ggRose`

Draw an interactive Rose plot

Description

Draw an interactive Rose plot

Usage

```
ggRose(data, mapping, palette = "Reds", color = "black", size = 0.1, ...)
```

Arguments

<code>data</code>	A data.frame
<code>mapping</code>	Set of aesthetic mappings created by aes or aes_.
<code>palette</code>	A character string indicating the color palette
<code>color</code>	Bar colour
<code>size</code>	Bar size
<code>...</code>	other arguments passed on to geom_bar_interactive.

Value

An interactive Rose plot

Examples

```
require(moonBook)
require(ggplot2)
require(ggiraph)
require(plyr)
ggRose(rose,aes(x=Month,fill=group,y=value),stat="identity",interactive=TRUE)
ggRose(acs,aes(x=Dx,fill=smoking),interactive=TRUE)
```

ggSpine

Draw an interactive spinogram

Description

Draw an interactive spinogram

Usage

```
ggSpine(
  data,
  mapping,
  stat = "count",
  position = "fill",
  palette = "Blues",
  interactive = FALSE,
  polar = FALSE,
  reverse = FALSE,
  width = NULL,
  maxylev = 6,
  digits = 1,
  colour = "black",
  size = 0.2,
  addlabel = TRUE,
  labelsize = 5,
  minlabelgroup = 0.04,
  minlabel = 2,
  hide.legend = TRUE,
  ylabelMean = FALSE,
  sec.y.axis = FALSE,
  use.label = TRUE,
  use.labels = TRUE,
  labeller = NULL,
  facetbycol = TRUE,
  xangle = NULL,
  yangle = NULL,
  xreverse = FALSE,
  yreverse = FALSE,
  xlab = NULL,
```

```

filllab = NULL,
family = NULL,
...
)

```

Arguments

<code>data</code>	A <code>data.frame</code>
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>stat</code>	The statistical transformation to use on the data for this layer, as a string c("count", "identity")
<code>position</code>	Position adjustment. One of the c("fill", "stack", "dodge")
<code>palette</code>	A character string indicating the color palette
<code>interactive</code>	A logical value. If TRUE, an interactive plot will be returned
<code>polar</code>	A logical value. If TRUE, <code>coord_polar()</code> function will be added
<code>reverse</code>	If true, reverse palette colors
<code>width</code>	Bar width
<code>maxylev</code>	integer indicating threshold of unique value to be treated as a categorical variable
<code>digits</code>	integer indicating the number of decimal places
<code>colour</code>	Bar colour
<code>size</code>	Bar size
<code>addlabel</code>	A logical value. If TRUE, label will be added to the plot
<code>labelsize</code>	label size
<code>minlabelgroup</code>	minimal threshold of label group. Default is 0.04
<code>minlabel</code>	minimal threshold of label. Default is 2
<code>hide.legend</code>	A logical value. If TRUE, the legend is removed and y labels are recreated
<code>ylabelMean</code>	Logical. If TRUE, y axis labels are positioned at mean value.
<code>sec.y.axis</code>	Logical. If TRUE, secondary y axis is shown at the right side.
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data
<code>labeller</code>	A function that takes one data frame of labels and returns a list or data frame of character vectors.
<code>facetbycol</code>	Logical. If TRUE, facet by column.
<code>xangle</code>	angle of axis label
<code>yangle</code>	angle of axis label
<code>xreverse</code>	Logical. Whether or not reverse x-axis
<code>yreverse</code>	Logical. Whether or not reverse y-axis
<code>xlab</code>	Label for x-axis
<code>filllab</code>	Label for fill aes
<code>family</code>	font family
<code>...</code>	other arguments passed on to <code>geom_rect_interactive</code> .

Value

An interactive spinogram

Examples

```
require(moonBook)
require(ggplot2)
acs$Dx=factor(acs$Dx,levels=c("Unstable Angina","NSTEMI","STEMI"))
ggSpine(data=acs,aes(x=age,fill=Dx,facet=sex),palette="Reds")
ggSpine(data=acs,aes(x=age,fill=Dx,facet=sex),facetbycol=FALSE,minlabelgroup=0.02)
ggSpine(data=acs,aes(x=age,fill=Dx),palette="Reds")
ggSpine(data=acs,aes(x=smoking,fill=Dx),palette="Reds")
ggSpine(data=acs,aes(x=DM,fill=Dx,facet=sex),palette="Reds")
ggSpine(data=acs,aes(x=Dx,fill=smoking,facet=sex),palette="Reds")
ggSpine(data=acs,aes(x=DM,facet=smoking,fill=Dx),sec.y.axis=TRUE)
ggSpine(data=acs,aes(x=DM,facet=smoking,fill=Dx),facetbycol=FALSE)
ggSpine(mtcars,aes(x=gear,fill=carb),interactive=TRUE)
ggSpine(mtcars,aes(x=gear,fill=carb,facet=am))
ggSpine(data=acs,aes(x=Dx,fill=smoking),position="dodge")
ggSpine(data=acs,aes(x=Dx,fill=smoking),position="stack")
```

ggViolin*Draw violin plots of a data.frame***Description**

Draw violin plots of a data.frame

Usage

```
ggViolin(
  data,
  mapping = NULL,
  rescale = FALSE,
  horizontal = FALSE,
  alpha = 0.1,
  addBoxplot = TRUE,
  addMean = TRUE,
  use.label = TRUE,
  use.labels = TRUE,
  ...
)
```

Arguments

<code>data</code>	a data.frame
<code>mapping</code>	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> .
<code>rescale</code>	if true, rescale the data.frame

<code>horizontal</code>	if true, horizontal boxplots will be made
<code>alpha</code>	An integer. Default value is 0.1.
<code>addBoxplot</code>	Whether add boxplots on the plot
<code>addMean</code>	Whether add mean point on the plot
<code>use.label</code>	Logical. Whether or not use column label in case of labelled data
<code>use.labels</code>	Logical. Whether or not use value labels in case of labelled data
<code>...</code>	other arguments passed on to <code>geom_boxplot_interactive</code>

Examples

```
require(ggplot2)
require(ggiraph)
require(reshape2)
ggViolin(iris)
ggViolin(iris,aes(fill=Species),rescale=TRUE)
ggViolin(mtcars,aes(x=c(mpg,cyl,disp,hp,drat),color=am),rescale=TRUE)
ggViolin(mtcars,aes(x=c(mpg,cyl,disp,hp,drat)),rescale=TRUE)
```

Description

Make a regression equation of a model

Usage

```
makeEq(model, digits = 2)
```

Arguments

<code>model</code>	A model of class "lm" or "glm" or "loess"
<code>digits</code>	integer indicating the number of decimal places

model2df*Make a data.frame of yhat with a model*

Description

Make a data.frame of yhat with a model

Usage

```
model2df(model, x = NULL, n = 100)
```

Arguments

- | | |
|-------|---|
| model | A model of class "lm" or "glm" or "loess" |
| x | A optional vector of explanatory variable |
| n | number of observations. |

myscale*Rescale a vector with which minimum value 0 and maximum value 1*

Description

Rescale a vector with which minimum value 0 and maximum value 1

Usage

```
myscale(x)
```

Arguments

- | | |
|---|------------------|
| x | A numeric vector |
|---|------------------|

myscale2*Rescale a vector with which minimum value 0 and maximum value 1***Description**

Rescale a vector with which minimum value 0 and maximum value 1

Usage

```
myscale2(x, minx = 0, maxx = 1)
```

Arguments

<code>x</code>	A numeric vector
<code>minx</code>	The minimum value
<code>maxx</code>	The maximum value

newColName*find new column name***Description**

find new column name

Usage

```
newColName(df)
```

Arguments

<code>df</code>	a data.frame
-----------------	--------------

num2cut

Computing breaks for make a histogram of a continuous variable

Description

Computing breaks for make a histogram of a continuous variable

Usage

```
num2cut(x)
```

Arguments

x A continuous variables

Value

A list contains a factor and a numeric vector

num2factorDf

Make numeric column of a data.frame to factor

Description

Make numeric column of a data.frame to factor

Usage

```
num2factorDf(data, colnames, maxfactorno = 6)
```

Arguments

data	a data.frame
colnames	Column names to be converted
maxfactorno	maximum unique value of column

p2chr *Convert p values to character*

Description

Convert p values to character

Usage

```
p2chr(x)
```

Arguments

x	A vector
---	----------

palette2colors *Extract colors from a palette*

Description

Extract colors from a palette

Usage

```
palette2colors(name, reverse = FALSE)
```

Arguments

name	A palette name from the RColorBrewer package
reverse	if true, reverse colors

pastecolon *Paste character vectors separated by colon*

Description

Paste character vectors separated by colon

Usage

```
pastecolon(...)
```

Arguments

...	Arguments passed on to paste()
-----	--------------------------------

pastecomma	<i>Add comma to vectors</i>
------------	-----------------------------

Description

Add comma to vectors

Usage

```
pastecomma(...)
```

Arguments

...	Argument passed to paste0
-----	---------------------------

rescale_df	<i>Rescale all numeric variables of a data.frame except grouping variable</i>
------------	---

Description

Rescale all numeric variables of a data.frame except grouping variable

Usage

```
rescale_df(data, groupvar = NULL)
```

Arguments

data	A data.frame
groupvar	A column name used as a grouping variable

Value

A rescaled data.frame

rose*Rose sales among 7 groups in a year***Description**

A phony dataset representing rose sales

Usage

```
rose
```

Format

An object of class `data.frame` with 84 rows and 3 columns.

Details

`@format` A `data.frame` with 84 rows and 3 columns

group group A to G

Month Month 1 to 12

value Rose sales amount

subcolors*Make a subcolors according to the mainCol***Description**

Make a subcolors according to the mainCol

Usage

```
subcolors(.dta, main, mainCol)
```

Arguments

`.dta` A `data.frame`

`main` A character string of column name used as a main variable

`mainCol` A main color

summarySE*Summarize a continuous variable by groups with mean, sd and SE*

Description

Summarize a continuous variable by groups with mean, sd and SE

Usage

```
summarySE(  
  data = NULL,  
  measurevar,  
  groupvars = NULL,  
  conf.interval = 0.95,  
  na.rm = TRUE,  
  .drop = TRUE  
)
```

Arguments

data	A data.frame
measurevar	A name of variable to measure a mean and sd
groupvars	Name(s) of variable used as a grouping variables
conf.interval	confidence interval
na.rm	A logical value indicating whether or not remove NA values
.drop	should combinations of variables that do not appear in the input data be preserved (FALSE) or dropped (TRUE, default)

Value

A data.frame summarized a continuous variable by groups with mean, sd and SE

taco*Taco ratings by age group*

Description

Taco ratings by ShellType, AgeGroup and Filling source: [Communicating experiment results with R](#)

Usage

taco

Format

An object of class `data.frame` with 136 rows and 4 columns.

Details

@format A `data.frame` with 136 rows and 4 columns

ShellType Hard or Soft

Fillings Fillings of taco

AgeGroup AgeGroup One of the `c("<13", "13-20", "21-39", "40+",)`

Rating A numeric. Rating of taco

`theme_clean`

Clean theme for PieDonut plot

Description

Clean theme for `PieDonut` plot

Usage

```
theme_clean(base_size = 12)
```

Arguments

`base_size` An integer, default 12.

`theme_clean2`

Clean theme for ggCor

Description

Clean theme for `ggCor`

Usage

```
theme_clean2(base_size = 12, xangle = 45, yangle = 0)
```

Arguments

`base_size` base font size

`xangle` x-axis text angle

`yangle` y-axis text angle

unselectNumeric *Unselect numeric column of a data.frame*

Description

Unselect numeric column of a data.frame

Usage

```
unselectNumeric(data, colnames, maxfactorno = 6)
```

Arguments

data	a data.frame
colnames	Column names to be converted
maxfactorno	maximum unique value of column

Index

* **datasets**
 browsers, 3
 rose, 40
 taco, 41

 addLabelDf, 3

 browsers, 3

 coord_radar, 4

 getMapping, 4
 ggAncova, 5
 ggArea, 6
 ggBar, 7
 ggBoxplot, 8
 ggCatepillar, 9
 ggChoropleth, 10
 ggCLE, 11
 ggCor, 12
 ggDensity, 14
 ggDonut, 15
 ggDot, 16
 ggEffect, 18
 ggErrorBar, 19
 ggHeatmap, 20
 ggHSD, 22
 ggPair, 23
 ggPie, 24
 ggPieDonut, 25
 ggPoints, 26
 ggPredict, 28
 ggRadar, 29
 ggRose, 30
 ggSpine, 31
 ggViolin, 33

 makeEq, 34
 model2df, 35
 myscale, 35
 myscale2, 36

 newColName, 36
 num2cut, 37
 num2factorDf, 37

 p2chr, 38
 palette2colors, 38
 pastecolon, 38
 pastecomma, 39

 rescale_df, 39
 rose, 40

 subcolors, 40
 summarySE, 41

 taco, 41
 theme_clean, 42
 theme_clean2, 42

 unselectNumeric, 43