

Package ‘kit’

April 17, 2025

Type Package

Title Data Manipulation Functions Implemented in C

Version 0.0.20

Date 2025-04-17

Author Morgan Jacob [aut, cre, cph],
Sebastian Krantz [ctb]

Maintainer Morgan Jacob <morgan.emailbox@gmail.com>

Description Basic functions, implemented in C, for large data manipulation. Fast vectorised ifelse()/nested if()/switch() functions, psum()/pprod() functions equivalent to pmin()/pmax() plus others which are missing from base R. Most of these functions are callable at C level.

License GPL-3

Depends R (>= 3.1.0)

Encoding UTF-8

BugReports <https://github.com/2005m/kit/issues>

NeedsCompilation yes

ByteCompile TRUE

Repository CRAN

Date/Publication 2025-04-17 20:20:02 UTC

Contents

charToFact	2
count	3
fduplicated/funique	4
fpos	6
iif	7
nif	9
parallel-funs	10
psort	13
setlevels	14

shareData/getData/clearData	15
topn	16
vswitch/nswitch	18

Index**21****charToFact***Convert Character Vector to Factor***Description**

Similar to `base::as.factor` but much faster and only for converting character vector to factor.

Usage

```
charToFact(x, decreasing=FALSE, addNA=TRUE,
           nThread=getOption("kit.nThread"))
```

Arguments

<code>x</code>	A vector of type character
<code>decreasing</code>	A boolean. Whether to order levels in decreasing order or not. Default is FALSE.
<code>addNA</code>	A boolean. Whether to include NA in levels of the output or not. Default is TRUE.
<code>nThread</code>	Number of thread to use.

Value

The character vector input as a factor. Please note that, unlike `as.factor`, NA levels are preserved by default, however this can be changed by setting argument `addNA` to FALSE.

Examples

```
x = c("b", "A", "B", "a", "\xe4", "a")
Encoding(x) = "latin1"
identical(charToFact(x), as.factor(x))
identical(charToFact(c("a", "b", NA, "a")), addNA(as.factor(c("a", "b", NA, "a"))))
identical(charToFact(c("a", "b", NA, "a")), addNA=FALSE), as.factor(c("a", "b", NA, "a"))

# Benchmarks
# -----
# x = sample(letters, 3e7, TRUE)
# microbenchmark::microbenchmark(
#   kit=kit::charToFact(x, nThread = 1L),
#   base=as.factor(x),
#   times = 5L
# )
# Unit: milliseconds
# expr  min   lq   mean median   uq   max neval
# kit  188  190    196    194  200   208     5
# base 1402 1403   1455   1414 1420  1637     5
```

count	<i>count, countNA and countOccur</i>
-------	--------------------------------------

Description

Simple functions to count the number of times an element occurs.

Usage

```
count(x, value)
countNA(x)
countOccur(x)
```

Arguments

x	A vector or list for countNA. A vector for count and a vector or data.frame for countOccur.
value	An element to look for. Must be non NULL, of length 1 and same type as x.

Value

For a vector countNA will return the total number of NA value. For a list, countNA will return a list with the number of NA in each item of the list. This is a major difference with sum(is.na(x)) which will return the aggregated number of NA. Also, please note that every item of a list can be of different type and countNA will take them into account whether they are of type logical (NA), integer (NA_integer_), double (NA_real_), complex (NA_complex_) or character (NA_character_). As opposed to countNA, count does not support list type and requires x and value to be of the same type. Function countOccur takes vectors or data.frame as inputs and returns a data.frame with the number of times each value in the vector occurs or number of times each row in a data.frame occurs.

Author(s)

Morgan Jacob

See Also

[pcount](#)

Examples

```
x = c(1, 3, NA, 5)
count(x, 3)

countNA(x)
countNA(as.list(x))

countOccur(x)
```

```

# Benchmarks countNA
# -----
# x = sample(c(TRUE,NA,FALSE),1e8,TRUE) # 382 Mb
# microbenchmark::microbenchmark(
#   countNA(x),
#   sum(is.na(x)),
#   times=5L
# )
# Unit: milliseconds
#      expr     min      lq    mean  median      uq     max neval
# countNA(x)  98.7  99.2 101.2 100.1 101.4 106.4     5
# sum(is.na(x)) 405.4 441.3 478.9 461.1 523.9 562.6     5
#
# Benchmarks count0ccur
# -----
# x = rnorm(1e6)
# y = data.table::data.table(x)
# microbenchmark::microbenchmark(
#   kit= count0ccur(x),
#   data.table = y[, .N, keyby = x],
#   table(x),
#   times = 10L
# )
# Unit: milliseconds
# expr     min      lq    mean  median      uq     max neval
# kit    62.26  63.88  89.29  75.49  95.17 162.40    10
# data.table 189.17 194.08 235.30 227.43 263.74 337.74    10 # setDTthreads(1L)
# data.table 140.15 143.91 190.04 182.85 234.48 261.43    10 # setDTthreads(2L)
# table(x) 3560.77 3705.06 3843.47 3807.12 4048.40 4104.11    10

```

fduplicated/funique *Fast duplicated and unique*

Description

Similar to base R functions duplicated and unique, fduplicated and funique are slightly faster for vectors and much faster for data.frame. Function uniqLen is equivalent to base R length(unique) or data.table::uniqueN.

Usage

```

fduplicated(x, fromLast = FALSE)
funique(x, fromLast = FALSE)
uniqLen(x)

```

Arguments

- | | |
|-----------------------|--|
| <code>x</code> | A vector, data.frame or matrix. |
| <code>fromLast</code> | A logical value to indicate whether the search should start from the end or beginning. Default is FALSE. |

Value

Function `fduplicated` returns a logical vector and `funique` returns a vector of the same type as `x` without the duplicated value. Function `uniqLen` returns an integer.

Author(s)

Morgan Jacob

Examples

```
# Example 1: fduplicated
fduplicated(iris$Species)

# Example 2: funique
funique(iris$Species)

# Example 3: uniqLen
uniqLen(iris$Species)

# Benchmarks
# -----
# x = sample(c(1:10,NA_integer_),1e8,TRUE) # 382 Mb
# microbenchmark::microbenchmark(
#   duplicated(x),
#   fduplicated(x),
#   times = 5L
# )
# Unit: seconds
#           expr  min   lq   mean   median   uq   max neval
# duplicated(x) 2.21 2.21  2.48    2.21 2.22  3.55     5
# fduplicated(x) 0.38 0.39  0.45    0.48 0.49  0.50     5
#
# vs data.table
# -----
# df = iris[,5:1]
# for (i in 1:16) df = rbind(df, df) # 338 Mb
# dt = data.table::as.data.table(df)
# microbenchmark::microbenchmark(
#   kit = funique(df),
#   data.table = unique(dt),
#   times = 5L
# )
# Unit: seconds
#           expr  min   lq   mean   median   uq   max neval
# kit      1.22 1.27  1.33    1.27 1.36  1.55     5
# data.table 6.20 6.24  6.43    6.33 6.46  6.93     5 # (setDTthreads(1L))
# data.table 4.20 4.25  4.47    4.26 4.32  5.33     5 # (setDTthreads(2L))
#
# microbenchmark::microbenchmark(
#   kit=uniqLen(x),
#   data.table=uniqueN(x),
#   times = 5L, unit = "s"
```

```

# )
# Unit: seconds
#      expr   min    lq   mean   median    uq   max neval
# kit      0.17  0.17  0.17    0.17  0.17    5
# data.table 1.66  1.68  1.70    1.71  1.71  1.72    5 # (setDTthreads(1L))
# data.table 1.13  1.15  1.16    1.16  1.18  1.18    5 # (setDTthreads(2L))

```

fpos*Find a matrix position inside a larger matrix***Description**

The function `fpos` returns the locations (row and column index) where a small matrix may be found in a larger matrix. The function also works with vectors.

Usage

```
fpos(needle, haystack, all=TRUE, overlap=TRUE)
```

Arguments

<code>needle</code>	A matrix or vector to search for in the larger matrix or vector <code>haystack</code> . Note that the <code>needle</code> dimensions (row and column size) must be smaller than the <code>haystack</code> dimensions.
<code>haystack</code>	A matrix or vector to look into.
<code>all</code>	A logical value to indicate whether to return all occurrences (TRUE) or only the first one (FALSE). Default value is TRUE.
<code>overlap</code>	A logical value to indicate whether to allow the small matrix occurrences to overlap or not. Default value is TRUE.

Value

A two columns matrix that contains the position or index where the small matrix (`needle`) can be found in the larger matrix. The first column refers to rows and the second to columns. In case both the `needle` and `haystack` are vectors, a vector is returned.

Author(s)

Morgan Jacob

Examples

```

# Example 1: find a matrix inside a larger one
big_matrix = matrix(c(1:30), nrow = 10)
small_matrix = matrix(c(14, 15, 24, 25), nrow = 2)

fpos(small_matrix, big_matrix)

```

```

# Example 2: find a vector inside a larger one
fpos(14:15, 1:30)

# Example 3:
big_matrix = matrix(c(1:5), nrow = 10, ncol = 5)
small_matrix = matrix(c(2:3), nrow = 2, ncol = 2)

# return all occurrences
fpos(small_matrix, big_matrix)

# return only the first
fpos(small_matrix, big_matrix, all = FALSE)

# return non overlapping occurrences
fpos(small_matrix, big_matrix, overlap = FALSE)

# Benchmarks
# -----
# x = matrix(1:5, nrow=1e4, ncol=5e3) # 191Mb
# microbenchmark::microbenchmark(
#   fpos=kit:::fpos(1L, x),
#   which=which(x==1L, arr.ind=TRUE),
#   times=10L
# )
# Unit: milliseconds
# expr   min    lq    mean median    uq    max neval
# fpos  202  206  220    221  231  241    10
# which 612  637  667    653  705  724    10

```

iif

Fast ifelse

Description

iif is a faster and more robust replacement of `ifelse`. It is comparable to `dplyr::if_else`, `hutils::if_else` and `data.table::ifelse`. It returns a value with the same length as `test` filled with corresponding values from `yes`, `no` or eventually `na`, depending on `test`. It does not support S4 classes.

Usage

```
iif(test, yes, no, na=NULL, tprom=FALSE, nThread=getOption("kit.nThread"))
```

Arguments

<code>test</code>	A logical vector.
<code>yes, no</code>	Values to return depending on TRUE/FALSE element of <code>test</code> . They must be the same type and be either length 1 or the same length of <code>test</code> .

na	Value to return if an element of test is missing. It must be the same type as yes/no and be either length 1 or the same length of test. Please note that NA is treated as logical value of length 1 as per the R documentation. NA_integer_, NA_real_, NA_complex_ and NA_character_ are equivalent to NA but for integer, double, complex and character. Default value for argument na is NULL and will automatically default to the equivalent NA type of argument yes.
tprom	Argument to indicate whether type promotion of yes and no is allowed or not. Either FALSE or TRUE, default is FALSE to not allow type promotion.
nThread	A integer for the number of threads to use with <i>openmp</i> . Default value is getOption("kit.nThread").

Details

In contrast to `ifelse` attributes are copied from yes to the output. This is useful when returning Date, factor or other classes. Like `dplyr::if_else` and `hutils::if_else`, the na argument is by default set to NULL. This argument is set to NA in `data.table::ifelse`. Similarly to `dplyr::if_else` and when `tprom=FALSE`, iif requires same type for arguments yes and no. This is not strictly the case for `data.table::ifelse` which will coerce integer to double. When `tprom=TRUE`, iif behavior is similar to `base::ifelse` in the sense that it will promote or coerce yes and no to the "highest" used type. Note, however, that unlike `base::ifelse` attributes are still conserved.

Value

A vector of the same length as test and attributes as yes. Data values are taken from the values of yes and no, eventually na.

Author(s)

Morgan Jacob

See Also

[nif vswitch](#)

Examples

```
x = c(1:4, 3:2, 1:4)
iif(x > 2L, x, x - 1L)

# unlike ifelse, iif preserves attributes, taken from the 'yes' argument
dates = as.Date(c("2011-01-01", "2011-01-02", "2011-01-03", "2011-01-04", "2011-01-05"))
ifelse(dates == "2011-01-01", dates - 1, dates)
iif(dates == "2011-01-01", dates - 1, dates)
yes = factor(c("a", "b", "c"))
no = yes[1L]
ifelse(c(TRUE, FALSE, TRUE), yes, no)
iif(c(TRUE, FALSE, TRUE), yes, no)

# Example of using the 'na' argument
iif(test = c(-5L:5L < 0L, NA), yes = 1L, no = 0L, na = 2L)
```

```
# Example of using the 'tprom' argument
iif(test = c(-5L:5L < 0L, NA), yes = 1L, no = "0", na = 2L, tprom = TRUE)
```

nif

Nested if else

Description

nif is a fast implementation of SQL CASE WHEN statement for R. Conceptually, nif is a nested version of [iif](#) (with smarter implementation than manual nesting). It is not the same but it is comparable to `dplyr::case_when` and `data.table::fcase`.

Usage

```
nif(..., default=NULL)
```

Arguments

...	A sequence consisting of logical condition (when)-resulting value (value) <i>pairs</i> in the following order when1, value1, when2, value2, ..., whenN, valueN. Logical conditions when1, when2, ..., whenN must all have the same length, type and attributes. Each value may either share length with when or be length 1. Please see Examples section for further details.
default	Default return value, NULL by default, for when all of the logical conditions when1, when2, ..., whenN are FALSE or missing for some entries. Argument default can be a vector either of length 1 or length of logical conditions when1, when2, ..., whenN. Note that argument 'default' must be named explicitly.

Details

Unlike `data.table::fcase`, the default argument is set to NULL. In addition, nif can be called by other packages at C level. Note that at C level, the function has an additional argument SEXP md which is either TRUE for lazy evaluation or FALSE for non lazy evaluation. This argument is not exposed to R users and is more for C users.

Value

Vector with the same length as the logical conditions (when) in ..., filled with the corresponding values (value) from ..., or eventually default. Attributes of output values value1, value2, ...valueN in ... are preserved.

Author(s)

Morgan Jacob

See Also

[iif](#) [vswitch](#)

Examples

```

x = 1:10
nif(
  x < 5L, 1L,
  x > 5L, 3L
)

nif(
  x < 5L, 1L:10L,
  x > 5L, 3L:12L
)

# Lazy evaluation example
nif(
  x < 5L, 1L,
  x >= 5L, 3L,
  x == 5L, stop("provided value is an unexpected one!")
)

# nif preserves attributes, example with dates
nif(
  x < 5L, as.Date("2019-10-11"),
  x > 5L, as.Date("2019-10-14")
)

# nif example with factor; note the matching levels
nif(
  x < 5L, factor("a", levels=letters[1:3]),
  x > 5L, factor("b", levels=letters[1:3])
)

# Example of using the 'default' argument
nif(
  x < 5L, 1L,
  x > 5L, 3L,
  default = 5L
)

nif(
  x < 5L, 1L,
  x > 5L, 3L,
  default = rep(5L, 10L)
)

```

Description

Vector-valued (statistical) functions operating in parallel over vectors passed as arguments, or a single list of vectors (such as a data frame). Similar to [pmin](#) and [pmax](#), except that these functions

do not recycle vectors.

Usage

```
psum(..., na.rm = FALSE)
pprod(..., na.rm = FALSE)
pmean(..., na.rm = FALSE)
pfirst(...) # (na.rm = TRUE)
plast(...) # (na.rm = TRUE)
pall(..., na.rm = FALSE)
pallNA(...)
pallv(..., value)
pany(..., na.rm = FALSE)
panyNA(...)
panyv(..., value)
pcount(..., value)
pcountNA(...)
```

Arguments

...	suitable (atomic) vectors of the same length, or a single list of vectors (such as a <code>data.frame</code>). See Details on the allowed data types for each function, and Examples.
<code>na.rm</code>	A logical indicating whether missing values should be removed. Default value is <code>FALSE</code> , except for <code>pfirst</code> and <code>plast</code> .
<code>value</code>	A non <code>NULL</code> value of length 1.

Details

Functions `psum`, `pprod` work for integer, logical, double and complex types. `pmean` only supports integer, logical and double types. All 3 functions will error if used with factors.

`pfirst/plast` select the first/last non-missing value (or non-empty or `NULL` value for list-vectors). They accept all vector types with defined missing values + lists, but can only jointly handle integer and double types (not numeric and complex or character and factor). If factors are passed, they all need to have identical levels.

`pany` and `pall` are derived from base functions `all` and `any` and only allow logical inputs.

`pcount` counts the occurrence of `value`, and expects arguments of the same data type (except for `value = NA`). `pcountNA` is equivalent to `pcount` with `value = NA`, and they both allow NA counting in mixed-type data. `pcountNA` additionally supports list vectors and counts empty or `NULL` elements as `NA`.

Functions `panyv/pallv` are wrappers around `pcount`, and `panyNA/pallNA` are wrappers around `pcountNA`. They return a logical vector instead of the integer count.

None of these functions recycle vectors i.e. all input vectors need to have the same length. All functions support long vectors with up to $2^{64}-1$ elements.

Value

`psum/pprod/pmean` return the sum, product or mean of all arguments. The value returned will be of the highest argument type (integer < double < complex). `pprod` only returns double or complex. `pall[v/NA]` and `pany[v/NA]` return a logical vector. `pcount[NA]` returns an integer vector. `pfirst/plast` return a vector of the same type as the inputs.

Author(s)

Morgan Jacob and Sebastian Krantz

See Also

Package 'collapse' provides column-wise and scalar-valued analogues to many of these functions.

Examples

```
x = c(1, 3, NA, 5)
y = c(2, NA, 4, 1)
z = c(3, 4, 4, 1)

# Example 1: psum
psum(x, y, z, na.rm = FALSE)
psum(x, y, z, na.rm = TRUE)

# Example 2: pprod
pprod(x, y, z, na.rm = FALSE)
pprod(x, y, z, na.rm = TRUE)

# Example 3: pmean
pmean(x, y, z, na.rm = FALSE)
pmean(x, y, z, na.rm = TRUE)

# Example 4: pfirst and plast
pfirst(x, y, z)
plast(x, y, z)

# Adjust x, y, and z to use in pall and pany
x = c(TRUE, FALSE, NA, FALSE)
y = c(TRUE, NA, TRUE, TRUE)
z = c(TRUE, TRUE, FALSE, NA)

# Example 5: pall
pall(x, y, z, na.rm = FALSE)
pall(x, y, z, na.rm = TRUE)

# Example 6: pany
pany(x, y, z, na.rm = FALSE)
pany(x, y, z, na.rm = TRUE)

# Example 7: pcount
pcount(x, y, z, value = TRUE)
pcountNA(x, y, z)
```

```

# Example 8: list/data.frame as an input
pprod(iris[,1:2])
psum(iris[,1:2])
pmean(iris[,1:2])

# Benchmarks
# -----
# n = 1e8L
# x = rnorm(n) # 763 Mb
# y = rnorm(n)
# z = rnorm(n)
#
# microbenchmark::microbenchmark(
#   kit=psum(x, y, z, na.rm = TRUE),
#   base=rowSums(do.call(cbind,list(x, y, z))), na.rm=TRUE),
#   times = 5L, unit = "s"
# )
# Unit: Second
# expr  min    lq  mean median    uq   max neval
# kit  0.52 0.52 0.65  0.55 0.83 0.84     5
# base 2.16 2.27 2.34  2.35 2.43 2.49     5
#
# x = sample(c(TRUE, FALSE, NA), n, TRUE) # 382 Mb
# y = sample(c(TRUE, FALSE, NA), n, TRUE)
# z = sample(c(TRUE, FALSE, NA), n, TRUE)
#
# microbenchmark::microbenchmark(
#   kit=pany(x, y, z, na.rm = TRUE),
#   base=sapply(1:n, function(i) any(x[i],y[i],z[i],na.rm=TRUE)),
#   times = 5L
# )
# Unit: Second
# expr  min    lq  mean median    uq   max neval
# kit  1.07 1.09 1.15  1.10 1.23 1.23     5
# base 111.31 112.02 112.78 112.97 113.55 114.03     5

```

Description

Similar to `base::sort` but just for character vector and partially using parallelism. It is currently experimental and might change in the future. Use with caution.

Usage

```
psort(x, decreasing=FALSE, na.last=NA,
      nThread=getOption("kit.nThread"), c.locale=TRUE)
```

Arguments

<code>x</code>	A vector of type character. If other, it will default to <code>base::sort</code>
<code>na.last</code>	For controlling the treatment of NAs. If TRUE, missing values in the data are put last; if FALSE, they are put first; if NA, they are removed.
<code>decreasing</code>	A boolean indicating where to sort the data in decreasing way. Default is FALSE.
<code>nThread</code>	Number of thread to use. Default value is 1L.
<code>c.locale</code>	A boolean, whether to use C Locale or R session locale. Default TRUE.

Value

Returns the input `x` in sorted order similar to `base::sort` but usually faster. If `c.locale=FALSE`, `psort` will return the same output as `base::sort` with `method="quick"`, i.e. using R session locale. If `c.locale=TRUE`, `psort` will return the same output as `base::sort` with `method="radix"`, i.e. using C locale. See example below.

Author(s)

Morgan Jacob

Examples

```

x = c("b", "A", "B", "a", "\xe4")
Encoding(x) = "latin1"
identical(psort(x, c.locale=FALSE), sort(x))
identical(psort(x, c.locale=TRUE), sort(x, method="radix"))

# Benchmarks
# -----
# strings = as.character(as.hexmode(1:1000))
# x = sample(strings, 1e8, replace=TRUE)
# system.time({kit::psort(x, na.last = TRUE, nThread = 1L)})
#   user  system elapsed
# 2.833  0.434  3.277
# system.time({sort(x,method="radix",na.last = TRUE)})
#   user  system elapsed
# 5.597  0.559  6.176
# system.time({x[order(x,method="radix",na.last = TRUE)]})
#   user  system elapsed
# 5.561  0.563  6.143

```

Description

A function to set levels of a factor object.

Usage

```
setlevels(x, old=levels(x), new, skip_absent=FALSE)
```

Arguments

x	A factor object.
old	A character vector containing the factor levels to be changed. Default is levels of x.
new	The new character vector containing the factor levels to be added.
skip_absent	Skip items in old that are missing (i.e. absent) in ‘names(x)’. Default FALSE halts with error if any are missing.

Value

Returns an invisible and modified factor object.

Author(s)

Morgan Jacob

Examples

```
x = factor(c("A", "A", "B", "B", "B", "C")) # factor vector with levels A B C
setlevels(x, new = c("X", "Y", "Z"))          # set factor levels to: X Y Z
setlevels(x, old = "X", new = "A")             # set factor levels X to A
```

Description

Experimental functions that enable the user to share a R object between 2 R sessions.

Usage

```
shareData(data, map_name, verbose=FALSE)
getData(map_name, verbose=FALSE)
clearData(x, verbose=FALSE)
```

Arguments

data	A R object like a vector or a data.frame.
map_name	A character. A name for the memory map location where to store the data.
x	An external pointer like the one returned by function shareData.
verbose	A logical value TRUE or FALSE to provide or not information to the user.

Value

`shareData` returns a external pointer. `getData` returns an R object stored in the memory location `map_name`. `clearData` returns TRUE or FALSE depending on whether the data have been cleared in memory.

Author(s)

Morgan Jacob

Examples

```
# In R session 1: share data in memory
# > x = shareData(mtcars,"share1")
#
# In R session 2: get data from session 1
# > getData("share1")
#
# In R session 1: clear data in memory
# > clearData(x)
```

topn

*Top N values index***Description**

`topn` is used to get the indices of the few values of an input. This is an extension of `which.max/which.min` which provide *only* the first such index.

The output is the same as `order(vec)[1:n]`, but internally optimized not to sort the irrelevant elements of the input (and therefore much faster, for small n relative to input size).

Usage

```
topn(vec, n=6L, decreasing=TRUE, hasna=TRUE, index=TRUE)
```

Arguments

<code>vec</code>	A numeric vector of type numeric or integer. Other types are not supported yet.
<code>n</code>	A positive integer value greater or equal to 1.
<code>decreasing</code>	A logical value (default TRUE) to indicate whether to sort vec in decreasing or increasing order. Equivalent to argument <code>decreasing</code> in function <code>base::order</code> . Please note that unlike <code>topn</code> default value in <code>base::order</code> is FALSE.
<code>hasna</code>	A logical value (default TRUE) to indicate whether vec contains NA values.
<code>index</code>	A logical value (default TRUE) to indicate whether indexes or values of vec.

Value

integer vector of indices of the most extreme (according to decreasing) n values in vector vec. Please note that for large value of n, i.e. 1500 or 2000 (depending on the value of hasna), topn will default to base R function order.

Author(s)

Morgan Jacob

Examples

```
x = rnorm(1e4)

# Example 1: index of top 6 negative values
topn(x, 6L, decreasing=FALSE)
order(x)[1:6]

# Example 2: index of top 6 positive values
topn(x, 6L, decreasing = TRUE)
order(x, decreasing=TRUE)[1:6]

# Example 3: top 6 negative values
topn(x, 6L, decreasing=FALSE, index=FALSE)
sort(x)[1:6]

# Benchmarks
# -----
# x = rnorm(1e7) # 76Mb
# microbenchmark::microbenchmark(
#   topn=kit::topn(x, 6L),
#   order=order(x, decreasing=TRUE)[1:6],
#   times=10L
# )
# Unit: milliseconds
# expr min lq mean median uq max neval
# topn 11 11 13 11 12 18 10
# order 563 565 587 566 602 661 10
#
# microbenchmark::microbenchmark(
#   topn=kit::topn(x, 6L, decreasing=FALSE, index=FALSE),
#   sort=sort(x, partial=1:6)[1:6],
#   times=10L
# )
# Unit: milliseconds
# expr min lq mean median uq max neval
# topn 11 11 11 11 12 12 10
# sort 167 175 197 178 205 303 10
```

vswitch/nswitch	<i>Vectorised switch</i>
------------------------	--------------------------

Description

`vswitch/ nswitch` is a vectorised version of base function `switch`. This function can also be seen as a particular case of function `nif`, as shown in examples below, and should also be faster.

Usage

```
vswitch(x, values, outputs, default=NULL,
       nThread=getOption("kit.nThread"),
       checkEnc=TRUE)
nswitch(x, ..., default=NULL,
        nThread=getOption("kit.nThread"),
        checkEnc=TRUE)
```

Arguments

<code>x</code>	A vector or list.
<code>values</code>	A vector or list with values from <code>x</code> to match. Note that <code>x</code> and <code>values</code> must have the same class and attributes.
<code>outputs</code>	A list or vector with the outputs to return for every matching values. Each item of the list must be of length 1 or length of <code>x</code> . Note that if all list items are of length 1 then it might be simpler to use a vector.
<code>...</code>	A sequence of values and outputs in the following order <code>value1, output1, value2, output2, ..., valueN, outputN</code> . Values <code>value1, value2, ..., valueN</code> must all have length 1, same type and attributes. Each output may either share length with <code>x</code> or be length 1. Please see Examples section for further details.
<code>default</code>	Values to return is no match. Must be a vector or list of length 1 or same length as <code>x</code> . Also, <code>default</code> must have the same type, class and attributes as items from <code>outputs</code> .
<code>nThread</code>	A integer for the number of threads to use with <code>openmp</code> . Default value is <code>getOption("kit.nThread")</code> .
<code>checkEnc</code>	A logical value whether or not to check if <code>x</code> and <code>values</code> have comparable and consistent encoding. Default is TRUE.

Value

A vector or list of the same length as `x` with values from `outputs` items and from `default` if missing.

Author(s)

Morgan Jacob

See Also**if nif****Examples**

```
x = sample(c(10L, 20L, 30L, 40L, 50L, 60L), 3e2, replace=TRUE)

# The below example of 'vswitch' is
a1 = vswitch(
  x = x,
  values = c(10L,20L,30L,40L,50L),
  outputs = c(11L,21L,31L,41L,51L),
  default = NA_integer_
)

# equivalent to the following 'nif' example.
# However for large vectors 'vswitch' should be faster.
b1 = nif(
  x==10L, 11L,
  x==20L, 21L,
  x==30L, 31L,
  x==40L, 41L,
  x==50L, 51L,
  default = NA_integer_
)
identical(a1, b1)

# nswitch can also be used as follows:
c1 = nswitch(x,
  10L, 11L,
  20L, 21L,
  30L, 31L,
  40L, 41L,
  50L, 51L,
  default = NA_integer_
)
identical(a1, c1)

# Example with list in 'outputs' argument
y = c(1, 0, NA_real_)
a2 = vswitch(
  x = y,
  values = c(1, 0),
  outputs = list(c(2, 3, 4), c(5, 6, 7)),
  default = 8
)

b2 = nif(
  y==1, c(2, 3, 4),
  y==0, c(5, 6, 7),
  default = 8
)
```

```
identical(a2, b2)

c2 = nswitch(y,
  1, c(2, 3, 4),
  0, c(5, 6, 7),
  default = 8
)

identical(a2, c2)

# Benchmarks
# -----
# x = sample(1:100, 3e8, TRUE) # 1.1Gb
# microbenchmark::microbenchmark(
#   nif=kit::nif(
#     x==10L, 0L,
#     x==20L, 10L,
#     x==30L, 20L,
#     default= 30L
#   ),
#   vswitch=kit::vswitch(
#     x, c( 10L, 20L, 30L), list(0L, 10L, 20L), 30L
#   ),
#   times=10L
# )
# Unit: seconds
#   expr   min    lq   mean median   uq   max neval
#   nif   4.27  4.37  4.43   4.42  4.52  4.53    10
#   vswitch 1.08  1.09  1.20   1.10  1.43  1.44    10 # 1 thread
#   vswitch  0.46  0.57  0.57   0.58  0.58  0.60    10 # 2 threads
```

Index

charToFact, 2
clearData
 (shareData/getData/clearData),
 15
count, 3
countNA (count), 3
countOccur (count), 3

fduplicated (fduplicated/funique), 4
fduplicated/funique, 4
fpos, 6
funique (fduplicated/funique), 4

getData (shareData/getData/clearData),
 15

ifelse, 7, 8
iif, 7, 9, 19

nif, 8, 9, 19
nswitch (vswitch/nswitch), 18

pall (parallel-funs), 10
pallNA (parallel-funs), 10
pallv (parallel-funs), 10
pany (parallel-funs), 10
panyNA (parallel-funs), 10
panyv (parallel-funs), 10
parallel-funs, 10
pcount, 3
pcount (parallel-funs), 10
pcountNA (parallel-funs), 10
pfirst (parallel-funs), 10
plast (parallel-funs), 10
pmax, 10
pmean (parallel-funs), 10
pmin, 10
pprod (parallel-funs), 10
psort, 13
psum (parallel-funs), 10

setlevels, 14
shareData
 (shareData/getData/clearData),
 15
shareData/getData/clearData, 15

topn, 16

uniqLen (fduplicated/funique), 4

vswitch, 8, 9
vswitch (vswitch/nswitch), 18
vswitch/nswitch, 18

which.max, 16
which.min, 16