

Package ‘markmyassignment’

January 29, 2024

Type Package

Title Automatic Marking of R Assignments

Version 0.8.8

Author Mans Magnusson, Oscar Pettersson

Maintainer Mans Magnusson <mons.magnusson@gmail.com>

Description Automatic marking of R assignments for students and teachers based
on ‘testthat’ test suites.

License BSD_2_clause + file LICENSE

Encoding UTF-8

Depends R (>= 3.6.0)

Imports methods, yaml, testthat (>= 2.0.0), httr (>= 1.0.0), checkmate
>= 1.0.0), codetools, rlang

RoxygenNote 7.2.3

Suggests covr, htptest, knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2024-01-29 09:20:06 UTC

R topics documented:

markmyassignment	2
mark_my_assignment	2
mark_my_file	3
set_assignment	4
show_tasks	4

Index

6

markmyassignment *Automatic Marking of R Assignments*

Description

Automatic marking of R assignments for students and teachers based on testthat test suites.

mark_my_assignment *Mark assignment in global environment*

Description

Mark assignment in global environment.

Usage

```
mark_my_assignment(
  tasks = NULL,
  mark_file = NULL,
  force_get_tests = FALSE,
  quiet = FALSE,
  ...
)
```

Arguments

<code>tasks</code>	Which task should be corrected (if more than one). Default is all. To see the different task, see show_tasks .
<code>mark_file</code>	Argument is deprecated, use <code>mark_my_file</code> instead.
<code>force_get_tests</code>	Argument is deprecated, use <code>set_assignment()</code> instead.
<code>quiet</code>	Should test be run without output?
<code>...</code>	further arguments sent to <code>test_dir()</code> .

Examples

```
assignment_path <-
  file.path(system.file(package = "markmyassignment"), "extdata", "example_assignment01.yml")
set_assignment(assignment_path)
source(file.path(system.file(package = "markmyassignment"), "extdata", "example_lab_file.R"))
mark_my_assignment()
```

mark_my_file	<i>Mark assignment file</i>
--------------	-----------------------------

Description

Mark a specific assignment file

Usage

```
mark_my_file(  
  tasks = NULL,  
  mark_file = file.choose(),  
  assignment_path = NULL,  
  force_get_tests = FALSE,  
  quiet = FALSE,  
  ...  
)
```

Arguments

tasks	Which task should be corrected (if more than one). Default is all. To see the different task, see show_tasks .
mark_file	Path to the file to mark.
assignment_path	Assignment file to set before marking the assignment (url or local path).
force_get_tests	Argument is deprecated, use <code>set_assignment()</code> instead.
quiet	Should test be run without output?
...	further arguments sent to <code>test_dir()</code> .

Examples

```
## Not run:  
assignment_path <-  
  file.path(system.file(package = "markmyassignment"), "extdata", "example_assignment01.yml")  
file_path <- file.path(system.file(package = "markmyassignment"), "extdata", "example_lab_file.R")  
mark_my_file(mark_file = file_path, assignment_path = assignment_path)  
  
## End(Not run)
```

<code>set_assignment</code>	<i>Set and remove assignments</i>
-----------------------------	-----------------------------------

Description

Sets the assignment to mark and downloads necessary files.

Usage

```
set_assignment(path, auth = NULL)

remove_assignment()

is_assignment_set()

show_assignment()
```

Arguments

<code>path</code>	Path to the yml file
<code>auth</code>	Authorization object generated by <code>httr::authenticate()</code> . See <code>authenticate</code> and https://github.com/r-lib/httr/blob/master/demo/oauth2-github.r on details on how to use <code>authenticate()</code> .

Examples

```
assignment_path <-
  file.path(system.file(package = "markmyassignment"),
            "/extdata/example_assignment01.yml")
set_assignment(assignment_path)
```

<code>show_tasks</code>	<i>Get the name of the tasks in the assignment.</i>
-------------------------	---

Description

Get the name of the tasks in the assignment.

Usage

```
show_tasks()
```

show_tasks

5

Examples

```
# We first set the assignment
assignment_path <-
  file.path(system.file(package = "markmyassignment"), "extdata/example_assignment01.yml")
set_assignment(assignment_path)

show_tasks()
```

Index

is_assignment_set (set_assignment), [4](#)

mark_my_assignment, [2](#)

mark_my_file, [3](#)

markmyassignment, [2](#)

remove_assignment (set_assignment), [4](#)

set_assignment, [4](#)

show_assignment (set_assignment), [4](#)

show_tasks, [2](#), [3](#), [4](#)