

Package ‘polle’

July 23, 2025

Title Policy Learning

Version 1.5

Description Package for evaluating user-specified finite stage policies and learning optimal treatment policies via doubly robust loss functions. Policy learning methods include doubly robust learning of the blip/conditional average treatment effect and sequential policy tree learning. The package also include methods for optimal subgroup analysis. See Nordland and Holst (2022) <[doi:10.48550/arXiv.2212.02335](https://doi.org/10.48550/arXiv.2212.02335)> for documentation and references.

License Apache License (>= 2)

Encoding UTF-8

Depends R (>= 4.0), SuperLearner

Imports data.table (>= 1.14.5), lava (>= 1.7.0), future.apply, progressr, methods, polycytree (>= 1.2.0), survival, targeted (>= 0.4), DynTxRegime

Suggests DTRlearn2, glmnet (>= 4.1-6), mgcv, xgboost, knitr, ranger, rmarkdown, testthat (>= 3.0), ggplot2

RoxygenNote 7.3.2

BugReports <https://github.com/AndreasNordland/polle/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Andreas Nordland [aut, cre],
Klaus Holst [aut] (ORCID: <<https://orcid.org/0000-0002-1364-6789>>)

Maintainer Andreas Nordland <andreasnordland@gmail.com>

Repository CRAN

Date/Publication 2024-09-06 14:30:13 UTC

Contents

conditional	3
control_blip	4
control_drql	4

control_earl	5
control_owl	6
control_ptl	7
control_rwl	8
copy_policy_data	9
fit_g_functions	10
get_actions	11
get_action_set	11
get_g_functions	12
get_history_names	13
get_id	14
get_id_stage	15
get_K	16
get_n	16
get_policy	17
get_policy_actions	18
get_policy_functions.blip	19
get_policy_object	21
get_q_functions	22
get_stage_action_sets	23
get_utility	24
g_model	25
history	28
nuisance_functions	30
partial	31
plot.policy_data	32
plot.policy_eval	33
policy	34
policy_data	35
policy_def	38
policy_eval	40
policy_learn	47
predict.nuisance_functions	51
q_model	52
sim_multi_stage	55
sim_single_stage	56
sim_single_stage_multi_actions	58
sim_two_stage	58
sim_two_stage_multi_actions	59
subset_id	60

conditional	<i>Conditional Policy Evaluation</i>
-------------	--------------------------------------

Description

`conditional()` is used to calculate the policy value for each group defined by a given baseline variable.

Usage

```
conditional(object, policy_data, baseline)
```

Arguments

<code>object</code>	Policy evaluation object created by <code>policy_eval()</code> .
<code>policy_data</code>	Policy data object created by <code>policy_data()</code> .
<code>baseline</code>	Character string.

Value

object of inherited class 'estimate', see `lava::estimate.default`. The object is a list with elements 'coef' (policy value estimate for each group) and 'IC' (influence curve estimate matrix).

Examples

```
library("polle")
library("data.table")
setDTthreads(1)
d <- sim_single_stage(n=2e3)
pd <- policy_data(d,
  action = "A",
  baseline = c("B"),
  covariates = c("Z", "L"),
  utility = "U")

# static policy:
p <- policy_def(1)

pe <- policy_eval(pd,
  policy = p)

# conditional value for each group defined by B
conditional(pe, pd, "B")
```

control_blip *Control arguments for doubly robust blip-learning*

Description

control_blip sets the default control arguments for doubly robust blip-learning, type = "blip".

Usage

```
control_blip(blip_models = q_glm(~.))
```

Arguments

blip_models Single element or list of V-restricted blip-models created by `q_glm()`, `q_rf()`, `q_sl()` or similar functions.

Value

list of (default) control arguments.

control_drql *Control arguments for doubly robust Q-learning*

Description

control_drql sets the default control arguments for doubly robust Q-learning, type = "drql".

Usage

```
control_drql(qv_models = q_glm(~.))
```

Arguments

qv_models Single element or list of V-restricted Q-models created by `q_glm()`, `q_rf()`, `q_sl()` or similar functions.

Value

list of (default) control arguments.

control_earl	<i>Control arguments for Efficient Augmentation and Relaxation Learning</i>
--------------	---

Description

control_earl sets the default control arguments for efficient augmentation and relaxation learning, type = "earl". The arguments are passed directly to `DynTxRegime::earl()` if not specified otherwise.

Usage

```
control_earl(
  moPropen,
  moMain,
  moCont,
  regime,
  iter = 0L,
  fSet = NULL,
  lambdas = 0.5,
  cvFolds = 0L,
  surrogate = "hinge",
  kernel = "linear",
  kparam = NULL,
  verbose = 0L
)
```

Arguments

moPropen	Propensity model of class "ModelObj", see modelObj::modelObj .
moMain	Main effects outcome model of class "ModelObj".
moCont	Contrast outcome model of class "ModelObj".
regime	An object of class formula specifying the design of the policy/regime.
iter	Maximum number of iterations for outcome regression.
fSet	A function or NULL defining subset structure.
lambdas	Numeric or numeric vector. Penalty parameter.
cvFolds	Integer. Number of folds for cross-validation of the parameters.
surrogate	The surrogate 0-1 loss function. The options are "logit", "exp", "hinge", "sqhinge", "huber".
kernel	The options are "linear", "poly", "radial".
kparam	Numeric. Kernel parameter
verbose	Integer.

Value

list of (default) control arguments.

 control_owl

Control arguments for Outcome Weighted Learning

Description

control_owl() sets the default control arguments for backwards outcome weighted learning, type = "owl". The arguments are passed directly to `DTRlearn2::owl()` if not specified otherwise.

Usage

```
control_owl(
  policy_vars = NULL,
  reuse_scales = TRUE,
  res.lasso = TRUE,
  loss = "hinge",
  kernel = "linear",
  augment = FALSE,
  c = 2^(-2:2),
  sigma = c(0.03, 0.05, 0.07),
  s = 2^(-2:2),
  m = 4
)
```

Arguments

policy_vars	Character vector/string or list of character vectors/strings. Variable names used to restrict the policy. The names must be a subset of the history names, see <code>get_history_names()</code> . Not passed to <code>owl()</code> .
reuse_scales	The history matrix passed to <code>owl()</code> is scaled using <code>scale()</code> as advised. If TRUE, the scales of the history matrix will be saved and reused when applied to (new) test data.
res.lasso	If TRUE a lasso penalty is applied.
loss	Loss function. The options are "hinge", "ramp", "logit", "logit.lasso", "l2", "l2.lasso".
kernel	Type of kernel used by the support vector machine. The options are "linear", "rbf".
augment	If TRUE the outcomes are augmented.
c	Regularization parameter.
sigma	Tuning parameter.
s	Slope parameter.
m	Number of folds for cross-validation of the parameters.

Value

list of (default) control arguments.

control_ptl

Control arguments for Policy Tree Learning

Description

control_ptl sets the default control arguments for doubly robust policy tree learning, type = "ptl". The arguments are passed directly to `policytree::policy_tree()` (or `policytree::hybrid_policy_tree()`) if not specified otherwise.

Usage

```
control_ptl(
  policy_vars = NULL,
  hybrid = FALSE,
  depth = 2,
  search.depth = 2,
  split.step = 1,
  min.node.size = 1
)
```

Arguments

policy_vars	Character vector/string or list of character vectors/strings. Variable names used to construct the V-restricted policy tree. The names must be a subset of the history names, see <code>get_history_names()</code> . Not passed to <code>policy_tree()</code> .
hybrid	If TRUE, <code>policytree::hybrid_policy_tree()</code> is used to fit a policy tree. Not passed to <code>policy_tree()</code> .
depth	Integer or integer vector. The depth of the fitted policy tree for each stage.
search.depth	(only used if hybrid = TRUE) Integer or integer vector. Depth to look ahead when splitting at each stage.
split.step	Integer or integer vector. The number of possible splits to consider when performing policy tree search at each stage.
min.node.size	Integer or integer vector. The smallest terminal node size permitted at each stage.

Value

list of (default) control arguments.

control_rwl

*Control arguments for Residual Weighted Learning***Description**

control_rwl sets the default control arguments for residual learning , type = "rwl". The arguments are passed directly to `DynTxRegime::rwl()` if not specified otherwise.

Usage

```
control_rwl(
  moPropen,
  moMain,
  regime,
  fSet = NULL,
  lambdas = 2,
  cvFolds = 0L,
  kernel = "linear",
  kparam = NULL,
  responseType = "continuous",
  verbose = 2L
)
```

Arguments

moPropen	Propensity model of class "ModelObj", see <code>modelObj::modelObj</code> .
moMain	Main effects outcome model of class "ModelObj".
regime	An object of class <code>formula</code> specifying the design of the policy/regime.
fSet	A function or NULL defining subset structure.
lambdas	Numeric or numeric vector. Penalty parameter.
cvFolds	Integer. Number of folds for cross-validation of the parameters. "logit", "exp", "hinge", "sqhinge", "huber".
kernel	The options are "linear", "poly", "radial".
kparam	Numeric. Kernel parameter
responseType	Character string. Options are "continuous", "binary", "count".
verbose	Integer.

Value

list of (default) control arguments.

copy_policy_data	<i>Copy Policy Data Object</i>
------------------	--------------------------------

Description

Objects of class `policy_data` contains elements of class `data.table::data.table`. `data.table` provide functions that operate on objects by reference. Thus, the `policy_data` object is not copied when modified by reference, see examples. An explicit copy can be made by `copy_policy_data`. The function is a wrapper of `data.table::copy()`.

Usage

```
copy_policy_data(object)
```

Arguments

`object` Object of class `policy_data`.

Value

Object of class `policy_data`.

Examples

```
library("polle")
### Single stage case: Wide data
d1 <- sim_single_stage(5e2, seed=1)
head(d1, 5)
# constructing policy_data object:
pd1 <- policy_data(d1,
                  action="A",
                  covariates=c("Z", "B", "L"),
                  utility="U")

pd1

# True copy
pd2 <- copy_policy_data(pd1)
# manipulating the data.table by reference:
pd2$baseline_data[, id := id + 1]
head(pd2$baseline_data$id - pd1$baseline_data$id)

# False copy
pd2 <- pd1
# manipulating the data.table by reference:
pd2$baseline_data[, id := id + 1]
head(pd2$baseline_data$id - pd1$baseline_data$id)
```

<code>fit_g_functions</code>	<i>Fit g-functions</i>
------------------------------	------------------------

Description

`fit_g_functions` is used to fit a list of g-models.

Usage

```
fit_g_functions(policy_data, g_models, full_history = FALSE)
```

Arguments

<code>policy_data</code>	Policy data object created by <code>policy_data()</code> .
<code>g_models</code>	List of action probability models/g-models for each stage created by <code>g_empir()</code> , <code>g_glm()</code> , <code>g_rf()</code> , <code>g_sl()</code> or similar functions.
<code>full_history</code>	If TRUE, the full history is used to fit each g-model. If FALSE, the single stage/"Markov type" history is used to fit each g-model.

Examples

```
library("polle")
### Simulating two-stage policy data
d <- sim_two_stage(2e3, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))
pd

# fitting a single g-model across all stages:
g_functions <- fit_g_functions(policy_data = pd,
  g_models = g_glm(),
  full_history = FALSE)
g_functions

# fitting a g-model for each stage:
g_functions <- fit_g_functions(policy_data = pd,
  g_models = list(g_glm(), g_glm()),
  full_history = TRUE)
g_functions
```

`get_actions`*Get Actions*

Description

`get_actions` returns the actions at every stage for every observation in the policy data object.

Usage

```
get_actions(object)
```

Arguments

`object` Object of class `policy_data`.

Value

`data.table::data.table` with keys `id` and `stage` and character variable `A`.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
                   C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

pd

# getting the actions:
head(get_actions(pd))
```

`get_action_set`*Get Action Set*

Description

`get_action_set` returns the action set, i.e., the possible actions at each stage for the policy data object.

Usage

```
get_action_set(object)
```

Arguments

object Object of class [policy_data](#).

Value

Character vector.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))
pd

# getting the actions set:
get_action_set(pd)
```

get_g_functions	<i>Get g-functions</i>
-----------------	------------------------

Description

get_g_functions() returns a list of (fitted) g-functions associated with each stage.

Usage

```
get_g_functions(object)
```

Arguments

object Object of class [policy_eval](#) or [policy_object](#).

Value

List of class [nuisance_functions](#).

See Also

[predict.nuisance_functions](#)

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

pd

# evaluating the static policy a=1 using inverse propensity weighting
# based on a GLM model at each stage
pe <- policy_eval(type = "ipw",
  policy_data = pd,
  policy = policy_def(1, reuse = TRUE, name = "A=1"),
  g_models = list(g_glm(), g_glm()))

pe

# getting the g-functions
g_functions <- get_g_functions(pe)
g_functions

# getting the fitted g-function values
head(predict(g_functions, pd))

```

get_history_names	<i>Get history variable names</i>
-------------------	-----------------------------------

Description

get_history_names() returns the state covariate names of the history data table for a given stage. The function is useful when specifying the design matrix for [g_model](#) and [q_model](#) objects.

Usage

```
get_history_names(object, stage)
```

Arguments

object	Policy data object created by policy_data() .
stage	Stage number. If NULL, the state/Markov-type history variable names are returned.

Value

Character vector.

Examples

```

library("polle")
### Multiple stages:
d3 <- sim_multi_stage(5e2, seed = 1)
pd3 <- policy_data(data = d3$stage_data,
                  baseline_data = d3$baseline_data,
                  type = "long",
                  id = "id",
                  stage = "stage",
                  event = "event",
                  action = "A",
                  utility = "U")

pd3
# state/Markov type history variable names (H):
get_history_names(pd3)
# full history variable names (H_k) at stage 2:
get_history_names(pd3, stage = 2)

```

`get_id`*Get IDs*

Description

`get_id` returns the ID for every observation in the policy data object.

Usage

```
get_id(object)
```

Arguments

`object` Object of class `policy_data` or `history`.

Value

Character vector.

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
                 action = c("A_1", "A_2"),
                 baseline = c("B"),
                 covariates = list(L = c("L_1", "L_2"),
                                   C = c("C_1", "C_2")),
                 utility = c("U_1", "U_2", "U_3"))

pd

```

```
# getting the IDs:  
head(get_id(pd))
```

get_id_stage	<i>Get IDs and Stages</i>
--------------	---------------------------

Description

get_id returns the stages for every ID for every observation in the policy data object.

Usage

```
get_id_stage(object)
```

Arguments

object Object of class [policy_data](#) or [history](#).

Value

[data.table::data.table](#) with keys id and stage.

Examples

```
### Two stages:  
d <- sim_two_stage(5e2, seed=1)  
# constructing policy_data object:  
pd <- policy_data(d,  
                  action = c("A_1", "A_2"),  
                  baseline = c("B"),  
                  covariates = list(L = c("L_1", "L_2"),  
                                    C = c("C_1", "C_2")),  
                  utility = c("U_1", "U_2", "U_3"))  
  
pd  
  
# getting the IDs and stages:  
head(get_id_stage(pd))
```

get_K	<i>Get Maximal Stages</i>
-------	---------------------------

Description

get_K returns the maximal number of stages for the observations in the policy data object.

Usage

```
get_K(object)
```

Arguments

object Object of class [policy_data](#).

Value

Integer.

Examples

```
d <- sim_multi_stage(5e2, seed = 1)
pd <- policy_data(data = d$stage_data,
                  baseline_data = d$baseline_data,
                  type = "long",
                  id = "id",
                  stage = "stage",
                  event = "event",
                  action = "A",
                  utility = "U")

pd
# getting the maximal number of stages:
get_K(pd)
```

get_n	<i>Get Number of Observations</i>
-------	-----------------------------------

Description

get_n returns the number of observations in the policy data object.

Usage

```
get_n(object)
```

Arguments

object Object of class [policy_data](#).

Value

Integer.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

pd

# getting the number of observations:
get_n(pd)
```

get_policy

Get Policy

Description

get_policy extracts the policy from a policy object or a policy evaluation object. The policy is a function which takes a policy data object as input and returns the policy actions.

Usage

```
get_policy(object, threshold = NULL)
```

Arguments

object Object of class [policy_object](#) or [policy_eval](#).
threshold Numeric vector. Thresholds for the first stage policy function.

Value

function of class [policy](#).

Examples

```
library("polle")
### Two stages:
d <- sim_two_stage(5e2, seed = 1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("BB"),
  covariates = list(
```

```

    L = c("L_1", "L_2"),
    C = c("C_1", "C_2")
  ),
  utility = c("U_1", "U_2", "U_3")
)
pd

### V-restricted (Doubly Robust) Q-learning

# specifying the learner:
pl <- policy_learn(
  type = "drql",
  control = control_drql(qv_models = q_glm(formula = ~C))
)

# fitting the policy (object):
po <- pl(
  policy_data = pd,
  q_models = q_glm(),
  g_models = g_glm()
)

# getting and applying the policy:
head(get_policy(po)(pd))

# the policy learner can also be evaluated directly:
pe <- policy_eval(
  policy_data = pd,
  policy_learn = pl,
  q_models = q_glm(),
  g_models = g_glm()
)

# getting and applying the policy again:
head(get_policy(pe)(pd))

```

get_policy_actions *Get Policy Actions*

Description

get_policy_actions() extract the actions dictated by the (learned and possibly cross-fitted) policy a every stage.

Usage

```
get_policy_actions(object)
```

Arguments

object Object of class [policy_eval](#).

Value

`data.table::data.table` with keys `id` and `stage` and action variable `d`.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

pd

# defining a policy learner based on cross-fitted doubly robust Q-learning:
pl <- policy_learn(type = "drql",
  control = control_drql(qv_models = list(q_glm(~C_1), q_glm(~C_1+C_2))),
  full_history = TRUE,
  L = 2) # number of folds for cross-fitting

# evaluating the policy learner using 2-fold cross fitting:
pe <- policy_eval(type = "dr",
  policy_data = pd,
  policy_learn = pl,
  q_models = q_glm(),
  g_models = g_glm(),
  M = 2) # number of folds for cross-fitting

# Getting the cross-fitted actions dictated by the fitted policy:
head(get_policy_actions(pe))
```

```
get_policy_functions.blip
```

Get Policy Functions

Description

`get_policy_functions()` returns a function defining the policy at the given stage. `get_policy_functions()` is useful when implementing the learned policy.

Usage

```
## S3 method for class 'blip'
get_policy_functions(
  object,
  stage,
  threshold = NULL,
  include_g_values = FALSE,
  ...
```

```

)

## S3 method for class 'drql'
get_policy_functions(
  object,
  stage,
  threshold = NULL,
  include_g_values = FALSE,
  ...
)

get_policy_functions(object, stage, threshold, ...)

## S3 method for class 'ptl'
get_policy_functions(object, stage, threshold = NULL, ...)

## S3 method for class 'ql'
get_policy_functions(
  object,
  stage,
  threshold = NULL,
  include_g_values = FALSE,
  ...
)

```

Arguments

object	Object of class "policy_object" or "policy_eval", see policy_learn and policy_eval .
stage	Integer. Stage number.
threshold	Numeric, threshold for not choosing the reference action at stage 1.
include_g_values	If TRUE, the g-values are included as an attribute.
...	Additional arguments.

Value

Functions with arguments:

H [data.table::data.table](#) containing the variables needed to evaluate the policy (and g-function).

Examples

```

library("polle")
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = "BB",
  covariates = list(L = c("L_1", "L_2"),

```

```
                                C = c("C_1", "C_2")),
utility = c("U_1", "U_2", "U_3"))
pd

### Realistic V-restricted Policy Tree Learning
# specifying the learner:
pl <- policy_learn(type = "ptl",
                   control = control_ptl(policy_vars = list(c("C_1", "BB"),
                                                           c("L_1", "BB"))),
                   full_history = TRUE,
                   alpha = 0.05)

# evaluating the learner:
pe <- policy_eval(policy_data = pd,
                  policy_learn = pl,
                  q_models = q_glm(),
                  g_models = g_glm())

# getting the policy function at stage 2:
pf2 <- get_policy_functions(pe, stage = 2)
args(pf2)

# applying the policy function to new data:
set.seed(1)
L_1 <- rnorm(n = 10)
new_H <- data.frame(C = rnorm(n = 10),
                    L = L_1,
                    L_1 = L_1,
                    BB = "group1")
d2 <- pf2(H = new_H)
head(d2)
```

get_policy_object *Get Policy Object*

Description

Extract the fitted policy object.

Usage

```
get_policy_object(object)
```

Arguments

object Object of class `policy_eval`.

Value

Object of class `policy_object`.

Examples

```

library("polle")
### Single stage:
d1 <- sim_single_stage(5e2, seed=1)
pd1 <- policy_data(d1, action="A", covariates=list("Z", "B", "L"), utility="U")
pd1

# evaluating the policy:
pe1 <- policy_eval(policy_data = pd1,
                  policy_learn = policy_learn(type = "drql",
                                             control = control_drql(qv_models = q_glm(~.))),
                  g_models = g_glm(),
                  q_models = q_glm())

# extracting the policy object:
get_policy_object(pe1)

```

get_q_functions	<i>Get Q-functions</i>
-----------------	------------------------

Description

get_q_functions() returns a list of (fitted) Q-functions associated with each stage.

Usage

```
get_q_functions(object)
```

Arguments

object Object of class [policy_eval](#) or [policy_object](#).

Value

List of class [nuisance_functions](#).

See Also

[predict.nuisance_functions](#)

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed = 1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(

```

```

      L = c("L_1", "L_2"),
      C = c("C_1", "C_2")
    ),
    utility = c("U_1", "U_2", "U_3")
  )
pd

# evaluating the static policy a=1 using outcome regression
# based on a GLM model at each stage.
pe <- policy_eval(
  type = "or",
  policy_data = pd,
  policy = policy_def(1, reuse = TRUE, name = "A=1"),
  q_models = list(q_glm(), q_glm())
)
pe

# getting the Q-functions
q_functions <- get_q_functions(pe)

# getting the fitted g-function values
head(predict(q_functions, pd))

```

get_stage_action_sets *Get Stage Action Sets*

Description

get_stage_action_sets returns the action sets at each stage, i.e., the possible actions at each stage for the policy data object.

Usage

```
get_stage_action_sets(object)
```

Arguments

object Object of class [policy_data](#).

Value

List of character vectors.

Examples

```

### Two stages:
d <- sim_two_stage_multi_actions(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
  action = c("A_1", "A_2"),

```

```

        baseline = c("B"),
        covariates = list(L = c("L_1", "L_2"),
                          C = c("C_1", "C_2")),
        utility = c("U_1", "U_2", "U_3"))
pd

# getting the stage actions set:
get_stage_action_sets(pd)

```

get_utility

Get the Utility

Description

get_utility() returns the utility, i.e., the sum of the rewards, for every observation in the policy data object.

Usage

```
get_utility(object)
```

Arguments

object Object of class [policy_data](#).

Value

[data.table::data.table](#) with key id and numeric variable U.

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
                    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))
pd

# getting the utility:
head(get_utility(pd))

```

g_model	<i>g_model class object</i>
---------	-----------------------------

Description

Use `g_glm()`, `g_empir()`, `g_glmnet()`, `g_rf()`, `g_sl()`, `g_xgboost` to construct an action probability model/g-model object. The constructors are used as input for `policy_eval()` and `policy_learn()`.

Usage

```
g_empir(formula = ~1, ...)
```

```
g_glm(  
  formula = ~.,  
  family = "binomial",  
  model = FALSE,  
  na.action = na.pass,  
  ...  
)
```

```
g_glmnet(formula = ~., family = "binomial", alpha = 1, s = "lambda.min", ...)
```

```
g_rf(  
  formula = ~.,  
  num.trees = c(500),  
  mtry = NULL,  
  cv_args = list(nfolds = 5, rep = 1),  
  ...  
)
```

```
g_sl(  
  formula = ~.,  
  SL.library = c("SL.mean", "SL.glm"),  
  family = binomial(),  
  env = as.environment("package:SuperLearner"),  
  onlySL = TRUE,  
  ...  
)
```

```
g_xgboost(  
  formula = ~.,  
  objective = "binary:logistic",  
  params = list(),  
  nrounds,  
  max_depth = 6,  
  eta = 0.3,  
  nthread = 1,
```

```
cv_args = list(nfolds = 3, rep = 1)
)
```

Arguments

formula	An object of class formula specifying the design matrix for the propensity model/g-model. Use get_history_names() to view the available variable names.
...	Additional arguments passed to glm() , glmnet::glmnet , ranger::ranger or SuperLearner::SuperLearner .
family	A description of the error distribution and link function to be used in the model.
model	(Only used by g_glm) If FALSE model frame will not be saved.
na.action	(Only used by g_glm) A function which indicates what should happen when the data contain NAs, see na.pass .
alpha	(Only used by g_glmnet) The elastic net mixing parameter between 0 and 1. alpha equal to 1 is the lasso penalty, and alpha equal to 0 the ridge penalty.
s	(Only used by g_glmnet) Value(s) of the penalty parameter lambda at which predictions are required, see glmnet::predict.glmnet() .
num.trees	(Only used by g_rf) Number of trees.
mtry	(Only used by g_rf) Number of variables to possibly split at in each node.
cv_args	(Only used by g_rf and g_xgboost) Cross-validation parameters. Only used if multiple hyper-parameters are given. K is the number of folds and rep is the number of replications.
SL.library	(Only used by g_sl) Either a character vector of prediction algorithms or a list containing character vectors, see SuperLearner::SuperLearner .
env	(Only used by g_sl) Environment containing the learner functions. Defaults to the calling environment.
onlySL	(Only used by g_sl) Logical. If TRUE, only saves and computes predictions for algorithms with non-zero coefficients in the super learner object.
objective	(Only used by g_xgboost) specify the learning task and the corresponding learning objective, see xgboost::xgboost .
params	(Only used by g_xgboost) list of parameters.
nrounds	(Only used by g_xgboost) max number of boosting iterations.
max_depth	(Only used by g_xgboost) maximum depth of a tree.
eta	(Only used by g_xgboost) learning rate.
nthread	(Only used by g_xgboost) number of threads.

Details

[g_glm\(\)](#) is a wrapper of [glm\(\)](#) (generalized linear model).

[g_empir\(\)](#) calculates the empirical probabilities within the groups defined by the formula.

[g_glmnet\(\)](#) is a wrapper of [glmnet::glmnet\(\)](#) (generalized linear model via penalized maximum likelihood).

[g_rf\(\)](#) is a wrapper of [ranger::ranger\(\)](#) (random forest). When multiple hyper-parameters are given, the model with the lowest cross-validation error is selected.

[g_sl\(\)](#) is a wrapper of [SuperLearner::SuperLearner](#) (ensemble model).

[g_xgboost\(\)](#) is a wrapper of [xgboost::xgboost](#).

Value

g-model object: function with arguments 'A' (action vector), 'H' (history matrix) and 'action_set'.

See Also

[get_history_names\(\)](#), [get_g_functions\(\)](#).

Examples

```
library("polle")
### Two stages:
d <- sim_two_stage(2e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))
pd

# available state history variable names:
get_history_names(pd)
# defining a g-model:
g_model <- g_glm(formula = ~B+C)

# evaluating the static policy (A=1) using inverse propensity weighting
# based on a state glm model across all stages:
pe <- policy_eval(type = "ipw",
  policy_data = pd,
  policy = policy_def(1, reuse = TRUE),
  g_models = g_model)
# inspecting the fitted g-model:
get_g_functions(pe)

# available full history variable names at each stage:
get_history_names(pd, stage = 1)
get_history_names(pd, stage = 2)

# evaluating the same policy based on a full history
# glm model for each stage:
pe <- policy_eval(type = "ipw",
  policy_data = pd,
  policy = policy_def(1, reuse = TRUE),
  g_models = list(g_glm(~ L_1 + B),
    g_glm(~ A_1 + L_2 + B)),
  g_full_history = TRUE)
# inspecting the fitted g-models:
get_g_functions(pe)
```

history	<i>Get History Object</i>
---------	---------------------------

Description

`get_history` summarizes the history and action at a given stage from a `policy_data` object.

Usage

```
get_history(object, stage = NULL, full_history = FALSE)
```

Arguments

<code>object</code>	Object of class <code>policy_data</code> .
<code>stage</code>	Stage number. If <code>NULL</code> , the state/Markov-type history across all stages is returned.
<code>full_history</code>	Logical. If <code>TRUE</code> , the full history is returned. If <code>FALSE</code> , only the state/Markov-type history is returned.

Details

Each observation has the sequential form

$$O = B, U_1, X_1, A_1, \dots, U_K, X_K, A_K, U_{K+1},$$

for a possibly stochastic number of stages K .

- B is a vector of baseline covariates.
- U_k is the reward at stage k (not influenced by the action A_k).
- X_k is a vector of state covariates summarizing the state at stage k .
- A_k is the categorical action at stage k .

Value

Object of class `history`. The object is a list containing the following elements:

<code>H</code>	<code>data.table::data.table</code> with keys <code>id</code> and <code>stage</code> and with variables $\{B, X_k\}$ (state history) or $\{B, X_1, A_1, \dots, X_k\}$ (full history), see details.
<code>A</code>	<code>data.table::data.table</code> with keys <code>id</code> and <code>stage</code> and variable A_k , see details.
<code>action_name</code>	Name of the action variable in <code>A</code> .
<code>action_set</code>	Sorted character vector defining the action set.
<code>U</code>	(If <code>stage</code> is not <code>NULL</code>) <code>data.table::data.table</code> with keys <code>id</code> and <code>stage</code> and with variables <code>U_bar</code> and <code>U_Aa</code> for every <code>a</code> in the actions set. <code>U_bar</code> is the accumulated rewards up till and including the given stage, i.e., $\sum_{j=1}^k U_j$. <code>U_Aa</code> is the deterministic reward of action <code>a</code> .

Examples

```

library("polle")
### Single stage:
d1 <- sim_single_stage(5e2, seed=1)
# constructing policy_data object:
pd1 <- policy_data(d1, action="A", covariates=list("Z", "B", "L"), utility="U")
pd1

# In the single stage case, set stage = NULL
h1 <- get_history(pd1)
head(h1$H)
head(h1$A)

### Two stages:
d2 <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd2 <- policy_data(d2,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))
pd2
# getting the state/Markov-type history across all stages:
h2 <- get_history(pd2)
head(h2$H)
head(h2$A)

# getting the full history at stage 2:
h2 <- get_history(pd2, stage = 2, full_history = TRUE)
head(h2$H)
head(h2$A)
head(h2$U)

# getting the state/Markov-type history at stage 2:
h2 <- get_history(pd2, stage = 2, full_history = FALSE)
head(h2$H)
head(h2$A)

### Multiple stages
d3 <- sim_multi_stage(5e2, seed = 1)
# constructing policy_data object:
pd3 <- policy_data(data = d3$stage_data,
  baseline_data = d3$baseline_data,
  type = "long",
  id = "id",
  stage = "stage",
  event = "event",
  action = "A",
  utility = "U")
pd3

```

```
# getting the full history at stage 2:
h3 <- get_history(pd3, stage = 2, full_history = TRUE)
head(h3$H)
# note that not all observations have two stages:
nrow(h3$H) # number of observations with two stages.
get_n(pd3) # number of observations in total.
```

nuisance_functions *Nuisance Functions*

Description

The fitted g-functions and Q-functions are stored in an object of class "nuisance_functions". The object is a list with a fitted model object for every stage. Information on whether the full history or the state/Markov-type history is stored as an attribute ("full_history").

S3 generics

The following S3 generic functions are available for an object of class nuisance_functions:

`predict` Predict the values of the g- or Q-functions based on a [policy_data](#) object.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
                 action = c("A_1", "A_2"),
                 covariates = list(L = c("L_1", "L_2"),
                                   C = c("C_1", "C_2")),
                 utility = c("U_1", "U_2", "U_3"))
pd

# evaluating the static policy a=1:
pe <- policy_eval(policy_data = pd,
                 policy = policy_def(1, reuse = TRUE),
                 g_models = g_glm(),
                 q_models = q_glm())

# getting the fitted g-functions:
(g_functions <- get_g_functions(pe))

# getting the fitted Q-functions:
(q_functions <- get_q_functions(pe))

# getting the fitted values:
head(predict(g_functions, pd))
head(predict(q_functions, pd))
```

partial	<i>Trim Number of Stages</i>
---------	------------------------------

Description

partial creates a partial policy data object by trimming the maximum number of stages in the policy data object to a fixed given number.

Usage

```
partial(object, K)
```

Arguments

object	Object of class policy_data .
K	Maximum number of stages.

Value

Object of class [policy_data](#).

Examples

```
library("polle")
### Multiple stage case
d <- sim_multi_stage(5e2, seed = 1)
# constructing policy_data object:
pd <- policy_data(data = d$stage_data,
                  baseline_data = d$baseline_data,
                  type = "long",
                  id = "id",
                  stage = "stage",
                  event = "event",
                  action = "A",
                  utility = "U")

pd
# Creating a partial policy data object with 3 stages
pd3 <- partial(pd, K = 3)
pd3
```

plot.policy_data *Plot policy data for given policies*

Description

Plot policy data for given policies

Usage

```
## S3 method for class 'policy_data'
plot(
  x,
  policy = NULL,
  which = c(1),
  stage = 1,
  history_variables = NULL,
  jitter = 0.05,
  ...
)
```

Arguments

x	Object of class policy_data
policy	An object or list of objects of class policy
which	A subset of the numbers 1:2 <ul style="list-style-type: none"> • 1 Spaghetti plot of the cumulative rewards • 2 Plot of the policy actions for a given stage
stage	Stage number for plot 2
history_variables	character vector of length 2 for plot 2
jitter	numeric
...	Additional arguments

Examples

```
library("polle")
library("data.table")
setDTthreads(1)
d3 <- sim_multi_stage(2e2, seed = 1)
pd3 <- policy_data(data = d3$stage_data,
                  baseline_data = d3$baseline_data,
                  type = "long",
                  id = "id",
                  stage = "stage",
                  event = "event",
                  action = "A",
```



```

        utility = "U")

# specifying two static policies:
p0 <- policy_def(c(1,1,0,0), name = "p0")
p1 <- policy_def(c(1,0,0,0), name = "p1")

plot(pd3)
plot(pd3, policy = list(p0, p1))

# learning and plotting a policy:
pe3 <- policy_eval(pd3,
                  policy_learn = policy_learn(),
                  q_models = q_glm(formula = ~t + X + X_lead))
plot(pd3, list(get_policy(pe3), p0))

# plotting the recommended actions at a specific stage:
plot(pd3, get_policy(pe3),
     which = 2,
     stage = 2,
     history_variables = c("t", "X"))

```

plot.policy_eval *Plot histogram of the influence curve for a policy_eval object*

Description

Plot histogram of the influence curve for a policy_eval object

Usage

```
## S3 method for class 'policy_eval'
plot(x, ...)
```

Arguments

x Object of class [policy_eval](#)
 ... Additional arguments

Examples

```

d <- sim_two_stage(2e3, seed=1)
pd <- policy_data(d,
                 action = c("A_1", "A_2"),
                 baseline = "BB",
                 covariates = list(L = c("L_1", "L_2"),
                                   C = c("C_1", "C_2")),
                 utility = c("U_1", "U_2", "U_3"))

pe <- policy_eval(pd,

```

```

policy_learn = policy_learn()

plot(pe)

```

policy	<i>Policy-class</i>
--------	---------------------

Description

A function of inherited class "policy" takes a policy data object as input and returns the policy actions for every observation for every (observed) stage.

Details

A policy can either be defined directly by the user using [policy_def](#) or a policy can be fitted using [policy_learn](#) (or [policy_eval](#)). [policy_learn](#) returns a [policy_object](#) from which the policy can be extracted using [get_policy](#).

Value

[data.table::data.table](#) with keys id and stage and action variable d.

S3 generics

The following S3 generic functions are available for an object of class policy:

print Basic print function

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

# defining a dynamic policy:
p <- policy_def(
  function(L) (L>0)*1,
  reuse = TRUE
)
p
head(p(pd), 5)

# V-restricted (Doubly Robust) Q-learning:
# specifying the learner:
pl <- policy_learn(type = "drql",
  control = control_drql(qv_models = q_glm(formula = ~ C)))

```

```

# fitting the policy (object):
po <- pl(policy_data = pd,
        q_models = q_glm(),
        g_models = g_glm())

p <- get_policy(po)
p

head(p(pd))

```

policy_data

Create Policy Data Object

Description

`policy_data()` creates a policy data object which is used as input to `policy_eval()` and `policy_learn()` for policy evaluation and data adaptive policy learning.

Usage

```

policy_data(
  data,
  baseline_data,
  type = "wide",
  action,
  covariates,
  utility,
  baseline = NULL,
  deterministic_rewards = NULL,
  id = NULL,
  stage = NULL,
  event = NULL,
  action_set = NULL,
  verbose = FALSE
)

## S3 method for class 'policy_data'
print(x, digits = 2, ...)

## S3 method for class 'policy_data'
summary(object, probs = seq(0, 1, 0.25), ...)

```

Arguments

`data` [data.frame](#) or [data.table::data.table](#); see Examples.
`baseline_data` [data.frame](#) or [data.table::data.table](#); see Examples.

type	Character string. If "wide", data is considered to be on wide format. If "long", data is considered to be on long format; see Examples.
action	Action variable name(s). Character vector or character string. <ul style="list-style-type: none"> • A vector is valid for wide data. The length of the vector determines the number of stages (K). • A string is valid for single stage wide data or long data.
covariates	Stage specific covariate name(s). Character vector or named list of character vectors. <ul style="list-style-type: none"> • A vector is valid for single stage wide data or long data. • A named list is valid for multiple stages wide data. Each element must be a character vector with length K. Each vector can contain NA elements, if a covariate is not available for the given stage(s).
utility	Utility/Reward variable name(s). Character string or vector. <ul style="list-style-type: none"> • A string is valid for long data and wide data with a single final utility. • A vector is valid for wide data with incremental rewards. Must have length K+1; see Examples.
baseline	Baseline covariate name(s). Character vector.
deterministic_rewards	Deterministic reward variable name(s). Named list of character vectors of length K. The name of each element must be on the form "U_Aa" where "a" corresponds to an action in the action set.
id	ID variable name. Character string.
stage	Stage number variable name.
event	Event indicator name.
action_set	Character string. Action set across all stages.
verbose	Logical. If TRUE, formatting comments are printed to the console.
x	Object to be printed.
digits	Minimum number of digits to be printed.
...	Additional arguments passed to print.
object	Object of class <code>policy_data</code>
probs	numeric vector (probabilities)

Details

Each observation has the sequential form

$$O = B, U_1, X_1, A_1, \dots, U_K, X_K, A_K, U_{K+1},$$

for a possibly stochastic number of stages K.

- B is a vector of baseline covariates.
- U_k is the reward at stage k (not influenced by the action A_k).
- X_k is a vector of state covariates summarizing the state at stage k.
- A_k is the categorical action at stage k.

The utility is given by the sum of the rewards, i.e., $U = \sum_{k=1}^{K+1} U_k$.

Value

policy_data() returns an object of class "policy_data". The object is a list containing the following elements:

stage_data	data.table::data.table containing the id, stage number, event indicator, action (A_k), state covariates (X_k), reward (U_k), and the deterministic rewards.
baseline_data	data.table::data.table containing the id and baseline covariates (B).
colnames	List containing the state covariate names, baseline covariate names, and the deterministic reward variable names.
action_set	Sorted character vector describing the action set, i.e., the possible actions at all stages.
stage_action_sets	List of sorted character vectors describing the observed actions at each stage.
dim	List containing the number of observations (n) and the number of stages (K).

S3 generics

The following S3 generic functions are available for an object of class policy_data:

[partial\(\)](#) Trim the maximum number of stages in a policy_data object.
[subset_id\(\)](#) Subset a policy_data object on ID.
[get_history\(\)](#) Summarize the history and action at a given stage.
[get_history_names\(\)](#) Get history variable names.
[get_actions\(\)](#) Get the action at every stage.
[get_utility\(\)](#) Get the utility.
[plot\(\)](#) Plot method.

See Also

[policy_eval\(\)](#), [policy_learn\(\)](#), [copy_policy_data\(\)](#)

Examples

```
library("polle")
### Single stage: Wide data
d1 <- sim_single_stage(n = 5e2, seed=1)
head(d1, 5)
# constructing policy_data object:
pd1 <- policy_data(d1,
                  action="A",
                  covariates=c("Z", "B", "L"),
                  utility="U")

pd1
# associated S3 methods:
methods(class = "policy_data")
head(get_actions(pd1), 5)
head(get_utility(pd1), 5)
```

```

head(get_history(pd1)$H, 5)

### Two stage: Wide data
d2 <- sim_two_stage(5e2, seed=1)
head(d2, 5)
# constructing policy_data object:
pd2 <- policy_data(d2,
  action = c("A_1", "A_2"),
  baseline = c("B"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

pd2
head(get_history(pd2, stage = 2)$H, 5) # state/Markov type history and action, (H_k,A_k).
head(get_history(pd2, stage = 2, full_history = TRUE)$H, 5) # Full history and action, (H_k,A_k).

### Multiple stages: Long data
d3 <- sim_multi_stage(5e2, seed = 1)
head(d3$stage_data, 10)
# constructing policy_data object:
pd3 <- policy_data(data = d3$stage_data,
  baseline_data = d3$baseline_data,
  type = "long",
  id = "id",
  stage = "stage",
  event = "event",
  action = "A",
  utility = "U")

pd3
head(get_history(pd3, stage = 3)$H, 5) # state/Markov type history and action, (H_k,A_k).
head(get_history(pd3, stage = 2, full_history = TRUE)$H, 5) # Full history and action, (H_k,A_k).

```

policy_def

Define Policy

Description

policy_def returns a function of class `policy`. The function input is a `policy_data` object and it returns a `data.table::data.table` with keys `id` and `stage` and action variable `d`.

Usage

```
policy_def(policy_functions, full_history = FALSE, reuse = FALSE, name = NULL)
```

Arguments

policy_functions

A single function/character string or a list of functions/character strings. The list must have the same length as the number of stages.

full_history

If TRUE, the full history at each stage is used as input to the policy functions.

reuse	If TRUE, the policy function is reused at every stage.
name	Character string.

Value

Function of class "policy". The function takes a [policy_data](#) object as input and returns a [data.table::data.table](#) with keys id and stage and action variable d.

See Also

[get_history_names\(\)](#), [get_history\(\)](#).

Examples

```
library("polle")
### Single stage"
d1 <- sim_single_stage(5e2, seed=1)
pd1 <- policy_data(d1, action="A", covariates=list("Z", "B", "L"), utility="U")
pd1

# defining a static policy (A=1):
p1_static <- policy_def(1)

# applying the policy:
p1_static(pd1)

# defining a dynamic policy:
p1_dynamic <- policy_def(
  function(Z, L) ((3*Z + 1*L -2.5)>0)*1
)
p1_dynamic(pd1)

### Two stages:
d2 <- sim_two_stage(5e2, seed = 1)
pd2 <- policy_data(d2,
  action = c("A_1", "A_2"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

# defining a static policy (A=0):
p2_static <- policy_def(0,
  reuse = TRUE)
p2_static(pd2)

# defining a reused dynamic policy:
p2_dynamic_reuse <- policy_def(
  function(L) (L > 0)*1,
  reuse = TRUE
)
p2_dynamic_reuse(pd2)
```

```

# defining a dynamic policy for each stage based on the full history:
# available variable names at each stage:
get_history_names(pd2, stage = 1)
get_history_names(pd2, stage = 2)

p2_dynamic <- policy_def(
  policy_functions = list(
    function(L_1) (L_1 > 0)*1,
    function(L_1, L_2) (L_1 + L_2 > 0)*1
  ),
  full_history = TRUE
)
p2_dynamic(pd2)

```

policy_eval

Policy Evaluation

Description

policy_eval() is used to estimate the value of a given fixed policy or a data adaptive policy (e.g. a policy learned from the data). policy_eval() is also used to estimate the average treatment effect among the subjects who would get the treatment under the policy.

Usage

```

policy_eval(
  policy_data,
  policy = NULL,
  policy_learn = NULL,
  g_functions = NULL,
  g_models = g_glm(),
  g_full_history = FALSE,
  save_g_functions = TRUE,
  q_functions = NULL,
  q_models = q_glm(),
  q_full_history = FALSE,
  save_q_functions = TRUE,
  target = "value",
  type = "dr",
  cross_fit_type = "pooled",
  variance_type = "pooled",
  M = 1,
  future_args = list(future.seed = TRUE),
  name = NULL
)

## S3 method for class 'policy_eval'
coef(object, ...)

```



```

## S3 method for class 'policy_eval'
IC(x, ...)

## S3 method for class 'policy_eval'
vcov(object, ...)

## S3 method for class 'policy_eval'
print(
  x,
  digits = 4L,
  width = 35L,
  std.error = TRUE,
  level = 0.95,
  p.value = TRUE,
  ...
)

## S3 method for class 'policy_eval'
summary(object, ...)

## S3 method for class 'policy_eval'
estimate(
  x,
  labels = get_element(x, "name", check_name = FALSE),
  level = 0.95,
  ...
)

## S3 method for class 'policy_eval'
merge(x, y, ..., paired = TRUE)

## S3 method for class 'policy_eval'
x + ...

```

Arguments

policy_data	Policy data object created by policy_data() .
policy	Policy object created by policy_def() .
policy_learn	Policy learner object created by policy_learn() .
g_functions	Fitted g-model objects, see nuisance_functions . Preferably, use <code>g_models</code> .
g_models	List of action probability models/g-models for each stage created by g_empir() , g_glm() , g_rf() , g_sl() or similar functions. Only used for evaluation if <code>g_functions</code> is NULL. If a single model is provided and <code>g_full_history</code> is FALSE, a single g-model is fitted across all stages. If <code>g_full_history</code> is TRUE the model is reused at every stage.
g_full_history	If TRUE, the full history is used to fit each g-model. If FALSE, the state/Markov type history is used to fit each g-model.

save_g_functions	If TRUE, the fitted g-functions are saved.
q_functions	Fitted Q-model objects, see nuisance_functions . Only valid if the Q-functions are fitted using the same policy. Preferably, use <code>q_models</code> .
q_models	Outcome regression models/Q-models created by <code>q_glm()</code> , <code>q_rf()</code> , <code>q_sl()</code> or similar functions. Only used for evaluation if <code>q_functions</code> is NULL. If a single model is provided, the model is reused at every stage.
q_full_history	Similar to <code>g_full_history</code> .
save_q_functions	Similar to <code>save_g_functions</code> .
target	Character string. Either "value" or "subgroup". If "value", the target parameter is the policy value. If "subgroup", the target parameter is the average treatment effect among the subgroup of subjects that would receive treatment under the policy, see details. "subgroup" is only implemented for <code>type = "dr"</code> in the single-stage case with a dichotomous action set.
type	Character string. Type of evaluation. Either "dr" (doubly robust), "ipw" (inverse propensity weighting), or "or" (outcome regression).
cross_fit_type	Character string. Either "stacked", or "pooled", see details. (Only used if $M > 1$ and <code>target = "subgroup"</code>)
variance_type	Character string. Either "pooled" (default), "stacked" or "complete", see details. (Only used if $M > 1$)
M	Number of folds for cross-fitting.
future_args	Arguments passed to <code>future.apply::future_apply()</code> .
name	Character string.
object, x, y	Objects of class "policy_eval".
...	Additional arguments.
digits	Integer. Number of printed digits.
width	Integer. Width of printed parameter name.
std.error	Logical. Should the std.error be printed.
level	Numeric. Level of confidence limits.
p.value	Logical. Should the p.value for associated confidence level be printed.
labels	Name(s) of the estimate(s).
paired	TRUE indicates that the estimates are based on the same data sample.

Details

Each observation has the sequential form

$$O = B, U_1, X_1, A_1, \dots, U_K, X_K, A_K, U_{K+1},$$

for a possibly stochastic number of stages K .

- B is a vector of baseline covariates.

- U_k is the reward at stage k (not influenced by the action A_k).
- X_k is a vector of state covariates summarizing the state at stage k .
- A_k is the categorical action within the action set \mathcal{A} at stage k .

The utility is given by the sum of the rewards, i.e., $U = \sum_{k=1}^{K+1} U_k$.

A policy is a set of functions

$$d = \{d_1, \dots, d_K\},$$

where d_k for $k \in \{1, \dots, K\}$ maps $\{B, X_1, A_1, \dots, A_{k-1}, X_k\}$ into the action set.

Recursively define the Q-models (q_models):

$$Q_K^d(h_K, a_K) = E[U | H_K = h_K, A_K = a_K]$$

$$Q_k^d(h_k, a_k) = E[Q_{k+1}(H_{k+1}, d_{k+1}(B, X_1, A_1, \dots, X_{k+1})) | H_k = h_k, A_k = a_k].$$

If `q_full_history = TRUE`, $H_k = \{B, X_1, A_1, \dots, A_{k-1}, X_k\}$, and if `q_full_history = FALSE`, $H_k = \{B, X_k\}$.

The g-models (g_models) are defined as

$$g_k(h_k, a_k) = P(A_k = a_k | H_k = h_k).$$

If `g_full_history = TRUE`, $H_k = \{B, X_1, A_1, \dots, A_{k-1}, X_k\}$, and if `g_full_history = FALSE`, $H_k = \{B, X_k\}$. Furthermore, if `g_full_history = FALSE` and `g_models` is a single model, it is assumed that $g_1(h_1, a_1) = \dots = g_K(h_K, a_K)$.

If `target = "value"` and `type = "or"` `policy_eval()` returns the empirical estimate of the value (coef):

$$E [Q_1^d(H_1, d_1(\cdot))]$$

If `target = "value"` and `type = "ipw"` `policy_eval()` returns the empirical estimates of the value (coef) and influence curve (IC):

$$E \left[\left(\prod_{k=1}^K I\{A_k = d_k(\cdot)\} g_k(H_k, A_k)^{-1} \right) U \right].$$

$$\left(\prod_{k=1}^K I\{A_k = d_k(\cdot)\} g_k(H_k, A_k)^{-1} \right) U - E \left[\left(\prod_{k=1}^K I\{A_k = d_k(\cdot)\} g_k(H_k, A_k)^{-1} \right) U \right].$$

If `target = "value"` and `type = "dr"` `policy_eval` returns the empirical estimates of the value (coef) and influence curve (IC):

$$E[Z_1(d, g, Q^d)(O)],$$

$$Z_1(d, g, Q^d)(O) - E[Z_1(d, g, Q^d)(O)],$$

where

$$Z_1(d, g, Q^d)(O) = Q_1^d(H_1, d_1(\cdot)) + \sum_{r=1}^K \prod_{j=1}^r \frac{I\{A_j = d_j(\cdot)\}}{g_j(H_j, A_j)} \{Q_{r+1}^d(H_{r+1}, d_{r+1}(\cdot)) - Q_r^d(H_r, d_r(\cdot))\}.$$

If target = "subgroup", type = "dr", $K = 1$, and $\mathcal{A} = \{0, 1\}$, `policy_eval()` returns the empirical estimates of the subgroup average treatment effect (coef) and influence curve (IC):

$$E[Z_1(1, g, Q)(O) - Z_1(0, g, Q)(O) | d_1(\cdot) = 1],$$

$$\frac{1}{P(d_1(\cdot) = 1)} I\{d_1(\cdot) = 1\} \left\{ Z_1(1, g, Q)(O) - Z_1(0, g, Q)(O) - E[Z_1(1, g, Q)(O) - Z_1(0, g, Q)(O) | d_1(\cdot) = 1] \right\}.$$

Applying M -fold cross-fitting using the `{M}` argument, let

$$\mathcal{Z}_{1,m}(a) = \{Z_1(a, g_m, Q_m^d)(O) : O \in \mathcal{O}_m\}.$$

If target = "subgroup", type = "dr", $K = 1$, $\mathcal{A} = \{0, 1\}$, and `cross_fit_type = "pooled"`, `policy_eval()` returns the estimate

$$\frac{1}{N^{-1} \sum_{i=1}^N I\{d(H_i) = 1\}} N^{-1} \sum_{m=1}^M \sum_{(Z,H) \in \mathcal{Z}_{1,m} \times \mathcal{H}_{1,m}} I\{d_1(H) = 1\} \{Z(1) - Z(0)\}$$

If `cross_fit_type = "stacked"` the returned estimate is

$$M^{-1} \sum_{m=1}^M \frac{1}{n^{-1} \sum_{h \in \mathcal{H}_{1,m}} I\{d(h) = 1\}} n^{-1} \sum_{(Z,H) \in \mathcal{Z}_{1,m} \times \mathcal{H}_{1,m}} I\{d_1(H) = 1\} \{Z(1) - Z(0)\},$$

where for ease of notation we let the integer n be the number of observations in each fold.

Value

`policy_eval()` returns an object of class "policy_eval". The object is a list containing the following elements:

coef	Numeric vector. The estimated target parameter: policy value or subgroup average treatment effect.
IC	Numeric matrix. Estimated influence curve associated with coef.
type	Character string. The type of evaluation ("dr", "ipw", "or").
target	Character string. The target parameter ("value" or "subgroup")
id	Character vector. The IDs of the observations.
name	Character vector. Names for the each element in coef.
coef_ipw	(only if type = "dr") Numeric vector. Estimate of coef based solely on inverse probability weighting.
coef_or	(only if type = "dr") Numeric vector. Estimate of coef based solely on outcome regression.
policy_actions	<code>data.table::data.table</code> with keys id and stage. Actions associated with the policy for every observation and stage.
policy_object	(only if policy = NULL and M = 1) The policy object returned by <code>policy_learn</code> , see policy_learn .
g_functions	(only if M = 1) The fitted g-functions. Object of class "nuisance_functions".

g_values	The fitted g-function values.
q_functions	(only if $M = 1$) The fitted Q-functions. Object of class "nuisance_functions".
q_values	The fitted Q-function values.
Z	(only if target = "subgroup") Matrix with the doubly robust stage 1 scores for each action.
subgroup_indicator	(only if target = "subgroup") Logical matrix identifying subjects in the subgroup. Each column represents a different subgroup threshold.
cross_fits	(only if $M > 1$) List containing the "policy_eval" object for every (validation) fold.
fold	(only if $M > 1$) The (validation) folds used for cross-fitting.
cross_fit_type	Character string.
variance_type	Character string.

S3 generics

The following S3 generic functions are available for an object of class `policy_eval`:

- `get_g_functions()` Extract the fitted g-functions.
- `get_q_functions()` Extract the fitted Q-functions.
- `get_policy()` Extract the fitted policy object.
- `get_policy_functions()` Extract the fitted policy function for a given stage.
- `get_policy_actions()` Extract the (fitted) policy actions.
- `plot.policy_eval()` Plot diagnostics.

References

- van der Laan, Mark J., and Alexander R. Luedtke. "Targeted learning of the mean outcome under an optimal dynamic treatment rule." *Journal of causal inference* 3.1 (2015): 61-95. doi:10.1515/jci-20130022
- Tsiatis, Anastasios A., et al. *Dynamic treatment regimes: Statistical methods for precision medicine*. Chapman and Hall/CRC, 2019. doi:10.1201/9780429192692.
- Victor Chernozhukov, Denis Chetverikov, Mert Demirer, Esther Duflo, Christian Hansen, Whitney Newey, James Robins, Double/debiased machine learning for treatment and structural parameters, *The Econometrics Journal*, Volume 21, Issue 1, 1 February 2018, Pages C1–C68, doi:10.1111/ectj.12097.

See Also

`lava::IC`, `lava::estimate.default`.


```

        utility = c("U_1", "U_2", "U_3"))
pd2

# defining a policy learner based on cross-fitted doubly robust Q-learning:
pl2 <- policy_learn(
  type = "drql",
  control = control_drql(qv_models = list(q_glm(~C_1),
                                         q_glm(~C_1+C_2))),
  full_history = TRUE,
  L = 2) # number of folds for cross-fitting

# evaluating the policy learner using 2-fold cross fitting:
pe2 <- policy_eval(type = "dr",
  policy_data = pd2,
  policy_learn = pl2,
  q_models = q_glm(),
  g_models = g_glm(),
  M = 2, # number of folds for cross-fitting
  name = "drql")

# summarizing the estimated value of the policy:
pe2

# getting the cross-fitted policy actions:
head(get_policy_actions(pe2))

```

policy_learn

Create Policy Learner

Description

policy_learn() is used to specify a policy learning method (Q-learning, doubly robust Q-learning, policy tree learning and outcome weighted learning). Evaluating the policy learner returns a policy object.

Usage

```

policy_learn(
  type = "ql",
  control = list(),
  alpha = 0,
  threshold = NULL,
  full_history = FALSE,
  L = 1,
  cross_fit_g_models = TRUE,
  save_cross_fit_models = FALSE,
  future_args = list(future.seed = TRUE),
  name = type
)

```

```
## S3 method for class 'policy_learn'
print(x, ...)

## S3 method for class 'policy_object'
print(x, ...)
```

Arguments

type	Type of policy learner method: <ul style="list-style-type: none"> • "ql": Quality/Q-learning. • "drql": Doubly Robust Q-learning. • "blip": Doubly Robust blip-learning (only for dichotomous actions). • "ptl": Policy Tree Learning. • "owl": Outcome Weighted Learning. • "earl": Efficient Augmentation and Relaxation Learning (only single stage). • "rwl": Residual Weighted Learning (only single stage).
control	List of control arguments. Values (and default values) are set using <code>control_{type}()</code> . Key arguments include: <p><code>control_drql()</code>:</p> <ul style="list-style-type: none"> • <code>qv_models</code>: Single element or list of V-restricted Q-models created by <code>q_glm()</code>, <code>q_rf()</code>, <code>q_sl()</code> or similar functions. <p><code>control_blip()</code>:</p> <ul style="list-style-type: none"> • <code>blip_models</code>: Single element or list of V-restricted blip-models created by <code>q_glm()</code>, <code>q_rf()</code>, <code>q_sl()</code> or similar functions. <p><code>control_ptl()</code>:</p> <ul style="list-style-type: none"> • <code>policy_vars</code>: Character vector/string or list of character vectors/strings. Variable names used to construct the V-restricted policy tree. The names must be a subset of the history names, see <code>get_history_names()</code>. • <code>hybrid</code>: If TRUE, <code>policytree::hybrid_policy_tree()</code> is used to fit a policy tree. • <code>depth</code>: Integer or integer vector. The depth of the fitted policy tree for each stage. <p><code>control_owl()</code>:</p> <ul style="list-style-type: none"> • <code>policy_vars</code>: As in <code>control_ptl()</code>. • <code>loss</code>: Loss function. The options are "hinge", "ramp", "logit", "logit.lasso", "l2", "l2.lasso". • <code>kernel</code>: Type of kernel used by the support vector machine. The options are "linear", "rbf". • <code>augment</code>: If TRUE the outcomes are augmented. <p><code>control_earl()/control_rwl()</code>:</p>

- moPropen: Propensity model of class "ModelObj", see [modelObj::modelObj](#).
- moMain: Main effects outcome model of class "ModelObj".
- moCont Contrast outcome model of class "ModelObj".
- regime: An object of class [formula](#) specifying the design of the policy.
- surrogate: The surrogate 0-1 loss function. The options are "logit", "exp", "hinge", "sqhinge", "huber".
- kernel: The options are "linear", "poly", "radial".

alpha	Probability threshold for determining realistic actions.
threshold	Numeric vector, thresholds for not choosing the reference action at stage 1.
full_history	If TRUE, the full history is used to fit each policy function (e.g. QV-model, policy tree). If FALSE, the single stage/ "Markov type" history is used to fit each policy function.
L	Number of folds for cross-fitting nuisance models.
cross_fit_g_models	If TRUE, the g-models will not be cross-fitted even if L > 1.
save_cross_fit_models	If TRUE, the cross-fitted models will be saved.
future_args	Arguments passed to future.apply::future_apply() .
name	Character string.
x	Object of class "policy_object" or "policy_learn".
...	Additional arguments passed to print.

Value

Function of inherited class "policy_learn". Evaluating the function on a [policy_data](#) object returns an object of class [policy_object](#). A policy object is a list containing all or some of the following elements:

q_functions	Fitted Q-functions. Object of class "nuisance_functions".
g_functions	Fitted g-functions. Object of class "nuisance_functions".
action_set	Sorted character vector describing the action set, i.e., the possible actions at each stage.
alpha	Numeric. Probability threshold to determine realistic actions.
K	Integer. Maximal number of stages.
qv_functions (only if type = "drql")	Fitted V-restricted Q-functions. Contains a fitted model for each stage and action.
ptl_objects (only if type = "ptl")	Fitted V-restricted policy trees. Contains a policytree::policy_tree for each stage.
ptl_designs (only if type = "ptl")	Specification of the V-restricted design matrix for each stage

S3 generics

The following S3 generic functions are available for an object of class "policy_object":

`get_g_functions()` Extract the fitted g-functions.

`get_q_functions()` Extract the fitted Q-functions.

`get_policy()` Extract the fitted policy object.

`get_policy_functions()` Extract the fitted policy function for a given stage.

`get_policy_actions()` Extract the (fitted) policy actions.

References

Doubly Robust Q-learning (type = "drql"): Luedtke, Alexander R., and Mark J. van der Laan. "Super-learning of an optimal dynamic treatment rule." *The international journal of biostatistics* 12.1 (2016): 305-332. doi:10.1515/ijb20150052.

Policy Tree Learning (type = "ptl"): Zhou, Zhengyuan, Susan Athey, and Stefan Wager. "Offline multi-action policy learning: Generalization and optimization." *Operations Research* (2022). doi:10.1287/opre.2022.2271.

(Augmented) Outcome Weighted Learning: Liu, Ying, et al. "Augmented outcome-weighted learning for estimating optimal dynamic treatment regimens." *Statistics in medicine* 37.26 (2018): 3776-3788. doi:10.1002/sim.7844.

See Also

`policy_eval()`

Examples

```
library("polle")
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = c("BB"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))
pd

### V-restricted (Doubly Robust) Q-learning

# specifying the learner:
pl <- policy_learn(
  type = "drql",
  control = control_drql(qv_models = list(q_glm(formula = ~ C_1 + BB),
    q_glm(formula = ~ L_1 + BB))),
  full_history = TRUE
)
```

```

# evaluating the learned policy
pe <- policy_eval(policy_data = pd,
                 policy_learn = pl,
                 q_models = q_glm(),
                 g_models = g_glm())

pe
# getting the policy object:
po <- get_policy_object(pe)
# inspecting the fitted QV-model for each action strata at stage 1:
po$qv_functions$stage_1
head(get_policy(pe)(pd))

```

predict.nuisance_functions

Predict g-functions and Q-functions

Description

predict() returns the fitted values of the g-functions and Q-functions when applied to a (new) policy data object.

Usage

```

## S3 method for class 'nuisance_functions'
predict(object, new_policy_data, ...)

```

Arguments

object	Object of class "nuisance_functions". Either g_functions or q_functions as returned by <code>policy_eval()</code> or <code>policy_learn()</code> .
new_policy_data	Policy data object created by <code>policy_data()</code> .
...	Additional arguments.

Value

`data.table::data.table` with keys id and stage and variables g_a or Q_a for each action a in the actions set.

Examples

```

library("polle")
### Single stage:
d <- sim_single_stage(5e2, seed=1)
pd <- policy_data(d, action="A", covariates=list("Z", "B", "L"), utility="U")
pd
# defining a static policy (A=1):

```

```

p1 <- policy_def(1, name = "A=1")

# doubly robust evaluation of the policy:
pe <- policy_eval(policy_data = pd,
                 policy = p1,
                 g_models = g_glm(),
                 q_models = q_glm())
# summarizing the estimated value of the policy:
pe

# getting the fitted g-function values:
head(predict(get_g_functions(pe), pd))

# getting the fitted Q-function values:
head(predict(get_q_functions(pe), pd))

```

q_model

q_model class object

Description

Use `q_glm()`, `q_glmnet()`, `q_rf()`, and `q_sl()` to construct an outcome regression model/Q-model object. The constructors are used as input for `policy_eval()` and `policy_learn()`.

Usage

```

q_glm(
  formula = ~A * .,
  family = gaussian(),
  model = FALSE,
  na.action = na.pass,
  ...
)

q_glmnet(
  formula = ~A * .,
  family = "gaussian",
  alpha = 1,
  s = "lambda.min",
  ...
)

q_rf(
  formula = ~.,
  num.trees = c(250, 500, 750),
  mtry = NULL,
  cv_args = list(nfolds = 3, rep = 1),
  ...
)

```

```

)

q_sl(
  formula = ~.,
  SL.library = c("SL.mean", "SL.glm"),
  env = as.environment("package:SuperLearner"),
  onlySL = TRUE,
  discreteSL = FALSE,
  ...
)

q_xgboost(
  formula = ~.,
  objective = "reg:squarederror",
  params = list(),
  nrounds,
  max_depth = 6,
  eta = 0.3,
  nthread = 1,
  cv_args = list(nfolds = 3, rep = 1)
)

```

Arguments

formula	An object of class formula specifying the design matrix for the outcome regression model/Q-model at the given stage. The action at the given stage is always denoted 'A', see examples. Use get_history_names() to see the additional available variable names.
family	A description of the error distribution and link function to be used in the model.
model	(Only used by q_glm) If FALSE model frame will not be saved.
na.action	(Only used by q_glm) A function which indicates what should happen when the data contain NAs, see na.pass .
...	Additional arguments passed to glm() , glmnet::glmnet , ranger::ranger or SuperLearner::SuperLearner .
alpha	(Only used by q_glmnet) The elasticnet mixing parameter between 0 and 1. alpha equal to 1 is the lasso penalty, and alpha equal to 0 the ridge penalty.
s	(Only used by q_glmnet) Value(s) of the penalty parameter lambda at which predictions are required, see glmnet::predict.glmnet() .
num.trees	(Only used by q_rf) Number of trees.
mtry	(Only used by q_rf) Number of variables to possibly split at in each node.
cv_args	(Only used by q_rf) Cross-validation parameters. Only used if multiple hyper-parameters are given. K is the number of folds and rep is the number of replications.
SL.library	(Only used by q_sl) Either a character vector of prediction algorithms or a list containing character vectors, see SuperLearner::SuperLearner .

env	(Only used by q_sl) Environment containing the learner functions. Defaults to the calling environment.
onlySL	(Only used by q_sl) Logical. If TRUE, only saves and computes predictions for algorithms with non-zero coefficients in the super learner object.
discreteSL	(Only used by q_sl) If TRUE, select the model with the lowest cross-validated risk.
objective	(Only used by q_xgboost) specify the learning task and the corresponding learning objective, see xgboost::xgboost .
params	(Only used by q_xgboost) list of parameters.
nrounds	(Only used by q_xgboost) max number of boosting iterations.
max_depth	(Only used by q_xgboost) maximum depth of a tree.
eta	(Only used by q_xgboost) learning rate.
nthread	(Only used by q_xgboost) number of threads.

Details

q_glm() is a wrapper of [glm\(\)](#) (generalized linear model).

q_glmnet() is a wrapper of [glmnet::glmnet\(\)](#) (generalized linear model via penalized maximum likelihood).

q_rf() is a wrapper of [ranger::ranger\(\)](#) (random forest). When multiple hyper-parameters are given, the model with the lowest cross-validation error is selected.

q_sl() is a wrapper of [SuperLearner::SuperLearner](#) (ensemble model). q_xgboost() is a wrapper of [xgboost::xgboost](#).

Value

q_model object: function with arguments 'AH' (combined action and history matrix) and 'V_res' (residual value/expected utility).

See Also

[get_history_names\(\)](#), [get_q_functions\(\)](#).

Examples

```
library("polle")
### Single stage case
d1 <- sim_single_stage(5e2, seed=1)
pd1 <- policy_data(d1,
  action="A",
  covariates=list("Z", "B", "L"),
  utility="U")

pd1

# available history variable names for the outcome regression:
get_history_names(pd1)

# evaluating the static policy a=1 using inverse
```

```

# propensity weighting based on the given Q-model:
pe1 <- policy_eval(type = "or",
                  policy_data = pd1,
                  policy = policy_def(1, name = "A=1"),
                  q_model = q_glm(formula = ~A*.))

pe1

# getting the fitted Q-function values
head(predict(get_q_functions(pe1), pd1))

### Two stages:
d2 <- sim_two_stage(5e2, seed=1)
pd2 <- policy_data(d2,
                  action = c("A_1", "A_2"),
                  covariates = list(L = c("L_1", "L_2"),
                                    C = c("C_1", "C_2")),
                  utility = c("U_1", "U_2", "U_3"))

pd2

# available full history variable names at each stage:
get_history_names(pd2, stage = 1)
get_history_names(pd2, stage = 2)

# evaluating the static policy a=1 using outcome
# regression based on a glm model for each stage:
pe2 <- policy_eval(type = "or",
                  policy_data = pd2,
                  policy = policy_def(1, reuse = TRUE, name = "A=1"),
                  q_model = list(q_glm(~ A * L_1),
                                q_glm(~ A * (L_1 + L_2))),
                  q_full_history = TRUE)

pe2

# getting the fitted Q-function values
head(predict(get_q_functions(pe2), pd2))

```

sim_multi_stage

Simulate Multi-Stage Data

Description

Simulate Multi-Stage Data

Usage

```

sim_multi_stage(
  n,
  par = list(tau = 10, gamma = c(0, -0.2, 0.3), alpha = c(0, 0.5, 0.2, -0.5, 0.4), beta =
    c(3, -0.5, -0.5), psi = 1, xi = 0.3),
  a = function(t, x, beta, ...) {

```

```

    prob <- lava::expit(beta[1] + (beta[2] * t^2) +
      (beta[3] * x))
    stats::rbinom(n = 1, size = 1, prob = prob)
  },
  seed = NULL
)

```

Arguments

n	Number of observations.
par	Named list with distributional parameters. <ul style="list-style-type: none"> • tau: τ • gamma: γ • alpha: α • beta: β • psi: ψ • xi: ξ
a	Function used to specify the action/treatment at every stage.
seed	Integer.

Details

sim_multi_stage samples n iid observation O with the following distribution:

$$W \sim \mathcal{N}(0, 1) B \sim \text{Ber}(\xi)$$

For $k \geq 1$ let

$$(T_k - T_{k-1}) | X_{k-1}, A_{k-1}, W \sim \begin{cases} \text{Exp} \left\{ \exp(\gamma^T [1, X_{k-1}, W]) \right\} + \psi & A_{k-1} = 1 \\ \infty & A_{k-1} = 0 \end{cases} \quad X_k | T_k, X_{k-1}, B \sim \begin{cases} \mathcal{N} \left\{ \alpha^T [1, T_k] \right\} & T_k = \infty \\ 0 & T_k = \infty \end{cases}$$

Note that ψ is the minimum increment.

Value

list with elements stage_data ([data.table::data.table](#)) and baseline_data ([data.table::data.table](#)).

sim_single_stage	<i>Simulate Single-Stage Data</i>
------------------	-----------------------------------

Description

Simulate Single-Stage Data

Usage

```

sim_single_stage(
  n = 10000,
  par = c(k = 0.1, d = 0.5, a = 1, b = -2.5, c = 3, p = 0.3),
  action_model = function(Z, L, B, k, d) {
    k * (Z + L - 1) * Z^(-2) + d * (B == 1)
  },
  utility_model = function(Z, L, A, a, b, c) {
    Z + L + A * (c * Z + a * L + b)
  },
  seed = NULL,
  return_model = FALSE,
  ...
)

```

Arguments

n	Number of observations.
par	Named vector with distributional parameters. <ul style="list-style-type: none"> • k: κ • d: δ • a: α • b: β • c: γ • p: π
action_model	Function used to specify the action/treatment probability (logit link).
utility_model	Function used to specify the conditional mean utility.
seed	Integer.
return_model	If TRUE, the <code>lava::lvm</code> model is returned.
...	Additional arguments passed to <code>lava::lvm()</code> .

Details

`sim_single_stage` samples n iid observation $O = (B, Z, L, A, U)$ with the following distribution:

$$B \sim \text{Bernoulli}(\pi) \mid Z, L, A \sim \mathcal{N}(Z + L, \sigma^2) \mid Z, L, B \sim \text{Bernoulli}(\text{expit}\{\kappa Z^{-2}(Z+L-1) + \delta B\}) \mid Z, L, A \sim \mathcal{N}(Z + L, \sigma^2)$$

Value

data.frame with n rows and columns $Z, L, B, A,$ and U .

sim_single_stage_multi_actions
Simulate Single-Stage Multi-Action Data

Description

Simulate Single-Stage Multi-Action Data

Usage

```
sim_single_stage_multi_actions(n = 1000, seed = NULL)
```

Arguments

n Number of observations.
seed Integer.

Details

sim_single_stage_multi_actions samples n iid observation $O = (z, x, a, u)$ with the following distribution:

$$z, x \sim \text{Uniform}([0, 1]) \quad \tilde{a} \sim \mathcal{N}(0, 1) \quad a \mid \tilde{a} \sim \begin{cases} 0 & \text{if } \tilde{a} < -1 \\ 1 & \text{if } \tilde{a} - 1 \leq a < 0.5 \\ 2 & \text{otherwise} \end{cases} \quad u \mid z, x \sim \mathcal{N}(x + z + I\{a = 2\}(x - 0.5) + I\{a =$$

Value

data.frame with n rows and columns z , x , a , and u .

sim_two_stage *Simulate Two-Stage Data*

Description

Simulate Two-Stage Data

Usage

```
sim_two_stage(  
  n = 10000,  
  par = c(gamma = 0.5, beta = 1),  
  seed = NULL,  
  action_model_1 = function(C_1, beta, ...) stats::rbinom(n = NROW(C_1), size = 1, prob =  
    lava::expit(beta * C_1)),
```

```

action_model_2 = function(C_2, beta, ...) stats::rbinom(n = NROW(C_1), size = 1, prob =
  lava::expit(beta * C_2)),
deterministic_rewards = FALSE
)

```

Arguments

n Number of observations.

par Named vector with distributional parameters.

- gamma: γ
- beta: β

seed Integer.

action_model_1 Function used to specify the action/treatment at stage 1.

action_model_2 Function used to specify the action/treatment at stage 2.

deterministic_rewards Logical. If TRUE, the deterministic reward contributions are returned as well (columns U_1_A0, U_1_A1, U_2_A0, U_2_A1).

Details

sim_two_stage samples n iid observation O with the following distribution: BB is a random categorical variable with levels group1, group2, and group3. Furthermore,

$$B \sim \mathcal{N}(0, 1) L_1 \sim \mathcal{N}(0, 1) C_1 \mid L_1 \sim \mathcal{N}(L_1, 1) A_1 \mid C_1 \sim \text{Bernoulli}(\text{expit}(\beta C_1)) L_2 \sim \mathcal{N}(0, 1) C_2 \mid A_1, L_1 \sim \mathcal{N}(\gamma L_1 +$$

The rewards are calculated as

$$U_1 = L_1 U_2 = A_1 \cdot C_1 + L_2 U_3 = A_2 \cdot C_2 + L_3.$$

Value

[data.table::data.table](#) with n rows and columns B, BB, L_1, C_1, A_1, L_2, C_2, A_2, L_3, U_1, U_2, U_3 (U_1_A0, U_1_A1, U_2_A0, U_2_A1).

sim_two_stage_multi_actions

Simulate Two-Stage Multi-Action Data

Description

Simulate Two-Stage Multi-Action Data

Usage

```
sim_two_stage_multi_actions(
  n = 1000,
  par = list(gamma = 0.5, beta = 1, prob = c(0.2, 0.4, 0.4)),
  seed = NULL,
  action_model_1 = function(C_1, beta, ...) stats::rbinom(n = NROW(C_1), size = 1, prob =
    lava::expit(beta * C_1))
)
```

Arguments

n Number of observations.

par Named vector with distributional parameters.

- gamma: γ
- beta: β
- prob: p

seed Integer.

action_model_1 Function used to specify the dichotomous action/treatment at stage 1.

Details

`sim_two_stage_multi_actions` samples n iid observation O with the following distribution: BB is a random categorical variable with levels `group1`, `group2`, and `group3`. Furthermore,

$$B \sim \mathcal{N}(0, 1) L_1 \sim \mathcal{N}(0, 1) C_1 | L_1 \sim \mathcal{N}(L_1, 1) P(A_1 = 'yes' | C_1) = \text{expit}(\beta C_1) P(A_1 = 'no' | C_1) = 1 - P(A_1 = 'yes')$$

The rewards are calculated as

$$U_1 = L_1 U_2 = A_1 \cdot C_1 + L_2 U_3 = A_2 \cdot C_2 + L_3.$$

Value

`data.table::data.table` with n rows and columns `B`, `BB`, `L_1`, `C_1`, `A_1`, `L_2`, `C_2`, `A_2`, `L_3`, `U_1`, `U_2`, `U_3`.

subset_id

Subset Policy Data on ID

Description

`subset_id` returns a policy data object containing the given IDs.

Usage

```
subset_id(object, id, preserve_action_set = TRUE)
```

Arguments

object Object of class `policy_data`.
id character vectors of IDs.
preserve_action_set
 If TRUE, the action sets must be preserved.

Value

Object of class `policy_data`.

Examples

```
library("polle")
### Single stage:
d <- sim_single_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d, action="A", covariates=list("Z", "B", "L"), utility="U")
pd

# getting the observation IDs:
get_id(pd)[1:10]

# subsetting on IDs:
pdsb <- subset_id(pd, id = 250:500)
pdsb
get_id(pdsb)[1:10]
```

Index

`+.policy_eval (policy_eval)`, 40

`coef.policy_eval (policy_eval)`, 40

`conditional`, 3

`control_blip`, 4

`control_blip()`, 48

`control_drql`, 4

`control_drql()`, 48

`control_earl`, 5

`control_earl()`, 48

`control_owl`, 6

`control_owl()`, 48

`control_ptl`, 7

`control_ptl()`, 48

`control_rwl`, 8

`control_rwl()`, 48

`copy_policy_data`, 9

`copy_policy_data()`, 37

`data.frame`, 35

`data.table::copy()`, 9

`data.table::data.table`, 9, 11, 15, 19, 20, 24, 28, 34, 35, 37–39, 44, 51, 56, 59, 60

`DTRlearn2::owl()`, 6

`DynTxRegime::earl()`, 5

`DynTxRegime::rwl()`, 8

`estimate.policy_eval (policy_eval)`, 40

`fit_g_functions`, 10

`formula`, 5, 8, 26, 49, 53

`future.apply::future_apply()`, 42, 49

`g_empir (g_model)`, 25

`g_empir()`, 10, 41

`g_glm (g_model)`, 25

`g_glm()`, 10, 41

`g_glmnet (g_model)`, 25

`g_model`, 13, 25

`g_rf (g_model)`, 25

`g_rf()`, 10, 41

`g_sl (g_model)`, 25

`g_sl()`, 10, 41

`g_xgboost (g_model)`, 25

`get_action_set`, 11

`get_actions`, 11

`get_actions()`, 37

`get_g_functions`, 12

`get_g_functions()`, 27, 45, 50

`get_history (history)`, 28

`get_history()`, 37, 39

`get_history_names`, 13

`get_history_names()`, 26, 27, 37, 39, 53, 54

`get_id`, 14

`get_id_stage`, 15

`get_K`, 16

`get_n`, 16

`get_policy`, 17, 34

`get_policy()`, 45, 50

`get_policy_actions`, 18

`get_policy_actions()`, 45, 50

`get_policy_functions`
(`get_policy_functions.blip`), 19

`get_policy_functions()`, 45, 50

`get_policy_functions.blip`, 19

`get_policy_object`, 21

`get_q_functions`, 22

`get_q_functions()`, 45, 50, 54

`get_stage_action_sets`, 23

`get_utility`, 24

`get_utility()`, 37

`glm()`, 26, 53, 54

`glmnet::glmnet`, 26, 53

`glmnet::glmnet()`, 26, 54

`glmnet::predict.glmnet()`, 26, 53

`history`, 14, 15, 28, 28

`IC.policy_eval (policy_eval)`, 40

lava::estimate.default, 3, 45
lava::IC, 45
lava::lvm, 57
lava::lvm(), 57

merge.policy_eval (policy_eval), 40
modelObj::modelObj, 5, 8, 49

na.pass, 26, 53
nuisance_functions, 12, 22, 30, 41, 42

partial, 31
partial(), 37
plot(), 37
plot.policy_data, 32
plot.policy_eval, 33
plot.policy_eval(), 45
policy, 17, 32, 34, 38
policy_data, 9, 11, 12, 14–16, 23, 24, 28,
30–32, 35, 36, 38, 39, 49, 61
policy_data(), 3, 10, 13, 41, 51
policy_def, 34, 38
policy_def(), 41
policy_eval, 12, 17, 18, 20–22, 33, 34, 40
policy_eval(), 3, 25, 35, 37, 50–52
policy_learn, 20, 34, 44, 47
policy_learn(), 25, 35, 37, 41, 51, 52
policy_object, 12, 17, 21, 22, 34, 49
policy_object (policy_learn), 47
policytree::hybrid_policy_tree(), 7, 48
policytree::policy_tree, 49
policytree::policy_tree(), 7
predict.nuisance_functions, 12, 22, 51
print.policy_data (policy_data), 35
print.policy_eval (policy_eval), 40
print.policy_learn (policy_learn), 47
print.policy_object (policy_learn), 47

q_glm (q_model), 52
q_glm(), 4, 42, 48
q_glmnet (q_model), 52
q_model, 13, 52
q_rf (q_model), 52
q_rf(), 4, 42, 48
q_sl (q_model), 52
q_sl(), 4, 42, 48
q_xgboost (q_model), 52

ranger::ranger, 26, 53

ranger::ranger(), 26, 54

scale(), 6
sim_multi_stage, 55
sim_single_stage, 56
sim_single_stage_multi_actions, 58
sim_two_stage, 58
sim_two_stage_multi_actions, 59
subset_id, 60
subset_id(), 37
summary.policy_data (policy_data), 35
summary.policy_eval (policy_eval), 40
SuperLearner::SuperLearner, 26, 53, 54

vcov.policy_eval (policy_eval), 40

xgboost::xgboost, 26, 54