

Package ‘sharpData’

October 14, 2022

Version 1.4

Title Data Sharpening

Author W. John Braun <john.braun@ubc.ca>

Maintainer W.J. Braun <john.braun@ubc.ca>

Depends R (>= 3.5.0), KernSmooth, stats, quadprog

Description Functions and data sets inspired by data sharpening -
data perturbation to achieve improved performance in
nonparametric estimation, as described in Choi, E., Hall, P.
and Rousson, V. (2000).

Capabilities for enhanced local linear regression function
and derivative estimation are included, as well as an
asymptotically correct iterated data sharpening estimator
for any degree of local polynomial regression estimation.

A cross-validation-based bandwidth selector is included which,
in concert with the iterated sharpener, will often provide
superior performance, according to a median integrated squared
error criterion. Sample data sets are provided to illustrate
function usage.

LazyLoad true

LazyData true

ZipData no

License Unlimited

NeedsCompilation yes

Repository CRAN

Date/Publication 2021-03-30 07:40:02 UTC

R topics documented:

burnRate	2
CVsharp	2
LLsharpen	4
Monopoly	5

MonoMat	6
MPG	7
sharpiteration	8
whale	9
Index	10

burnRate	<i>Firebrand Burning Properties</i>
----------	-------------------------------------

Description

The **burnRate** data frame contains laboratory data on the proportion of remaining fuel in a piece of wood that has burned for a fixed period of time subjected to a fixed windspeed.

Usage

```
data(burnRate)
```

Format

This data frame contains the following columns:

proportionBurned a numeric vector

densityRatio ratio of windspeed, multiplied by density of air, to density of firebrand

species factor listing tree species

diameter numeric vector of diameter of burned particle in cm

windspeed windspeed in cm per second

testTime length of test in seconds

Source

Albini, F. USDA Forest Service General Technical Report INT-56, 1979.

Description

Cross-validation bandwidth selector for iterated sharpened responses for bias reduction in function estimation.

Usage

```
CVsharp(x, y, deg, nsteps)
```

Arguments

x	a numeric vector containing the predictor variable values.
y	a numeric vector containing the response variable values.
deg	a numeric vector containing the local polynomial degree used.
nsteps	a numeric vector containing the number of iteration steps.

Details

If nsteps is specified to be 0, then the CV bandwidth for conventional local polynomial regression is provided.

Value

a list containing 3 elements: the candidate bandwidths; the corresponding CV scores; the selected optimal bandwidth.

Author(s)

W.J. Braun

See Also

locpoly

Examples

```
speed <- MPG[, 1]
mpg <- MPG[, 2]
h <- CVsharp(speed, mpg, 0, 0)$CVh # conventional local constant regression bandwidth
mpg.10 <- locpoly(speed, mpg, bandwidth=h, degree=0)
h <- CVsharp(speed, mpg, 0, 1)$CVh # 1-sharpened local constant regression bandwidth
mpgSharp <- sharpiteration(speed, mpg, 0, h, 1)
mpg.11 <- locpoly(speed, mpgSharp[[1]], bandwidth=h, degree=0)
h <- CVsharp(speed, mpg, 0, 5)$CVh # 5-sharpened local constant regression bandwidth
mpgSharp <- sharpiteration(speed, mpg, 0, h, 5)
mpg.15 <- locpoly(speed, mpgSharp[[5]], bandwidth=h, degree=0)
plot(mpg ~ speed)
lines(mpg.10) # unsharpened function estimation
lines(mpg.11, col=2, lty=2) # sharpened function estimation (1 steps)
lines(mpg.15, col=4, lty=3) # sharpened function estimation (5 steps)
```

LLsharpen*Data Sharpening for Local Linear Regression***Description**

Calculation of sharpened responses for bias reduction in function and first derivative estimation, assuming a gaussian kernel is used in bivariate scatterplot smoothing.

Usage

```
LLsharpen(x, y, h)
```

Arguments

- x a numeric vector containing the predictor variable values.
- y a numeric vector containing the response variable values.
- h a numeric vector containing the (scalar) bandwidth.

Value

a vector containing the sharpened (i.e. perturbed) response values, ready for input into a local linear regression estimator.

Author(s)

W.J. Braun

References

Choi, E., Hall, P. and Rousson, V. (2000) Data sharpening methods for bias reduction in nonparametric regression. *Annals of Statistics* 28(5) 1339-1355.

See Also

`locpoly`

Examples

```
speed <- MPG[, 1]
mpg <- MPG[, 2]
h <- dpill(speed, mpg)*2
mpgSharp <- LLsharpen(speed, mpg, h)
mpg.1S <- locpoly(speed, mpgSharp, bandwidth=h, drv=1, degree=1)
mpg.1X <- locpoly(speed, mpg, bandwidth=h, drv=1, degree=1)
plot(mpg.1X, type="l") # unsharpened derivative estimation
lines(mpg.1S, col=2, lty=2) # sharpened derivative estimation
```

Monopoly***Monotonized Local Regression***

Description

Local constant and local linear regression are applied to bivariate data. The response is ‘sharpened’ or perturbed in a way to render a monotonically increasing curve estimate.

Usage

```
Monopoly(x, y, h, d=1, xgrid, numgrid = 401, ...)
```

Arguments

x	a vector of explanatory variable observations
y	binary vector of responses
h	bandwidth
d	degree, can be either 0 or 1
xgrid	gridpoints on x-axis where monotonicity constraint is enforced
numgrid	number of equally-spaced gridpoints (if xgrid not specified)
...	other arguments for locpoly

Details

Data are perturbed the smallest possible L2 distance subject to the constraint that the local linear estimate is monotonically increasing.

Value

x	locations of function estimate evaluations
y	function estimate evaluations (sharpened - monotonized)
ysharp	sharpened responses

Author(s)

W.J.Braun

References

Braun, W.J. and Hall, P., Data Sharpening for Nonparametric Estimation Subject to Constraints, Journal of Computational and Graphical Statistics, 2001

Examples

```
gridpts <- seq(1, 10, length=101)
x <- seq(1, 10, length=51)
p <- exp(-1 + .2*x)/(1 + exp(-1 + .2*x))
y <- rbinom(51, 1, p)
plot(x, y)
lines(Monopoly(x, y, h=0.6, xgrid=gridpts))
##
plot(faithful)
with(faithful,
lines(Monopoly(eruptions, waiting, h=0.1, d=1,
range=c(1.55,5.15))))
```

MonoMat

Matrix of derivative coefficients for local polynomial estimates

Description

This computes a matrix of coefficients of the first derivatives of monotonic local linear sharpening problem.

Usage

```
MonoMat(xgrid, x, h, d)
```

Arguments

xgrid	numeric vector of locations where monotonicity constraint is to be enforced
x	numeric explanatory vector
h	numeric bandwidth
d	local polynomial degree, can be either 0 or 1

Value

a list containing the A matrix and the number of rows in A.

Author(s)

W.J. Braun

MPG*Mileage Data*

Description

The MPG data frame has 15 rows and 10 columns.

Usage

```
data(MPG)
```

Format

This data frame contains the following columns:

speed a numeric vector of cruising speeds in miles per hour
corsica88 miles per gallon for a 1988 Corsica
legacy93 miles per gallon for a 1993 Legacy
olds94 miles per gallon for a 1994 Oldsmobile
cutlass94 miles per gallon for a 1994 Oldsmobile Cutlass
chevpickup94 miles per gallon for a 1994 Chevrolet Pickup
cherokee94 miles per gallon for a 1994 Jeep Cherokee
villager94 miles per gallon for a 1994 Villager
prizm95 miles per gallon for a 1995 Prizm
celica97 miles per gallon for a 1997 Toyota Celica

Source

B.H. West, R.N. McGill, J.W. Hodgson, S.S. Sluder, D.E. Smith, Development and Verification of Light-Duty Modal Emissions and Fuel Consumption Values for Traffic Models, Washington, DC, April 1997, and additional project data, April 1998.

Examples

```
data(MPG)
plot(celica97 ~ speed, data = MPG)
```

sharpiteration

*Iterated Data Sharpening for Local Polynomial Regression***Description**

Calculation of sharpened responses for bias reduction in function and estimation, assuming a gaussian kernel is used in bivariate scatterplot smoothing.

Usage

```
sharpiteration(x, y, deg, h, nsteps, na.rm, ...)
```

Arguments

x	a numeric vector containing the predictor variable values.
y	a numeric vector containing the response variable values.
deg	a numeric vector containing the local polynomial degree used.
h	a numeric vector containing the (scalar) bandwidth.
nsteps	a numeric vector containing the number of iteration steps.
na.rm	a logical value indicating whether to remove missing values from fitted vectors
...	additional arguments to locpoly

Value

a list with elements containing the sharpened (i.e. perturbed) response values, ready for input into a local polynomial regression estimator. The ith list element corresponds to i steps of data sharpening.

Author(s)

W.J. Braun

See Also

locpoly

Examples

```
speed <- MPG[, 1]
mpg <- MPG[, 2]
h <- dpill(speed, mpg)
mpgSharp <- sharpiteration(speed, mpg, 1, h, 2)
mpg.1S <- locpoly(speed, mpgSharp[[2]], bandwidth=h, degree=1)
mpg.1X <- locpoly(speed, mpg, bandwidth=h, degree=1)
plot(mpg ~ speed)
lines(mpg.1X) # unsharpened function estimation
lines(mpg.1S, col=2, lty=2) # sharpened function estimation (2 steps)
```

whale

Whale data

Description

Nursing times for a baby beluga whale.

Usage

```
data(whale)
```

Format

A data frame with 228 observations on the following 3 variables.

V1 a numeric vector

V2 a numeric vector

V3 a factor with levels 0 104 118 119 126 127 132 135 137 14 144 146 150 151 153 156 157 160
166 167 168 169 170 171 172 174 175 176 180 186 187 189 191 192 193 196 197 198 199
200 204 205 216 218 222 223 225 226 228 229 230 231 232 236 239 243 244 247 252 253
255 257 260 267 271 274 275 277 284 285 286 288 291 292 299 308 320 323 326 332 338
339 340 344 345 349 351 353 354 359 360 362 371 372 377 380 386 404 409 411 419 423
426 429 430 432 433 435 438 440 441 442 443 444 445 446 449 450 453 456 462 463 464
470 473 477 48 485 491 492 494 495 497 504 506 509 51 513 515 524 528 533 537 538 541
565 579 59 590 600 605 613 644 648 659 68 688 69 693 694 702 714 72 720 737 74 750 756
772 80 805 813 825 84 85 870 873 888 92 93 954 96 98 M

Source

Simonoff, J. Smoothing Methods in Statistics, Springer, 1996.

Index

- * **datasets**
 - burnRate, [2](#)
 - MPG, [7](#)
 - whale, [9](#)
- * **models**
 - CVsharp, [2](#)
 - LLsharpen, [4](#)
 - Monopoly, [5](#)
 - MonoMat, [6](#)
 - sharpiteration, [8](#)
- burnRate, [2](#)
- CVsharp, [2](#)
- LLsharpen, [4](#)
- Monopoly, [5](#)
- MonoMat, [6](#)
- MPG, [7](#)
- sharpiteration, [8](#)
- whale, [9](#)