

Package ‘sparktex’

October 14, 2022

Version 0.1

Date 2013-06-06

Title Generate LaTeX sparklines in R

Depends R (>= 3.0.0)

Description Generate syntax for use with the sparklines package for
LaTeX.

License GPL-2

URL <http://thomasleeper.com/software.html>

Author Thomas Leeper [aut, cre],
Andy Barbour [ctb]

Maintainer Thomas Leeper <thosjleeper@gmail.com>

NeedsCompilation no

Repository CRAN

Date/Publication 2013-06-10 07:54:02

R topics documented:

sparktex-package	1
sparktex	2

Index

5

sparktex-package *Create LaTeX sparklines from R*

Description

Generate sparktex output for LaTeX from input value

Details

Package: sparktex
 Type: Package
 Version: 0.1
 Date: 2013-06-06
 License: GPL-2

Author(s)

Thomas J. Leeper, with contributions from Andy Barbour
 Maintainer: Thomas J. Leeper <thosjleeper@gmail.com>

sparktex

Generate sparktex output

Description

Generate sparktex output for LaTeX from input value

Usage

```
sparktex(y, x=NULL, height=1.75, width=NULL,
type=c("sparkline","sparkspike"),
color=NULL, linewidth=NULL,
rectangle=NULL, sparkdot=NULL,
normalize=FALSE, catfile="", ...)
```

Arguments

y	A vector of data values.
x	An optional vector containing horizontal positions of y values. If NULL, evenly spaced positions will be calculated automatically.
height	The height of the sparkplot as a percentage of line height. Default is 1.75, per sparklines documentation.
width	The width of the sparkline. See examples.
type	Either "sparkline" for a lineplot or "sparkspike" for a barplot.
color	Optionally, a two-element character specifying a LaTeX color model and color specification for the sparkline or sparkspikes.
linewidth	An optional value specifying the width of the sparkspikes or the width of the sparkline in pt.

<code>rectangle</code>	Optionally, a two- or four-element vector specifying the vertical lower and upper bounds of a background rectangle to draw behind the full width of the sparkline (if both values are equal, nothing is drawn) and, optionally, the LaTeX color model and color specification for the rectangles. If only the bounds are specified, the default color model and specification is used ("gray", "0.9"). See examples.
<code>sparkdot</code>	An optional argument which, if specified, should consist of a list of three-element vectors, where the elements are - respectively - an x value, a y value, and a color. If specifying sparkdot(s), it is probably best to specify x values to prevent misplacement due to automatic rescaling of x.
<code>normalize</code>	A logical specifying whether y should be rescaled to the dimensions (0,1). If <code>height=1</code> and <code>normalize=TRUE</code> , the entire sparkline fits within a single LaTeX line. If <code>normalize=FALSE</code> and/or <code>height > 1</code> (default is 1.75), the sparkline will spillover vertically.
<code>catfile</code>	An optional file where the output should be written. If "" (the default), the output is sent to <code>stdout</code> .
<code>...</code>	Optional arguments passed to <code>cat</code> .

Details

This package can be used to generate the LaTeX markup necessary to display sparklines (lineplots) and sparkspikes (barplots) for the `sparklines` environment from the “`sparklines`” LaTeX package. Markup can either be written to `stdout`, e.g. to incorporate directly in a `Sweave` or `knitr` output, or saved to file. The sparklines can be included in LaTeX body text or other environments, e.g., `tabular`, making it a relatively flexible means of incorporating simple in-text graphics.

Value

A call to `sparktex` invisibly returns a three-element list containing:

<code>x</code>	A numeric vector of (possibly adjusted) x positions.
<code>y</code>	A numeric vector of (possibly adjusted) y positions.
<code>tex</code>	A character string containing the LaTeX output.

If `file` is not an empty string, then the content of `tex` are written to the file, otherwise the content is sent to `stdout`.

Note

The `sparklines` environment is only available with `pdflatex`. `\usepackage{sparklines}` must be declared in the LaTeX preamble.

Author(s)

Thomas J. Leeper, with contributions from Andy Barbour

References

For information on the LaTeX `sparklines` package, see <http://www.ctan.org/pkg/sparklines>.

Examples

```
# Output from all examples included in `sparktex-examples.pdf`  
  

# data for sparklines  

vals <- sin(seq(1:10))  
  

# basic sparkline  

sparktex(vals)  
  

# a wider sparkline  

sparktex(vals, width=40)  
  

# a thicker sparkline  

sparktex(vals, linewidth=3)  
  

# a sparkspike/barplot  

sparktex(vals, type="sparkspike")  
  

# constrain y to (0,1)  

sparktex(vals, normalize=TRUE)  
  

# constrain the sparkline to LaTeX line height  

sparktex(vals, height=1)  
  

# a gray background  

sparktex(vals, rectangle=c(1,2))  
  

# a colored background  

sparktex(vals, rectangle=c(1,2,"rgb","0.5,0.7,0.3"))  
  

# two colored background rectangles  

sparktex(vals, rectangle=list(c(1,2,"rgb","0.5,0.7,0.3"), c(-1,0,"rgb","0.2,0.7,0.3")))  
  

# a sparkline with start and end points  

sparktex(vals, sparkdot=list(c(0.0864,sin(1),"blue"), c(0.9136,sin(10),"red")))  
  

# a thick purple sparkline  

sparktex(vals, linewidth=2, normalize=TRUE, color=c("named","purple"))
```

Index

[cat, 3](#)

[sparktex, 2](#)

[sparktex-package, 1](#)