

Package ‘tropAlgebra’

July 22, 2025

Type Package

Title Tropical Algebraic Functions

Version 0.1.1

Maintainer Muhammad Kashif Hanif <mkashifhanif@gcuf.edu.pk>

Description It includes functions like tropical addition, tropical multiplication for vectors and matrices. In tropical algebra, the tropical sum of two numbers is their minimum and the tropical product of two numbers is their ordinary sum. For more information see also I. Simon (1988) Recognizable sets with multiplicities in the tropical semi ring: Volume 324 Lecture Notes I Computer Science, pages 107-120 <[doi:10.1007/BFb0017135](https://doi.org/10.1007/BFb0017135)>.

Depends R (>= 3.3.0)

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

NeedsCompilation no

Author Muhammad Kashif Hanif [cre, aut],
Rehman Ahmad [aut],
Karl-Heinz Zimmermann [aut],
Zia ul Qayyum [aut]

Repository CRAN

Date/Publication 2018-01-21 17:27:24 UTC

Contents

copyMatrix	2
copyVector	3
swapMatrix	3
swapVector	4
tadd	5
tmatrixAdd	5
tmatrixMultiply	6

2

copyMatrix

tmultiply

transpose

tscale

tvectorAdd

tvectorMultiply

tvectorMatrixProduct

Index

7

8

8

9

10

10

12

copyMatrix	Copy Matrices
------------	---------------

Description

This function copies the first matrix in second one. This function will work only if both matrices are of same size.

Usage

```
copyMatrix(X,Y)
```

Arguments

- X
- A matrix to be copied.
- Y
- Target Matrix.

Details

If the size of source and target matrices are not same it generates an error.

Value

Returns Y Matrix.

Examples

```
X<-matrix(c('a','b','c','d'),nrow=2, ncol=2)
Y<-matrix(c(NA,NA,NA,NA),nrow=2, ncol=2)
copyMatrix(X,Y)
```

`copyVector`*Copy Vectors*

Description

This function copies the first vector in second one. This function will work only if both vectors are of same length.

Usage

```
copyVector(x,y)
```

Arguments

x	Vector to be copied.
y	Target vector.

Details

If the length of source and target vectors are not same it generates an error.

Value

Returns y.

Examples

```
x<-c(1,2,3,4)
y<-c(NA,NA,NA,NA)
copyVector(x,y)
```

`swapMatrix`*Swap Matrices*

Description

This function interchanges the values of both matrices. This function works only if both matrices are of same size.

Usage

```
swapMatrix(X,Y)
```

Arguments

X	A matrix.
Y	A matrix.

Details

If the size of both matrices are not same, it generates an error. This function swaps the matrices in memory (like pass by reference), it does not return the matrices, but interchanges their values.

Value

Swapped Matrix X and Y.

Examples

```
x<-matrix(c(2,3,5,7),ncol=2,nrow=2)
y<-matrix(c(6,3,1,9),ncol=2, nrow=2)
swapMatrix(x,y)
```

swapVector

Swap Vectors

Description

This function swaps the values of both vectors. This function works only if both vectors have equal length.

Usage

```
swapVector(x,y)
```

Arguments

x	A vector.
y	A vector.

Details

If the lengths of both vectors are not same, it generates an error. This function swaps the vectors in memory (like pass by reference), it does not return the vectors, but interchanges their values.

Value

Swapped vectors x and y.

Examples

```
x<-c(6,7,8)
y<-c(3,2,1)
swapVector(x,y)
```

tadd

Tropical Sum Function

Description

Calculates tropical sum of numeric values. This function workks only if arguments are numeric values. The tropical sum of two numbers is the minimum number. If arguments are not numeric values then it generates an error. If a vector is passed as argument to the funcion it will return the tropical sum of all the elements in the vector.

Usage

```
tadd(...)
```

Arguments

... Any number of numeric values or a single vector.

Details

The tropical sum of two numbers is the minimum number. This function returns the minimum of arguments. If arguments are not numeric values then it generates an error.

Value

Returns tropical sum of arguments.

Examples

```
x<-5
y<-6
tadd(x,y)
```

tmatrixAdd

Tropical Sum of Matrices

Description

This funciton sums two matrices(first matrix scaled by alpha, if user doesnt't pass alpha first matrix will not be scalled) and return the resultant matrix.This function works only if both matrices are numeric and of same size, and alpha is a numeric value.

Usage

```
tmatrixAdd(x,y,alpha=0)
```

Arguments

x	A numeric Matrix.
y	A numeric Matrix.
alpha	A numeric value.

Details

If either the size of both matrices is not same or if any one or both matrices are not numeric matrix or alpha is not a numeric value then it will generates an error.

Value

Returns the tropical sum of x(scaled by alpha) and y.

Examples

```
x<-matrix(c(2,3,5,7),ncol=2,nrow=2)
y<-matrix(c(6,3,1,9),ncol=2, nrow=2)
alpha<-5
tmatrixAdd(x,y,alpha)
```

tmatrixMultiply	<i>Tropical Product of Matrices</i>
-----------------	-------------------------------------

Description

This function returns the product of two matrices. This function works only if columns of first matrix equal to rows of second matrix.

Usage

```
tmatrixMultiply(X,Y)
```

Arguments

X	A numeric Matrix.
Y	A numeric Matrix.

Details

If number of columns of first matrix is not equal to the number of rows of second matrix or any one matrix is not a numeric matrix then this functions generates an error. If mxn is first matrix and axb is a second matrix then nxa will be the resultant matrix.

Value

Returns the tropical product of X and Y

Examples

```
X<-matrix(c(2,3,5,7),ncol=2,nrow=2)
Y<-matrix(c(6,3,1,9),ncol=2, nrow=2)
tmatrixMultiply(X,Y)
```

tmultiply*Tropical Product Function*

Description

The tropical product of two numbers is the ordinary sum of numbers. This function returns the tropical product of arguments. If arguments are not numeric values then it generates an error. If a vector is passed as argument to the function it will return the tropical product of all the elements in the vector.

Usage

```
tmultiply(...)
```

Arguments

... Any number of numeric values or a single vector.

Details

The tropical product of two numbers is the ordinary sum of numbers. This function returns the tropical product of arguments. If arguments are not numeric values then it generates an error.

Value

Returns tropical product of arguments.

Examples

```
x<-6
y<-5
tmultiply(x,y)
```


Details

If the given argument x is not a numeric value or argument Y is not a numeric matrix or a numeric vector then this function generates an error.

Value

Returns the scaled Y .

Examples

```
x<-5
y<-matrix(c(2,3,5,7),ncol=2,nrow=2)
tscale(x,y)
y<-c(1,2,3)
tscale(x,y)
```

tvectorAdd

Tropical Sum of Vectors

Description

This function add two or more vectors and returns the resultant vector. This function works only if vectors are of same length.

Usage

```
tvectorAdd(...)
```

Arguments

... Any number of numeric vectors.

Details

If the arguments are not numeric vectors and are not of same length, this function generates an error. If a single vector is passed to the function it will return the tropical sum of all the elements in the vector.

Value

Returns tropical sum of argumented vectors.

Examples

```
x<-c(5,6,7)
y<-c(1,2,3)
tvectorAdd(x,y)
```

tvectorMultiply	<i>Tropical Product of Vectors</i>
-----------------	------------------------------------

Description

This function multiplies two or more vectors and returns the resultant vector. This function works only if vectors are of same length.

Usage

```
tvectorMultiply(...)
```

Arguments

... Any number of numeric vectors.

Details

If the arguments are not numeric vectors and are not of same length, this function generates an error. If a single vector is passed to the function it will return the tropical product of all the elements in the vector.

Value

Returns the product of argumented vectors.

Examples

```
x<-c(5,6,7)
y<-c(1,2,3)
tvectorMultiply(x,y)
```

tvectotMatrixProduct	<i>Tropical Vector Matrix Product</i>
----------------------	---------------------------------------

Description

This function returns a vector in result of vector matrix tropical product. This function works only if length of vector equal to number of columns of matrix.

Usage

```
tvectotMatrixProduct(Y,x)
```

Arguments

Y	A numeric matrix.
x	A numeric vector.

Details

If the given argument x is not a numeric vector or argument Y is not a numeric matrix and the length of vector is not equal to the number of columns of matrix then the function generates an error.

Value

Returns the tropical product of vector x and matrix Y.

Examples

```
x<-c(1,2,3)
Y<-matrix(c(1,2,3,4,5,6,1,2,3), nrow = 3, ncol = 3)
tvectotMatrixProduct(Y,x)
```

Index

copyMatrix, [2](#)
copyVector, [3](#)

swapMatrix, [3](#)
swapVector, [4](#)

tadd, [5](#)
tmatrixAdd, [5](#)
tmatrixMultiply, [6](#)
tmultiply, [7](#)
transpose, [8](#)
tscale, [8](#)
tvectorAdd, [9](#)
tvectorMultiply, [10](#)
tvectorMatrixProduct, [10](#)